




# Lecture 09: Transformers


# OVERVIEW

1. Transformer architecture
2. How transformers work
3. How to calculate self-attention
4. Multi-head attention
5. Transfer Learning

# ATTENTION IS ALL YOU NEED




# TRANSFORMERS



- **The Transformer** – proposed by Vaswani A., 2017 (Attention is all you need)
  - uses attention to boost the speed with which these models can be trained.
  - The transformer is based on a feedforward neural network rather than RNN.
  - The biggest benefit of the Transformer is the speed of computation due to parallelization.
  - All input sequences are processed simultaneously.

# TRANSFORMER – ARCHITECTURE

- Architecture: stacked encoder – decoder architecture
  - The encoding component is a stack of **encoders** (original paper had six encoders)
    - **encoders are all identical in structure**
  - The decoding component is a stack of **decoders** of the same number as the encoder



# TRANSFORMER – ARCHITECTURE



## Encoder


Inputs first flow through a self-attention layer

Outputs of the self-attention layer are fed to a feed-forward neural network.



## Decoder

Input from encoder flows through self-attention layer then Encoder-Decoder Attention layer and finally through Feedforward layer




### Attention layer:

- helps decoder focus on relevant parts of the input


# HOW THE TRANSFORMER WORKS

- Convert input word into a word embedding vectors
- Each word in the sentence flows through its own path in the encoder



# HOW THE TRANSFORMER WORKS – ENCODING

- Encoder receive input words as vectors
- Self attention processes the input and sent to the feedforward network
- Feedforward sends output to next encoder layer.






# TRANSFORMER – WHAT IS SELF ATTENTION?

Example:

*The animal didn't cross the street because it was too tired.*


What does “**it**” in this sentence refer to?

- *Is it the street or*
- *the animal*
- self-attention allows the transformer model to associate “**it**” with “**animal**”.
- self attention allows it to look at other positions for clues to help the model better encode the word **it**




# HOW TO CALCULATE SELF ATTENTION – STEP 1

Create 3 vectors (**Q**uery, **k**ey, **V**alue – dimension 64) from each encoder's input vector



# HOW TO CALCULATE SELF ATTENTION – STEP 2

calculate self-attention score




# HOW TO CALCULATE SELF ATTENTION – STEP 3 & 4

## Step 3:

- divide the core by 8
- square root of the dimension of the key vector


## Step 4:

- apply SoftMax operation to normalizes scores




# HOW TO CALCULATE SELF ATTENTION – STEP 5 & 6

- **Step 5:**
  - multiply each value vector by the SoftMax score
  - **Intuition:** to amplify relevant words and downgrade irrelevant words
- **Step 6:**
  - sum up the weighted value vectors.
  - produces the output of the self-attention layer




# HOW TO CALCULATE SELF ATTENTION



# MULTI-HEADED ATTENTION

Multi-headed attention improves the performance of the attention layer by allowing for:

1. It expands the model's ability to focus on different positions.
2. It gives the attention layer multiple “representation subspaces”.




$$\text{softmax}\left(\frac{Q \times K^T}{\sqrt{d_k}}\right) V$$

=

The output of the attention mechanism is a 2x3 pink grid labeled  $Z$ .

# MULTI-HEADED ATTENTION

Assume we have multi-headed attention with 8 self attention (eight  $Z$  matrices)






# MULTI-HEADED ATTENTION

Assume we have multi-headed attention with 8 self attention (eight  $Z$  matrices)


- the feedforward layer expects a single matrix
- We concatenate the matrices then multiply them by an additional weight matrix  $W^O$

1) Concatenate all the attention heads




2) Multiply with a weight matrix  $W^O$  that was trained jointly with the model

x




3) The result would be the  $Z$  matrix that captures information from all the attention heads. We can send this forward to the FFNN



# MULTI-HEADED ATTENTION

Assume we have multi-headed attention with 8 self attention (eight  $Z$  matrices)


- the feedforward layer expects a single matrix



# MULTI-HEADED ATTENTION

## Multi head attention “*it*”


- one attention head is focusing on most on *the animal*
- another is focusing on *tired*



# MULTI-HEADED ATTENTION

## Multi head attention “*it*”


- one attention head is focusing on most on *the animal*
- another is focusing on *tired*
- Visualizing all 8 attention heads



# POSITIONAL ENCODING IN TRANSFORMERS


How do we account for the order of the words?

- Transformer adds a vector to each input embedding
- These vectors allow it to determine the position of each word




# POSITIONAL ENCODING IN TRANSFORMERS

- **Intuition:**
  - adding these values to the embeddings provides meaningful distances between the embedding vectors once they are projected into Q/K/V vectors and during dot-product attention.
  - These positional encoding are generated during training (detail in the paper)
- Assume encoding of dimension 4, the positioning will look like




# RESIDUAL CONNECTION

Residual connection: Each sub-layer (self-attention, feed forward neural network) in each encoder and decoder have a residual connection around it followed by a layer normalization



# THE DECODER SIDE


- The encoder process the input sentence
- Output of top encoder layer is converted to attention vectors K and V.
- K & V vectors are used by each decoder in its “encoder-decoder attention” layer
- K & V helps decoder focus on appropriate words.





# THE DECODER SIDE

The following steps repeat the process until a special symbol is reached indicating the transformer decoder has completed its output



## THE DECODER SIDE

The self attention layers is only allowed to focus on earlier positions in the output sequence.

- This is done by masking future positions (setting them to  $-\infty$ ) before the SoftMax step in the self-attention calculation.

The “Encoder-Decoder Attention” layer is like multiheaded self-attention

- except it creates its Queries matrix from the layer below it,
- takes the Keys and Values matrix from the output of the encoder stack.

# FINAL LINEAR AND SOFTMAX LAYER

## Final Linear Layer:

- fully connected connected neural network that projects the vector produced by the decoders into a logits vector.

Assume our model was trained on a 1000-word vocabulary

- Then logit vector has dimension 1000 cells
- Each cell the score of a unique word
- The SoftMax layers turns these scores into probabilities and the word with the highest probability is chosen.


Which word in our vocabulary  
is associated with this index?

Get the index of the cell  
with the highest value  
(argmax)

am

5

log\_probs



Softmax

logits




Linear

Decoder stack output




# OVERVIEW OF MOST PROMINENT TRANSFORMERS




# OVERVIEW OF BERT

Dual training of Masked language model and next sentence prediction.  
Masked language model




# OVERVIEW OF BERT – NEXT SENTENCE PREDICTION




# TRANSFER LEARNING

Transferring the knowledge of one model to perform a new task.



# TRANSFER LEARNING





# TRANSFER LEARNING

## Different types of transfer learning

Type	Description	Examples
Inductive	Adapt existing <b>supervised</b> training model on new <b>labeled</b> dataset	Classification, Regression
Transductive	Adapt existing <b>supervised</b> training model on new <b>unlabeled</b> dataset	Classification, Regression
Unsupervised	Adapt existing <b>unsupervised</b> training model on new <b>unlabeled</b> dataset	Clustering, Dimensionality Reduction

## USEFUL LINKS

- Attention is all you need <https://arxiv.org/abs/1706.03762>
- BERT <https://arxiv.org/pdf/1810.04805.pdf>
- Transfer learning <https://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.147.9185&rep=rep1&type=pdf>
- Hugging face
  - <https://huggingface.co/transformers/index.html>
  - <https://github.com/huggingface/transformers>
  - <https://huggingface.co/docs/transformers/training>
  - <https://neptune.ai/blog/hugging-face-pre-trained-models-find-the-best>