

AE333

Mechanics of Materials

Lecture 10 - Torsion

Dr. Nicholas Smith

Wichita State University, Department of Aerospace Engineering

February 18, 2019

schedule

- 18 Feb - Torsion, HW3
Due
- 20 Feb - Torsion
- 22 Feb - Bending
- 25 Feb - Bending, HW4
Due

outline


- force method
- thermal stress
- torsion
- power
transmission

force method

force method

- One way to solve statically indeterminate problems is using the principle of superposition
- We choose one redundant support and remove it
- We then add it back as a force separately (without the other forces in the problem)

force method




force method

- We connect the two problems by requiring that the displacement in both frames adds to 0 to meet the support requirements
- This is referred to as the equation of compatibility

procedure

- Choose one support as redundant, write the equation of compatibility
- Express the external load and redundant displacements in terms of load-displacement relationship
- Draw free body diagrams and use the equations of equilibrium to solve

example 4.9



The steel rod shown has a diameter of 10 mm. Determine the reactions at A and B'.

thermal stress

thermal stress


- A change in temperature causes a material to either expand or contract
- For most materials this is linear and can be described using the coefficient of linear expansion

$$\delta_T = \alpha \Delta T L$$

thermal stress

- When a body is free to expand, the deformation can be readily calculated using
- If it is not free to expand, however, thermal stresses develop
- We can use the force method described previously to find the thermal stresses developed

example 4.12




An aluminum tube with cross-section of 600 mm^2 is used as a sleeve for a steel bolt with cross-sectional area of 400 mm^2 . When $T=15$ degrees Celsius there is negligible force and a snug fit, find the force in the bolt and sleeve when $T=80$ degrees Celsius.

torsion

torsion

- Torque is a moment that tends to twist a member about its axis
- For small deformation problems, we assume that the length and radius do not change significantly under torsion
- The primary deformation we are concerned with in torsion is the angle of twist, denoted with ϕ

shear



torsion formula

- For a linearly elastic material, Hooke's Law in shear will hold ($\tau = G\gamma$)
- This means that, like shear strain, shear stress will vary linearly along the radius

torsion formula

- We can find the total force on an element, dA by multiplying the shear stress by the area

$$dF = \tau dA$$

- The torque ($dT = \rho dF$) produced by this force is then

$$dT = \rho(\tau dA)$$

torsion formula

- Integrating over the whole cross-section gives

$$T = \int_A \rho(\tau dA) = \frac{\tau_{max}}{c} \int_A \rho^2 dA$$

- The integral $\int_A \rho^2 dA$ is also called the Polar Moment of Inertia, J , so we can write

$$\tau_{max} = \frac{Tc}{J}$$

polar moment of inertia


- We know that $J = \int_A \rho^2 dA$, so we can compute this for some common shapes
- For a solid circular cross-section, we have

$$J = \int_0^c \rho^2 (2\pi\rho d\rho) = \frac{\pi}{2} c^4$$

- For a circular tube we have

$$J = \int_{c_1}^{c_2} \rho^2 (2\pi\rho d\rho) = \frac{\pi}{2} (c_2^4 - c_1^4)$$

example 5.1



The allowable shear stress is 75 MPa. Determine the maximum torque that can be applied to each of the cross-sections shown and find the stress acting on a small element at A, B and C.

power transmission

power transmission

- Shafts and tubes are often connected to belts and drives, and the torque, speed, and power are all related
- Power is the rate of work done, for rotation problems, $P = T\omega$
- We are often given the frequency f instead of the angular velocity, ω , in this case $P = 2\pi fT$

power units

- In SI Units, power is expressed in Watts $1 \text{ W} = 1 \text{ N m} / \text{sec}$
- In Freedom Units, power is expressed in Horsepower $1 \text{ hp} = 555 \text{ ft lb} / \text{sec}$

shaft design


- We often know the power and frequency of a drive, and need to design a shaft such that the shear stress is acceptable
- We can easily find the torque as $T = P/2\pi f$, we can use this combined with the torsion equation

$$\tau_{max} = \frac{Tc}{J}$$

to find the appropriate shaft diameter.

- For solid shafts we can solve for c uniquely, but not for hollow shafts

example 5.4



The steel shaft shown is connected to a 5 hp motor that rotates at $\omega = 175$ rpm. If $\tau_{allow} = 14.5$ ksi, determine the required shaft diameter.