AE333

Mechanics of Materials

Lecture 28 - Superposition

Dr. Nicholas Smith
Wichita State University, Department of Aerospace Engineering

12 Apr, 2019

schedule

- 12 Apr - Superposition
- 15 Apr - Deflection of Beams, HW 9 Due
- 17 Apr - Deflection of Beams
- 19 Apr - Deflection of Beams
- 22 Apr - Exam 3 Review, HW 10 Due
- 24 Apr - Exam 3

outline

- discontinuity functions
- group problems
- superposition

discontinuity functions

discontinuity functions

- Direct integration can be very cumbersome if multiple loads or boundary conditions are applied
- Instead of using a piecewise function, we can use discontinuity functions

Macaulay functions

- Macaulay functions can be used to describe various loading conditions, the general definition is

$$\langle x-a \rangle^n = \begin{cases} 0 & \text{for} x < a \\ (x-a)^2 & \text{for} x \geq a \end{cases}$$

singularity functions

- Singularity functions are used for concentrated forces and can be written

$$w = P\langle x-a\rangle^{-1} = \begin{cases} 0 & \text{for} x \neq a \\ P & \text{for} x = a \end{cases}$$

discontinuity functions

TABLE 12–2

Loading	Loading Function $w = w(x)$	Shear $V = \int w(x)dx$	Moment $M = \int V dx$
	$w = M_0\langle x-a\rangle^{-2}$	$V = M_0\langle x-a\rangle^{-1}$	$M = M_0\langle x-a\rangle^{0}$
	$w = P\langle x-a\rangle^{-1}$	$V = P\langle x-a\rangle^{0}$	$M = P\langle x-a\rangle^{1}$
	$w = w_0\langle x-a\rangle^{0}$	$V = w_0\langle x-a\rangle^{1}$	$M = \frac{w_0}{2}\langle x-a\rangle^{2}$
	$w = m\langle x-a\rangle^{1}$	$V = \frac{m}{2}\langle x-a\rangle^{2}$	$M = \frac{m}{6}\langle x-a\rangle^{3}$

example 12.5



group problems

group one



Find the maximum deflection using either direct integration or discontinuity functions.

group two



Find the maximum deflection using either direct integration or discontinuity functions.

group three



Find the maximum deflection using either direct integration or discontinuity functions.

superposition

superposition

- The differential equation $EId^4v/dx^4 = w(x)$ satisfies the requirements for superposition
- $w(x)$ is linearly related to $v(x)$
- Load does not significantly change the shape of the beam

superposition

- This means we can superpose multiple deflection solutions from simpler cases
- Appendix C in the text has many solutions that can be superposed

example 12.13



Use superposition to find the displacement at C and the slope at A

example 12.15



Use superposition to find the displacement at C

example 12.16



The steel bar is supported by springs with k=15 kip/ft originally unstretched. For the force shown, determine the displacement at C. Take $E_{st} = 29$ Msi and $I = 12$ in^4.