AE 737: Mechanics of Damage Tolerance

Lecture 3 - Superposition, Compounding

Dr. Nicholas Smith

Wichita State University, Department of Aerospace Engineering

25 January 2022

schedule

- 25 Jan - Superposition, Compounding
- 27 Jan - Curved Boundaries, HW 1 Due
- 1 Feb - Plastic Zone
- 3 Feb - Plastic Zone, HW 2 Due, HW 1 Self-grade due

homework notes

- Watch units (beam problem, foot-lbs vs. in-lbs)
- Significant figures
- My grading philosophy
- Individual work

outline

- Review
- Superposition
- Compounding

superposition

superposition

- Since the stress intensity factor is derived using Linear Elasticity, the principle of superposition applies
- Multiple applied loads can be superposed to find the effective stress intensity factor of the combined loading

superposition



superposition

$$K_I = K_{I(\sigma)} + K_{I(P)}$$

$$K_I = \sigma\sqrt{\pi a} + \frac{P}{t\sqrt{\pi a}} \frac{1 - 0.5\left(\frac{a}{W}\right) + 0.975\left(\frac{a}{W}\right)^2 - 0.16\left(\frac{a}{W}\right)^3}{\sqrt{1 - \left(\frac{a}{W}\right)}}$$

superposition

- Sometimes, the superposition needed to solve a problem is not obvious
- It can be helpful to subtract a known solution from the problem
- Note: Every super-posed solution must satisfy equilibrium.

superposition



example - pressurized crack



example - pressurized crack

- We can find the stress intensity for a pressurized crack using a non-obvious superposition
- An un-cracked panel with remote stress would be equal to a cracked panel under remote stress with a negative pressure applied to the crack

example - pressurized crack



group problems

group problems

- Purpose of group problems is not just to solve a problem
- By teaching or explaining concepts to other members of your group, you also reinforce the concept yourself
- When problems are discussed as a group, you will find questions and problems you might not have otherwise found

group 1



Figure 1: Semi-elliptical surface flaw in a pressurized cylinder

group 2



group 3





compounding

superposition vs. compounding

- In this course, we use *superposition* to combine loading conditions
- We use *compounding* to combine edge effects
- Both are very powerful tools and important concepts

compounding

- Different types of boundaries create different correction factors to the usual stress intensity factor
- We often use β to indicate the total correction factor
- When multiple boundaries are present, we can combine them into one effective correction factor
- There are two general methods we use to create a compound correction factor

method 1

- The first method uses linear superposition, and thus is restricted to cases where the effect of each boundary can be assumed to add linearly
- While in most cases this is not strictly true, it provides a reasonable approximation

$$K_r = \bar{K} + \sum_{i=1}^{N}(K_i - \bar{K})$$

method 1

- Where N is the number of boundaries, $\bar{K}$ is the stress intensity factor with no boundaries present and K_i is the stress intensity factor associated with the i^{th} boundary.

method 1

- We can rewrite this equation as

$$K_r = \sigma\sqrt{\pi a}\beta_r = \sigma\sqrt{\pi a} + \sum_{i=1}^{N}(\sigma\sqrt{\pi a}\beta_i - \sigma\sqrt{\pi a})$$

- Which leads to an expression for β_r as

$$\beta_r = 1 + \sum_{i=1}^{N}(\beta_i - 1)$$

method 2

- An alternative empirical method approximates the boundary effect as

$$\beta_r = \beta_1\beta_2...\beta_N$$

- If there is no interaction between the boundaries, method 1 and method 2 will give the same result

p. 68 - example 1

- A crack in a finite-width panel is centered between two stiffeners
- Assume the β correction factor for this stiffener configuration is $\beta_s = 0.9$
- Assume the β correction factor for this finite-width panel is $\beta_w = 1.075$
- Use both compounding methods to estimate the stress intensity
- How accurate do you expect this to be?

p. 69 - example 3



$b = 1$ inch

group 1



$b = 0.4$ inches

group 2



$b = 0.4$ inches
Hole diameter is 0.5 inches and spaced 0.5 inches away from the crack tip

group 3



Hole diameter is 0.5 inches and spaced 0.5 inches away from the crack tip

group 4



The right crack tip is 0.5 inches away from a 0.5 inch diameter hole and the left crack tip is 0.25 inches away from a 1 inch diameter hole.

errata and supplemental charts

textbook notes

- on p. 64 there is a + missing between two terms, see Lecture 2 for the fix
- Also on p. 64, in equation 29 it is not clear, but use the f_w from a previous equation, on p. 56
- Some of the black and white figures can be difficult to use, we have scanned and re-created the plots online
- Interactive versions of compounding figures from p. 50, 71-73 can be found at here[1]

[1] http://ndaman.github.io/damagetolerance/examples/Compounding%20Figures.html

finite height - p. 50



Figure 2: beta for finite height effects, see text p. 50 or interactive chart linked in previous slide

offset crack - p. 71



Figure 3: beta for offset internal crack, see text p. 71 or interactive chart linked previously

crack near hole - p. 72



Figure 4: beta for the crack tip farther away from a hole, see text p. 72 or interactive chart linked previously

crack near hole - p. 73



Figure 5: beta for the crack tip closer to a hole, see text p. 73 or interactive chart linked previously