AE731

Theory of Elasticity

Dr. Nicholas Smith

Wichita State University, Department of Aerospace Engineering
September 2, 2021

upcoming schedule

- Sep 2 - Strain Transformation
- Sep 3 - Homework 2 Due, Homework 1 Self-Grade Due
- Sep 7 - Exam 1 Review
- Sep 9 - Exam 1

outline

- example
- group problems
- principal strains
- special strain definitions
- strain transformation

example

example

- Calculate the deformation gradient, strain tensor, and rotation tensor for the given deformation

$$\left\{u_1 \ u_2 \ u_3\right\} = \left\{xy^2z \ xz \ z^3\right\}$$

example

- Deformation gradient:

$$F = u_{i,j} = \begin{bmatrix} y^2z & 2xyz & xy^2 \\ z & 0 & x \\ 0 & 0 & 3z^2 \end{bmatrix}$$

example

- Strain tensor

$$e_{ij} = \frac{1}{2}(u_{i,j} + u_{j,i})$$

$$e_{ij} = \begin{bmatrix} y^2z & xyz + \frac{1}{2}z & \frac{1}{2}xy^2 \\ xyz + \frac{1}{2}z & 0 & \frac{1}{2}x \\ \frac{1}{2}xy^2 & \frac{1}{2}x & 3z^2 \end{bmatrix}$$

example

- Rotation tensor

$$\omega_{ij} = \frac{1}{2}(u_{i,j} - u_{j,i})$$

$$\omega_{ij} = \begin{bmatrix} 0 & xyz - \frac{1}{2}z & \frac{1}{2}xy^2 \\ -xyz + \frac{1}{2}z & 0 & \frac{1}{2}x \\ -\frac{1}{2}xy^2 & -\frac{1}{2}x & 0 \end{bmatrix}$$

example

- As we did with the deformation gradient, we can integrate the strain tensor to find the deformation (symmetric portion)

$$e_{ij} = \begin{bmatrix} yz & xz & xy \\ xz & 2y & \frac{1}{2}x^2 \\ xy & \frac{1}{2}x^2 & 3z^2 \end{bmatrix}$$

example

- We start by integrating the diagonal terms
- $u = \int yzdx = xyz + f(y,z)$
- $v = \int 2ydy = y^2 + g(y,z)$
- $w = \int 3z^2dz = z^3 + h(x,y)$

example

- Next we need to find the shear terms

$$e_{xy} = \frac{1}{2}(u_{,y} + v_{,x})$$
$$xz = \frac{1}{2}(xz + f_{,y} + g_{,x})$$

$$e_{xz} = \frac{1}{2}(u_{,z} + w_{,x})$$
$$xy = \frac{1}{2}(xy + f_{,z} + h_{,x})$$

$$e_{yz} = \frac{1}{2}(v_{,z} + w_{,y})$$
$$\frac{1}{2}x^2 = \frac{1}{2}(g_{,z} + h_{,y})$$

example

- Note that we cannot uniquely solve this (any arbitrary rotation ω can be added and will still produce a valid strain)
- Let $f(y, z) = 0$

$$
\begin{aligned}
g_{,x} &= xz \\
g(x, z) &= \frac{1}{2}x^2 z
\end{aligned}
$$

$$
\begin{aligned}
h_{,x} &= xy \\
h(x, z) &= \frac{1}{2}x^2 y
\end{aligned}
$$

example

$$
\begin{aligned}
\frac{1}{2}x^2 &= \frac{1}{2}\left(g_{,z} + h_{,y}\right) \\
\frac{1}{2}x^2 &= \frac{1}{2}\left(\frac{1}{2}x^2 + \frac{1}{2}x^2\right)
\end{aligned}
$$

$$
\begin{aligned}
u &= xyz \\
v &= y^2 + \frac{1}{2}x^2 z \\
w &= z^3 + \frac{1}{2}x^2 y
\end{aligned}
$$

group problems

group 1

- Sketch the deformed and undeformed shape of a rectangle under the following deformation

$$u = 0.7x + 0.1y$$
$$v = 0.3x + 1.2y$$

group 2

- For the following deformation, find the deformation gradient, strain, and rotation

$$u = xyz$$
$$v = xy + z$$
$$z = y^2 z$$

group 3

- From the following strain field, find the displacements (you may assume no rotations)

$$\epsilon_{ij} = \begin{bmatrix} y & x+y \\ x+y & x \end{bmatrix}$$

principal strains

principal strains

- Principal strains are found in exactly the same way as principal values discussed in Chapter 1

$$\det[e_{ij} - e\delta_{ij}] = 0$$

- Invariants can also be found in the same fashion as in any other tensor

$$\vartheta_1 = e_1 + e_2 + e_3$$
$$\vartheta_2 = e_1 e_2 + e_2 e_3 + e_3 e_1$$
$$\vartheta_3 = e_1 e_2 e_3$$

principal strains

- Principal strains and invariants have some important physical meanings
- ϑ_1 is called the *cubical dilation*, and is related to the change in volume of the material
- Note that in the principal direction, there are no shear strains

$$\begin{bmatrix} e_1 & 0 & 0 \\ 0 & e_2 & 0 \\ 0 & 0 & e_3 \end{bmatrix}$$

- This means that there is only extensional strain in the principal direction (i.e. a cube will remain a rectangular prism, the corners will maintain 90° angles)

volume change

- Consider a rectangular prism with edges oriented in the principal directions



volume change

- The volume before deformation is $L = LWH$
- The volume after deformation is given by $V' = L'W'H'$
- We can relate the side lengths after deformation to strains

$$e_1 = \frac{L' - L}{L}$$

$$Le_1 + L = L'$$

- We can now write the volume as $V' = L(1 + e_1)W(1 + e_2)H(1 + e_3)$

volume change

- After multiplication, the deformed volume is given as
- $V' = LWH(1 + e_1 + e_2 + e_3 + e_1e_2 + e_2e_3 + e_1e_3 + e_1e_2e_3)$
- For small strains, $e_i << 1$, therefore e_1, e_2, and e_3 will be much larger than $e_1e_2 + e_2e_3 + e_1e_3 + e_1e_2e_3)$
- $V' = LWH(1 + e_1 + e_2 + e_3)$

volume change

- A "dilatation" is defined as the change in volume divided by the original volume

$$\frac{\Delta V}{V} = \frac{V' - V}{V}$$

- Substituting the relationships found earlier

$$\frac{V' - V}{V} = \frac{LWH(1 + e_1 + e_2 + e_3) - LWH}{LWH}$$

- Which simplifies to

$$e_1 + e_2 + e_3 = \vartheta_1$$

special strain definitions

- This dilatation can be used to find the so-called *spherical strain*

$$\tilde{e}_{ij} = \frac{1}{3} e_{kk} \delta_{ij} = \frac{1}{3} \vartheta_1 \delta_{ij}$$

- The *deviatoric strain* is found by subtracting the spherical strain from the strain tensor

$$\hat{e}_{ij} = e_{ij} - \frac{1}{3} e_{kk} \delta_{ij}$$

strain transformation

strain transformation

- The usual tensor transformation applies to the strain tensor as well
- $e'_{ij} = Q_{im} Q_{jn} e_{mn}$
- In many instances, however, we are only concerned with the strain within a plane (for example, when using strain gages).

strain transformation

- For an in-plane rotation (rotation about z-axis), we find

$$Q_{ij} = \begin{bmatrix} \cos\theta & \cos(90-\theta) & \cos 90 \\ \cos(90+\theta) & \cos\theta & \cos 90 \\ \cos 90 & \cos 90 & \cos 0 \end{bmatrix} = \begin{bmatrix} \cos\theta & \sin\theta & 0 \\ -\sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

strain transformation

- If we multiply this out, for the in-plane strain terms (e'_x, e'_y, and e'_{xy}) we find

$$
\begin{aligned}
e'_x &= e_x \cos^2\theta + e_y \sin^2\theta + 2e_{xy}\sin\theta\cos\theta \\
e'_y &= e_x \sin^2\theta + e_y \cos^2\theta - 2e_{xy}\sin\theta\cos\theta \\
e'_{xy} &= -e_x \sin\theta\cos\theta + e_y \sin\theta\cos\theta + e_{xy}(\cos^2\theta - \sin^2\theta)
\end{aligned}
$$

strain transformation

- This is often re-written using the double-angle formulas

$$
\begin{aligned}
e'_x &= \frac{e_x + e_y}{2} + \frac{e_x - e_y}{2}\cos 2\theta + e_{xy}\sin 2\theta \\
e'_y &= \frac{e_x + e_y}{2} - \frac{e_x - e_y}{2}\cos 2\theta - e_{xy}\sin 2\theta \\
e'_{xy} &= \frac{e_y - e_x}{2}\sin 2\theta + e_{xy}\cos 2\theta
\end{aligned}
$$

strain transformation

- Many times it is easy to measure the axial strain directly with strain gages, but the shear strain cannot be easily measured
- We can use an extra, off-axis strain gage, together with the strain transformation equations, to calculate the shear strain
- Many companies already do this with "rosettes" which have strain gages at specified angles built-in

example



example

- Given that $\epsilon_a = 0.005$, $\epsilon_b = -0.002$, and $\epsilon_c = 0.003$, find e_x, e_y and e_{xy}.
- Note that $e_y = \epsilon_b = -0.002$
- Set coordinate system so that $\epsilon_b = e'_x$
- Use equation for e'_x with $\theta = 30$.

$$e'_x = \frac{e_x + e_y}{2} + \frac{e_x - e_y}{2} \cos 60 + e_{xy} \sin 60$$

example

- We have two unknowns in this equation, so we need another
- We can use the equation for e'_y with $\theta = 60$ so that $\epsilon_b = e'_x$

$$e'_y = \frac{e_x + e_y}{2} - \frac{e_x - e_y}{2} \cos 120 - e_{xy} \sin 120$$

example

- Substituting known values and simplifying:

$$0.01 + 0.002 - 0.002\cos 60 = e_x(1 + \cos 60) + e_{xy}\sin 60$$
$$0.006 + 0.002 + 0.002\cos 120 = e_x(1 - \cos 120) - e_{xy}\sin 120$$

- And solving we find $e_x = 0.006$, $e_y = -0.002$, and $e_{xy} = 0.00231$