

Lecture 15 - Combined Loading

Dr. Nicholas Smith

Wichita State University, Department of Aerospace Engineering

5 April, 2021

1

schedule

- 5 April - Combined Loading, HW 6 Self-Grade Due
- 7 April - Stress Transformation
- 12 April - Stress Transformation, HW 7 Due
- 14 April - Strain Transformation

2

- pressure vessels
- combined loading
- group problems


pressure vessels

thin-walled pressure vessels

- If the radius to wall thickness ratio is 10 or more, we can treat a pressure vessel as “thin-walled”
- Cylindrical pressure vessels will have two primary sources of stress, and serve as an introduction to more general states of combined loading

4

cylindrical vessels




5

- From equilibrium of a section of a cylindrical vessel, we see that

$$\begin{aligned}\sum F_x &= 0 \\ &= 2(\sigma_1 t dy) - p(2r)dy \\ \sigma_1 &= \frac{pr}{t}\end{aligned}$$

6



7

- Considering another section we can find the longitudinal stress

$$\begin{aligned}\sum F_y &= 0 \\ &= \sigma_2(2\pi rt) - p(\pi r^2) \\ \sigma_2 &= \frac{pr}{2t}\end{aligned}$$

spherical vessels

- We can find the stress in spherical vessels using an identical section to the longitudinal section for a cylindrical vessel, and we find that

$$\sigma = \frac{pr}{2t}$$

- Which is valid everywhere in a cylindrical vessel

example 8.1

- A cylindrical pressure vessel has an inner diameter of 4 ft and a thickness of $1/2$ in.
- Determine the maximum internal pressure it can sustain if the maximum stress it can support is 20 ksi.
- What is the maximum internal pressure a spherical pressure vessel could sustain under identical conditions?

10

combined loading

- We can use the principle of superposition to treat various loading conditions separately and then add them together to find the total stress

11

procedure


- Section the member at the point of interest, internal force components should be drawn acting through the centroid of the section
- Moment components should be calculated about the centroidal axis

12

- Normal stress: $\sigma = N/A$
- Torsion: $\tau = \frac{T\rho}{J}$
- Bending: $\sigma = \frac{-My}{I}$
- Transverse Shear: $\tau = \frac{VQ}{It}$
- Pressure Vessels: $\sigma_1 = \frac{pr}{t}$, $\sigma_2 = \frac{pr}{2t}$

13


example 8.2



Neglect the weight of the member and find the stress at B and C.

14


example 8.4



Determine the stress at C and D.

15

example 8.5




The rod shown has a radius of 0.75 in. Find the stress at A.

16


group problems

group one



Find the stress at the corners A and B for the column shown.


group two



Find the stress at point A for the cantilever beam shown.

18

group three



Find the load P that will cause a maximum normal stress of $\sigma = 30$ ksi along the section a-a.

19