Mechanics of Materials

Lecture 20 - Superposition

Dr. Nicholas Smith

Wichita State University, Department of Aerospace Engineering

15 November, 2021

1

schedule

- 15 Nov Beam Deflection (superposition)
- 17 Nov Exam 3 Review
- 19 Nov HW 9 Due, HW 8 Self-grade Due
- 22 Nov Exam 3
- (24 Nov) No Class Thanksgiving Break
- 29 Nov Buckling, Stress Concentration
- 1 Dec Final Exam Review
- 3 Dec Project 3 Due, HW 10 & HW 9 Self-grade Due
- 6 Dec Final Exam 11:00 12:50

outline

- superposition
- statically indeterminate

superposition

superposition


- The differential equation $EI\frac{d^4v}{dx^4} = w(x)$ satisfies the requirements for superposition
- w(x) is linearly related to v(x)
- Load does not significantly change the shape of the beam

4

superposition

- This means we can superpose multiple deflection solutions from simpler cases
- Appendix C in the text has many solutions that can be superposed


example 12.13



Use superposition to find the displacement at ${\sf C}$ and the slope at ${\sf A}$


О

example 12.15



Use superposition to find the displacement at C

7



The steel bar is supported by springs with k=15 kip/ft originally unstretched. For the force shown, determine the displacement at C. Take $E_{st}=29$ Msi and I=12 in⁴.

statically indeterminate beams

8

statically indeterminate


- If we have redundant supports, we can have some difficulty finding the displacement
- There are several approaches to solve these problems, we will consider direct integration and superposition

9

integration


- We can take the extra unknowns and include them in our formulation for M(x)
- They will be solved for with the extra boundary conditions applied

example 12.17



11

example 12.18




indeterminate beams superposition

superposition

- To use superposition for finding deflection of statically indeterminate beams, we must first identify redundant reactions
- We initially remove these, then superpose them back such that the deflection at that point is 0
- The choice of which reaction(s) is redundant is arbitrary, we can choose whatever we are most comfortable with
- We use Appendix C to find deflection and slope


superposition




We can consider any reaction to be redundant.

14

higher order indeterminacy



We need to treat each reaction separately to match Appendix C.




Determine the moment at B.

16

group problems


group one



Determine the reactions at A and B (EI is constant).


17

group two



Determine the reactions at A and B (El is constant).

group three



Determine the reactions at A and B. The support at B settles 2 mm. E=200 GPa, I=65.0(10-6)m 4.