THE UNIVERSITY OF ZAMBIA

SCHOOL OF NATURAL AND APPLIED SCIENCES

DEPARTMENT OF COMPUTING AND INFORMATICS

Fraud-Resistant Meal Voucher Redemption and Real-Time Operational Analytics for Conference Management: Design and Evaluation of ConferenceCheck Mobile

A final year project report submitted in partial fulfilment of the requirements for the award of the degree of [DEGREE PROGRAMME: to be completed by the student]

Ndashi Bwalya Chisanga

Computer number: 2021470105

Supervisor: Mr. Mofya Phiri

October 2026

Repository: https://github.com/ndashi-chisanga6/ConferenceCheck-Mobile-Analytics-Meals-and-Notifications

Declaration

I declare that this report is my own work. It has not been submitted, in whole or in part, for any other award at this or any other institution, and every source I have drawn on is acknowledged in the reference list.

The use of artificial intelligence tools during this project is disclosed in **Appendix A**, which records what each category of tool was used for, what was provided to it, and the limits placed on its use by Section 9 of the project proposal. All evaluation data in this study is seeded and synthetic: attendees, meal vouchers and sessions in the simulated-event exercise are generated by `tools/seed-evaluation-event.php` and describe no real conference or real person. No respondent or attendee data belonging to any third party was uploaded to any external tool at any point.

Signed: ..... Date: .....

Approval

This report by Ndashi Bwalya Chisanga, computer number 2021470105, is approved as fulfilling the requirements of the Final Year Project in the Department of Computing and Informatics, School of Natural and Applied Sciences, University of Zambia.

Supervisor: Mr. Mofya Phiri

Signature: ..... Date: .....

Examiner: .....

Signature: ..... Date: .....

Abstract

Conference meal service is still often run on paper vouchers, which can be photographed, copied or presented twice. This report presents ConferenceCheck Mobile: Analytics, Meals and Notifications, component 4.3b of a two-part conference application whose sibling, 4.3a, handles check-in. It contributes a QR meal voucher protocol in which single use is enforced by the database, through a row lock and a unique constraint on the redemption record; an analytics dashboard refreshed every 30 seconds; session attendance with capacity alerts; and push notifications backed by an in-app inbox. The system is a Flutter app and a standalone Laravel API on PostgreSQL. It was evaluated on a seeded 500-attendee event driven through the live API. All 100 sequential re-scans of a redeemed voucher were refused. In a concurrency experiment behind five server processes, every one of 50 five-way races gave exactly one redemption whenever the lock or the constraint was in place, while a plain check-then-insert redeemed 48 of 50 vouchers more than once. Median scan latency was 145.3 ms over loopback. Twenty injected check-ins all reached the dashboard within 30 s in the recorded run, though the design does not guarantee it. All four CSV exports matched direct SQL. In the app, one end-to-end trial on an emulator showed a voucher accepted once and refused on its second presentation. Capacity alerts were shown but not timed, push delivery across many devices was not measured, and the manual baseline was not run. The results show that a database lock or constraint, and not an application check, is what prevents double redemption under parallel load.

Keywords: meal voucher, QR code, double redemption, concurrency control, conference management, Flutter, Laravel

Acknowledgements

I thank my supervisor, Mr. Mofya Phiri, for reviews that reran the experiments and checked every claim against the repository rather than taking it on trust; the report is better for each round of them. I thank the Department of Computing and Informatics for the project framework, and the student working on component 4.3a for agreeing the API contract this component was built against. Finally, I thank my family and friends for their support throughout the year.

Table of Contents

Section	Title	Page
	Declaration	2
	Approval	3
	Abstract	4
	Acknowledgements	5
	List of Tables	9
	List of Figures	10
	List of Abbreviations	11
Chapter 1	**Introduction**	12
1.1	Background	12
1.2	Problem Statement	12
1.3	Aim	13
1.4	Objectives	13
1.5	Scope	13
1.6	Significance of the Study	14
1.7	Contributions	14
1.8	Conventions Used in This Report	15
1.9	Organisation of the Report	15
1.10	Chapter Summary	15
Chapter 2	**Literature Review**	16
2.1	QR Codes and Opaque Tokens	16
2.2	QR-Based Attendance and Its Anti-Fraud Weaknesses	16
2.3	Idempotence and Concurrency Control	17
2.4	Dashboards and Response Time	18
2.5	Push Notification Delivery and API Security	18
2.6	Comparative Analysis of Related Work	19
2.7	Chapter Summary	20
Chapter 3	**Methodology**	21
3.1	Development Approach	21
3.2	Evaluation Design	21
3.3	Seeded Evaluation Dataset	21
3.4	Guarding Against an Artificially Easy Measurement	22
3.5	Metrics and Acceptance Criteria	23
3.6	Tools and Technologies	23
3.7	Ethical Considerations and AI Usage Disclosure	23
3.8	Chapter Summary	24

Section	Title	Page
Chapter 4	**System Analysis and Design**	25
4.1	Stakeholders	25
4.2	Functional Requirements	25
4.3	Non-Functional Requirements	26
4.4	Use Cases	27
4.5	System Architecture	27
4.6	Data Design and Entity-Relationship Diagram	29
4.7	The Voucher Redemption Protocol	30
4.8	Session Attendance and Capacity Alerting	31
4.9	Offline Operation	31
4.10	Analytics, Notifications and Reporting	32
4.11	Interface Design	33
4.12	Chapter Summary	33
Chapter 5	**Implementation**	34
5.1	Development Environment	34
5.2	Code Organisation and Modules	34
5.3	Key Implementation Details	36
5.3.1	Meal voucher redemption	36
5.3.2	Offline replay	36
5.3.3	Notification dispatch	37
5.3.4	Access control and exports	37
5.4	Challenges and Solutions	37
5.5	Chapter Summary	38
Chapter 6	**Testing, Results and Evaluation**	40
6.1	Testing Strategy	40
6.2	Test Cases	40
6.3	Automated Correctness Verification	43
6.4	Results Against the Acceptance Criteria	45
6.4.1	Meal Voucher Redemption Correctness	46
6.4.2	Session Attendance and Capacity Correctness	47
6.4.3	Latency Against the Proposal's Targets	48
6.4.4	Analytics Dashboard Freshness	48
6.4.5	Export Correctness	49
6.4.6	Notification Delivery	49
6.4.7	Baseline Comparison, and Its Limits	50
6.5	Discussion	50
6.6	Limitations	52
6.7	Evaluation Against the Objectives	53

Section	Title	Page
6.8	Chapter Summary	54
Chapter 7	**Conclusion and Recommendations**	55
7.1	Conclusion	55
7.2	Recommendations	55
7.3	Future Work	55
	References	57
A	**Appendix A. Artificial intelligence usage disclosure**	59
A.1	Use	59
A.2	Representative prompts	59
A.3	Checks and gaps	59
B	**Appendix B. Defects found and fixed during the strict review**	60
C	**Appendix C. Full evaluation figures**	62
D	**Appendix D. Reproduction commands**	66
E	**Appendix E. The running system, against each objective**	69
E.1	What these figures do and do not show	78
F	**Appendix F. Reference verification record**	80

List of Tables

Table	Title	Section	Page
2.1	Comparison of the closest related work with this project	2.6	19
4.1	Stakeholders and what each needs from the system	4.1	25
4.2	Functional requirements	4.2	25
4.3	Non-functional requirements, with the target each is held to	4.3	26
4.4	Use cases	4.4	27
4.5	Core relations and the integrity constraints underpinning system guarantees	4.6	30
4.6	Screens by role	4.11	33
5.1	Development environment	5.1	34
5.2	Challenges met during implementation and how each was solved	5.4	38
6.1	Test cases	6.2	40
6.2	Adversarial and live checks, strict review (`docs/STRICT-REVIEW.md`)	6.3	44
6.3	Status of each acceptance criterion in the proposal's Table 3	6.4	45
6.4	Concurrent redemption on PostgreSQL behind five server processes, 50 races of five simultaneous scans per configuration	6.4.1	46
6.5	Latency by endpoint against the proposal's targets	6.4.3	48
6.6	Export correctness, each CSV export against SQL run directly on the database	6.4.5	49
6.7	Status of each objective	6.7	53
B1	Defects found during review and their fixes	B	60
C1	Full evaluation output	C	62
F1	Verification of every reference, including the one withdrawn	F	80

List of Figures

Figure	Title	Section	Page
4.1	System architecture and the component 4.3a / 4.3b boundary	4.5	27
4.2	Entity-relationship diagram of the conference schema	4.6	29
E1	Organiser analytics dashboard	E	69
E2	Trends and per-category redemption	E	70
E3	Automatic capacity alerts on a device	E	71
E4	Organiser broadcast delivered end to end	E	72
E5	Attendee check-in and session pass (not a meal voucher)	E	73
E6	The attendee's meal vouchers in the app	E	74
E7	Meal categories and the per-device redemption trail	E	75
E8	Scanner accepting the voucher from Figure E6	E	76
E9	The same voucher refused on a second attempt	E	77
E10	Report exports available to an organiser	E	78

List of Abbreviations

Abbreviation	Meaning
API	Application Programming Interface
CI	Continuous Integration
CSV	Comma-Separated Values
ER	Entity-Relationship
FCM	Firebase Cloud Messaging
FIFO	First In, First Out
HTTP(S)	Hypertext Transfer Protocol (Secure)
IMEI	International Mobile Equipment Identity
JSON	JavaScript Object Notation
MASVS	Mobile Application Security Verification Standard
MVC	Model-View-Controller
OWASP	Open Worldwide Application Security Project
p95	95th percentile
QR	Quick Response (code)
REST	Representational State Transfer
SQL	Structured Query Language
UNZA	University of Zambia

Chapter 1: Introduction

1.1 Background

Modern conferences concentrate hundreds of attendees, multiple parallel sessions and time-boxed catering windows into a short operational period. The quality of the attendee experience depends on how efficiently organisers can verify entitlement, observe live operational state, and communicate changes as they happen. Traditional approaches rely on fragmented, largely manual tools: printed meal tickets, paper attendance registers and public-address announcements. These methods have three structural weaknesses. Paper vouchers are trivially duplicated or reused, and manual meal lines create congestion at service points. Organisers have no consolidated, real-time view of attendance or consumption, so operational decisions are made on stale or anecdotal information. Attendee communication is broadcast-only and unverifiable, with no record of who received a given update.

Quick Response (QR) codes provide a mature, standardised mechanism for machine-readable identification [1], and QR-based attendance has been proposed as a way to reclaim the lecture time that manual registers consume [3]. Cloud push-messaging services such as Firebase Cloud Messaging exist to send messages to mobile devices reliably [9], within the delivery guarantees Chapter 2 sets out, and modern cross-platform toolkits such as Flutter allow a single codebase to deliver the required scanning, charting and notification functionality [19]. This project applies these technologies to conference operations as component 4.3b of the ConferenceCheck capstone programme. A sibling component, 4.3a, handles the core attendee check-in capture and offline synchronisation engine separately; this project does not rebuild those features, and instead consumes check-in data through a shared REST API contract and focuses on what happens after check-in.

1.2 Problem Statement

Conference organisers lack integrated, trustworthy tools for the operational tasks that follow attendee registration and check-in. Meal distribution based on printed vouchers or name lists cannot enforce single use; duplicate collection is difficult to detect at the point of service, and

reconciliation after the event is manual and unreliable. Attendance and check-in data, even when captured digitally, is not surfaced to organisers in real time, so decisions about catering quantities, room allocation and staffing are made on guesswork. Session rooms have physical capacity limits, but organisers have no mechanism that tracks per-session attendance as it happens or warns them before rooms overcrowd. Communication with attendees is one-directional and unlogged, with no record of which attendees were reachable for a given schedule change. The consequence is operational inefficiency, measurable fraud exposure in catering budgets, safety risk from overcrowded rooms, and a degraded attendee experience.

1.3 Aim

To design, implement and evaluate the analytics, meal management, session capacity, notification and reporting component of the ConferenceCheck Mobile application, providing conference organisers with real-time operational insight, fraud-resistant meal voucher redemption and auditable attendee communication.

1.4 Objectives

1. To design and implement a real-time analytics dashboard showing check-in progress, check-in rates and trends for event organisers. "Real-time" was delivered as near-real-time by design: the dashboard polls every 30 seconds (Section 4.10).
2. To build a QR-code based meal voucher scanning and redemption system that enforces single-use redemption across multiple meal categories.
3. To implement session attendance tracking with capacity management and overcrowding alerts.
4. To build a push notification system for attendee communications and schedule updates, with per-recipient delivery records.
5. To implement reporting and data export (CSV) functionality for event organisers.
6. To evaluate redemption correctness, scan latency, dashboard freshness, notification delivery and export correctness against the Table 3 targets and a manual baseline.
7. To produce comprehensive technical documentation and a publication-ready paper.

1.5 Scope

The project covers Flutter mobile modules for the analytics dashboard, meal voucher generation and scanning, session attendance and capacity alerts, a notification inbox and report access, together with the corresponding server-side business logic in a standalone Laravel API. It is built against the REST API contract agreed with component 4.3a's core check-in module, consuming check-in data as a read-only input to analytics, with a minimal check-in stub standing in for 4.3a

so that this component can be built and tested on its own; check-in scanning, attendee search and the offline synchronisation engine are component 4.3a's remit and are out of scope here. Evaluation is performed on seeded, realistic event datasets including concurrent-scan fraud scenarios, described in full in Section 3.2. Payment processing, external ticketing integration and a full web-based administration panel are out of scope for both components.

1.6 Significance of the Study

Organisers gain a live view of check-ins, meal redemption and session occupancy, so catering, rooms and staffing can be adjusted during the event rather than reconciled afterwards. Caterers pay only for meals actually served once, because a voucher cannot be redeemed twice even when two scanners read it at the same moment. Attendees receive schedule changes through two channels and see their own meal vouchers on their phone. For the department, the project gives a measured answer, with a control that is designed to fail, to a question the related work in Chapter 2 leaves open: which mechanism actually prevents a second redemption under parallel load.

1.7 Contributions

This work makes four contributions, each carrying equal weight in the evaluation that follows. The first is a redemption protocol in which the single-use guarantee is carried by the database's constraint machinery: a unique constraint on an append-only redemption relation, enforced inside a transaction with a row lock on the voucher, rather than by an application-level check, which eliminates time-of-check-to-time-of-use races by construction rather than by defensive coding. The second is a near-real-time analytics dashboard whose staleness bound is a stated design parameter (a 30-second poll) rather than an incidental property, chosen explicitly over introducing a WebSocket layer within the project's scope. The third is session capacity tracking whose overcrowding alerts are dispatched automatically on a threshold transition, converting a safety problem into an alert delivered before a room reaches capacity rather than a discovery made after. The fourth is a dual-channel notification design, push plus an authenticated in-app inbox with per-recipient delivery records, that treats Firebase Cloud Messaging's best-effort delivery model as a known property to be compensated for rather than assumed away, together with an offline scan queue whose replay safety is a direct corollary of the same idempotent server design that makes the redemption protocol safe.

1.8 Conventions Used in This Report

Latencies are quoted in milliseconds to one decimal place in tables and rounded to the nearest whole millisecond in prose. Counts and rejection rates are exact throughout. Timings are wall-clock seconds or milliseconds for a single named run on PHP 8.5.8 with PostgreSQL 18, and the run is always named. Where a number also appears in `docs/validation_report.md`, the two are the same measurement and that file is the reproducible source; this report does not re-derive figures independently of it.

1.9 Organisation of the Report

The rest of this report is organised as follows. Chapter 2 reviews the literature on QR codes, QR-based attendance, idempotence and concurrency control, dashboards and push delivery, and compares the closest related work with this project in Table 2.1. Chapter 3 sets out the development approach and the evaluation method, including how the evaluation was kept from measuring only what the system was built to pass. Chapter 4 analyses the system: its stakeholders, functional and non-functional requirements and use cases, then its architecture, data design, redemption protocol and interface. Chapter 5 describes the implementation: the environment, the modules, the key implementation details and the challenges met and how they were solved. Chapter 6 presents the test cases and results, discusses them, states the limitations, and evaluates each objective. Chapter 7 concludes and makes recommendations. The appendices hold the AI usage disclosure, the defects found in review, the full evaluation output, the reproduction commands, screenshots of the running system, and the reference verification record.

1.10 Chapter Summary

This chapter set out the problem this component addresses, the aim and the seven objectives, the scope agreed with component 4.3a, the significance of the work and its contributions. The next chapter reviews the literature these design decisions rest on.

Chapter 2: Literature Review

2.1 QR Codes and Opaque Tokens

The QR Code symbology is standardised in ISO/IEC 18004 [1], which specifies its data capacity and, critically for verification applications, its four selectable error-correction levels, allowing codes to remain machine-readable when partially damaged or poorly displayed on low-brightness screens. Tiwari [2] surveys the structural properties that drove QR adoption over one-dimensional barcodes in ticketing and access-control contexts: high capacity in a small print area, omnidirectional scanning, and decode robustness on commodity camera hardware. A key design implication, adopted in this project, is that the QR payload should be an opaque server-issued token rather than semantically meaningful data, so that possession of the printed code confers no information and validation authority remains entirely server-side.

2.2 QR-Based Attendance and Its Anti-Fraud Weaknesses

Masalha and Hirzallah [3] propose a QR-based attendance system for a university setting, motivated by the observation that taking attendance manually consumes around ten minutes of each lecture, and they project that their design would remove most of that cost. Their paper describes the design and analyses it; it reports no experiment, and in particular no measured comparison against a manual register, so it should not be read as evidence of how much time or error such a system saves in practice. Its analysis does, however, identify the central weakness of naive QR attendance directly: a student outside the room can be sent an image of the displayed code by a student inside it, so any anti-fraud property must come from what the server does with a scan, not from the code itself. Their own answer to that is to bind the scan to a place and a person, through device location and a facial match. That weakness, rather than their proposed remedy for it, is what motivates the server-side single-use redemption design evaluated in this report, in which the database, not the scanning client, is the arbiter of whether a voucher has already been consumed.

That weakness has not gone away in the decade since, and the recent literature answers it by constraining the scan rather than the entitlement. Mohammed and Zidan [4] regenerate the code twice a second, so that a code which has been photographed is already stale by the time it is

presented again; they report improved accuracy and a positive reception from students and instructors, drawn from surveys and record analysis rather than from a controlled comparison. Nwabuwe et al. [5], writing in the same journal as Masalha and Hirzallah nine years later, still describe a shared code as the central vulnerability, and bind the scan to a place and a device: the venue's polygonal coordinates are encoded in the code itself and checked by geofence, and the registering handset's IMEI is verified so that one person cannot register for another. Alsuhibany [6] secures the symbol instead of the scan, embedding a watermark so that a substituted or tampered code can be detected, and reports high accuracy over a dataset of 5,000 samples.

Each of these binds the act of scanning more tightly, to the moment, the place, the device or the integrity of the symbol, and each is a reasonable answer to the problem it takes on. None of them makes the thing being claimed single-use, which is a different guarantee and the one this project pursues. The distinction is in what is being recorded: an attendance mark may legitimately be registered once per person per session, and the fraud is someone registering who is not there, whereas a meal entitlement is consumed, and the fraud is the same person consuming it twice. Binding a scan to a place or a handset does not prevent the second of these, because the attendee is genuinely present and holding their own phone both times.

It is also worth recording what this body of work does not contain. None of [4], [5] or [6] reports a measured comparison against a manual process, and neither does [3]. Section 6.4.7 therefore has no external figure to set its own against, and says so rather than implying that one exists.

2.3 Idempotence and Concurrency Control

For the redemption transaction itself, Helland [16] provides the canonical treatment of idempotence in distributed systems: operations that may be retried, as scans on unreliable venue networks will be, must be designed so that repeated submission cannot produce repeated effect. In this project, that principle is realised by recording redemptions in an append-only table with a database-level uniqueness constraint on the voucher identifier, making double-redemption a constraint violation rather than an application-level race condition, and it is the same property that makes the offline scan queue described in Section 4.9 safe to replay without reconciliation logic.

Helland's argument concerns repeated submission; the harder case is simultaneous submission. Berenson et al. [20] name the underlying anomaly the lost update: one transaction reads a data item, another updates it, and the first then writes on the basis of what it read. A redemption that checks a voucher's status and then marks it redeemed has exactly this shape, and an application-level status check cannot close it, because two transactions can both read the unredeemed status before either writes. Two database mechanisms can. A row lock taken with `SELECT ... FOR UPDATE` makes any other transaction that tries to lock or update the same row wait until the first transaction ends [21], so the second reader sees the committed redemption. A unique index makes a second insert of the same key wait for the first inserting transaction, and fail if that transaction commits [22]. Section 6.4.1 tests each mechanism on its own, and the two together, against the case they are meant to prevent.

2.4 Dashboards and Response Time

On the presentation side, Few [7] establishes design principles for operational dashboards: a dashboard must fit on a single screen, prioritise the small number of measures that drive action, and use visual encoding rather than tables of numbers for trend perception. Nielsen [8] provides the response-time thresholds that inform this project's latency targets: feedback within one second preserves a user's flow of thought, which sets the budget for scan-validation round trips at a catering service point where queue throughput matters, and is the threshold against which Section 6.4.3 reports the measured results.

2.5 Push Notification Delivery and API Security

For attendee communication, Firebase Cloud Messaging documentation describes an architecture in which each app instance registers for messages and is identified by its own registration token [10], and states that a message accepted by FCM has not thereby been delivered: a message for an offline device is stored and delivered when the device reconnects, and delivery may be delayed or may not happen at all [11]. Delivery is therefore best-effort rather than guaranteed, tokens expire, and devices without Google Play services are unreachable, all of which motivate the dual-channel design evaluated in Section 6.4.6, in which every notification is also persisted to an in-app inbox with per-recipient delivery records. The service interface between the mobile client and backend follows the REST architectural style [12]; endpoint authentication uses bearer

tokens as specified in RFC 6750 [13] and implemented by Laravel Sanctum [14], with mobile-specific hardening guided by the OWASP Mobile Application Security Verification Standard [15]. The client architecture applies the separation of presentation, state and data access descended from the Model-View- Controller pattern [17], realised in Flutter's widget and provider model [19].

2.6 Comparative Analysis of Related Work

Table 2.1. Comparison of the closest related work with this project.

Work	Approach	What it secures	Single-use entitlement	Meals, capacity and live analytics	Measured against a manual process
Masalha and Hirzallah [3]	QR attendance, with device location and a facial match	the scan, to a place and a person	No	No	No: a design with an analysis
Mohammed and Zidan [4]	code regenerated twice a second	the moment of the scan	No	No	No: surveys and record analysis
Nwabuwe et al. [5]	venue geofence in the code, handset IMEI check	the place and the device	No	No	No
Alsuhibany [6]	watermark embedded in the QR symbol	the integrity of the symbol	No	No	No: accuracy over 5,000 samples
This project	opaque token; database row lock and unique constraint	the entitlement itself	Yes	Yes	No: baseline not run; measured under parallel load with a control

Table 2.1 sets out the difference the previous sections describe. The related systems secure the act of scanning, each in a different way; none makes the thing being claimed single-use, none combines catering with session capacity and a live view for organisers, and none was measured against a manual process.

Taken together, this body of work indicates that the individual technologies are mature, but that existing systems apply them piecemeal: attendance tools do not manage catering, catering tools

do not track session capacity, and none provide the organiser with a consolidated live operational view. This project's contribution, set out in Section 1.7, is that integration, with each design decision traceable to a specific finding in this literature rather than to convention.

2.7 Chapter Summary

QR symbology is mature and decodes reliably on ordinary phones, but a QR code on its own prevents nothing. The related attendance systems answer the shared code by binding the scan to a moment, place, device or symbol; none of them makes an entitlement single-use, which is what a meal voucher needs. Idempotence and two database mechanisms, the row lock and the unique index, are the tools for that guarantee, and dashboard and push-delivery literature shapes the rest of the design. Chapter 3 describes how the system was built and how it was evaluated.

Chapter 3: Methodology

3.1 Development Approach

The project was developed incrementally, one module at a time, following the phases of the proposal's Table 4: proposal and planning; requirements and design; environment and foundations; the meal voucher module; analytics and sessions; notifications; reporting and integration; evaluation; and documentation. Each phase ended in a working, tested increment, and three progress reviews (weeks 8, 16 and 24) checked the work with the supervisor. The API contract with component 4.3a was agreed first, so this component could be built and tested on its own against a minimal check-in stub. After the first submission, the supervisor's comments were worked through as a list of individually committed fixes, each with a test that fails on the earlier code; `docs/remaining_work.md` lists them with their dates.

3.2 Evaluation Design

Evaluation proceeds at two levels: correctness of individual business rules, verified continuously through automated tests and, once, through an adversarial manual pass; and end-to-end operational performance, verified in a structured simulated-event exercise on seeded data with scripted fraud scenarios.

3.3 Seeded Evaluation Dataset

The evaluation dataset is generated by `tools/seed-evaluation-event.php`: one event, 500 attendees, three meal categories with a voucher issued per attendee per category for 1,500 vouchers in all, and ten sessions. Three categories rather than one because the single-use guarantee is held per (attendee, category): with one category nothing would distinguish it from a per-attendee guarantee, and the second project objective is redemption across several. The proposal specified four categories for the simulated event; three were used, which is enough to test that redeeming one category leaves the others redeemable, and the proposal's targets are kept unchanged. The dataset is driven through the live HTTP API, against a running backend, rather than through unit-level mocks or direct database manipulation, so that the measured latencies include routing, middleware, authentication and serialisation overhead exactly as a real scanner

client would experience them. Three scripts do this: `tools/run-evaluation.py` for correctness, latency and export correctness, `tools/run-concurrency-experiment.py` for redemption under parallel load, and `tools/measure-dashboard-freshness.py` for dashboard freshness.

3.4 Guarding Against an Artificially Easy Measurement

Three design choices keep this evaluation from measuring only what the system was built to pass.

First, the concurrency claim is tested by an experiment that can fail. A race test run on a server that executes one request at a time cannot tell a locked, constrained redemption apart from a plain check-then-insert, because the requests never overlap: every losing scan is refused by the ordinary status check. The first version of this evaluation had exactly that weakness. The concurrency experiment therefore runs five separate PHP server processes against PostgreSQL, sends each race's five scans to a different process at the same instant, and repeats the races with the row lock removed, with the unique constraint removed, and with both removed, each configuration served from a scratch copy of the same commit. The configuration with both removed is the negative control: if it also produced one redemption per race, the test would show nothing. A second run injects a 50 ms pause between the check and the write in every configuration, so the result does not depend on how often the natural timing happens to overlap.

Second, freshness is measured by injecting check-ins and timing their appearance through a poller that reproduces the app's refresh cycle, rather than derived from the poll interval.

Third, export correctness is checked against SQL run directly on the database, not against another API endpoint that could share a fault with the export, and on a total per export as well as on the row count.

The adversarial pass recorded in `docs/STRICT-REVIEW.md` and reproduced in Appendix B was conducted separately from, and before, the quantitative round in Section 6.4, using live API calls with invalid QR tokens, wrong roles and missing authentication. It did not find the authorisation defects described in Section 6.3, which were found by the supervisor after submission.

3.5 Metrics and Acceptance Criteria

Success criteria were set in the proposal's Table 3: 100% of duplicate scans rejected including concurrent submissions; median scan latency under 500 ms with a 95th percentile under 1 second; dashboard data no more than 30 seconds behind database state; a capacity warning delivered before a session reaches 100% occupancy; 95% or more of online devices receiving a push within 30 seconds, with 100% of recipients reachable via the in-app inbox on next open; and CSV export row counts and totals equal to database ground truth exactly; and a comparison with a manual baseline. Each criterion is given a status in Table 6.3 and addressed by name in Section 6.4.

3.6 Tools and Technologies

Mobile: Flutter 3.x / Dart, Riverpod for state management, `fl_chart` for charting, `qr_flutter` for QR rendering, `mobile_scanner` for camera decoding, and `firebase_messaging` for push. Backend: Laravel 13 (PHP), started from the Laravel starter kit, Laravel Sanctum for token authentication, and PHPUnit for API tests. Database: PostgreSQL, with MySQL and SQLite remaining supported through Laravel migrations. Infrastructure: Firebase Cloud Messaging, Git for version control.

3.7 Ethical Considerations and AI Usage Disclosure

The system processes personal data such as names, contact details and attendance behaviour, and therefore observes the data-minimisation and consent requirements of the Data Protection Act No. 3 of 2021 of Zambia [18]. Attendee records hold only fields required for event operations, QR tokens are opaque and carry no personal data, API access is authenticated and role-scoped following OWASP MASVS guidance [15], and evaluation is performed exclusively on synthetically seeded data, so no real attendee data was processed during development or evaluation. Client-server traffic must be encrypted in any deployment; the development build talks to a local server over plain HTTP (Section 6.6). The system should not be demonstrated with real attendee data until the deployment hardening listed in Section 6.6 is done. The use of artificial intelligence tools is disclosed in **Appendix A**, against the scope limits set out in Section 9 of the project proposal (v4, submission 144, approved).

3.8 Chapter Summary

The system was built in increments against an agreed API contract and evaluated on a seeded 500-attendee event driven through the live API, against the targets in the proposal's Table 3. The evaluation includes a concurrency experiment with a negative control, freshness measured by injection, and exports checked against SQL. Chapter 4 analyses and designs the system.

Chapter 4: System Analysis and Design

4.1 Stakeholders

Table 4.1. Stakeholders and what each needs from the system.

Stakeholder	Role in the system	What they need
Organiser	manages the event; role `organiser`	live check-in, meal and session figures; overcrowding alerts; broadcasts; CSV reports
Scanner operator	catering and session-door staff; role `scanner`	a fast, unambiguous accept or refuse for each scan; a manual entry fallback; scans kept when offline
Attendee	conference participant; role `attendee`	their own pass and meal vouchers on the phone; schedule changes and announcements
Caterer	serves meals	one meal per voucher per category; a redemption record to reconcile against
Component 4.3a	sibling check-in and sync engine	a stable REST contract; check-in data read, not rewritten
Supervisor and department	assess the project	evidence that each objective was met, measured and reproducible

4.2 Functional Requirements

Table 4.2. Functional requirements.

ID	Requirement	Objective
FR-01	Users sign in with email and password and receive a bearer token; every API call is authenticated	all
FR-02	Access is scoped by event and role: organiser, scanner or attendee	all
FR-03	The dashboard shows registrations, check-in count and rate, meal redemption progress, session occupancy and notifications sent, and refreshes every 30 s	1
FR-04	The dashboard shows check-ins over time and redemptions per meal category	1
FR-05	One meal voucher with an opaque QR token is issued per attendee per meal category	2
FR-06	A scanner submits a voucher token by camera or by typing it; the server accepts it once and refuses every later attempt with the time of the first	2
FR-07	A voucher is refused outside its category's time window or when the category is inactive	2
FR-08	Each redemption records the scanner and the device, and cannot be edited or deleted	2
FR-09	Attendees see their own meal vouchers as QR codes, with category and	2

ID	Requirement	Objective
	status	
FR-10	Session entry is recorded once per attendee per session, with the scanning device	3
FR-11	Crossing the warning fraction (default 90%) or full capacity sends an alert to organisers	3
FR-12	Organisers send notifications to all attendees or to role-based groups; each recipient gets a delivery record	4
FR-13	Every notification also appears in the recipient's in-app inbox	4
FR-14	Organisers download attendance, meal, session and notification reports as CSV	5
FR-15	Scans made without a connection are queued on the device and replayed in order	2, 3

4.3 Non-Functional Requirements

Table 4.3. Non-functional requirements, with the target each is held to.

ID	Quality	Requirement and target	Where it is evaluated
NFR-01	Correctness	no voucher redeemed twice, including under simultaneous scans: 100% of duplicates refused	Section 6.4.1
NFR-02	Performance	scan decision median under 500 ms and 95th percentile under 1 s	Section 6.4.3
NFR-03	Freshness	dashboard no more than 30 s behind the database	Section 6.4.4
NFR-04	Reliability	a scan is never lost when the network drops; a notification reaches every recipient through the inbox even if push fails	Sections 4.9 and 6.4.6
NFR-05	Security	bearer-token authentication; role and ownership checks on every route; opaque QR tokens carrying no personal data	Section 6.3
NFR-06	Privacy	data minimisation under the Data Protection Act No. 3 of 2021 [18]; evaluation on synthetic data only	Section 3.7
NFR-07	Usability	single-screen dashboard [7]; a scan result that is unmistakable at a busy serving point	Section 4.11
NFR-08	Maintainability	static analysis at PHPStan level 7, Pint, `flutter analyze`; automated tests for every business rule	Section 6.3
NFR-09	Portability	Android; iOS through Flutter, not verified	Section 6.6

4.4 Use Cases

Table 4.4. Use cases.

ID	Actor	Use case	Main flow	Outcome
UC-01	Any user	Sign in and choose an event	enter credentials; select the event	token issued; screens shown for the user's role
UC-02	Organiser	Monitor the event	open the dashboard; it refreshes every 30 s	live check-in, meal, session and notification figures
UC-03	Attendee	Show a meal voucher	open My meals; present the unused voucher's QR	the scanner can read the voucher token
UC-04	Scanner operator	Redeem a meal voucher	scan the QR or type the token; submit	200 and "redeemed", or 409 already redeemed, 404 invalid, 422 outside the window
UC-05	Scanner operator	Scan without a connection	scan while offline	scan queued; screen says the voucher is not redeemed and the meal is not served
UC-06	Scanner operator	Record session entry	scan the attendee pass at the door	attendance recorded once; capacity state updated
UC-07	System	Alert on capacity	a scan crosses 90% or 100% of capacity	push alert to the event's organisers
UC-08	Organiser	Send a notification	write the message; choose the audience; send	push to devices; inbox entry and delivery record per recipient
UC-09	Attendee	Read notifications	open the Alerts tab	only notifications sent to this attendee
UC-10	Organiser	Export a report	open Reports; choose an export	CSV file of attendance, meals, sessions or notifications

4.5 System Architecture

The system is a client-server architecture with three tiers: a Flutter mobile application, a standalone Laravel backend exposing a REST API [12], and a PostgreSQL database, with Firebase Cloud Messaging as the external push channel.

Figure 4.1. System architecture and the component 4.3a / 4.3b boundary.

ConferenceCheck Mobile: Flutter application (Android)	

ConferenceCheck Mobile: Flutter application (Android)	
Component 4.3a: Core Check-in and Sync Engine *(sibling, developed separately, out of scope)*: attendee check-in capture; offline synchronisation engine	**Component 4.3b: Analytics, Meals and Notifications** *(this project)*: analytics dashboard; meal voucher scan and redemption; session capacity and overcrowding alerts; notification inbox; reports and CSV export
REST API contract agreed with 4.3a, Sanctum bearer-token authenticated. 4.3b consumes check-in data from seeded fixtures and a minimal check-in stub during independent development	
Standalone Laravel REST API implementing the agreed contract, with a minimal check-in stub + PostgreSQL database	
Push dispatch: Laravel → Firebase Cloud Messaging (external) then to the device, for component 4.3b notifications only	

The mobile application follows a layered structure derived from the Model-View-Controller separation [17]: a presentation layer of Flutter widgets, a state layer of Riverpod providers holding screen state and orchestrating asynchronous calls, and a data layer of repository classes wrapping a single authenticated REST client. Platform services, camera access via `mobile_scanner` and push token registration via `firebase_messaging`, are isolated behind interfaces so that they can be stubbed in widget tests. The backend is a standalone Laravel 13 application, started from the Laravel starter kit, that implements the API contract agreed with component 4.3a, with a minimal check-in stub so that this component can be built and tested on its own. Every endpoint requires a Sanctum-issued bearer token [13, 14] and returns a uniform JSON envelope with `success`, `message` and `data` fields. Authorisation is role-based and scoped to the event: organisers manage the event, view analytics and download reports; scanners submit scans and read the attendee list, vouchers and redemption history the scanner app needs; attendees read only their own vouchers and the notifications sent to them. The first submitted version did not enforce the attendee restrictions on four routes; Section 6.3 describes the defects and the tests that now cover them.

4.6 Data Design and Entity-Relationship Diagram

Figure 4.2 shows the entities and relationships of the conference schema, as created by the migration `2026_07_06_000001_create_conferencecheck_tables.php`. Laravel's own framework tables (cache, jobs, sessions, passkeys and access tokens) are left out. `events` is at the centre: every other conference table belongs to one event. The keys that carry the system's guarantees are marked: the unique `qr_token` on vouchers and attendees, the unique `(attendee, category)` pair on vouchers, the unique `meal_voucher_id` on redemptions, which makes the voucher-to-redemption relationship one to at most one, and the unique `(session, attendee)` pair on session attendance.

Figure 4.2. Entity-relationship diagram of the conference schema.




Table 4.5 lists the relations whose constraints matter most.

The system's anti-fraud properties are carried by relations and constraints rather than by application code.

Table 4.5. Core relations and the integrity constraints underpinning system guarantees.

Relation	Purpose	Key integrity constraint
`attendees`	Event attendee records, shared with 4.3a	Unique `ticket_code`; unique `qr_token`
`meal_categories`	Meal windows, for example Breakfast, Lunch, VIP Lunch	Owned by event; time-windowed
`meal_vouchers`	One voucher per attendee per category	Unique `qr_token`; unique `(attendee, category)` pair
`meal_redemptions`	Append-only record of each redemption; the model refuses updates and deletes	Unique `meal_voucher_id` enforces single use; foreign keys restrict rather than cascade deletes
`event_sessions` / `session_attendance`	Conference sessions and per-session attendance	Unique `(session, attendee)` prevents duplicate attendance
`device_tokens` / `notification_recipients`	FCM registration and per-recipient delivery records	Delivery auditable per user and per notification

4.7 The Voucher Redemption Protocol

Voucher issuance generates exactly one voucher per attendee per meal category, each carrying a cryptographically random, globally unique QR token that is opaque: it encodes no attendee or entitlement information, so possession of a screenshot confers nothing beyond what the server chooses to honour [2, 3]. The protocol has four steps. A scanner device decodes the QR token and submits it with its own device identifier to the scan endpoint. The server resolves the token to a voucher, verifying that it belongs to the event being served and that the category's service window is open. Within a database transaction, the server locks the voucher row (`lockForUpdate()`), so a second scan of the same voucher waits until the first transaction ends. It then checks that the voucher is still unused; a scan that finds it already redeemed receives a definitive "already redeemed" response naming the earlier redemption time [16]. Only then does it mark the voucher redeemed and insert the redemption record. The unique constraint on the record's voucher identifier is a second, independent guarantee: if the lock were ever missing, the second insert would fail, and that failure is caught and returned as the same "already redeemed" response rather than as a server error. The redemption record, including the redeeming device identifier and timestamp, cannot be changed afterwards: the model refuses updates and deletes, and the foreign keys restrict, rather than cascade, the deletion of the event, attendee, category, voucher or user it refers to, so it remains a complete audit trail for post-event reconciliation.

Section 6.4.1 measures the protocol under real parallel load, including with each of the two guarantees removed.

4.8 Session Attendance and Capacity Alerting

Each session carries a room capacity. Attendee entry is recorded by scanning the attendee's QR badge at the session door; the unique `(session, attendee)` constraint prevents double counting. The backend evaluates occupancy against capacity on every scan, under a lock on the session row that serialises scans of one session, and exposes threshold states: `available`, `warning` at or above a configurable fraction of capacity (default 90%), and `over_capacity`. A threshold transition dispatches an organiser-targeted push notification after the attendance transaction commits, so a push is never sent for attendance that ends up rolled back, converting room overcrowding from a discovery made after the fact into an alert intended to arrive before the room reaches capacity; Section 6.4.2 states how far that was shown.

4.9 Offline Operation

Scans captured without connectivity are persisted to a durable FIFO queue on the device and replayed in order when the network returns. Replay safety is a direct corollary of the server's idempotent scan semantics described in Section 4.7: an entry that already reached the server resolves to a definitive duplicate answer rather than a second effect, so the queue can be drained without reconciliation logic. A definitive business answer settles an entry: success, already redeemed or duplicate (409), invalid token (404), or not redeemable now (422). Anything else, including no connection, an expired login, rate limiting or a server fault, keeps that entry and every entry after it for the next attempt, and an entry queued while a replay is running is kept. The replay tests are listed in Section 6.3.

Service rule for meal scans made offline. A queued meal scan is not a redemption. Only the server decides whether a voucher is valid and unused, so while a scan sits in the queue nothing has been checked, and the meal is not served until the server has answered 200. This is consistent with the proposal's statement that voucher redemption needs connectivity: the queue exists so that a scan is not lost, not so that a meal can be served without the check. The scanner says so on screen. When a meal scan is queued it shows "No connection — voucher NOT redeemed. Do not serve this meal; the scan is saved and will be checked when back online." The earlier message,

"scan saved and will sync", read as though the meal could be served, and was changed for that reason. Session scans are different, because a queued session entry only delays a count and does not hand anything over.

4.10 Analytics, Notifications and Reporting

The analytics dashboard consumes four aggregate endpoints, namely summary, check-ins over time, meal redemptions by category, and session attendance, computed directly from the operational tables, including check-in data produced by component 4.3a. Following Few's single-screen principle [7], the landing view presents total registrations, check-in count and rate, and voucher redemption progress as headline figures, with time-series charts beneath. The client self-refreshes on a 30-second polling interval, a deliberate trade-off documented in Section 6.6: polling over the existing REST API avoids introducing a WebSocket layer while keeping data staleness within one operational decision cycle. Section 6.4.4 measures the resulting freshness by injecting check-ins and timing their appearance.

Organisers compose notifications targeted at all attendees or at role-scoped groups. The dispatch service resolves the target set into per-recipient delivery records, then delivers via Firebase Cloud Messaging to every registered device token [10]. Because FCM delivery is best-effort [11], every notification is simultaneously persisted and served through an authenticated in-app inbox, so an attendee whose device was offline, or lacks Google Play services, still receives the message on next application open; the inbox shows each user only the notifications they were a recipient of, and the per-recipient records make delivery auditable. Firebase demo mode, used to try the app without credentials, records a send as `demo` on the notification and every recipient, never as `sent`, so it cannot be mistaken for delivery.

The reporting module exposes CSV exports of attendance, per-category meal redemptions, per-session attendance and notifications to organisers. Each export is written while its rows are read from the database in chunks of 1,000, so the whole export is never held in memory. Export correctness is an explicit evaluation criterion, reported in Section 6.4.5.

4.11 Interface Design

The interface is organised by role, with a bottom navigation bar whose tabs depend on who has signed in (`mobile/lib/app/router.dart`). Table 4.6 lists them; Appendix E shows the screens running.

Table 4.6. Screens by role.

Role	Tabs	Purpose
Organiser	Dashboard, Meals, Sessions, Alerts, Reports	monitor the event, manage meals and sessions, send notifications, export
Scanner	Meal scanner, Session scanner, History, Profile	redeem vouchers, record session entry, review redemptions
Attendee	Home, Alerts, My QR, My meals, Profile	read notifications, show the check-in pass, show meal vouchers

Four design decisions shape the screens. The dashboard follows Few's single-screen principle [7]: headline figures first, trends beneath (Figures E1 and E2). A scan result is shown as a large green or red banner with the server's own message, so an operator at a busy serving point can tell accept from refuse at a glance (Figures E8 and E9). The scanner keeps a manual token field under the camera view, so a damaged code or a failed camera does not stop service. The attendee's check-in pass (Figure E5) and meal vouchers (Figure E6) are separate screens, because they are separate tokens: the meal scanner refuses the pass, and the session door does not take a meal voucher.

4.12 Chapter Summary

This chapter identified the stakeholders, fifteen functional and nine non-functional requirements and ten use cases, and set out the design that meets them: a Flutter client and a standalone Laravel API on PostgreSQL, a schema whose constraints carry the anti-fraud guarantee, a redemption protocol with two independent safeguards, an offline queue that is safe to replay, and an interface organised by role. Chapter 5 describes how it was implemented.

Chapter 5: Implementation

5.1 Development Environment

Table 5.1. Development environment.

Item	Used
Operating system	Windows 11; Android emulator (Pixel 7 profile, API 36)
Languages	Dart, PHP 8.5.8, Python 3.14 for the evaluation and document scripts
Mobile framework	Flutter 3.44 (stable), Riverpod, `fl_chart`, `qr_flutter`, `mobile_scanner`, `firebase_messaging`
Backend framework	Laravel 13 with Sanctum, started from the Laravel starter kit
Database	PostgreSQL 18.2
Quality tools	PHPUnit, PHPStan level 7, Pint, `flutter analyze`, `flutter test`
Version control and services	Git and GitHub, with continuous integration; Firebase Cloud Messaging v1
Documents	pandoc 3.9 and Microsoft Word 16 for the Word and PDF deliverables

5.2 Code Organisation and Modules

What in this repository is this component's work. The repository is a standalone Laravel 13 application, started from the Laravel starter kit, so it also carries the starter kit's own pages, settings and authentication code and their 39 tests, none of which is this component's work. The backend exposes 47 API routes: `MealController` 10, `AttendeeController` 8, `SessionController` 7, `NotificationController` 5, `EventController` 5, `AnalyticsController` 4, `ReportController` 4 and `AuthController` 4. Two of those, the check-in scan and check-in endpoints on `AttendeeController`, are a minimal stub for component 4.3a's check-in capture, written here so this component can be built and tested on its own; this component only reads check-in data, for analytics, and integration with 4.3a's own API was not demonstrated. `AuthController` and `EventController` are the authentication and event scaffolding both components need. The remaining groups, together with `GET /events/{event}/attendees/me` added for the attendee QR screen, are this component's. The mobile application is this component's alone, and its feature modules bear the boundary out directly: `mobile/lib/features/` holds `dashboard`, `meals`, `sessions`, `notifications`,

`reports`, `attendee`, `events`, `auth`, `profile` and `sync`, with no check-in capture module anywhere in it.

How the history and tags should be read. The git history before 10 July 2026 was reconstructed from the working prototype in one session (9 and 10 July, with follow-on commits to 14 July), grouping the development done before then into module-by-module commits; `docs/milestone_tracker.md` and `docs/STRICT-REVIEW.md` record this. The milestone tags were created in September and mark the commit that best represents each phase's deliverable, not the dates in the proposal's Table 4, so they do not by themselves show when the work happened. The work done after the supervisor's comments on the first submission is listed with its commit dates in `docs/remaining_work.md`.

The backend is organised around one controller per resource domain, covering events, attendees, analytics, meals, sessions, notifications and reports, with cross-cutting notification delivery and recipient resolution factored into a `NotificationDispatchService`, since both the notification-send path and the session capacity-alert path need it. This structure replaced an earlier single controller that had grown to cover six unrelated resource domains in one file; the split changed no route, no business rule and no test outcome, and is recorded as its own commit for that reason (`46cee57`). The mobile application follows the layered structure described in Section 4.5. Code quality is enforced by PHPStan at level 7 and Pint on the backend, `flutter analyze` on the client, and continuous integration across the PHP 8.4 and 8.5 matrix; all are clean at the time of writing.

The work divides into six modules, each a feature folder in `mobile/lib/features/` with its routes in the API:

- **Analytics dashboard**: four aggregate endpoints (summary, check-ins over time, meals by category, sessions) and a dashboard that refreshes every 30 s.
- **Meal vouchers**: voucher generation, the scan endpoint, the scanner screen with camera and manual entry, the redemption history, and the attendee's My meals screen.
- **Sessions**: session list and details, the door scanner, attendance and capacity states, and the organiser alerts.
- **Notifications**: composing and sending, `NotificationDispatchService`, device token registration, per-recipient records and the inbox.
- **Reports**: the four CSV exports, read from the database in chunks of 1,000.
- **Offline sync**: the durable scan queue and the replay controller.

5.3 Key Implementation Details

5.3.1 Meal voucher redemption

`MealController::scanVoucher` wraps the redemption in a check for the unique constraint, and the redemption itself runs in one transaction that locks the voucher row:

```
$voucher = MealVoucher::query()->where('qr_token', $request->string('qr_token
'))->lockForUpdate()->first();


if (! $voucher || $voucher->event_id !== $event->id) {
    return $this->fail('Invalid meal voucher QR token.', [...], 404);
}
if ($voucher->status !== 'unused') {
    return $this->fail('Meal voucher has already been redeemed or is not usab
le.', [...], 409);
}
// category inactive or outside its window: 422
$voucher->update(['status' => 'redeemed', 'redeemed_at' => $now, ...]);
MealRedemption::query()->create([... 'device_id' => $request->input('device_i
d')]);
```

The 409 check comes before the 422 checks, so an already redeemed voucher always answers "already redeemed". If the insert ever hits the unique constraint on `meal_voucher_id`, which can only happen if the lock is missing, the exception is caught outside the transaction and returned as the same 409, never a 500.

5.3.2 Offline replay

The replay controller (`mobile/lib/features/sync/application/scan_sync_controller.dart`) sends queued scans in order. Only 404, 409 and 422 settle a scan, because they are final answers about the token and a retry would get the same answer. No connection, 401, 403, 408, 429 and server errors are about the conditions, so the scan is kept with every scan after it, and the run stops.

Replay removes only the scans it handled, so a scan queued during a replay is not lost. A meal scan that is queued is not a redemption, and the scanner says so on screen.

5.3.3 Notification dispatch

`NotificationDispatchService` resolves the audience into recipient rows and commits them before anything is pushed, so a push is never sent for a notification that is rolled back. Each device token is mapped back to its recipient: a recipient is `sent` only when one of their own tokens was accepted, `failed` with a reason when all of theirs were refused, and `pending` when they have no device and will see the message in the inbox. Demo mode records `demo`, never `sent`.

5.3.4 Access control and exports

Routes carry an `event.role` middleware listing the roles allowed. Within a route, attendees are further limited to their own records: their own voucher, their own notifications. Reports are organiser only. Each rule has a test that expects 403 and fails on the earlier code. The CSV exports use Laravel's `lazy()` to read rows in chunks of 1,000 while the file is written, so a large export is never held in memory.

5.4 Challenges and Solutions

A strict, evidence-based review of the system against the portal objectives and the proposal was carried out by the student partway through development, with assistance from Claude (Appendix A), using the full backend test suite, live adversarial API calls, `flutter analyze` and `flutter test`, and code inspection of every claimed safeguard (`docs/STRICT-REVIEW.md`). Six defects were found in that pass, and a further two in the later verification pass described in Appendix B; all eight are recorded here rather than omitted, because a defect found and fixed under review is stronger evidence of correctness than a system that was never checked closely enough to find one. Firebase Cloud Messaging delivery was implemented as a stub that returned success without contacting Firebase, the biggest gap against both objective lists; it was fixed by implementing real FCM v1 sends with per-token failure counting, verified live end to end on a device. The attendee-facing QR code was fabricated client-side from a naming convention rather than fetched from the server, which would have broken for any non-seeded user; it was fixed by adding an authenticated endpoint that returns the caller's real attendee record. The API documentation had

drifted from the actual notification request fields; it was corrected. Capacity-status vocabulary was inconsistent between the CSV export and the analytics endpoints; it was unified. No offline scan queue existed despite the proposal's risk table promising one; the durable FIFO queue described in Section 4.9 was built to close that gap. Mobile test coverage was thin, at four tests across roughly fifteen screens; it was broadened to nineteen tests covering the offline queue's persistence, ordering and replacement semantics, core widgets, formatters and model parsing, and later to twenty-seven with the replay tests described in Section 6.3. That review did not find the authorisation and replay defects the supervisor later identified; those, and their fixes, are in Section 6.3. The full defect list, verification evidence and fix log are reproduced in **Appendix B**.

Table 5.2. Challenges met during implementation and how each was solved.

Challenge	Why it mattered	Solution
The first race test passed for the wrong reason	it ran on a server that handles one request at a time, so it could not tell a safe design from a naive one	five server processes on PostgreSQL, every combination of the two safeguards, and a control with neither, expected to fail (Section 3.4)
Attendees could read other people's data	another attendee's voucher, the exports, the redemption history and organiser notifications were open to any attendee of the event	role and ownership checks on each route, each with a 403 test
The voucher flow did not work in the app	the app showed only the check-in pass, which the meal scanner rightly refuses	the My meals screen; one end-to-end trial gave 200 then 409 (Section 6.4.1)
Offline replay dropped scans	an expired login or a server fault was treated as final	only 404, 409 and 422 settle a scan; anything else is kept, in order
Push delivery was a stub	the first version reported success without contacting Firebase	real FCM v1 sends with per-recipient outcomes, verified on a device
Measuring freshness honestly	deriving it from the poll interval would assume the result	check-ins injected at random moments and timed to their appearance

5.5 Chapter Summary

The system was implemented in Flutter and Laravel on PostgreSQL in six modules. The redemption path holds a row lock and a unique constraint, the offline queue settles only on final

answers, notification outcomes are recorded per recipient, and every access rule is tested. The challenges met were solved in ways that are themselves tested. Chapter 6 presents the results.

Chapter 6: Testing, Results and Evaluation

6.1 Testing Strategy

Testing ran at four levels. Feature tests in PHPUnit drive the API through HTTP against a real database (31 for this component). Flutter unit and widget tests cover the client's parsing, offline queue, replay and key screens (30). The evaluation scripts drive a seeded 500-attendee event through the live API, including the concurrency experiment and the freshness measurement (Chapter 3). Finally, one end-to-end trial ran the voucher flow on an Android emulator. Every test case at these levels is listed in Section 6.2.

6.2 Test Cases

Table 6.1 lists every test case: the 31 component API tests (TC-01 to TC-31), the evaluation steps (TC-32 to TC-46), the Flutter tests that bear on the voucher flow and offline replay (TC-47 to TC-51), and the device trial (TC-52 to TC-55). The same table is Section 12 of the validation document, and its rows are traceable to named tests and results files there.

Table 6.1. Test cases.

ID	What is tested	Expected result	Actual result	Pass/fail
TC-01	login returns a token	200 with a Sanctum token	200 with token	Pass
TC-02	registration cannot choose the organiser role	account created as attendee	created as attendee	Pass
TC-03	analytics summary	200 with the summary totals	200, totals as seeded	Pass
TC-04	valid meal voucher scan	200; voucher redeemed; one redemption row	as expected	Pass
TC-05	second scan of a redeemed voucher	409 with the earlier redemption time	409 with redeemed_at	Pass
TC-06	duplicate caught by the unique constraint	409, not 500	409	Pass
TC-07	unknown meal token	404 Invalid meal voucher QR token	404	Pass
TC-08	redeeming one category leaves the	other categories still 200	200 for each other category	Pass

ID	What is tested	Expected result	Actual result	Pass/fail
	others redeemable			
TC-09	valid session attendance scan	200; attendance recorded	as expected	Pass
TC-10	duplicate session scan	409 duplicate	409	Pass
TC-11	check-in that loses a race	duplicate answer, not 500	duplicate, no 500	Pass
TC-12	session scan that loses a race	409, not 500	409	Pass
TC-13	notification send in demo mode	recorded as demo, never sent	demo	Pass
TC-14	missing Firebase config with demo mode off	send fails; nothing marked sent	failed	Pass
TC-15	custom notification target	rejected with 422	422	Pass
TC-16	CSV report download	200, text/csv attachment	as expected	Pass
TC-17	every export has one row per database record	row counts equal the database	equal for all four	Pass
TC-18	pushes go out after recipient rows commit	no push inside the transaction	as expected	Pass
TC-19	send through FCM v1 when configured	v1 request sent with OAuth token	as expected	Pass
TC-20	delivery recorded per recipient	sent / failed / pending per recipient	as expected	Pass
TC-21	session scan records the scanning device	device id stored	stored	Pass
TC-22	capacity threshold transitions alert organisers	warning and over-capacity pushes to organisers	both sent	Pass
TC-23	attendee fetches own QR token and vouchers	200 with own token and meal_vouchers	as expected	Pass
TC-24	attendee on staff or organiser routes	403	403	Pass
TC-25	attendee opens another attendee's voucher	403	403	Pass
TC-26	notification read by a non-recipient	403; list holds only own	403	Pass

ID	What is tested	Expected result	Actual result	Pass/fail
TC-27	device token deleted by a non-owner	403	403	Pass
TC-28	linking an attendee record to a scanner	scanner keeps scanner role	role kept	Pass
TC-29	edit or delete a redemption, or cascade it away	refused; 409 on parent delete	refused / 409	Pass
TC-30	scanner downloads a report	403	403	Pass
TC-31	attendees/me with no linked record	404	404	Pass
TC-32	200 first scans of fresh vouchers	200 of 200 accepted	200 of 200	Pass
TC-33	100 sequential re-scans of a redeemed voucher	100 of 100 refused (409)	100 of 100	Pass
TC-34	20 cross-category attendees, three categories each	60 of 60 accepted; repeat refused	20 of 20 attendees	Pass
TC-35	20 sequential duplicate session scans	20 of 20 refused	20 of 20	Pass
TC-36	concurrency, lock and constraint on (as built), 50 races	one success per race	50 of 50	Pass
TC-37	concurrency, lock off, constraint on	one success per race	50 of 50	Pass
TC-38	concurrency, lock on, constraint off	one success per race	50 of 50	Pass
TC-39	concurrency negative control, both off	double redemption detected (expected to fail)	48 of 50 redeemed more than once	Pass (control failed as designed)
TC-40	voucher scan latency, n=200	median < 500 ms, p95 < 1 s	145.3 ms / 261.0 ms (loopback)	Pass
TC-41	session scan latency, n=40	median < 500 ms, p95 < 1 s	128.4 ms / 228.7 ms (loopback)	Pass
TC-42	dashboard freshness, 20 injected check-ins (poller, not the app)	each visible within 30 s	20 of 20 in recorded run; 19 of 20 in supervisor's rerun	Pass in recorded run; not guaranteed
TC-43	attendance.csv against SQL	rows and checked-in total equal	500 / 40, equal	Pass
TC-44	meals.csv against SQL	rows and per-category totals equal	280 / 94, 93, 93, equal	Pass

ID	What is tested	Expected result	Actual result	Pass/fail
TC-45	sessions.csv against SQL	rows and per-session totals equal	10 rows; one non-zero session, equal	Pass
TC-46	notifications.csv against SQL	rows and recipients equal	0 against 0 (unit test is the real check)	Pass
TC-47	My meals parses vouchers from attendees/me	vouchers with category and status kept	as expected	Pass
TC-48	My meals shows a QR only for an unused voucher	one QR, for the unused voucher	one QR	Pass
TC-49	replay settles only on 404, 409 and 422	other answers keep the scan	as expected	Pass
TC-50	queued scans survive a restart	replayed on the next run	as expected	Pass
TC-51	manual token trimming	surrounding spaces removed	as expected	Pass
TC-52	attendee app shows the meal voucher	Supper voucher shown as QR, status Unused	shown; QR decodes to MEAL-DEMO-1-3	Pass
TC-53	first scan of MEAL-DEMO-1-3 from the scanner app	200, Voucher redeemed successfully	200; redeemed 18:09:25 UTC	Pass
TC-54	second scan of the same token	409, already redeemed	409, twice	Pass
TC-55	attendee pass token at the meal scanner	404 Invalid meal voucher QR token	404	Pass

TC-42 measures a poller that reproduces the app's refresh, not the app on a device (Section 6.4.4). TC-46 compares zero with zero and is backed by TC-17. TC-40 and TC-41 were measured over loopback on one machine (Section 6.4.3). Not in the table because they were not run or not measured: the manual baseline, push delivery across a fleet of devices, and a timed capacity alert.

6.3 Automated Correctness Verification

The backend test suite passes in full: 70 tests, 288 assertions, on PHP 8.5.8 with PostgreSQL 18.2. Of those, 31 tests (152 assertions) in `tests/Feature/ConferenceApiTest.php` exercise this component; the other 39 are the Laravel starter kit's example, dashboard, authentication and settings tests, which came with the application scaffold. The 31 are named in Section 0.1 of the validation report. PHPStan at level 7 and Pint are both clean. The Flutter client is analyzer-clean

with 30 of 30 tests passing. The twelve starter-kit tests that render pages need the frontend built first (`npm run build`); without it they fail on the missing Vite manifest.

Access control. After submission the supervisor found that an authenticated attendee assigned to the event could read another attendee's voucher token, the attendance export, the event's redemption history and a notification addressed to organisers, on a local database with synthetic data. These were defects in the authorisation rules, contradicting what Section 4.5 then claimed. They are fixed: an attendee can open only their own voucher, reports are organiser only, the redemption history, attendee list, voucher list and session attendance are staff only, and notifications are listed and opened only by their recipients. Four further defects of the same kind were fixed with them: registration let a caller choose the organiser role, any organiser could delete any user's device token, the `custom` notification target was sent to every attendee, and linking an attendee record to a scanner demoted them. Each fix has a test that expects 403 and that fails against the earlier code (validation report, Section 7).

Offline replay. Two defects in the replay path were fixed: every HTTP error, including an expired login or a server fault, was treated as settled and the scan dropped; and a scan queued while a replay was running could be overwritten. Eight tests now drive the replay itself with a fake API, covering an authentication failure, a server fault, a scan queued during a replay, a queue left by an earlier app run, and a scan kept after a 401 surviving a restart (validation report, Section 8). Camera decoding of QR codes was checked by hand and not measured; the only QR test covers the trimming of a manually entered token.

Every test case, with its expected and actual result, is listed in one table, TC-01 to TC-55, in Section 12 of the validation document.

Beyond the automated suite, the adversarial checks from the strict review confirmed behaviour under conditions the unit tests did not then exercise.

Table 6.2. Adversarial and live checks, strict review (`docs/STRICT-REVIEW.md`).

Verification	Result
Live API exercise, all endpoint groups	all responded correctly, including 401/403 enforcement for the checks made
Double meal-voucher scan	rejected

Verification	Result
Duplicate check-in / session scan	flagged `duplicate: true` / rejected
Over-capacity session scan	recorded with `over_capacity`, warning, and an automatic organiser alert
Notification send to `all_attendees`	recipient records created, per-recipient delivery status recorded
Four CSV report downloads	all well-formed

6.4 Results Against the Acceptance Criteria

Table 6.3. Status of each acceptance criterion in the proposal's Table 3. Sources: `tools/evaluation-results.json`, `tools/concurrency-results.json`, `tools/freshness-results.json`.

Criterion (proposal Table 3)	Target	Result	Status
Duplicate redemption rejection, including concurrent submissions	100%	100/100 sequential re-scans refused; on PostgreSQL behind five server processes, 50/50 five-way races with exactly one redemption with the lock, the constraint or both in place; with both removed, 48/50 vouchers redeemed more than once (Section 6.4.1)	Met
Scan validation latency	median < 500 ms, p95 < 1 s	voucher scan 145.3 ms / 261.0 ms (n=200); session scan 128.4 ms / 228.7 ms (n=40)	Met on loopback only (Section 6.6)
Dashboard freshness	≤ 30 s behind the database	20 injected check-ins, measured with a poller that reproduces the app's refresh, not the app on a device: median 18.1 s, p95 28.4 s, max 28.5 s	20 of 20 within 30 s in the recorded run; not guaranteed by design (a rerun gave 19 of 20, one at 30.02 s) (Section 6.4.4)
Capacity warning before 100% occupancy	warning delivered before full	two automated transition tests; one observation on an emulator	Partly met: shown, not timed
Push delivery	≥ 95% of online devices within 30 s	one device, one observed delivery of about 5 s	Not measured
In-app inbox reach	100% of recipients on next open	a recipient record for every recipient, inbox reads filtered to recipients and tested; not measured on devices	Partly met
Export	row counts	all four exports equal to direct SQL on	Met, with those two

Criterion (proposal Table 3)	Target	Result	Status
correctness	and totals equal to the database	row counts and on a total each; `notifications.csv` checked as 0 against 0, its real check being a unit test; the sessions total has one non-zero session of ten (Section 6.4.5)	limits
Comparison with a manual baseline	measured against a staffed paper line	not run (Section 6.4.7)	Not run

Two further results are not Table 3 criteria but test the guarantees the design rests on: all three categories were redeemable independently for 20 of 20 attendees, and 20 of 20 sequential duplicate session scans were refused. Two criteria are met, one of them on loopback only, and export correctness is met with the two limits stated in its row; dashboard freshness held in the recorded run but is not guaranteed by design; two criteria are partly met; push delivery across a fleet was not measured; and the manual baseline was not run.

6.4.1 Meal Voucher Redemption Correctness

Sequentially, 100 of 100 re-scans of an already-redeemed voucher were refused.

The evaluation script's own race step, 20 races of five simultaneous scans of one token, resolved to exactly one success each, but it ran on a development server that executes one request at a time, so it cannot distinguish the design from a plain check-then-insert and is not the evidence for the concurrency claim (Section 3.4). The evidence is the concurrency experiment, in which five separate server processes received each race's five scans at the same instant, 50 races per configuration (Table 6.4).

Table 6.4. Concurrent redemption on PostgreSQL behind five server processes, 50 races of five simultaneous scans per configuration. Source: `tools/concurrency-results.json`.

Row lock	Unique constraint	Races with one success	Vouchers redeemed more than once	With a 50 ms window: one success / redeemed more than once
on	on (as built)	50/50	0	50/50 / 0
off	on	50/50	0	50/50 / 0
on	off	50/50	0	50/50 / 0

Row lock	Unique constraint	Races with one success	Vouchers redeemed more than once	With a 50 ms window: one success / redeemed more than once
off	off	2/50	48	0/50 / 50

With both safeguards removed, 48 of 50 vouchers were redeemed more than once even without the injected pause, so the race is real under this load and the experiment can detect it. With either safeguard in place, every race produced exactly one redemption and no response was a server error. Each safeguard is therefore sufficient on its own, and the system as built carries both: with the lock in place, losing scans wait for the winner and are then refused by the status check; the unique constraint refuses the second insert if the lock is missing.

The guarantee is held per (attendee, category) rather than per attendee, and that distinction is measured rather than assumed: twenty attendees were reserved before any other step, each holding a voucher in all three categories, and each had all three redeemed in turn. All sixty redemptions were accepted and every repeat of the first was refused, so redeeming one category neither consumes nor blocks another. Ground truth is exact: 280 redemption rows exist for 200 successful batch scans, 20 race winners and 60 cross-category redemptions, equal to a direct SQL count.

In the app, end to end. Until 14 October 2026 the attendee app showed only the check-in and session pass, which the meal scanner rightly answers with 404, so the voucher flow worked at the API but not in the app. The My meals screen now shows each of the attendee's vouchers as a QR code (Figure E6). One trial was then run on an Android emulator: the seeded attendee's unused Supper voucher, `MEAL-DEMO-1-3`, was shown in the attendee app and submitted from the scanner app by manual entry. The server answered 200 and recorded the redemption; the same token submitted again was answered 409 with the time of that redemption (Figures E8 and E9; validation document Section 11). That is one trial on one emulator, without the camera.

6.4.2 Session Attendance and Capacity Correctness

The unique `(session, attendee)` constraint held under the same sequential treatment: 20 of 20 duplicate session check-ins were refused. Session scans now lock the session row, and a scan that reaches the unique constraint returns 409 rather than a server error; that path is tested by inserting a competing row between the check and the insert, but the session path was not part of

the parallel experiment, so it has not been tested under real parallel load. Capacity threshold transitions are covered by an automated test and were observed once on an Android emulator, where crossing the 90% warning threshold delivered a push to the organiser before the over-capacity state was reached. The alert was not timed, so the criterion that the warning arrives before the session is full is shown, not measured.

6.4.3 Latency Against the Proposal's Targets

Table 6.5. Latency by endpoint against the proposal's targets. Source: `tools/evaluation-results.json`.

Endpoint	n	Mean	Median	p95	Max	Target (median / p95)
Meal voucher scan	200	164.0 ms	145.3 ms	261.0 ms	316.6 ms	< 500 ms / < 1,000 ms
Session scan	40	143.3 ms	128.4 ms	228.7 ms	242.1 ms	< 500 ms / < 1,000 ms
Analytics summary	20	124.0 ms	117.9 ms	138.7 ms	208.2 ms	part of each dashboard refresh (Section 6.4.4)

Every measured latency clears its target against Nielsen's response-time threshold [8]. These figures are taken on a single local machine over loopback HTTP, not on venue Wi-Fi as the proposal's target scenario assumes; Section 6.6 states the spread across runs and what follows from the difference.

6.4.4 Analytics Dashboard Freshness

Freshness was measured by injecting check-ins and timing their appearance, as the proposal's method describes. A poller reproducing the app's refresh, the same four endpoints fetched in parallel with the next refresh 30 seconds after the previous one started, ran while 20 check-ins were injected one at a time at random moments; each was timed from the start of the injecting request to the end of the first dashboard fetch that showed it. In the recorded run the median was 18.1 s, the 95th percentile 28.4 s and the maximum 28.5 s, and all 20 appeared within 30 s. The measurement is a poller that reproduces the app's refresh, not the app running on a device, so it covers the data path to the app and not the time Flutter takes to repaint. By design the worst case is one full 30 s cycle plus the duration of a fetch, so a check-in landing just after a fetch starts can appear fractionally later than 30 s. That case does happen: when the supervisor reran the same

script, 19 of 20 appeared within 30 s and one at 30.02 s, with a median of 11.4 s. The result is therefore 20 of 20 within 30 s in the recorded run, not a guaranteed 30 s ceiling.

6.4.5 Export Correctness

Table 6.6. Export correctness, each CSV export against SQL run directly on the database. Source: `tools/evaluation-results.json`.

Export	Check	CSV	SQL
`attendance.csv`	rows / attendees checked in	500 / 40	500 / 40
`meals.csv`	rows / redemptions per category	280 / 94, 93, 93	280 / 94, 93, 93
`sessions.csv`	rows / attendance per session	10 / 40, then 0 for the other nine	10 / 40, then 0 for the other nine
`notifications.csv`	rows / total recipients	0 / 0	0 / 0

All four exports equal the database on their row count and on one total each, but two of those checks are weaker than they look. The evaluation event has no notifications, because sending one would have used live Firebase credentials, so `notifications.csv` was checked as 0 against 0 in the run, which shows only that the export is well formed. Its real check is the unit test `test_every_export_has_one_row_per_database_record`, which runs on seeded data that does contain a notification. The sessions total is also thin: only one of the ten sessions has any attendance, so it compares one non-zero value and nine zeros. An earlier version of this check compared two exports with other API endpoints on row counts only, which could not have caught a fault shared between the export and those endpoints.

6.4.6 Notification Delivery

Live Firebase Cloud Messaging v1 delivery was observed once, end to end, on an Android emulator: an organiser send travelled from Laravel, through service-account OAuth and FCM v1, to the device's notification shade, and arrived about 5 seconds after sending. These are single observations, with the screenshot as evidence, and no run log of delivery across devices was committed. The proposal's target of 95% of online devices within 30 seconds therefore requires a measurement this evaluation does not provide. Delivery is recorded per recipient, a recipient being `sent` only when one of their own tokens was accepted, and a demo-mode send is recorded as `demo`, never `sent`. Because push delivery is best-effort by design [11], the in-app inbox is the

channel that reaches every recipient who opens the application; that every recipient gets a record and that the inbox is filtered to recipients is tested, but it was not measured on devices.

6.4.7 Baseline Comparison, and Its Limits

The proposal's evaluation plan calls for comparing the voucher module against a simulated, human-staffed paper-register meal line. That live human-trial baseline was **not** conducted, because organising a staffed comparison exercise was not feasible within the project's scope, and this is stated plainly rather than approximated with an invented number, which would be worse than admitting the gap. What the evaluation does establish is the system-side bound: a median scan-to-decision time of 145.3 ms with single-use enforcement that a paper register cannot provide at any speed, since a photographed or reused paper voucher has no server-side check to fail. The evaluation run refused all 200 duplicate submissions it made: 100 sequential re-scans, the 80 losing scans of the 20 single-server races, and 20 cross-category repeats; in the concurrency experiment, every losing scan was refused in every configuration with a safeguard in place. No published figure is available to compare these against: the closest prior work [3] proposes a QR attendance system without measuring one, so there is no external baseline in the literature to set these numbers beside.

6.5 Discussion

The central design argument tested by this evaluation is that a correctness guarantee should not rest on application logic that checks for a condition before acting on it, because two requests can both pass the check before either acts. Table 6.4 shows that race happening: with the row lock and the unique constraint both removed, five simultaneous scans of one voucher produced more than one redemption in 48 of 50 races, although the status check was present throughout. It also shows that either database mechanism closes it on its own. The row lock does so by making the second request wait until the first has committed, so its status check sees the redemption; the unique constraint does so by refusing the second redemption row outright, whatever the application did before the insert. The system carries both, so that the guarantee does not depend on any one line of application code being right. The same property is what makes the offline scan queue in Section 4.9 safe without reconciliation logic, because an idempotent server means a

queue can simply retry until it gets a definitive answer, whatever that answer is, rather than needing to reason about whether an earlier attempt already succeeded.

The first version of this evaluation did not show this. Its race test ran on a server that executes one request at a time, so every losing scan was refused by the status check and the test would have passed for a plain check-then-insert too. The lesson is a methodological one: a concurrency test needs a negative control that is expected to fail, or a pass means nothing.

This design has a cost, which is schema rigidity: the guarantee lives in a unique constraint on `meal_redemptions`, so any future requirement to permit a voucher to be redeemed more than once, for example a multi-serving meal category, is a schema change rather than a business-rule change, and that trade-off should be named rather than left implicit.

The latency results in Section 6.4.3 show that this correctness comes at an acceptable cost at the scale tested: the measured median voucher scan of 145.3 ms leaves roughly 355 ms against the 500 ms target for the network latency that venue Wi-Fi would add and that this loopback measurement does not include. The cost of the lock itself was not measured separately: no run compared the endpoint with and without it.

The relationship between this project's results and the closest prior work, Masalha and Hirzallah's QR attendance proposal [3], should be stated carefully. Their paper is a design proposal with an analysis and no measurements; this study measures a seeded, scripted event against explicit latency and correctness targets. There is therefore nothing in that work to compare these numbers against, which is a gap in the literature rather than a difference in method, and it is part of why Section 6.4.7 has no baseline to report. What the two agree on is the underlying claim that motivates both: a QR code alone provides no anti-fraud property, because it can be photographed and reused, so any guarantee has to come from what the verifying system does with a scan. This project's contribution is a specific mechanism for that guarantee, evaluated under parallel load against a control rather than only under repetition, which their study did not test.

6.6 Limitations

Evaluation is simulated rather than live. The seeded 500-attendee event, scripted duplicate scans and single test devices approximate a real conference but do not reproduce its full operational variability: real network conditions, real device diversity, and real human queueing behaviour at a meal line. The results in Section 6.4 should be read as a controlled measurement on synthetic data, not as a field measurement.

Measurements are single-machine and loopback. All latency figures in Section 6.4.3 were taken on one development machine over loopback HTTP. Venue Wi-Fi will add round-trip latency that this measurement does not include; the margin against the target (Section 6.5) is the basis for expecting that added latency to be absorbed, not a demonstration that it has been.

The latency figures are a property of the run, not of the system. Four runs of the evaluation script have been recorded on this machine, returning voucher-scan medians of 114.0 ms, 199.0 ms, 187.5 ms and the 145.3 ms reported in Section 6.4.3, with 95th percentiles of 210.5 ms, 304.3 ms, 286.7 ms and 261.0 ms. The spread is machine load rather than code. Every correctness result was identical across runs. The envelope the latency claim should be read in is therefore a median between roughly 110 ms and 200 ms and a 95th percentile between roughly 210 ms and 305 ms on a development machine, inside the proposal's 500 ms and 1,000 ms targets in every run observed, and no narrower claim than that is supported by a single-machine measurement.

Concurrency was tested for correctness, not throughput, and for meal vouchers only. The concurrency experiment establishes that the redemption path gives one redemption per voucher under parallel load, and which mechanism is responsible. It does not establish how many scanners the system can serve at once, and it ran on five PHP built-in server processes on one machine rather than on a production server. The session scan path has the same kind of lock and constraint, but it was tested for a lost race only by fault injection in a unit test, not under parallel load.

Some criteria were shown rather than measured. Capacity alerts were observed once on an emulator and covered by an automated test, but not timed. Push delivery was observed once, at about 5 seconds, on one device; the proposal's 95%-within-30-seconds target is a fleet-level

claim this evaluation cannot support. Camera decoding of QR codes was checked by hand. Offline replay was tested against a fake API in the test harness, not on a device.

No live human-staffed baseline. As stated in Section 6.4.7, the proposal's manual-register comparison was not run. The qualitative argument in that section follows from the system's measured properties and from prior literature on a different deployment, not from a controlled comparison conducted in this project.

Integration with component 4.3a was not demonstrated. This component was built and tested against its own minimal check-in stub, as agreed, and against seeded check-in data. Running it against component 4.3a's own API is future work.

Deployment hardening is out of scope. The development build talks to a local server over plain HTTP; the API login is not rate-limited and access tokens do not expire; and organiser and scanner accounts can only be created by the seed, since registration always creates an attendee. Each would need attention before the system handled real attendee data.

iOS is unverified. Development and testing targeted Android; iOS compatibility is expected from Flutter's cross-platform model [19] but was not systematically verified within this project.

6.7 Evaluation Against the Objectives

Table 6.7 evaluates each objective in Section 1.4 against the evidence above.

Table 6.7. Status of each objective (Section 1.4).

Objective	Status	Evidence
1. Analytics dashboard	Built, as near-real-time: a 30 s poll by design rather than a live stream; freshness within 30 s held in the recorded run but is not guaranteed by design	Figures E1 and E2; 20/20 within 30 s in the recorded run, 19/20 in a rerun, measured with a poller rather than the app (Section 6.4.4)
2. Single-use meal vouchers across categories	Met at the API; in the app, shown end to end once on an emulator with manual token entry, camera reading not shown	Section 6.4.1 and the concurrency experiment; cross-category independence 20/20; Figures E6, E8 and E9 and validation document Section 11
3. Session attendance, capacity and	Met in function; alert timing not measured	Section 6.4.2; two transition tests and one emulator observation

Objective	Status	Evidence
overcrowding alerts		
4. Push notifications with per-recipient delivery records	Built and verified end to end on one device; delivery across a fleet not measured	Section 6.4.6
5. Reporting and CSV export	Met	All four exports equal to direct SQL (Section 6.4.5); `notifications.csv` was 0 against 0 in the run and is checked by a unit test
6. Evaluation against Table 3 and a manual baseline	Partly met: every criterion was measured or tested except fleet push delivery and the manual baseline, which was not run	Table 6.3
7. Documentation and a publication-ready paper	Documentation done; the paper is substantially done but not yet publication-ready	this report, `docs/`

6.8 Chapter Summary

All 55 test cases pass, with three stated qualifications: freshness held in the recorded run but not by design, the notifications export was compared at zero, and latency was measured over loopback. Either database safeguard alone prevented double redemption under parallel load, where a plain check did not. Objective 2 is met at the API and was shown once in the app on an emulator; the manual baseline, fleet push delivery and a timed capacity alert were not run or not measured.

Chapter 7: Conclusion and Recommendations

7.1 Conclusion

This project set out to deliver the analytics, meal management, session capacity, notification and reporting half of a two-part conference management application, and produced a working system: a redemption protocol whose single-use guarantee is enforced by the database rather than by application code, a near-real-time analytics dashboard whose staleness was measured but is not guaranteed below 30 s, session capacity tracking with automatic overcrowding alerts, dual-channel notifications that compensate explicitly for best-effort push delivery, and an offline scan queue whose safety is a direct consequence of the same idempotent design that protects the redemption protocol. Table 6.3 gives the status of each criterion in the proposal's Table 3: two are met, one of them on loopback only; export correctness is met with two stated limits; dashboard freshness held in the recorded run but is not guaranteed by design; two are partly met; fleet-scale push delivery was not measured; and the manual baseline was not run. Table 6.7 evaluates each objective.

7.2 Recommendations

For anyone deploying or extending the system, this project recommends:

1. **Before any live use**, serve the API over HTTPS, rate-limit the login, give access tokens an expiry, and provide a proper way to create organiser and scanner accounts (Section 6.6).
2. **Run a two-phone camera trial and a pilot at a real event**, so that camera decoding, venue Wi-Fi latency and device diversity are measured rather than assumed.
3. **Run the manual baseline** the proposal describes, a staffed paper line against the scanner, to give the speed comparison this report could not.
4. **Train scanner staff that a queued meal scan is not a redemption**: when the scanner says it is offline, the meal is not served.
5. **Keep the guarantee in the database** when extending the system. A multi-serving meal category is a schema change, not a business-rule change (Section 6.5).
6. **Integrate with component 4.3a's own API** and test the two components together.

7.3 Future Work

Future work should validate the system against a live conference, replace dashboard polling with a WebSocket stream, extend offline redemption with conflict resolution jointly with component

4.3a's synchronisation engine, verify iOS behaviour systematically, time the capacity alert, and measure push delivery across a fleet of devices.

References

1. ISO/IEC 18004:2015, *Information technology — Automatic identification and data capture techniques — QR Code bar code symbology specification*. Geneva, Switzerland: International Organization for Standardization, 2015.
2. S. Tiwari, "An introduction to QR code technology," in *Proc. 2016 Int. Conf. on Information Technology (ICIT)*, Bhubaneswar, India, 2016, pp. 39-44.
3. F. Masalha and N. Hirzallah, "A students attendance system using QR code," *International Journal of Advanced Computer Science and Applications*, vol. 5, no. 3, pp. 75-79, 2014.
4. M. Mohammed and K. Zidan, "Enhancing attendance tracking using animated QR codes: a case study," *Indonesian Journal of Electrical Engineering and Computer Science*, vol. 31, no. 3, pp. 1716-1723, 2023.
5. A. Nwabuwe, B. Sanghera, T. Alade and F. Olajide, "Fraud mitigation in attendance monitoring systems using dynamic QR code, geofencing and IMEI technologies," *International Journal of Advanced Computer Science and Applications*, vol. 14, no. 4, pp. 938-945, 2023.
6. S. Alsuhibany, "Innovative QR code system for tamper-proof generation and fraud-resistant verification," *Sensors*, vol. 25, no. 13, art. 3855, 2025.
7. S. Few, *Information Dashboard Design: The Effective Visual Communication of Data*. Sebastopol, CA, USA: O'Reilly Media, 2006.
8. J. Nielsen, *Usability Engineering*. San Francisco, CA, USA: Morgan Kaufmann, 1993.
9. Google, "Firebase Cloud Messaging," *Firebase Documentation*, 2025. [Online]. Available: https://firebase.google.com/docs/cloud-messaging
10. Google, "FCM architectural overview," *Firebase Documentation*, 2025. [Online]. Available: https://firebase.google.com/docs/cloud-messaging/fcm-architecture
11. Google, "Understanding message delivery," *Firebase Documentation*, 2025. [Online]. Available: https://firebase.google.com/docs/cloud-messaging/understand-delivery
12. R. T. Fielding, "Architectural styles and the design of network-based software architectures," Ph.D. dissertation, Univ. of California, Irvine, CA, USA, 2000.
13. M. Jones and D. Hardt, "The OAuth 2.0 Authorization Framework: Bearer Token Usage," IETF RFC 6750, Oct. 2012.
14. Laravel, "Laravel Sanctum," *Laravel Documentation*, 2025. [Online]. Available: https://laravel.com/docs/sanctum
15. OWASP Foundation, *OWASP Mobile Application Security Verification Standard (MASVS)*, v2.0, 2023. [Online]. Available: https://mas.owasp.org
16. P. Helland, "Idempotence is not a medical condition," *Communications of the ACM*, vol. 55, no. 5, pp. 56-65, 2012.
17. G. E. Krasner and S. T. Pope, "A cookbook for using the Model-View-Controller user interface paradigm in Smalltalk-80," *Journal of Object-Oriented Programming*, vol. 1, no. 3, pp. 26-49, 1988.
18. Republic of Zambia, *Data Protection Act No. 3 of 2021*. Lusaka: Government Printer, 2021.
19. Google, "Flutter documentation," 2025. [Online]. Available: https://docs.flutter.dev
20. H. Berenson, P. Bernstein, J. Gray, J. Melton, E. O'Neil and P. O'Neil, "A critique of ANSI SQL isolation levels," in *Proc. 1995 ACM SIGMOD Int. Conf. Management of Data*, San Jose, CA, USA, 1995, pp. 1-10, doi: 10.1145/223784.223785.
21. PostgreSQL Global Development Group, "Explicit locking," Section 13.3, *PostgreSQL 18 Documentation*, 2025. [Online]. Available: https://www.postgresql.org/docs/current/explicit-locking.html

22. PostgreSQL Global Development Group, "Index uniqueness checks," Section 63.5, *PostgreSQL 18 Documentation*, 2025. [Online]. Available: https://www.postgresql.org/docs/current/index-unique-checks.html

Fourteen of the fifteen sources in the proposal are cited above. The fifteenth, the Scrum Guide, is not cited anywhere in this report and has been removed from the list rather than left standing as an entry nothing refers to. Three recent attendance-fraud sources, [4], [5] and [6], and three sources on concurrency control, [20], [21] and [22], were added after the proposal. Every source was checked against its own text; Appendix F records that check and what it changed.

Appendix A. Artificial intelligence usage disclosure

A.1 Use

The tool used was Claude (Anthropic), through Claude Code.

Period	Use
To 30 September 2026	Boilerplate, library and syntax questions, proofreading; help with the strict review and evaluation scripts
7 to 14 October 2026	Code and tests for the fixes the supervisor asked for; the design and scripts of the concurrency and freshness experiments; the My meals screen, `tools/build_proposal_v4.py`, and drafts of the revised report, validation document and proposal

From 7 October this went beyond the proposal's scope (Section 9). The student chose what to fix and in what order, reviewed every change before committing it, and checked the test and experiment results. Each change is a commit in the repository history, and `docs/ai_usage_log.md` is the log.

A.2 Representative prompts

1. 7 October: the supervisor's comments pasted in, then "what would we start with fixing".
2. 9 and 10 October: "do the next 6 commits".
3. 14 October: the supervisor's comments pasted in, then "work on everything he wants us to".

A.3 Checks and gaps

Each fix has a test that fails on the old code and passes now, and the concurrency experiment has a negative control that failed as expected. The per-use log promised in proposal Section 9.4 was not kept before October.

Appendix B. Defects found and fixed during the strict review

Rows 1 to 6 are reproduced from `docs/STRICT-REVIEW.md`: each was found during a single review pass and fixed before the milestone recorded in `docs/milestone_tracker.md` as Progress Review 2. Rows 7 and 8 were found later, during a verification pass that re-ran every command in Appendix D and checked each claim in this report against the behaviour of the running system rather than against the code's intent. They are listed here, in the same table and on the same terms, because a defect found by checking a claim is worth no less than one found by checking the code, and separating them would suggest otherwise.

Table B1. Defects found during review and their fixes. Sources: `docs/STRICT-REVIEW.md` for rows 1 to 6, and the verification pass recorded in `docs/validation_report.md` for rows 7 and 8.

#	Defect found	Fix
1	FCM delivery was a stub returning success without contacting Firebase	Real FCM v1 sends with per-token failure counting; verified live end to end on a device
2	Attendee QR code fabricated client-side from a naming convention	Authenticated `GET /events/{event}/attendees/me` endpoint added; My QR screen fetches the real token
3	`docs/api.md` documented stale notification request fields	Corrected to match `NotificationSendRequest`
4	Inconsistent capacity-status vocabulary between the sessions CSV and analytics endpoints	Unified on `available` / `full` / `over_capacity`
5	No offline scan queue, despite the proposal's risk table promising one	Durable FIFO queue added, with ordered replay on reconnect
6	Thin mobile test coverage: 4 tests across roughly 15 screens	Broadened to 19 tests covering the offline queue, core widgets, formatters and model parsing
7	Per-recipient delivery records carried one aggregate outcome, so a send Firebase partly refused still marked every recipient `sent`	Each token is mapped back to its recipient; `sent` only on that recipient's own accepted token, `failed` with a reason when all theirs were refused, `pending` when they have no device
8	Redemption across multiple meal categories was implemented but unevidenced: no test proved that redeeming one category leaves the attendee's other categories redeemable	Test added for the `(attendee, category)` guarantee

Verification after these fixes, at the time: backend 51/51 tests passing at the strict review (185 assertions), then 55/55 with 213 assertions once the tests for rows 7 and 8 were added; PHPStan level 7 clean, Pint clean, `flutter analyze` clean, `flutter test` 19/19. These are historical counts for this table only. The October fixes added more tests since, and the current counts are the ones in Section 6.3: 70 backend tests with 288 assertions, 31 of them this component's, and 30 of 30 Flutter tests.

Appendix C. Full evaluation figures

Table C1. Full evaluation output. Source: `tools/evaluation-results.json`, produced by `tools/run-evaluation.py` against the dataset seeded by `tools/seed-evaluation-event.php`.


```
{
  "voucher_scan_latency": {
    "n": 200,
    "mean_ms": 164.0,
    "median_ms": 145.3,
    "p95_ms": 261.0,
    "max_ms": 316.6
  },
  "voucher_scan_success": 200,
  "sequential_duplicate_rejection": {
    "attempts": 100,
    "rejected": 100
  },
  "concurrent_duplicate_rejection": {
    "races": 20,
    "exactly_one_success": 20
  },
  "cross_category_independence": {
    "attendees": 20,
    "categories_per_attendee": 3,
    "all_categories_redeemable": 20,
    "redemptions": 60
  },
  "session_scan_latency": {
    "n": 40,
    "mean_ms": 143.3,
    "median_ms": 128.4,
```

```
    "p95_ms": 228.7,
    "max_ms": 242.1
  },
  "session_duplicate_rejection": {
    "attempts": 20,
    "rejected": 20
  },
  "analytics_summary_latency": {
    "n": 20,
    "mean_ms": 124.0,
    "median_ms": 117.9,
    "p95_ms": 138.7,
    "max_ms": 208.2
  },
  "export_correctness": {
    "attendance.csv": {
      "rows": {
        "csv": 500,
        "sql": 500,
        "match": true
      },
      "checked_in": {
        "csv": 40,
        "sql": 40,
        "match": true
      }
    },
    "meals.csv": {
      "rows": {
        "csv": 280,
        "sql": 280,
        "match": true
      },
```

```
    "per_category": {
      "csv": {
        "Evaluation Breakfast": 94,
        "Evaluation Lunch": 93,
        "Evaluation Supper": 93
      },
      "sql": {
        "Evaluation Breakfast": 94,
        "Evaluation Lunch": 93,
        "Evaluation Supper": 93
      },
      "match": true
    }
  },
  "sessions.csv": {
    "rows": {
      "csv": 10,
      "sql": 10,
      "match": true
    },
    "attendance_per_session": {
      "csv": {
        "Evaluation Session 1": 40,
        "Evaluation Session 10": 0,
        "Evaluation Session 2": 0,
        "Evaluation Session 3": 0,
        "Evaluation Session 4": 0,
        "Evaluation Session 5": 0,
        "Evaluation Session 6": 0,
        "Evaluation Session 7": 0,
        "Evaluation Session 8": 0,
        "Evaluation Session 9": 0
      },
```

```
        "sql": {
          "Evaluation Session 1": 40,
          "Evaluation Session 10": 0,
          "Evaluation Session 2": 0,
          "Evaluation Session 3": 0,
          "Evaluation Session 4": 0,
          "Evaluation Session 5": 0,
          "Evaluation Session 6": 0,
          "Evaluation Session 7": 0,
          "Evaluation Session 8": 0,
          "Evaluation Session 9": 0
        },
        "match": true
      }
    },
    "notifications.csv": {
      "rows": {
        "csv": 0,
        "sql": 0,
        "match": true
      },
      "recipients": {
        "csv": 0,
        "sql": 0,
        "match": true
      }
    },
    "all_match": true
  }
}
```


The concurrency experiment and the freshness measurement write their own files, `tools/concurrency-results.json` and `tools/freshness-results.json`; their figures are in Tables 6.4 and 6.3, and the freshness file lists all 20 measured delays.

Appendix D. Reproduction commands

These are the commands as they were actually run. Every script named below is committed in the repository.

The environment they assume. PHP 8.5.8 for Windows with the `pdo_pgsql` and `pgsql` extensions enabled in its `php.ini`, along with `openssl`, `curl`, `mbstring`, `zip`, `gd` and `fileinfo`; a PHP without those loaded cannot reach the database and none of these commands will run. PostgreSQL 18.2. Python 3.14.0 and pandoc 3.9.0.1 for the document build, with Microsoft Word 16.0, which `tools/paginate_report.py` drives to export the PDFs and so to measure the page numbers printed in the contents lists. The Python packages the document build imports are pinned in `tools/requirements-docs.txt`; the evaluation scripts import only the standard library.

The PHP build used here is a portable one installed to a directory on the user `PATH`, so the commands below are the ordinary `php artisan ...` a reader would expect. Where PHP is not on `PATH`, the repository carries `php-pgsql.bat`, a one-line wrapper resolving to a PHP under a `.tools` directory beside the repository, and substituting it for `php` makes every command work unchanged. The interpreter is not committed, since a platform-specific binary distribution does not belong in a source repository, but its version and required extension set are recorded here so the environment can be rebuilt rather than guessed at.

Full evaluation round, against a local backend:

```
php artisan serve
php artisan tinker tools/seed-evaluation-event.php
python tools/run-evaluation.py
python tools/measure-dashboard-freshness.py
```

The concurrency experiment, which needs PostgreSQL as configured in `.env` and creates and drops its own scratch database, so no server needs to be running:

```
python tools/run-concurrency-experiment.py
```

These regenerate `tools/evaluation-results.json`, `tools/freshness-results.json` and `tools/concurrency-results.json`, and overwrite the recorded runs in doing so; the figures in Section 6.4 come from the runs committed in those files, and Section 6.6 states the spread observed between runs.

Backend test suite. Twelve of the starter kit's page tests need the frontend built first, and the build calls `php artisan`, so PHP must be on `PATH`:

```
npm install
npm run build
php artisan test
```

Static analysis:

```
php vendor/bin/phpstan analyse --memory-limit=1G
php vendor/bin/pint --test
```

PHPStan analyses in parallel worker processes that each receive PHP's `memory_limit`, 128 MB by default, and on this project a worker exhausts it often enough that the default cannot be relied on, in which case the run dies with a fatal error rather than producing a report. The raised limit above makes it deterministic. Whenever the analysis completes it reports zero errors at level 7, so the condition is a property of the analyser's memory use rather than a defect in the code.

Mobile:

```
flutter analyze
flutter test
```

Word and PDF deliverables, rebuilt from the markdown sources:

```
python tools/build_docx_deliverables.py
python tools/paginate_report.py
```

`tools/paginate_report.py --check` fails if the page numbers printed in the contents, tables and figures lists no longer match the rendered documents.

Validated state, and the commit it resolves to:

```
git rev-list -n1 final-resubmission
```

Appendix E. The running system, against each objective

Every figure below is a screenshot of the built application running against the seeded demo event, not a mock-up or a design rendering. Each is mapped to the objective it evidences. Where an objective has no screenshot, that is stated rather than left for the reader to notice.

Figure E1. Organiser analytics dashboard (Objective 1).



Check-in progress as both a count and a percentage, 19 of 30 at 63%, with meal vouchers issued and redeemed, redemption rate, session attendance, the count of sessions over capacity and the count of notifications sent. This is the single-screen view Section 4.10 describes, following Few's principle that a dashboard prioritises the small number of measures that drive action [7].


Figure E2. Trends and per-category redemption (Objectives 1 and 2).



Check-ins over time is the trend view required by Objective 1. Meal redemptions are broken down by category, Breakfast, Lunch and Supper, which is Objective 2's multiple-category

requirement shown in the interface rather than only in the schema. Session capacity appears as occupancy against seats for each session, 20% and 65% in this state, which is the reading Objective 3's capacity management is built on.


Figure E3. Automatic capacity alerts on a device (Objectives 3 and 4).



Both threshold transitions arriving as real push notifications on an Android device: the warning fraction, "Session filling up", and "Session over capacity". This is the evidence that the alerting


in Section 4.8 reaches an organiser rather than only changing a value on a dashboard, and it exercises the same Firebase path as Objective 4.

Figure E4. Organiser broadcast delivered end to end (Objective 4).



An organiser-composed message travelling from the backend through service-account authentication and Firebase Cloud Messaging v1 to a real device's notification shade. Section 6.4.6 reports the delivery measurements; this is the end of that path.

Figure E5. Attendee check-in and session pass (not a meal voucher).




The attendee's own pass for event check-in and session doors, carrying a token fetched from the authenticated endpoint rather than constructed on the device. This screen is the fix for the second defect in Appendix B. It is not evidence for Objective 2: the pass token is not a meal voucher, and the meal scanner answers 404 "Invalid meal voucher QR token." to it, which is correct.

Figure E6. The attendee's meal vouchers in the app (Objective 2).



The My meals screen added on 14 October 2026. It shows each of the attendee's vouchers from `GET /events/{event}/attendees/me` with its category and status. An unused voucher is shown as a QR code of its `qr_token`; a redeemed one shows when it was redeemed and no code. The QR code in this screenshot was decoded off the device and reads `MEAL-DEMO-1-3`, the seeded Supper voucher used in Figures E8 and E9.

Figure E7. Meal categories and the per-device redemption trail (Objective 2).



Three categories active at once, which is Objective 2's multiple-category requirement in the interface, and a redemption list in which each entry names the device that recorded it, which is the audit trail Section 4.7 describes.

Figure E8. Scanner accepting the voucher from Figure E6 (Objective 2).






Figure E9. The same voucher refused on a second attempt (Objective 2).



Figures E6, E8 and E9 are one end-to-end trial, run on 14 October 2026 and recorded in Section 11 of the validation document: the attendee app shows the voucher, the scanner submits it and the server answers 200, and the same token is then answered 409. The evaluation in Section 6.4.7 refused 200 duplicate submissions of this kind; these are what a scanner operator sees when it happens.

Figure E10. Report exports available to an organiser (Objective 5).



The four CSV exports whose row counts are checked against database ground truth in Section 6.4.5.

E.1 What these figures do and do not show

In the trial behind Figures E8 and E9 the scanner read the token by manual entry, not with the camera: both roles ran in turn on one Android emulator, and an emulator's camera cannot see

another screen. The submission path is identical from the server's point of view, and it is the server that enforces single use, so the guarantee shown is the real one. What is not shown is the camera decode itself. The QR code in Figure E6 was decoded off the device and reads the right token, but no figure shows the scanner's camera reading one, and the Flutter tests do not cover camera decoding: `qr_parser_test.dart` tests only the trimming of a manually entered token.

The figures were captured on an Android emulator against the seeded demo and evaluation events, so the device diversity limitation in Section 6.6 applies to them as it does to the push-delivery timing.

Appendix F. Reference verification record

Every reference was checked against its own source on 22-23 September 2026 for authors, title, venue, year and pages, and, where the report relies on a source for a specific claim, for whether the source actually makes that claim. The check is recorded here because a reference list that has never been opened is not evidence of anything, and because one entry did not survive it.

Table F1. Verification of every reference, including the one withdrawn.

Ref	Bibliographic check	Claim check
[1] ISO/IEC 18004:2015	Correct; title and year match the ISO record exactly	Cited for the symbology and its error-correction levels, which the standard specifies. A 2024 edition now exists; the 2015 edition is the one consulted
[2] Tiwari, ICIT 2016, pp. 39-44	Correct; venue, year and pages match	Cited for QR capacity, omnidirectional scanning and decode robustness, all of which the paper covers
[3] Masalha and Hirzallah, IJACSA 5(3), pp. 75-79, 2014	Correct; volume, issue, pages and year all match	**Overstated, and corrected.** The report previously said this work "evaluated" a system and "found substantial reductions" in processing time and recording error, and that it "measured processing time and recording accuracy... against a real manual register". The full text contains no experiment, no measurement and no manual-register comparison; it is a design proposal with an analysis section. Four passages were rewritten. What the source does support, and is still cited for, is the photographed-code weakness, which its analysis states directly
[4] Mohammed and Zidan, *IJEECS* 31(3), pp. 1716-1723, 2023	Verified in the Crossref record for DOI 10.11591/ijeecs.v31.i3.pp1716-1723; authors, venue, volume, issue and year all match	Cited for regenerating the code twice a second so a photographed code is stale on re-presentation. The abstract states the method and reports improved accuracy and a positive reception from surveys and record analysis; it gives no figures, and none are attributed to it here
[5] Nwabuwe, Sanghera, Alade and Olajide, *IJACSA* 14(4), pp. 938-945, 2023	Verified in Crossref and against the article PDF, whose running head and page numbers confirm the volume, issue and range	Cited for geofencing by encoding the venue polygon in the code, and for IMEI verification against proxy registration. Both appear in the abstract, and the full text states plainly that a generated code "can be easily shared amongst colleagues". Its evaluation is reported qualitatively, so no measured result is attributed to it
[6] Alsuhibany,	Verified in the Crossref record	Cited for watermarking a QR symbol so

Ref	Bibliographic check	Claim check
Sensors 25(13), art. 3855, 2025	for DOI 10.3390/s25133855	tampering can be detected, evaluated on 5,000 samples. The abstract reports high accuracy without a single headline figure, and none is invented here
[7] Few, O'Reilly Media, 2006	Correct; first edition, publisher and year match	Cited for the single-screen dashboard principle, which the book argues
[8] Nielsen, Morgan Kaufmann, 1993	Correct as a real 1993 edition. The original hardcover was Academic Press; Morgan Kaufmann published the 1993 paperback, which is the form cited	Cited for the response-time thresholds, which the book sets out
[9] Firebase Cloud Messaging documentation, landing page	Live and official	**Narrowed.** The page describes FCM as a solution that "lets you reliably send messages"; it does not mention latency or cost. Chapter 1 had cited it for "reliable, low-latency delivery... at no marginal cost", so the latency and cost claims were dropped. What remains is what the page states
[10] Google, "FCM architectural overview"	Live and official	**Added** so that the registration-token claim cites the page that makes it: "An instance of a client app registers to receive messages, obtaining a registration token that uniquely identifies the app instance"
[11] Google, "Understanding message delivery"	Live and official	**Added** so that the best-effort claim cites the page that makes it. The page states that a message ID returned to the sender means the message "was accepted for delivery", not delivered, that a message for an offline device is stored until the device reconnects, and that delivery may be delayed
[12] Fielding, PhD dissertation, UC Irvine, 2000	Correct; institution and year match	Cited for the REST architectural style, which the dissertation introduces
[13] RFC 6750, Jones and Hardt, Oct. 2012	Correct; authors, number, title and date match the RFC Editor record	Cited for bearer-token usage, which is the RFC's subject
[14] Laravel Sanctum documentation	Live and official	Cited for token authentication, which it documents
[15] OWASP MASVS v2.0, 2023	Correct; v2.0.0 was released in April 2023	Cited for mobile hardening guidance, which it provides
[16] Helland, *CACM* 55(5), pp. 56-65, 2012	Correct; volume, issue, pages and year all match	Cited for idempotence under retry, which is the article's argument
[17] Krasner and	Correct; volume, issue, pages	Cited for the Model-View-Controller separation,

Ref	Bibliographic check	Claim check
Pope, *JOOP* 1(3), pp. 26-49, 1988	and year all match	which the paper describes
[18] Data Protection Act No. 3 of 2021, Zambia	Correct; the Act exists under that number and year	Cited for data-minimisation and consent obligations, which it imposes
[19] Flutter documentation	Live and official	Cited for cross-platform delivery from one codebase
[20] Berenson, Bernstein, Gray, Melton, O'Neil and O'Neil, SIGMOD 1995, pp. 1-10	Checked against the paper's own text (the authors' PDF) and the DBLP record for DOI 10.1145/223784.223785	Cited for the lost update anomaly (its P4): a transaction reads an item, another updates it, and the first then writes on the basis of its read. No other claim is attributed to it
[21] PostgreSQL 18 documentation, Section 13.3 "Explicit locking"	Live and official; checked against Section 13.3.2, "Row-Level Locks"	Cited for `FOR UPDATE` blocking other transactions that lock, update or delete the row until the locking transaction ends
[22] PostgreSQL 18 documentation, Section 63.5 "Index uniqueness checks"	Live and official	Cited for a would-be inserter of a duplicate key waiting for the uncommitted inserting transaction, and failing with a uniqueness violation if that transaction commits
Schwaber and Sutherland, *The Scrum Guide*, 2020	The document exists as cited	**Withdrawn.** Not cited anywhere in this report, and Scrum is not discussed in it. Removed from the list rather than left as an entry nothing refers to

Both items this check first recorded as outstanding have since been closed. The Firebase citation, which pointed at the documentation root rather than at the pages carrying the claims, was split into [9], [10] and [11]. The recent event-technology literature Chapter 2 lacked has been added as [4], [5] and [6]: each was located through Crossref, verified against its own record, and read before being cited, and what each is cited for is recorded above alongside what it does not support. Three sources on concurrency control, [20], [21] and [22], were added after the supervisor noted that the literature the central claim rests on was missing; each was checked against its own text before being cited.