

Lab 08 - Adaptive Refinement

Deal.II Users and Developers Training

SMR2909 - MHPC P2.5

Timo Heister heister@clemson.edu and Luca Heltai luca.heltai@sissa.it

1. The topic of this lab session is a modified version of step-4 made available for you and the goal is to implement adaptive refinement based on step-6, see https://www.dealii.org/8.4.0/doxygen/deal.II/step_6.html
2. Modify the included program to support adaptive refinement by adding a `ConstraintMatrix` and the necessary function calls in `setup` (to create the constraints), `assembly` (`distribute_local_to_global` and no `apply_boundary_values`), `solve` (`distribute`), and replace the logic in `refine_mesh`.
3. What happens if you “forget” the call `constraints.distribute(solution)` after solving the linear system?
4. Use `constraints.print (std::cout);` to show the constraints if you have the following mesh in 2d:

```
GridGenerator::hyper_cube(triangulation);
triangulation.refine_global (1);
triangulation.begin_active()->set_refine_flag ();
triangulation.execute_coarsening_and_refinement ();
```

and also look at this mesh (for example in paraview). Does the result make sense to you? Also compare with/without adding boundary conditions!

5. Change the problem to be an L-shape in 3d (start with 2 global refinements) and manufactured solution

$$u(x, y, z) = \frac{1}{r^2 + 0.001}.$$

Make sure you apply the correct right-hand side and boundary conditions.

6. Compute the L2 error with respect to the number of DoFs with a) global refinement and
b) adaptive refinement using a `KellyEstimator` like in step-6.
7. Plot the two graphs in 4) in a log-log plot and include the line for a quadratic rate (note that $h^2 = N^{-2/3}$).