Adaptive RDMA Optimization for Distributed LLM Workloads

Week 6: Adaptive Transport Middleware for Distributed LLM Inference

Nathan Gopee
MS Computer Science, SUNY New Paltz
gopeen1@newpaltz.edu

Advisors: Dr. Wafi Danesh & Dr. Ashley Suchy

February 2026

1 Overview

This week focused on building a middleware layer that abstracts transport selection for distributed vLLM inference, enabling dynamic switching between TCP, Soft-RoCE, and Tesla TTPoe. The middleware provides a unified interface for transport operations and NCCL configuration, simplifying multi-node deployment and performance comparison. Key accomplishments include:

- Implemented transport abstraction layer with pluggable backends
- Created TCP, Soft-RoCE, and TTPoe transport wrappers
- Built NCCL configuration manager for automatic environment setup
- Developed unified benchmark suite for transport comparison
- Created cluster management scripts with `--transport` flag

2 Architecture

2.1 Middleware Design

The ScuffedRDMA transport middleware provides a clean abstraction over different networking technologies, allowing the same vLLM deployment to switch transports via environment variables or command-line flags.



Figure 1: ScuffedRDMA transport middleware architecture—applications use a unified API while the middleware handles transport-specific details

2.2 Component Overview

Component	File	Purpose
Transport Base	`transport_base.py`	Abstract base class with `send()`, `recv()`, `get_metrics()`
TCP Transport	`tcp_transport.py`	Standard socket wrapper with latency measurement
RoCE Transport	`roce_transport.py`	RDMA verbs wrapper using rdma-core/pyverbs
TTPoe Transport	`ttpoe_transport.py`	Kernel module loader and character device interface
Selector	`selector.py`	Runtime transport selection and factory
NCCL Config	`nccl_config.py`	NCCL environment variable management

Table 1: Middleware component overview

3 Transport Abstraction Layer

3.1 Base Interface

The `TransportBase` class defines the contract that all transport implementations must follow:

```python
# middleware/transport_base.py
from abc import ABC, abstractmethod
from dataclasses import dataclass

@dataclass
class TransportMetrics:
    min_latency: float = 0.0
    max_latency: float = 0.0
    avg_latency: float = 0.0
    bytes_sent: int = 0
    bytes_received: int = 0
    cpu_usage: float = 0.0

class TransportBase(ABC):
    @abstractmethod
    def connect(self, host: str, port: int, **kwargs) -> bool:
        """Establish connection to remote host."""
        pass

    @abstractmethod
    def send(self, data: bytes) -> int:
        """Send data and return bytes sent."""
        pass

    @abstractmethod
    def recv(self, size: int, timeout: float = None) -> bytes:
        """Receive data with optional timeout."""
        pass

    @abstractmethod
    def is_available(self) -> bool:
        """Check if transport is available on this system."""
        pass

    def get_latency(self) -> float:
        """Get average measured latency in seconds."""
        return self.metrics.avg_latency

    def get_bandwidth(self) -> float:
        """Get measured bandwidth in Mbps."""
        return self.metrics.send_bandwidth_mbps
```

3.2 TCP Transport

The TCP transport provides the baseline implementation using standard Berkeley sockets:

```python
# middleware/tcp_transport.py
class TCPTransport(TransportBase):
    def connect(self, host: str, port: int, **kwargs) -> bool:
        self._socket = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
        self._socket.setsockopt(socket.IPPROTO_TCP, socket.TCP_NODELAY, 1)
        self._socket.connect((host, port))
        return True

    def send(self, data: bytes) -> int:
        start = time.perf_counter()
        sent = self._socket.send(data)
        latency = time.perf_counter() - start
        self.metrics.update_latency(latency)
        return sent
```

```
    def is_available(self) -> bool:
        return True  # TCP always available
```

3.3 Soft-RoCE Transport

The RoCE transport wraps RDMA verbs operations using pyverbs from rdma-core [1]:

```
# middleware/roce_transport.py
class RoCETransport(TransportBase):
    def connect(self, host: str, port: int, **kwargs) -> bool:
        import pyverbs.device as d
        import pyverbs.qp as qp

        # Open RDMA device context
        self._context = d.Context(name='rxe0')
        self._pd = pd.PD(self._context)
        self._qp = qp.QP(self._pd, qp_init)

        # Exchange QP info via TCP (out-of-band)
        remote_info = self._exchange_qp_info(host, port)
        self._transition_qp_to_rts(remote_info)
        return True

    def is_available(self) -> bool:
        # Check for rdma_rxe module and rxe0 device
        return 'rdma_rxe' in subprocess.run(['lsmod']).stdout
```

3.4 TTPoe Transport

The TTPoe transport manages kernel module loading and provides a character device interface [2]:

```
# middleware/ttpoe_transport.py
class TTPoeTransport(TransportBase):
    def load_modules(self, dst_mac: str, verbose: int = 1) -> bool:
        subprocess.run([
            'insmod', f'{self._ttpoe_dir}/modttpoe/modttpoe.ko',
            f'dev={self._device}', f'dst={dst_mac}', f'verbose={verbose}'
        ])
        return True

    def connect(self, host: str, port: int, **kwargs) -> bool:
        if not self._check_module_loaded():
            self.load_modules(kwargs.get('dst_mac'))
        self._fd = os.open('/dev/ttpoe', os.O_RDWR)
        return True

    def send(self, data: bytes) -> int:
        return os.write(self._fd, data)

    def is_available(self) -> bool:
        return os.path.exists(f'{self._ttpoe_dir}/modttpoe/modttpoe.ko')
```

4 NCCL Configuration

The middleware automatically configures NCCL environment variables based on the selected transport:

```
# middleware/nccl_config.py
class NCCLConfig:
    @classmethod
    def for_tcp(cls):
        return cls(ib_disable=True, net_gdr_level=0)

    @classmethod
    def for_softroce(cls, device='rxe0'):
        return cls(ib_hca=device, ib_gid_index=1, net_gdr_level=0)

    @classmethod
    def for_hardware_roce(cls, hca='mlx5_0'):
        return cls(ib_hca=hca, net_gdr_level=5)

    def to_env(self) -> Dict[str, str]:
        env = {'NCCL_DEBUG': 'INFO'}
        if self.ib_disable:
            env['NCCL_IB_DISABLE'] = '1'
        if self.ib_hca:
            env['NCCL_IB_HCA'] = self.ib_hca
        return env
```

4.1 NCCL Environment Variables

Transport	Key Variables	Effect
TCP	`NCCL_IB_DISABLE=1`	Disable InfiniBand, use TCP sockets
Soft-RoCE	`NCCL_IB_HCA=rxe0`	Use software RDMA device
Hardware RoCE	`NCCL_IB_HCA=mlx5_0, NCCL_NET_GDR_LEVEL=5`	Use Mellanox NIC with GPUDirect
TTPoe	`NCCL_IB_DISABLE=1, TTPOE_ENABLED=1`	Use TTPoe socket layer

Table 2: NCCL configuration by transport type

5 Transport Selector

The `TransportSelector` class provides runtime transport selection:

```python
# middleware/selector.py
class TransportSelector:
    def __init__(self, transport: str = None):
        # Read from env or use provided value
        self._transport = transport or os.environ.get('SCUFFED_TRANSPORT', 'auto')

    def get_transport(self) -> TransportBase:
        if self._transport == 'auto':
            return self._auto_select()
        elif self._transport == 'tcp':
            return TCPTransport()
        elif self._transport == 'roce':
            return RoCETransport()
        elif self._transport == 'ttpoe':
            return TTPoeTransport()

    def _auto_select(self) -> TransportBase:
        # Priority: TTPoe > Hardware RoCE > Soft-RoCE > TCP
        if TTPoeTransport().is_available():
            return TTPoeTransport()
        if RoCETransport().is_available():
            return RoCETransport()
        return TCPTransport()
```

5.1 Usage Example

```python
from middleware import TransportSelector

# Select via environment (SCUFFED_TRANSPORT=roce)
ts = TransportSelector()
transport = ts.get_transport()

# Or explicit selection
ts = TransportSelector('tcp')
print(ts.get_config())

# Apply NCCL settings to environment
ts.apply_nccl_config()

# Use transport
transport.connect('192.168.1.233', 12345)
transport.send(b'tensor data...')
response = transport.recv(4096)
```

6 Cluster Management Scripts

6.1 Start Cluster Script

The `start_cluster.sh` script provides unified cluster management with transport selection:

```bash
#!/bin/bash
# scripts/start_cluster.sh

# Usage: ./start_cluster.sh --transport=roce --model=llama4

TRANSPORT="${SCUFFED_TRANSPORT:-auto}"

case "$TRANSPORT" in
    tcp)
        NCCL_ENV="NCCL_IB_DISABLE=1 NCCL_NET_GDR_LEVEL=0"
        ;;
    roce)
        NCCL_ENV="NCCL_IB_HCA=rxe0 NCCL_IB_GID_INDEX=1"
        ;;
    ttpoe)
        # Load TTPoe modules first
        ./load_ttpoe.sh load --dev=eth0 --dst=$PEER_MAC
```

```
        NCCL_ENV="NCCL_IB_DISABLE=1 TTPOE_ENABLED=1"
        ;;
esac

# Start worker
ssh infra@$CERBERUS_IP "$NCCL_ENV docker compose -f docker-compose.worker.yaml up -d"

# Start head
ssh infra@$CHIMERA_IP "$NCCL_ENV docker compose -f docker-compose.head.yaml up -d"
```

6.2 TTPoe Module Loader

```
#!/bin/bash
# scripts/load_ttpoe.sh

load_modules() {
    insmod $TTPOE_DIR/modttpoe/modttpoe.ko \
        dev=$INTERFACE dst=$DST_MAC verbose=2
}

unload_modules() {
    rmmod modttpoe 2>/dev/null
}

case "$1" in
    load)   load_modules ;;
    unload) unload_modules ;;
    status) lsmod | grep modttpoe ;;
esac
```

7 Benchmark Suite

7.1 Unified Benchmark Tool

The `benchmark_transports.py` script tests all transports with identical workloads:

```
# benchmarks/benchmark_transports.py
class TransportBenchmarker:
    def benchmark_vllm(self, transport: str) -> TransportBenchmark:
        """Benchmark vLLM inference with specified transport."""
        benchmark = TransportBenchmark(transport=transport)

        for i in range(self.iterations):
            start = time.perf_counter()
            response = requests.post(f"{self.vllm_url}/completions",
                json={"model": self.model, "prompt": prompt})
            duration = time.perf_counter() - start

            benchmark.results.append(BenchmarkResult(
                tokens=response.json()['usage']['completion_tokens'],
                time_sec=duration,
                tokens_per_sec=tokens / duration
            ))

        return benchmark

    def generate_latex(self, output_dir: str) -> str:
        """Generate LaTeX table from results."""
        # ... generates publication-ready tables
```

7.2 Benchmark Shell Script

```
#!/bin/bash
# scripts/benchmark_all.sh

for transport in tcp roce ttpoe; do
    ./start_cluster.sh --transport=$transport
    sleep 120  # Wait for model load

    python benchmarks/benchmark_transports.py \
        --transport=$transport \
        --iterations=5 \
        --output=$OUTPUT_DIR

    ./start_cluster.sh --stop
done
```

8 Expected Performance

Based on prior testing (Update 3) and transport specifications:

Transport	Latency	Expected Throughput	CPU Overhead	Status
TCP	∼1ms	Baseline	High	Always available
Soft-RoCE	∼190μs	+10–15%	Medium	Deprecated
Hardware RoCE	<2μs	+15–25%	Low	Requires Mellanox
Tesla TTPoe	∼2μs	+20–30%	Near-zero	Requires module

Table 3: Expected transport performance for distributed LLM inference

8.1 Performance Comparison Visualization



Figure 2: Transport latency comparison—TCP baseline vs RDMA alternatives. Hardware RoCE and TTPoe achieve 100× lower latency than software solutions.

9 File Structure

```
ScuffedRDMA/
  middleware/
    __init__.py              # Package exports
    transport_base.py        # Abstract base class
    tcp_transport.py         # TCP socket wrapper
    roce_transport.py        # RDMA verbs wrapper
    ttpoe_transport.py       # TTPoe kernel module interface
    selector.py              # Runtime transport selection
    nccl_config.py           # NCCL environment management
  scripts/
    start_cluster.sh         # Multi-node startup with --transport
    benchmark_all.sh         # Run all transport benchmarks
    load_ttpoe.sh            # TTPoe module management
  benchmarks/
    benchmark_transports.py  # Unified benchmark suite
    results/                 # Benchmark output directory
  Update6/
    update6.tex              # This document
```

10 Verification

To verify the middleware installation:

```
# Test middleware import and transport selection
python -c "from middleware import TransportSelector; \
           ts = TransportSelector('tcp'); \
           print(ts.get_config())"

# Start cluster with RoCE transport
./scripts/start_cluster.sh --transport=roce --model=llama4

# Run benchmark suite
./scripts/benchmark_all.sh --transports=tcp,roce --output=results/

# Compile this document
cd Update6 && pdflatex update6.tex
```

11 Integration with vLLM

The middleware integrates with vLLM via NCCL configuration. When starting the cluster:

1. `start_cluster.sh` reads `--transport` flag
2. Calls `NCCLConfig.for_*` to get appropriate settings
3. Exports NCCL environment variables before launching containers
4. vLLM/NCCL automatically uses the configured transport

11.1 Docker Compose Integration

```
# docker-compose.head.yaml (YAML)
services:
  vllm-server:
    image: vllm/vllm-openai:latest
    environment:
      # These are set by start_cluster.sh based on --transport
      - NCCL_IB_HCA=${NCCL_IB_HCA:-}
      - NCCL_IB_DISABLE=${NCCL_IB_DISABLE:-0}
      - NCCL_NET_GDR_LEVEL=${NCCL_NET_GDR_LEVEL:-0}
      - NCCL_DEBUG=INFO
```

12 Limitations and Future Work

12.1 Current Limitations

- **TTPoe integration**: Character device interface requires custom NCCL plugin for full integration
- **pyverbs dependency**: RoCE transport requires rdma-core with Python bindings
- **Module permissions**: TTPoe module loading requires root access

12.2 Planned Enhancements

- Implement NCCL socket plugin for TTPoe transport
- Add hardware RoCE detection and configuration
- Create Prometheus metrics exporter for transport monitoring
- Integrate with vLLM tensor transfer hooks for fine-grained control

13 Next Steps

1. **Hardware RoCE**: Test middleware with Mellanox ConnectX NICs
2. **TTPoe Benchmarks**: Load modules on cluster and measure actual latency
3. **Tensor Telemetry**: Instrument vLLM tensor transfers per thesis plan
4. **Adaptive Routing**: Implement hot/cold tensor classification with WFA
5. **Production Testing**: Run Llama 4 Scout benchmarks across all transports

14 EXO Distributed Inference Integration

In addition to the vLLM middleware, we integrated RDMA support into the **exo** distributed inference framework [**?**], which provides an alternative approach to multi-node LLM serving using libp2p networking and peer-to-peer topology.

14.1 Motivation

While vLLM with Ray provides robust distributed inference, it requires complex session management between containers. The exo framework offers:

- Native peer-to-peer topology with automatic node discovery
- Existing `RDMAConnection` type in topology system (previously unimplemented)
- Support for heterogeneous GPU clusters (mixing RTX 3090 + RTX 5090)
- Active development with PyTorch backend support (PR #1284)

14.2 Integration Architecture



Figure 3: EXO + RDMA integration architecture—RDMATransport wraps ScuffedRDMA middleware and integrates with exo's topology system

14.3 Components Created

Three new modules were created under `exo/src/exo/networking/`:

Module	Lines	Purpose
`rdma_transport.py`	369	RDMA transport wrapper with discovery, connection management, and NCCL config
`rdma_discovery_integration.py`	247	Topology integration for automatic RDMA connection discovery
`__init__.py`	27	Module exports for networking package

Table 4: EXO RDMA integration components

14.4 Key Classes

14.4.1 RDMADiscovery

Discovers RDMA-capable interfaces using `rdma link show` and `ibv_devinfo`:

```
# exo/src/exo/networking/rdma_transport.py
class RDMADiscovery:
    @staticmethod
    def get_rdma_devices() -> list[str]:
        """Get list of RDMA device names via 'rdma link show'."""
        result = subprocess.run(['rdma', 'link', 'show'], capture_output=True)
        # Parse device names from output...

    @classmethod
    def get_best_interface(cls) -> Optional[RDMAInterface]:
        """Priority: mlx5_* (hardware) > rxe* (soft-RoCE)"""
        interfaces = cls.discover_all()
        for iface in interfaces:
            if iface.device.startswith('mlx5_'):
                return iface
        for iface in interfaces:
            if iface.device.startswith('rxe'):
                return iface
        return interfaces[0] if interfaces else None
```

14.4.2 RDMATransport

Wraps ScuffedRDMA middleware for tensor transfer:

```
class RDMATransport:
    def connect(self, peer_node_id: str, peer_host: str, peer_port: int) -> bool:
        selector = TransportSelector('roce')
        self._transport = selector.get_transport(device=self._interface)
        self._transport.connect(peer_host, peer_port)
        return True

    def get_nccl_config(self) -> Dict[str, str]:
        """Get NCCL configuration for this transport."""
        if not self.is_available:
            return NCCLConfig.for_tcp().to_env()
        return NCCLConfig.for_softroce(device=self._interface).to_env()
```

14.4.3 RDMATopologyManager

Integrates with exo's topology system:

```
# exo/src/exo/networking/rdma_discovery_integration.py
```

```python
class RDMATopologyManager:
    def __init__(self, node_id: NodeId, topology: Topology):
        self.node_id = node_id
        self.topology = topology
        self._local_interface = RDMADiscovery.get_best_interface()

    def discover_and_update(self) -> int:
        """Discover RDMA connections and add to topology."""
        return update_topology_with_rdma(self.topology, self.node_id)

    def get_rdma_peers(self) -> list[NodeId]:
        """Get peers with RDMA connectivity."""
        return [conn.sink for conn in self.topology.out_edges(self.node_id)
                if isinstance(conn.edge, RDMAConnection)]
```

14.5 Leveraging Existing exo Types

The integration leverages exo's existing `RDMAConnection` type (previously unimplemented):

```python
# exo/src/exo/shared/types/topology.py (existing)
class RDMAConnection(FrozenModel):
    source_rdma_iface: str
    sink_rdma_iface: str
```

The placement utilities in `exo/master/placement_utils.py` already check for RDMA connections when selecting the jaccl backend:

```python
# exo/src/exo/master/placement_utils.py (existing, line 152-156)
def get_mlx_jaccl_devices_matrix(topology, cycle_node_ids):
    # jaccl requires all-to-all RDMA connections
    for conn in topology.get_all_connections_between(src, snk):
        if isinstance(conn.edge, RDMAConnection):
            # Can use jaccl backend with this connection
```

14.6 Integration Test Results

Tested on Hydra (control node without RDMA hardware):

```
$ python test_exo_rdma_integration.py

Testing EXO + RDMA Integration...
----------------------------------------
1. Testing middleware import... OK
2. Testing EXO RDMA transport import... OK
3. Testing RDMA discovery... OK (correctly shows unavailable)
4. Testing transport selector...
   - TCP: available
   - RoCE: not available (no rxe device)
   - TTPoe: not available (no kernel module)
5. Testing NCCL config generation... OK
6. Testing RDMA connection manager... OK
7. Testing topology integration... FAILED (Python 3.10 Self type)
----------------------------------------
```

The topology integration failure is due to Python 3.10 lacking the `Self` type hint (available in 3.11+). This can be resolved by using `from typing_extensions import Self` or updating the type hints.

14.7 Cluster Deployment

The integration enables RDMA-accelerated inference on the GPU cluster:

Node	IP	GPUs	RDMA Status
Chimera	192.168.1.150	3× RTX 3090	Soft-RoCE (rxe0)
Cerberus	192.168.1.233	2× RTX 5090	Soft-RoCE (rxe0)
Hydra	192.168.1.100	None (control)	N/A

Table 5: Cluster configuration for exo + RDMA testing

14.8 Source References

- **exo repository**: https://github.com/exo-explore/exo
- **PyTorch backend PR**: https://github.com/exo-explore/exo/pull/1284
- **exo topology types**: `exo/src/exo/shared/types/topology.py`
- **exo placement utilities**: `exo/src/exo/master/placement_utils.py`

15 Summary

This update delivers a complete transport middleware layer for ScuffedRDMA plus integration with the exo distributed inference framework:

- **Transport abstraction**: Unified API across TCP, RoCE, and TTPoe
- **Dynamic selection**: Runtime transport switching via environment or CLI
- **NCCL integration**: Automatic environment configuration for vLLM/Ray
- **Benchmark tooling**: Unified suite for transport comparison
- **Cluster management**: Scripts for multi-node deployment with transport flags
- **EXO integration**: RDMA transport modules for exo distributed inference (639 lines of code)
- **Topology discovery**: Automatic RDMA connection discovery and topology updates

The middleware establishes the foundation for adaptive transport selection in distributed LLM inference. The exo integration provides an alternative to vLLM+Ray with native peer-to-peer RDMA support, enabling testing on heterogeneous GPU clusters (RTX 3090 + RTX 5090).

15.1 Files Created This Session

```
exo/src/exo/networking/
  __init__.py                    # 27 lines - Module exports
  rdma_transport.py              # 369 lines - RDMA transport wrapper
  rdma_discovery_integration.py  # 247 lines - Topology integration
```

References

[1] exo-explore. (2025). *exo: Run your own AI cluster at home with everyday devices*. https://github.com/exo-explore/exo

[2] Linux RDMA. (2024). *rdma-core Documentation*. https://github.com/linux-rdma/rdma-core

[3] Tesla, Inc. (2024). *TTPoe: Time-Triggered Protocol over Ethernet*. https://github.com/teslamotors/ttpoe

[4] NVIDIA. (2024). *NCCL Documentation*. https://docs.nvidia.com/deeplearning/nccl/user-guide/docs/

[5] vLLM Team. (2024). *vLLM Documentation*. https://docs.vllm.ai/

[6] Anyscale. (2024). *Ray Documentation*. https://docs.ray.io/

[7] Linux RDMA. (2024). *pyverbs - Python bindings for rdma-core*. https://github.com/linux-rdma/rdma-core/tree/master/pyverbs