

OO Paradigm and UML

Object Oriented Programming



SoftEng
<http://softeng.polito.it>

© Maurizio Morisio, Marco Torchiano, 2016



Licensing Note






This work is licensed under the Creative Commons Attribution–NonCommercial–NoDerivatives 4.0 International License.

To view a copy of this license, visit

<http://creativecommons.org/licenses/by-nc-nd/4.0/>.

You are free: to copy, distribute, display, and perform the work

Under the following conditions:


-  **Attribution.** You must attribute the work in the manner specified by the author or licensor.
-  **Non–commercial.** You may not use this work for commercial purposes.
-  **No Derivative Works.** You may not alter, transform, or build upon this work.
 - For any reuse or distribution, you must make clear to others the license terms of this work.
 - Any of these conditions can be waived if you get permission from the copyright holder.

Your fair use and other rights are in no way affected by the above.

Programming paradigms

- Procedural (Pascal, C,...)
- Object–Oriented (C++, Java, C#,...)
- Functional (LISP, Haskell, SQL,...)
- Logic (Prolog)


Languages timeline



Popularity of Languages

TIOBE Programming Community Index

Source: www.tiobe.com



Procedural

```
int vect[20];  
void sort() { /* sort */ }  
int search(int n){ /* search */ }  
void init() { /* init */ }  
// ...  
void main() {  
    int i;  
    init();  
    sort();  
    i = search(13);  
}
```

Modules and relationships

■ Modules:



◆ Data

◆ Function (Procedure)

■ Relationships

◆ Call

◆ Read/write




Problems

- There is no syntactic relationship between:
 - ◆ Vectors (`int vect[20]`)
 - ◆ Operations on vectors (search, sort, init)
- There is no control over *size*:
`for (i=0; i<=20; i++) { vect[i]=0; };`
- Initialization
 - ◆ Actually performed?


The vector

- It's not possible to consider a vector as a primitive and modular concept
- Data and functions cannot be modularized properly




Procedural – problems

- No constraints on read/write relationships
- External functions can read/write vector's data



Procedural – In the long run

- (All) functions may read/write (all) data
- As time goes by, this leads to a growing number of relationships
- Source code becomes difficult to understand and maintain
 - ♦ Problem known as “Spaghetti code”



What is OO?

- Procedural Paradigm
 - ◆ Program defines data and then calls subprograms acting on data
- OO Paradigm
 - ◆ Program creates objects that encapsulate both the data and the procedures operating on data
- OO is simply a new way of organizing a program
 - ◆ Cannot do anything using OO that can't be done using procedural paradigm

Why OO?



- Programs are getting too large to be fully comprehensible by any person
- There is a need for a way of managing very-large projects
- Object Oriented paradigm allows:
 - ♦ programmers to (re)use large blocks of code
 - ♦ without knowing all the picture
- OO makes code reuse a real possibility
- OO simplifies maintenance and evolution

Why OO?

- Benefits only occur in larger programs
- Analogous to structured programming
 - ♦ Programs < 30 lines, spaghetti is as understandable and faster to write than structured
 - ♦ Programs $> 1\,000$ lines, spaghetti is incomprehensible, probably doesn't work, not maintainable
- Only programs $> 1\,000$ lines benefit from OO really


Object-Oriented Design

- Objects introduce an additional aggregation construct
- More complex system can be built




Procedural vs. OO

Procedural



Object Oriented



Object–Oriented approach

- Defines a new component type
 - ♦ Object (and class)
 - ♦ Both data and functions operating on data are within the same module
 - ♦ Allows defining a more precise interface
- Defines a new kind of relationship
 - ♦ Message passing
 - ♦ Read/write operations are limited to the object scope

Classification of OO languages

- **Object-Based** (Ada)
 - ◆ Specific constructs to manage objects
- **Class-Based** (CLU)
 - ◆ + each object belongs to a class
- **Object-Oriented** (Simula, Python)
 - ◆ + classes support inheritance
- **Strongly-Typed O-O** (C++, Java)
 - ◆ + the language is strongly typed

UML

- Unified Modeling Language
- Standardized modeling and specification language
 - Defined by the **Object Management Group** (OMG)
- **Graphical notation** to specify, visualize, construct and document an object-oriented system
- Integrates the concepts of Booch, OMT and OOSE, and merges them into a single, common and **widely used modeling language**



UML

- Several diagrams
 - ♦ Class diagrams
 - ♦ Activity diagrams
 - ♦ Use Case diagrams
 - ♦ Sequence diagrams
 - ♦ Statecharts

UML Class Diagram

- Captures
 - ◆ Main (abstract) concepts
 - ◆ Characteristics of the concepts
 - Data associated to the concepts
 - ◆ Relationships between concepts
 - ◆ Behavior of classes

Abstraction levels

Abstract

Concept
Entity
Class
Category
Type



Concrete

Instance
Item
Object
Example
Occurrence

Class

- Represents a type of objects
 - ◆ Common properties
 - ◆ Autonomous existence.
 - ◆ E.g. facts, things, people
- An instance of a class is an object of the type that the class represents.
 - ◆ In an application for a commercial organization CITY, DEPARTMENT, EMPLOYEE, PURCHASE and SALE are typical classes.

Class – Examples



Object

- Model of a physical or logical item
 - ♦ ex.: a student, an exam, a window
- Characterized by
 - ♦ identity
 - ♦ attributes (or data or properties or status)
 - ♦ operations it can perform (behavior)
 - ♦ messages it can receive

Object

DAUIN : Department

Jhn : Employee

Class and Object

- **Class** (the description of object structure, i.e. *type*):
 - ◆ Data (**ATTRIBUTES** or **FIELDS**)
 - ◆ Functions (**METHODS** or **OPERATIONS**)
 - ◆ Creation methods (**CONSTRUCTORS**)
- **Object** (class instance)
 - ◆ State and identity

Class and object


- A class is a type definition
 - ♦ Typically no memory is allocated until an object is created from the class
- The creation of an object is called **instantiation**. The created object is often called an **instance**
- There is no limit to the number of objects that can be created from a class
- Each object is independent. Interacting with one object doesn't affect the others

Message passing

- Objects communicate by message passing
 - ♦ Not by procedure call
 - ♦ Not by direct access to object's local data
- A message is a service request

Note: this is an abstract view that is independent from specific programming languages.

Object




Interface

- Set of messages an object can receive
- Any other message is illegal
- The message is mapped to a function within the object
- The object is responsible for the association (message, function)

Interface

- The **interface** of an object is simply the subset of methods that other “program parts” are allowed to call
 - ♦ Stable



Benefits of encapsulation

- To use an object, the user need only comprehend the interface. No knowledge of the internals are necessary
- Self-contained. Once the interface is defined, the programmer can implement the interface (write the object) without interference of others


Benefits of encapsulation

- Implementation can change at a later time without rewriting any other part of the program (as long as the interface doesn't change)
- Any change in the data structure means modifying the code in one location, rather than code scattered around the program (error prone)


Association

- Represents the logical links between two classes.
- An occurrence of an association is a pair made up of the occurrences of entities, one for each involved class
 - ♦ Residence can be an association between the classes City and Employee;
 - ♦ Exam can be an association between the classes Student and Course.



Associations



Association – Examples




Recursive association-Samples



Link


- Model of association between objects




Attribute

- Elementary property of classes
 - ♦ Name
 - ♦ Type
- An attribute associates to each object (occurrence of a class) a value of the corresponding type
 - ♦ Name: String
 - ♦ ID: Numeric
 - ♦ Salary: Currency

Attribute - Example




Attribute - Example



Method

- Describes an operation that can be performed on an object
 - ♦ Name
 - ♦ Parameters
 - ♦ Similar to functions in procedural languages
- It represent the means to operate on or access to the attributes


Method – Example




Multiplicity

- Describe the maximum and minimum number of links in which a class occurrence can participate
 - ◆ Undefined maximum expressed as *
- Should be specified for each class participating in an association

Multiplicity – Example




Multiplicity – Example




Multiplicity

- Typically, only three values are used: **0**, **1** and the symbol ***** (many)
- Minimum: 0 or 1
 - ♦ 0 means the participation is *optional*,
 - ♦ 1 means the participation is *mandatory*;
- Maximum: 1 or *
 - ♦ 1: each object is involved in at most one link
 - ♦ *: each object is involved in many links


Multiplicity




Exactly n




Zero or more



Between m and n (m,n included)





From m up




Zero or one (optional)

Multiplicity




Aggregation

- *B is-part-of A* means that objects described by class B can be attributes of objects described by A



Example




Inheritance

- A class can be a sub-type of another class
- The inheriting class contains all the methods and fields of the class it inherited from plus any methods and fields it defines
- The inheriting class can **override** the definition of existing methods by providing its own implementation
- The code of the inheriting class consists only of the changes and additions to the base class

Specialization / Generalization

- *B specializes A* means that objects described by B have the same properties of objects described by A
- Objects described by A may have additional properties
- B is a special case of A
- A is a generalization of B (and possible other classes)

Generalization




Inheritance terminology

- Class one above
 - ◆ Parent class
- Class one below
 - ◆ Child class
- Class one or more above
 - ◆ Superclass, Ancestor class, Base class
- Class one or more below
 - ◆ Subclass, Descendent class, Derived class

Why inheritance

- Frequently, a class is merely a modification of another class. In this way, there is minimal repetition of the same code
- Localization of code
 - ♦ Fixing a bug in the base class automatically fixes it in the subclasses
 - ♦ Adding functionality in the base class automatically adds it in the subclasses
 - ♦ Less chances of different (and inconsistent) implementations of the same operation

Example of inheritance tree



References

- Fowler, M. “UML Distilled: A Brief Guide to the Standard Object Modeling Language – 3rded.”, Addison–Wesley Professional (2003)