

Introduction to the Tidyverse

Lessons from DataCamp

Neil Yetz

Contents

Introduction	2
Course Description	2
Chapter 1: Data wrangling	2
Loading the gapminder and dplyr packages	2
Understanding a data frame	3
Filtering for one year	4
Filtering for one country and one year	4
Arranging observations by life expectancy	5
Filtering and arranging	5
Using mutate to change or create a column	6
Combining filter, mutate, and arrange	7
Chapter 2: Data Visualization	8
Variable assignment	8
Comparing population and GDP per capita	8
Comparing population and life expectancy	9
Putting the x-axis on a log scale	10
Putting the x- and y- axes on a log scale	11
Adding color to a scatter plot	12
Adding size and color to a plot	13
Creating a subgraph for each continent	14
Faceting by year	15
Chapter 3: Grouping and summarizing	16
Summarizing the median life expectancy	16
Summarizing the median life expectancy in 1957	17
Summarizing multiple variables in 1957	17
Summarizing by year	18
Summarizing by continent	18
Summarizing by continent and year	19
Comparing median life expectancy and median GDP per continent in 2007	20
Visualizing median life expectancy over time	21
Visualizing median GDP per capita per continent over time	22
Chapter 4: Types of Visualization	23
Visualizing median GDP per capita over time	23
Visualizing median GDP per capita by continent over time	24
Visualizing median GDP per capita by continent	25
Visualizing GDP per capita by country in Oceania	26
Visualizing population	27
Visualizing population with x-axis on a log scale	28
Comparing GDP per capita across continents	29
Adding a title to your graph	30

Introduction

The following document outlines the written portion of the lessons from DataCamp's Introduction to the Tidyverse. This works to develop skills within the tidyverse package.

As a note: All text is completely copied and pasted from the course. There are instances where the document refers to the “editor on the right”, please note, that in this notebook document all of these instances are noted in the “r-chunks” (areas containing working r-code), which occurs below the text, rather than to the right. Furthermore, This lesson contained instructional videos at the beginning of new concepts that are not detailed in this document. However, even without these videos, the instructions are quite clear in indicating what the code is accomplishing.

If you have this document open on “R-Notebook”, simply click “run” -> “Run all” (Or just press ‘ctrl + alt + r’), let the “r-chunks” run (This might take a bit of time) then click “Preview”. There are 5 necessary datasets to run this program, please create an r-project with this data or set a working directory (required files names are available in the “Required data for this session” section)

This document was created by Neil Yetz on 05/17/2018. Please send any questions or concerns in this document to Neil at ndyetz@gmail.com

Course Description

This is an introduction to the programming language R, focused on a powerful set of tools known as the “tidyverse”. In the course you’ll learn the intertwined processes of data manipulation and visualization through the tools dplyr and ggplot2. You’ll learn to manipulate data by filtering, sorting and summarizing a real dataset of historical country data in order to answer exploratory questions. You’ll then learn to turn this processed data into informative line plots, bar plots, histograms, and more with the ggplot2 package. This gives a taste both of the value of exploratory data analysis and the power of tidyverse tools. This is a suitable introduction for people who have no previous experience in R and are interested in learning to perform data analysis.

Chapter 1: Data wrangling

In this chapter, you’ll learn to do three things with a table: filter for particular observations, arrange the observations in a desired order, and mutate to add or change a column. You’ll see how each of these steps lets you answer questions about your data.

Loading the gapminder and dplyr packages

Before you can work with the `gapminder` dataset, you’ll need to load two R packages that contain the tools for working with it, then display the `gapminder` dataset so that you can see what it contains.

To your right, you’ll see two windows inside which you can enter code: The `script.R` window, and the R Console. All of your code to solve each exercise must go inside `script.R`.

If you hit Submit Answer, your R script is executed and the output is shown in the R Console. DataCamp checks whether your submission is correct and gives you feedback. You can hit Submit Answer as often as you want. If you’re stuck, you can ask for a hint or a solution.

You can use the R Console interactively by simply typing R code and hitting Enter. When you work in the console directly, your code will not be checked for correctness so it is a great way to experiment and explore.

INSTRUCTIONS

Use the `library()` function to load the `dplyr` package, just like we've loaded the `gapminder` package for you.

Type `gapminder`, on its own line, to look at the `gapminder` dataset.

```
# Load the gapminder package
#install.packages("gapminder")
library(gapminder)

# Load the dplyr package
#install.packages("dplyr")
library(dplyr)

##
## Attaching package: 'dplyr'

## The following objects are masked from 'package:stats':
##
##   filter, lag

## The following objects are masked from 'package:base':
##
##   intersect, setdiff, setequal, union

# Look at the gapminder dataset
gapminder

## # A tibble: 1,704 x 6
##   country      continent year lifeExp      pop gdpPercap
##   <fct>         <fct>    <int>  <dbl>    <int>    <dbl>
## 1 Afghanistan Asia      1952   28.8  8425333    779.
## 2 Afghanistan Asia      1957   30.3  9240934    821.
## 3 Afghanistan Asia      1962   32.0 10267083    853.
## 4 Afghanistan Asia      1967   34.0 11537966    836.
## 5 Afghanistan Asia      1972   36.1 13079460    740.
## 6 Afghanistan Asia      1977   38.4 14880372    786.
## 7 Afghanistan Asia      1982   39.9 12881816    978.
## 8 Afghanistan Asia      1987   40.8 13867957    852.
## 9 Afghanistan Asia      1992   41.7 16317921    649.
## 10 Afghanistan Asia      1997   41.8 22227415    635.
## # ... with 1,694 more rows
```

Understanding a data frame

Now that you've loaded the `gapminder` dataset, you can start examining and understanding it.

We've already loaded the `gapminder` and `dplyr` packages. Type `gapminder` in your R terminal, to the lower right, to display the object.

How many observations (rows) are in the dataset?

Possible Answers (Correct Answer is **Bolded**)

1704

6

1694

1952

Filtering for one year

The `filter` verb extracts particular observations based on a condition. In this exercise you'll filter for observations from a particular year.

INSTRUCTIONS

Add a `filter()` line after the pipe (`%>%`) to extract only the observations from the year 1957. Remember that you use `==` to compare two values.

```
library(gapminder)
library(dplyr)

# Filter the gapminder dataset for the year 1957
gapminder %>%
  filter(year == 1957)
```

```
## # A tibble: 142 x 6
##   country    continent  year lifeExp      pop gdpPercap
##   <fct>      <fct>    <int> <dbl>    <int>    <dbl>
## 1 Afghanistan Asia      1957  30.3  9240934    821.
## 2 Albania    Europe    1957  59.3  1476505   1942.
## 3 Algeria    Africa    1957  45.7 10270856   3014.
## 4 Angola     Africa    1957  32.0  4561361   3828.
## 5 Argentina  Americas  1957  64.4 19610538   6857.
## 6 Australia  Oceania   1957  70.3  9712569  10950.
## 7 Austria    Europe    1957  67.5  6965860   8843.
## 8 Bahrain    Asia      1957  53.8   138655  11636.
## 9 Bangladesh Asia      1957  39.3 51365468    662.
## 10 Belgium   Europe    1957  69.2  8989111   9715.
## # ... with 132 more rows
```

Filtering for one country and one year

You can also use the `filter()` verb to set two conditions, which could retrieve a single observation.

Just like in the last exercise, you can do this in two lines of code, starting with `gapminder %>%` and having the `filter()` on the second line. Keeping one verb on each line helps keep the code readable. Note that each time, you'll put the pipe `%>%` at the end of the first line (like `gapminder %>%`); putting the pipe at the beginning of the second line will throw an error.

```
library(gapminder)
library(dplyr)

# Filter for China in 2002
gapminder %>%
  filter(country == "China", year == 2002)
```

```
## # A tibble: 1 x 6
##   country continent  year lifeExp      pop gdpPercap
##   <fct>    <fct>    <int> <dbl>    <int>    <dbl>
## 1 China   Asia      2002  72.0 1280400000   3119.
```

Arranging observations by life expectancy

You use `arrange()` to sort observations in ascending or descending order of a particular variable. In this case, you'll sort the dataset based on the `lifeExp` variable.

INSTRUCTIONS

Sort the `gapminder` dataset in ascending order of life expectancy (`lifeExp`). Sort the `gapminder` dataset in descending order of life expectancy.

```
library(gapminder)
library(dplyr)

# Sort in ascending order of lifeExp
gapminder %>%
  arrange(lifeExp)

## # A tibble: 1,704 x 6
##   country      continent year lifeExp      pop gdpPercap
##   <fct>         <fct>    <int>   <dbl>   <int>    <dbl>
## 1 Rwanda        Africa    1992    23.6  7290203    737.
## 2 Afghanistan  Asia      1952    28.8  8425333    779.
## 3 Gambia        Africa    1952    30.0   284320    485.
## 4 Angola        Africa    1952    30.0  4232095   3521.
## 5 Sierra Leone Africa    1952    30.3  2143249    880.
## 6 Afghanistan  Asia      1957    30.3  9240934    821.
## 7 Cambodia      Asia      1977    31.2  6978607    525.
## 8 Mozambique    Africa    1952    31.3  6446316    469.
## 9 Sierra Leone Africa    1957    31.6  2295678   1004.
## 10 Burkina Faso Africa    1952    32.0  4469979    543.
## # ... with 1,694 more rows
```

```
# Sort in descending order of lifeExp
gapminder %>%
  arrange(desc(lifeExp))

## # A tibble: 1,704 x 6
##   country      continent year lifeExp      pop gdpPercap
##   <fct>         <fct>    <int>   <dbl>   <int>    <dbl>
## 1 Japan        Asia      2007    82.6 127467972  31656.
## 2 Hong Kong, China Asia      2007    82.2  6980412   39725.
## 3 Japan        Asia      2002    82.0 127065841  28605.
## 4 Iceland      Europe    2007    81.8   301931   36181.
## 5 Switzerland Europe    2007    81.7  7554661   37506.
## 6 Hong Kong, China Asia      2002    81.5  6762476   30209.
## 7 Australia    Oceania   2007    81.2 20434176  34435.
## 8 Spain        Europe    2007    80.9  40448191  28821.
## 9 Sweden       Europe    2007    80.9  9031088   33860.
## 10 Israel      Asia      2007    80.7  6426679   25523.
## # ... with 1,694 more rows
```

Filtering and arranging

You'll often need to use the pipe operator (`%>%`) to combine multiple dplyr verbs in a row. In this case, you'll combine a `filter()` with an `arrange()` to find the highest population countries in a particular year.

INSTRUCTIONS

Use `filter()` to extract observations from just the year 1957, then use `arrange()` to sort in descending order of population (`pop`).

```
library(gapminder)
library(dplyr)

# Filter for the year 1957, then arrange in descending order of population

gapminder %>%
  filter(year == 1957) %>%
  arrange(desc(pop))
```

```
## # A tibble: 142 x 6
##   country      continent  year lifeExp      pop gdpPercap
##   <fct>        <fct>    <int>  <dbl>    <int>    <dbl>
## 1 China        Asia      1957   50.5 637408000    576.
## 2 India        Asia      1957   40.2 409000000    590.
## 3 United States Americas  1957   69.5 171984000   14847.
## 4 Japan        Asia      1957   65.5  91563009    4318.
## 5 Indonesia    Asia      1957   39.9  90124000    859.
## 6 Germany      Europe    1957   69.1  71019069   10188.
## 7 Brazil       Americas  1957   53.3  65551171    2487.
## 8 United Kingdom Europe    1957   70.4  51430000   11283.
## 9 Bangladesh   Asia      1957   39.3  51365468    662.
## 10 Italy        Europe    1957   67.8  49182000   6249.
## # ... with 132 more rows
```

Using mutate to change or create a column

Suppose we want life expectancy to be measured in months instead of years: you'd have to multiply the existing value by 12. You can use the `mutate()` verb to change this column, or to create a new column that's calculated this way.

INSTRUCTIONS

Use `mutate()` to change the existing `lifeExp` column, by multiplying it by 12: `12 * lifeExp`.

Use `mutate()` to add a new column, called `lifeExpMonths`, calculated as `12 * lifeExp`.

```
library(gapminder)
library(dplyr)

# Use mutate to change lifeExp to be in months
gapminder %>%
  mutate(lifeExp = lifeExp * 12)
```

```
## # A tibble: 1,704 x 6
##   country      continent  year lifeExp      pop gdpPercap
##   <fct>        <fct>    <int>  <dbl>    <int>    <dbl>
## 1 Afghanistan Asia      1952   346.  8425333    779.
## 2 Afghanistan Asia      1957   364.  9240934    821.
## 3 Afghanistan Asia      1962   384. 10267083    853.
## 4 Afghanistan Asia      1967   408. 11537966    836.
## 5 Afghanistan Asia      1972   433. 13079460    740.
## 6 Afghanistan Asia      1977   461. 14880372    786.
```

```
## 7 Afghanistan Asia      1982    478. 12881816    978.
## 8 Afghanistan Asia      1987    490. 13867957    852.
## 9 Afghanistan Asia      1992    500. 16317921    649.
## 10 Afghanistan Asia     1997    501. 22227415    635.
## # ... with 1,694 more rows
```

```
# Use mutate to create a new column called lifeExpMonths
gapminder %>%
  mutate(lifeExpMonths = 12 * lifeExp)
```

```
## # A tibble: 1,704 x 7
##   country      continent  year lifeExp      pop gdpPercap lifeExpMonths
##   <fct>         <fct>    <int>  <dbl>    <int>    <dbl>      <dbl>
## 1 Afghanistan Asia      1952   28.8  8425333    779.        346.
## 2 Afghanistan Asia      1957   30.3  9240934    821.        364.
## 3 Afghanistan Asia      1962   32.0 10267083    853.        384.
## 4 Afghanistan Asia      1967   34.0 11537966    836.        408.
## 5 Afghanistan Asia      1972   36.1 13079460    740.        433.
## 6 Afghanistan Asia      1977   38.4 14880372    786.        461.
## 7 Afghanistan Asia      1982   39.9 12881816    978.        478.
## 8 Afghanistan Asia      1987   40.8 13867957    852.        490.
## 9 Afghanistan Asia      1992   41.7 16317921    649.        500.
## 10 Afghanistan Asia     1997   41.8 22227415    635.        501.
## # ... with 1,694 more rows
```

Combining filter, mutate, and arrange

In this exercise, you'll combine all three of the verbs you've learned in this chapter, to find the countries with the highest life expectancy, in months, in the year 2007.

INSTRUCTIONS

- In one sequence of pipes on the gapminder dataset:
- `filter()` for observations from the year 2007,
- `mutate()` to create a column `lifeExpMonths`, calculated as `12 * lifeExp`, and
- `arrange()` in descending order of that new column

```
library(gapminder)
library(dplyr)

# Filter, mutate, and arrange the gapminder dataset
gapminder %>%
  filter(year == 2007) %>%
  mutate(lifeExpMonths = lifeExp * 12) %>%
  arrange(desc(lifeExpMonths))
```

```
## # A tibble: 142 x 7
##   country      continent  year lifeExp      pop gdpPercap lifeExpMonths
##   <fct>         <fct>    <int>  <dbl>    <int>    <dbl>      <dbl>
## 1 Japan        Asia      2007   82.6  1.27e8   31656.        991.
## 2 Hong Kong, China Asia      2007   82.2  6.98e6   39725.        986.
## 3 Iceland      Europe    2007   81.8  3.02e5   36181.        981.
## 4 Switzerland Europe    2007   81.7  7.55e6   37506.        980.
## 5 Australia    Oceania   2007   81.2  2.04e7   34435.        975.
```

```
## 6 Spain           Europe      2007      80.9 4.04e7      28821.      971.
## 7 Sweden          Europe      2007      80.9 9.03e6      33860.      971.
## 8 Israel          Asia        2007      80.7 6.43e6      25523.      969.
## 9 France          Europe      2007      80.7 6.11e7      30470.      968.
## 10 Canada         Americas   2007      80.7 3.34e7      36319.      968.
## # ... with 132 more rows
```

Chapter 2: Data Visualization

You’ve already been able to answer some questions about the data through `dplyr`, but you’ve engaged with them just as a table (such as one showing the life expectancy in the US each year). Often a better way to understand and present such data is as a graph. Here you’ll learn the essential skill of data visualization, using the `ggplot2` package. Visualization and manipulation are often intertwined, so you’ll see how the `dplyr` and `ggplot2` packages work closely together to create informative graphs.

Variable assignment

Throughout the exercises in this chapter, you’ll be visualizing a subset of the `gapminder` data from the year 1952. First, you’ll have to load the `ggplot2` package, and create a `gapminder_1952` dataset to visualize.

INSTRUCTIONS

Load the `ggplot2` package after the `gapminder` and `dplyr` packages. Filter `gapminder` for observations from the year 1952, and assign it to a new dataset `gapminder_1952` using the assignment operator (`<-`).

```
# Load the ggplot2 package as well
library(gapminder)
library(dplyr)
library(ggplot2)

# Create gapminder_1952
gapminder_1952 <- gapminder %>%
  filter(year == 1952)
```

Comparing population and GDP per capita

In the video you learned to create a scatter plot with GDP per capita on the x-axis and life expectancy on the y-axis (the code for that graph is shown here). When you’re exploring data visually, you’ll often need to try different combinations of variables and aesthetics.

INSTRUCTIONS

Change the scatter plot of `gapminder_1952` so that (`pop`) is on the x-axis and GDP per capita (`gdpPercap`) is on the y-axis.


```
library(gapminder)
library(dplyr)
library(ggplot2)

gapminder_1952 <- gapminder %>%
  filter(year == 1952)

# Change to put pop on the x-axis and gdpPercap on the y-axis
```



```
ggplot(gapminder_1952, aes(x = pop, y = gdpPercap)) +  
  geom_point()
```




Comparing population and life expectancy

In this exercise, you'll use `ggplot2` to create a scatter plot from scratch, to compare each country's population with its life expectancy in the year 1952.

INSTRUCTIONS

Create a scatter plot of `gapminder_1952` with population (`pop`) on the x-axis and life expectancy (`lifeExp`) on the y-axis.

```
library(gapminder)  
library(dplyr)  
library(ggplot2)  
  
gapminder_1952 <- gapminder %>%  
  filter(year == 1952)  
  
# Create a scatter plot with pop on the x-axis and lifeExp on the y-axis  
ggplot(gapminder_1952, aes(x = pop, y = lifeExp)) +  
  geom_point()
```



Putting the x-axis on a log scale

You previously created a scatter plot with population on the x-axis and life expectancy on the y-axis. Since population is spread over several orders of magnitude, with some countries having a much higher population than others, it's a good idea to put the x-axis on a log scale.


INSTRUCTIONS

Change the existing scatter plot (code provided) to put the x-axis (representing population) on a log scale.

```
library(gapminder)
library(dplyr)
library(ggplot2)

gapminder_1952 <- gapminder %>%
  filter(year == 1952)

# Change this plot to put the x-axis on a log scale
ggplot(gapminder_1952, aes(x = pop, y = lifeExp)) +
  geom_point() +
  scale_x_log10()
```



Putting the x- and y- axes on a log scale

Suppose you want to create a scatter plot with population on the x-axis and GDP per capita on the y-axis. Both population and GDP per-capita are better represented with log scales, since they vary over many orders of magnitude.


INSTRUCTIONS

Create a scatter plot with population (`pop`) on the x-axis and GDP per capita (`gdpPerCap`) on the y-axis. Put both the x- and y- axes on a log scale.

```
library(gapminder)
library(dplyr)
library(ggplot2)

gapminder_1952 <- gapminder %>%
  filter(year == 1952)

# Scatter plot comparing pop and gdpPerCap, with both axes on a log scale
ggplot(gapminder_1952, aes(x = pop, y = gdpPerCap)) +
  geom_point() +
  scale_x_log10() +
  scale_y_log10()
```



Adding color to a scatter plot

In this lesson you learned how to use the color aesthetic, which can be used to show which continent each point in a scatter plot represents.


INSTRUCTIONS

Create a scatter plot with population (`pop`) on the x-axis, life expectancy (`lifeExp`) on the y-axis, and with continent (`continent`) represented by the color of the points. Put the x-axis on a log scale.

```
library(gapminder)
library(dplyr)
library(ggplot2)

gapminder_1952 <- gapminder %>%
  filter(year == 1952)

# Scatter plot comparing pop and lifeExp, with color representing continent
ggplot(gapminder_1952, aes(x = pop, y = lifeExp, color = continent)) +
  geom_point() +
  scale_x_log10()
```



Adding size and color to a plot

In the last exercise, you created a scatter plot communicating information about each country's population, life expectancy, and continent. Now you'll use the size of the points to communicate even more.


INSTRUCTIONS

Modify the scatter plot so that the size of the points represents each country's GDP per capita (`gdpPercap`).

```
library(gapminder)
library(dplyr)
library(ggplot2)

gapminder_1952 <- gapminder %>%
  filter(year == 1952)

# Add the size aesthetic to represent a country's gdpPercap
ggplot(gapminder_1952, aes(x = pop, y = lifeExp, color = continent,
                           size = gdpPercap)) +
  geom_point() +
  scale_x_log10()
```



Creating a subgraph for each continent

You've learned to use faceting to divide a graph into subplots based on one of its variables, such as the continent.


INSTRUCTIONS

Create a scatter plot of `gapminder_1952` with the x-axis representing population (`pop`), the y-axis representing life expectancy (`lifeExp`), and faceted to have one subplot per continent (`continent`). Put the x-axis on a log scale.

```
library(gapminder)
library(dplyr)
library(ggplot2)

gapminder_1952 <- gapminder %>%
  filter(year == 1952)

# Scatter plot comparing pop and lifeExp, faceted by continent
ggplot(gapminder_1952, aes(x = pop, y = lifeExp)) +
  geom_point() +
  scale_x_log10() +
  facet_wrap(~ continent)
```



Faceting by year

All of the graphs in this chapter have been visualizing statistics within one year. Now that you're able to use faceting, however, you can create a graph showing all the country-level data from 1952 to 2007, to understand how global statistics have changed over time.

INSTRUCTIONS

Create a scatter plot of the gapminder data:

- Put GDP per capita (`gdpPercap`) on the x-axis and life expectancy (`lifeExp`) on the y-axis, with continent (`continent`) represented by color and population (`pop`) represented by size.
- Put the x-axis on a log scale
- Facet by the `year` variable

```
library(gapminder)
library(dplyr)
library(ggplot2)

# Scatter plot comparing gdpPercap and lifeExp, with color representing continent
# and size representing population, faceted by year

ggplot(gapminder, aes(x = gdpPercap, y = lifeExp, color = continent,
                      size = pop)) +
  geom_point() +
```

```
scale_x_log10() +  
facet_wrap(~ year)
```



Chapter 3: Grouping and summarizing

So far you've been answering questions about individual country-year pairs, but we may be interested in aggregations of the data, such as the average life expectancy of all countries within each year. Here you'll learn to use the `group by` and `summarize` verbs, which collapse large datasets into manageable summaries.

Summarizing the median life expectancy

You've seen how to find the mean life expectancy and the total population across a set of observations, but `mean()` and `sum()` are only two of the functions R provides for summarizing a collection of numbers. Here, you'll learn to use the `median()` function in combination with `summarize()`.

By the way, `dplyr` displays some messages when it's loaded that we've been hiding so far. They'll show up in red and start with:

```
Attaching package: 'dplyr'
```

```
The following objects are masked from 'package:stats':
```

This will occur in future exercises each time you load `dplyr`: it's mentioning some built-in functions that are overwritten by `dplyr`. You won't need to worry about this message within this course.

INSTRUCTIONS

Use the `median()` function within a `summarize()` to find the median life expectancy. Save it into a column called `medianLifeExp`.

```
library(gapminder)
library(dplyr)

# Summarize to find the median life expectancy
gapminder %>%
  summarize(medianLifeExp = median(lifeExp))
```

```
## # A tibble: 1 x 1
##   medianLifeExp
##           <dbl>
## 1           60.7
```

Summarizing the median life expectancy in 1957

Rather than summarizing the entire dataset, you may want to find the median life expectancy for only one particular year. In this case, you'll find the median in the year 1957.

INSTRUCTIONS

Filter for the year 1957, then use the `median()` function within a `summarize()` to calculate the median life expectancy into a column called `medianLifeExp`

.

```
library(gapminder)
library(dplyr)

# Filter for 1957 then summarize the median life expectancy
gapminder %>%
  filter(year == 1957) %>%
  summarize(medianLifeExp = median(lifeExp))
```

```
## # A tibble: 1 x 1
##   medianLifeExp
##           <dbl>
## 1           48.4
```

Summarizing multiple variables in 1957

The `summarize()` verb allows you to summarize multiple variables at once. In this case, you'll use the `median()` function to find the median life expectancy and the `max()` function to find the maximum GDP per capita.

INSTRUCTIONS

Find both the median life expectancy (`lifeExp`) and the maximum GDP per capita (`gdpPercap`) in the year 1957, calling them `medianLifeExp` and `maxGdpPercap` respectively. You can use the `max()` function to find the maximum.

```
library(gapminder)
library(dplyr)
```

```
# Filter for 1957 then summarize the median life expectancy and the maximum GDP per capita
gapminder %>%
  filter(year == 1957) %>%
  summarize(medianLifeExp = median(lifeExp), maxGdpPerCap = max(gdpPerCap))

## # A tibble: 1 x 2
##   medianLifeExp maxGdpPerCap
##           <dbl>         <dbl>
## 1         48.4       113523.
```

Summarizing by year

In a previous exercise, you found the median life expectancy and the maximum GDP per capita in the year 1957. Now, you'll perform those two summaries within each year in the dataset, using the `group_by` verb.

INSTRUCTIONS

Find the median life expectancy (`lifeExp`) and maximum GDP per capita (`gdpPerCap`) within each year, saving them into `medianLifeExp` and `maxGdpPerCap`, respectively.

```
library(gapminder)
library(dplyr)

# Find median life expectancy and maximum GDP per capita in each year
gapminder %>%
  group_by(year) %>%
  summarize(medianLifeExp = median(lifeExp), maxGdpPerCap = max(gdpPerCap))
```

```
## # A tibble: 12 x 3
##   year medianLifeExp maxGdpPerCap
##   <int>         <dbl>         <dbl>
## 1  1952         45.1       108382.
## 2  1957         48.4       113523.
## 3  1962         50.9        95458.
## 4  1967         53.8        80895.
## 5  1972         56.5       109348.
## 6  1977         59.7        59265.
## 7  1982         62.4        33693.
## 8  1987         65.8        31541.
## 9  1992         67.7        34933.
## 10 1997         69.4        41283.
## 11 2002         70.8        44684.
## 12 2007         71.9        49357.
```

Summarizing by continent

You can group by any variable in your dataset to create a summary. Rather than comparing across time, you might be interested in comparing among continents. You'll want to do that within one year of the dataset: let's use 1957.

INSTRUCTIONS

Filter the `gapminder` data for the year 1957. Then find the median life expectancy (`lifeExp`) and maximum GDP per capita (`gdpPerCap`) within each continent, saving them into `medianLifeExp` and `maxGdpPerCap`, respectively.

```
library(gapminder)
library(dplyr)

# Find median life expectancy and maximum GDP per capita in each continent in 1957
gapminder %>%
  filter(year == 1957) %>%
  group_by(continent) %>%
  summarize(medianLifeExp = median(lifeExp), maxGdpPercap = max(gdpPercap))

## # A tibble: 5 x 3
##   continent medianLifeExp maxGdpPercap
##   <fct>         <dbl>         <dbl>
## 1 Africa         40.6         5487.
## 2 Americas       56.1        14847.
## 3 Asia           48.3       113523.
## 4 Europe         67.6        17909.
## 5 Oceania        70.3        12247.
```

Summarizing by continent and year

Instead of grouping just by year, or just by continent, you'll now group by both continent and year to summarize within each.

INSTRUCTIONS

Find the median life expectancy (`lifeExp`) and maximum GDP per capita (`gdpPercap`) within each combination of continent and year, saving them into `medianLifeExp` and `maxGdpPercap`, respectively.

```
library(gapminder)
library(dplyr)

# Find median life expectancy and maximum GDP per capita in each year/continent combination
gapminder %>%
  group_by(continent, year) %>%
  summarize(medianLifeExp = median(lifeExp), maxGdpPercap = max(gdpPercap))

## # A tibble: 60 x 4
## # Groups:   continent [?]
##   continent year medianLifeExp maxGdpPercap
##   <fct>     <int>         <dbl>         <dbl>
## 1 Africa   1952          38.8         4725.
## 2 Africa   1957          40.6         5487.
## 3 Africa   1962          42.6         6757.
## 4 Africa   1967          44.7        18773.
## 5 Africa   1972          47.0        21011.
## 6 Africa   1977          49.3        21951.
## 7 Africa   1982          50.8        17364.
## 8 Africa   1987          51.6        11864.
## 9 Africa   1992          52.4        13522.
## 10 Africa  1997          52.8        14723.
## # ... with 50 more rows
```

Comparing median life expectancy and median GDP per continent in 2007

In these exercises you've generally created plots that show change over time. But as another way of exploring your data visually, you can also use ggplot2 to plot summarized data to compare continents within a single year.


INSTRUCTIONS

- Filter the gapminder dataset for the year 2007, then summarize the median GDP per capita and the median life expectancy within each continent, into columns called `medianLifeExp` and `medianGdpPercap`. Save this as `by_continent_2007`.
- Use the `by_continent_2007` data to create a scatterplot comparing these summary statistics for continents in 2007, putting the median GDP per capita on the x-axis to the median life expectancy on the y-axis. Color the scatter plot by `continent`. You don't need to add `expand_limits(y = 0)` for this plot.

```
library(gapminder)
library(dplyr)
library(ggplot2)

# Summarize the median GDP and median life expectancy per continent in 2007
by_continent_2007 <- gapminder %>%
  filter(year == 2007) %>%
  group_by(continent) %>%
  summarize(medianLifeExp = median(lifeExp),
            medianGdpPercap = median(gdpPercap)
  )

# Use a scatter plot to compare the median GDP and median life expectancy
ggplot(by_continent_2007, aes(x = medianGdpPercap, y = medianLifeExp, color = continent)) +
  geom_point()
```



Visualizing median life expectancy over time

In the last chapter, you summarized the gapminder data to calculate the median life expectancy within each year. This code is provided for you, and is saved (with <-) as the `by_year` dataset.

Now you can use the `ggplot2` package to turn this into a visualization of changing life expectancy over time.


INSTRUCTIONS

Use the `by_year` dataset to create a scatter plot showing the change of median life expectancy over time, with `year` on the x-axis and `medianLifeExp` on the y-axis. Be sure to add `expand_limits(y = 0)` to make sure the plot's y-axis includes zero.

```
library(gapminder)
library(dplyr)
library(ggplot2)

by_year <- gapminder %>%
  group_by(year) %>%
  summarize(medianLifeExp = median(lifeExp),
            maxGdpPercap = max(gdpPercap))

# Create a scatter plot showing the change in medianLifeExp over time
ggplot(by_year, aes(x = year, y = medianLifeExp)) +
  geom_point() +
  expand_limits(y = 0)
```



Visualizing median GDP per capita per continent over time

In the last exercise you were able to see how the median life expectancy of countries changed over time. Now you'll examine the median GDP per capita instead, and see how the trend differs among continents.

INSTRUCTIONS


Summarize the `gapminder` dataset by continent and year, finding the median GDP per capita (`medianGdpPercap`) within each and putting it into a column called `medianGdpPercap`. Use the assignment operator `<-` to save this summarized data as `by_year_continent`.

Create a scatter plot showing the change in `medianGdpPercap` by continent over time. Use color to distinguish between continents, and be sure to add `expand_limits(y = 0)` so that the y-axis starts at zero.

```
library(gapminder)
library(dplyr)
library(ggplot2)

# Summarize medianGdpPercap within each continent within each year: by_year_continent
by_year_continent <- gapminder %>%
  group_by(year, continent) %>%
  summarize(medianGdpPercap = median(gdpPercap))

# Plot the change in medianGdpPercap in each continent over time
ggplot(by_year_continent, aes(x = year, y = medianGdpPercap, color = continent)) +
  geom_point() +
  expand_limits(y = 0)
```



Chapter 4: Types of Visualization

You've learned to create scatter plots with `ggplot2`. In this chapter you'll learn to create line plots, bar plots, histograms, and boxplots. You'll see how each plot needs different kinds of data manipulation to prepare for it, and understand the different roles of each of these plot types in data analysis.

Visualizing median GDP per capita over time

A line plot is useful for visualizing trends over time. In this exercise, you'll examine how the median GDP per capita has changed over time.

INSTRUCTIONS

Use `group_by()` and `summarize()` to find the median GDP per capita within each year, calling the output column `medianGdpPerCap`. Use the assignment operator `<-` to save it to a dataset called `by_year`.


Use the `by_year` dataset to create a line plot showing the change in median GDP per capita over time. Be sure to use `expand_limits(y = 0)` to include 0 on the y-axis.

```
library(gapminder)
library(dplyr)
library(ggplot2)

# Summarize the median gdpPerCap by year, then save it as by_year
by_year <- gapminder %>%
```

```
group_by(year) %>%
  summarize(medianGdpPercap = median(gdpPercap))

# Create a line plot showing the change in medianGdpPercap over time
ggplot(by_year, aes(x = year, y = medianGdpPercap)) +
  geom_line() +
  expand_limits(y = 0)
```



Visualizing median GDP per capita by continent over time

In the last exercise you used a line plot to visualize the increase in median GDP per capita over time. Now you'll examine the change within each continent.

INSTRUCTIONS

Use `group_by()` and `summarize()` to find the median GDP per capita within each year and continent, calling the output column `medianGdpPercap`. Use the assignment operator `<-` to save it to a dataset called `by_year_continent`.

Use the `by_year_continent` dataset to create a line plot showing the change in median GDP per capita over time, with color representing continent. Be sure to use `expand_limits(y = 0)` to include 0 on the y-axis.


```
library(gapminder)
library(dplyr)
library(ggplot2)

# Summarize the median gdpPercap by year & continent, save as by_year_continent
```



```
by_year_continent <- gapminder %>%
  group_by(year, continent) %>%
  summarize(medianGdpPercap = median(gdpPercap))

# Create a line plot showing the change in medianGdpPercap by continent over time
ggplot(by_year_continent, aes(x = year, y = medianGdpPercap, color = continent)) +
  geom_line() +
  expand_limits(y = 0)
```



Visualizing median GDP per capita by continent

A bar plot is useful for visualizing summary statistics, such as the median GDP in each continent.

INSTRUCTIONS

Use `group_by()` and `summarize()` to find the median GDP per capita within each continent in the year 1952, calling the output column `medianGdpPercap`. Use the assignment operator `<-` to save it to a dataset called `by_continent`.

Use the `by_continent` dataset to create a bar plot showing the median GDP per capita in each continent.

```
library(gapminder)
library(dplyr)
library(ggplot2)


# Summarize the median gdpPercap by year and continent in 1952
by_continent <- gapminder %>%
```

```

filter(year == 1952) %>%
group_by(continent) %>%
summarize(medianGdpPercap = median(gdpPercap))

# Create a bar plot showing medianGdp by continent
ggplot(by_continent, aes(x = continent, y = medianGdpPercap)) +
  geom_col()

```



Visualizing GDP per capita by country in Oceania

You've created a plot where each bar represents one continent, showing the median GDP per capita for each. But the x-axis of the bar plot doesn't have to be the continent: you can instead create a bar plot where each bar represents a country.

In this exercise, you'll create a bar plot comparing the GDP per capita between the two countries in the Oceania continent (Australia and New Zealand).

INSTRUCTIONS

Filter for observations in the Oceania continent in the year 1952. Save this as `oceania_1952`.

Use the `oceania_1952` dataset to create a bar plot, with `country` on the x-axis and `gdpPercap` on the y-axis.


```

library(gapminder)
library(dplyr)
library(ggplot2)

```

```
# Filter for observations in the Oceania continent in 1952
oceania_1952 <- gapminder %>%
  filter(continent == "Oceania" & year == 1952) %>%
  group_by(country)

# Create a bar plot of gdpPerCap by country
ggplot(oceania_1952, aes(x = country, y = gdpPerCap)) +
  geom_col()
```



Visualizing population

A histogram is useful for examining the distribution of a numeric variable. In this exercise, you'll create a histogram showing the distribution of country populations in the year 1952.

INSTRUCTIONS


Use the `gapminder_1952` dataset (code for generating that dataset is provided) to create a histogram of country population (`pop`) in the year 1952.

```
library(gapminder)
library(dplyr)
library(ggplot2)

gapminder_1952 <- gapminder %>%
  filter(year == 1952)
```

```
# Create a histogram of population (pop)
ggplot(gapminder_1952, aes(x = pop)) +
  geom_histogram()
```

```
## `stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```



Visualizing population with x-axis on a log scale

In the last exercise you created a histogram of populations across countries. You might have noticed that there were several countries with a much higher population than others, which causes the distribution to be very skewed, with most of the distribution crammed into a small part of the graph. (Consider that it's hard to tell the median or the minimum population from that histogram).

To make the histogram more informative, you can try putting the x-axis on a log scale.

INSTRUCTIONS


Use the `gapminder_1952` dataset (code is provided) to create a histogram of country population (`pop`) in the year 1952, putting the x-axis on a log scale with `scale_x_log10()`.

```
library(gapminder)
library(dplyr)
library(ggplot2)

gapminder_1952 <- gapminder %>%
  filter(year == 1952)
```

```
# Create a histogram of population (pop), with x on a log scale
ggplot(gapminder_1952, aes(x = pop)) +
  geom_histogram() +
  scale_x_log10()
```

```
## `stat_bin()` using `bins = 30`. Pick better value with `binwidth`.
```



Comparing GDP per capita across continents

A boxplot is useful for comparing a distribution of values across several groups. In this exercise, you'll examine the distribution of GDP per capita by continent. Since GDP per capita varies across several orders of magnitude, you'll need to put the y-axis on a log scale.

INSTRUCTIONS


Use the `gapminder_1952` dataset (code is provided) to create a boxplot comparing GDP per capita (`gdpPercap`) among continents. Put the y-axis on a log scale with `scale_y_log10()`.

```
library(gapminder)
library(dplyr)
library(ggplot2)
```

```
gapminder_1952 <- gapminder %>%
  filter(year == 1952)
```

```
# Create a boxplot comparing gdpPercap among continents
```

```
ggplot(gapminder_1952, aes(x = continent, y = gdpPercap)) +  
  geom_boxplot() +  
  scale_y_log10()
```



Adding a title to your graph

There are many other options for customizing a `ggplot2` graph, which you can learn about in other DataCamp courses. You can also learn about them from online resources, which is an important skill to develop.

As the final exercise in this course, you'll practice looking up `ggplot2` instructions by completing a task we haven't shown you how to do.

INSTRUCTIONS

Add a title to the graph: Comparing GDP per capita across continents. Use a search engine, such as Google or Bing, to learn how to do so.

```
library(gapminder)
library(dplyr)
library(ggplot2)

gapminder_1952 <- gapminder %>%
  filter(year == 1952)

# Add a title to this graph: "Comparing GDP per capita across continents"
ggplot(gapminder_1952, aes(x = continent, y = gdpPercap)) +  
  geom_boxplot() +
```

```
scale_y_log10() +  
ggtitle("Comparing GDP per capita across continents")
```

