

# BML Project: Learning Priors for Adversarial Autoencoders

Teammates: Belozerova Polina, Safin Alexander, Pavlovskaja Natalia

## Abstract

This work is a reproducing of the [1].

Most deep latent factor models choose simple priors for simplicity, tractability or not knowing what prior to use. Recent studies show that the choice of the prior may have a profound effect on the expressiveness of the model, especially when its generative network has limited capacity. In this paper, we propose to learn a proper prior from data for adversarial autoencoders (AAEs). We introduce the notion of code generators to transform manually selected simple priors into ones that can better characterize the data distribution. Experimental results show that the proposed model can generate better image quality and learn better disentangled representations than AAEs in both supervised and unsupervised settings. Lastly, we present its ability to do cross-domain translation in a text-to-image synthesis task.

## Problem Statement

We decided to reproduce the following:

- Unsupervised images generation
- Supervised images generation

## Data

The Datasets used:

- MNIST
- CIFAR-10

## Results

- Unsupervised images generation

Dataset	Model	Inception score
MNIST	Our	??
	Original Paper	Unknown
CIFAR	Our	??
	Original Paper	6.52

- Supervised images generation




Figure 1: Results for supervised learning the different datasets

## Contribution

- Belozerova Polina: reading papers, ...
- Safin Alexander: reading papers, ...
- Pavlovskaja Natalia: reading papers, code for training procedure, images generation

## References

- [1] Learning priors for adversarial autoencoders. 2018.