

Competitive Programming Notebook

py.Sandu

Contents

1	Geometry	2	7	DP	10
1.1	Cross Product	2	7.1	Binary Lifting	10
1.2	Convex Hull	2	7.2	Knapsack	10
1.3	Isleft	2	7.3	Coins Change	10
1.4	Winding Number	2	7.4	Longest Increasing Subsequence	10
1.5	Point	2	7.5	Kadane Algorithm	11
2	DS	2			
2.1	Lazy Seg Tree	2			
2.2	Union Find	3			
2.3	Trie	3			
2.4	Fenwick Tree	4			
2.5	Monotonic Stack	4			
2.6	Seg Tree	4			
3	General	5			
3.1	Mex	5			
3.2	Josephus	5			
4	String	5			
4.1	Kmp	5			
4.2	Duval	6			
5	Math	6			
5.1	Siege Of Eratosthenes	6			
5.2	Matrix Fibonacci	6			
5.3	Matrix Multiplication	6			
5.4	Solve Linear System	6			
5.5	Modular Exponentiation	7			
5.6	Spf	7			
5.7	Gcd	7			
5.8	Extended Euclidean Algorithm	7			
5.9	Factorial	7			
6	Graph	8			
6.1	Bellman-ford	8			
6.2	Floyd-warshall	8			
6.3	Ford-fulkerson	8			
6.4	Mst Prim	8			
6.5	Dfs	9			
6.6	Bfs	9			
6.7	Reverse Graph	9			
6.8	Eulerean Path	9			
6.9	Dijkstra	10			

1 Geometry

1.1 Cross Product

```
1 double cross_product(Point O, Point A, Point B)
2 {
3     return (A.x - O.x) * (B.y - O.y)
4           - (A.y - O.y) * (B.x - O.x);
5 }
```

1.2 Convex Hull

```
1 // Returns a list of points on the convex hull
2 // in counter-clockwise order
3 vector<Point> convex_hull(vector<Point> A)
4 {
5     int n = A.size(), k = 0;
6
7     if (n <= 3)
8         return A;
9
10    vector<Point> ans(2 * n);
11
12    // Sort points lexicographically
13    sort(A.begin(), A.end());
14
15    // Build lower hull
16    for (int i = 0; i < n; ++i) {
17
18        // If the point at K-1 position is not a part
19        // of hull as vector from ans[k-2] to ans[k
20        -1]
21        // and ans[k-2] to A[i] has a clockwise turn
22        while (
23            k >= 2
24            && cross_product(ans[k - 2], ans[k - 1],
25                A[i])
26                <= 0)
27            k--;
28        ans[k++] = A[i];
29    }
30
31    // Build upper hull
32    for (size_t i = n - 1, t = k + 1; i > 0; --i) {
33
34        // If the point at K-1 position is not a part
35        // of hull as vector from ans[k-2] to ans[k
36        -1]
37        // and ans[k-2] to A[i] has a clockwise turn
38        while (k >= t
39            && cross_product(ans[k - 2], ans[k -
40                1],
41                A[i - 1])
42                <= 0)
43            k--;
44        ans[k++] = A[i - 1];
45    }
46
47    // Resize the array to desired size
48    ans.resize(k - 1);
49
50    return ans;
51 }
```

1.3 Isleft

```
1 // Check if a point is to the left of a segment
2 // defined by two points
3 bool isLeft(const Point& p, const Point& v1, const
4     Point& v2) {
5     return (v2.x - v1.x) * (p.y - v1.y) - (v2.y - v1.
6     y) * (p.x - v1.x) > 0;
```

```
4 }
```

1.4 Winding Number

```
1 // Check if a point is inside a polygon using the
2 // winding number algorithm
3 bool isInsidePolygon(const Point& p, const vector<
4     Point>& polygon) {
5     int windingNumber = 0;
6     int n = polygon.size();
7
8     for (int i = 0; i < n; i++) {
9         const Point& v1 = polygon[i];
10        const Point& v2 = polygon[(i + 1) % n];
11
12        if (v1.y <= p.y) {
13            if (v2.y > p.y && isLeft(p, v1, v2)) {
14                ++windingNumber;
15            }
16        } else {
17            if (v2.y <= p.y && !isLeft(p, v1, v2)) {
18                --windingNumber;
19            }
20        }
21    }
22
23    return windingNumber != 0;
```

1.5 Point

```
1 struct Point {
2     double x, y;
3 };
```

2 DS

2.1 Lazy Seg Tree

```
1 // Segment Tree com Lazy Propagation
2 // Complexidade: O(log N) para atualizações em
3 // range e consultas
4 struct LazySegTree {
5     int n;
6     vector<long long> tree, lazy;
7
8     LazySegTree(int n) : n(n), tree(4 * n, 0), lazy(4
9         * n, 0) {}
10
11     void push(int node, int tl, int tr) {
12         if (lazy[node] != 0) {
13             tree[node] += lazy[node] * (tr - tl + 1);
14             // Exemplo para Soma
15             if (tl != tr) {
16                 lazy[node * 2] += lazy[node];
17                 lazy[node * 2 + 1] += lazy[node];
18             }
19             lazy[node] = 0;
20         }
21     }
22
23     void update(int node, int tl, int tr, int l, int
24         r, long long addend) {
25         push(node, tl, tr);
26         if (l > tr || r < tl) return;
27         if (l <= tl && tr <= r) {
28             lazy[node] += addend;
29             push(node, tl, tr);
30             return;
31         }
```

```

28     int tm = t1 + (tr - t1) / 2;
29     update(node * 2, t1, tm, l, r, addend);
30     update(node * 2 + 1, tm + 1, tr, l, r, addend);
31   };
32   tree[node] = tree[node * 2] + tree[node * 2 + 1];
33 }
34
35 long long query(int node, int t1, int tr, int l,
36 int r) {
37   push(node, t1, tr);
38   if (l > tr || r < t1) return 0; // Elemento
39   neutro
40   if (l <= t1 && tr <= r) return tree[node];
41   int tm = t1 + (tr - t1) / 2;
42   return query(node * 2, t1, tm, l, r) +
43     query(node * 2 + 1, tm + 1, tr, l, r);
44 }
45 };

```

2.2 Union Find

```

1 // Time complexity: all O(1) for n < 10^600
2 // Memory complexity: O(n)
3
4 class UnionFind{
5   vector<int> parent;
6   vector<int> setSize;
7 public:
8   UnionFind(int size){
9     parent.resize(size);
10    setSize.assign(size, 1);
11    iota(parent.begin(), parent.end(), 0); // If
12    needed to index by 1, size = size+1
13  }
14
15   int find(int i){
16     return parent[i] == i ? i : parent[i] = find(
17     parent[i]);
18   }
19
20   bool join(int I, int J){
21     int i = find(I), j = find(J);
22     if(i == j) return false;
23
24     if(setSize[i] < setSize[j]) swap(i, j);
25
26     parent[j] = i;
27
28     setSize[i] += setSize[j];
29     return true;
30   }
31
32   int size(int i){ return setSize[find(i)]; }
33 };

```

2.3 Trie

```

1 // class for a node of the trie
2 class TrieNode {
3 public:
4   bool endofWord;
5   TrieNode* children[26];
6
7   // Constructore to initialize a trie node
8   TrieNode()
9   {
10     endofWord = false;
11     for (int i = 0; i < 26; i++) {
12       children[i] = nullptr;
13     }
14   }

```

```

15   };
16
17   // class for the Trie implementation
18   class Trie {
19   private:
20     TrieNode* root;
21
22   public:
23     Trie() { root = new TrieNode(); }
24
25     // Function to insert a word into the trie
26     void insert(string word)
27     {
28       TrieNode* node = root;
29       for (char c : word) {
30         int index = c - 'a';
31         if (!node->children[index]) {
32           node->children[index] = new TrieNode
33           ();
34         }
35         node = node->children[index];
36       }
37       node->endofWord = true;
38     }
39
40     // Function to search a word in the trie
41     bool search(string word)
42     {
43       TrieNode* node = root;
44       for (char c : word) {
45         int index = c - 'a';
46         if (!node->children[index]) {
47           return false;
48         }
49         node = node->children[index];
50       }
51       return node->endofWord;
52     }
53
54     // Function to check if there is any word in the
55     // trie
56     // that starts with the given prefix
57     bool startsWith(string prefix)
58     {
59       TrieNode* node = root;
60       for (char c : prefix) {
61         int index = c - 'a';
62         if (!node->children[index]) {
63           return false;
64         }
65         node = node->children[index];
66       }
67       return true;
68     }
69
70     // Function to delete a word from the trie
71     void deleteWord(string word)
72     {
73       TrieNode* node = root;
74       for (char c : word) {
75         int index = c - 'a';
76         if (!node->children[index]) {
77           return;
78         }
79         node = node->children[index];
80       }
81       if (node->endofWord == true) {
82         node->endofWord = false;
83       }
84     }
85
86     // Function to print the trie
87     void print(TrieNode* node, string prefix) const

```

```

86     {
87         if (node->endofWord) {
88             cout << prefix << endl;
89         }
90         for (int i = 0; i < 26; i++) {
91             if (node->children[i]) {
92                 print(node->children[i],
93                     prefix + char('a' + i));
94             }
95         }
96     }
97
98     // Function to start printing from the root
99     void print() const { print(root, ""); }
100 };

```

2.4 Fenwick Tree

```

1 // Fenwick Tree (1-based index)
2 // Time complexity: O(log N) for queries and updates
3
4 int sum(int i) {
5     int s = 0;
6     for (; i > 0; i -= i & -i) {
7         s += T[i];
8     }
9     return s;
10 }
11
12 void add(int i, int k) {
13     // i deve ser >= 1
14     for (; i < T.size(); i += i & -i) {
15         T[i] += k;
16     }
17 }
18
19 // Construção em O(N)
20 void make() {
21     for (int i = 1; i < T.size(); i++) {
22         int p = i + (i & -i);
23         if (p < T.size()) {
24             T[p] += T[i];
25         }
26     }
27 }

```

2.5 Monotonic Stack

```

1 // Increasing Monotonic Stack
2 // Time Complexity: O(n)
3 // Space Complexity: O(n)
4
5 vector<int> nextGreaterElements(vector<int>& arr) {
6     int n = arr.size();
7     vector<int> res(n, -1);
8     stack<int> st;
9
10    for (int i = 0; i < 2 * n; i++) {
11        int num = arr[i % n];
12        while (!st.empty() && arr[st.top()] < num) {
13            res[st.top()] = num;
14            st.pop();
15        }
16        if (i < n) {
17            st.push(i);
18        }
19    }
20
21    return res;
22 }
23
24 // Decreasing Monotonic Stack

```

```

25 // Time Complexity: O(n)
26 // Space Complexity: O(n)
27
28 vector<int> nextSmallerElements(vector<int>& arr) {
29     int n = arr.size();
30     vector<int> res(n, -1);
31     stack<int> st;
32
33     for (int i = 0; i < 2 * n; ++i) {
34         int num = arr[i % n];
35         while (!st.empty() && arr[st.top()] > num) {
36             res[st.top()] = num;
37             st.pop();
38         }
39         if (i < n) {
40             st.push(i);
41         }
42     }
43
44     return res;
45 }

```

2.6 Seg Tree

```

1 // Segment Tree implementation
2 // Time complexity: O(log n) for updates and queries
3
4 template<typename T>
5 class SegmentTree {
6 private:
7     int n;
8     vector<T> tree;
9     T combine(T a, T b) {
10         // Combine function for the segment tree (e.g.
11         // sum, min, max)
12         return a + b; // Example: sum
13     }
14     void build(vector<T>& arr, int v, int tl, int tr)
15     {
16         if (tl == tr) {
17             tree[v] = arr[tl];
18         } else {
19             int tm = (tl + tr) / 2;
20             build(arr, v * 2, tl, tm);
21             build(arr, v * 2 + 1, tm + 1, tr);
22             tree[v] = combine(tree[v * 2], tree[v * 2
23                 + 1]);
24         }
25     }
26     void update(int v, int tl, int tr, int pos, T
27         new_val) {
28         if (tl == tr) {
29             tree[v] = new_val;
30         } else {
31             int tm = (tl + tr) / 2;
32             if (pos <= tm) {
33                 update(v * 2, tl, tm, pos, new_val);
34             } else {
35                 update(v * 2 + 1, tm + 1, tr, pos,
36                     new_val);
37             }
38             tree[v] = combine(tree[v * 2], tree[v * 2
39                 + 1]);
40         }
41     }
42     T query(int v, int tl, int tr, int l, int r) {
43         if (l > r) {
44             return T(); // Return identity element (e
45                 .g., 0 for sum)
46         }
47         if (l == tl && r == tr) {
48             return tree[v];
49         }

```

```

43         int tm = (tl + tr) / 2;
44         return combine(query(v * 2, tl, tm, l, min(r,
45             tm)),
46             query(v * 2 + 1, tm + 1, tr,
47                 max(l, tm + 1), r));
48     }
49 public:
50     SegmentTree(vector<T>& arr) {
51         n = arr.size();
52         tree.resize(4 * n);
53         build(arr, 1, 0, n - 1);
54     }
55     void update(int pos, T new_val) {
56         update(1, 0, n - 1, pos, new_val);
57     }
58     T query(int l, int r) {
59         return query(1, 0, n - 1, l, r);
60     }
61 };

```

3 General

3.1 Mex

```

1 // Minimal excluded number of a sequence
2
3 // O(N log N) approach
4 int mex(vector<int> const& A) {
5     set<int> b(A.begin(), A.end());
6
7     int result = 0;
8     while (b.count(result))
9         ++result;
10    return result;
11 }
12
13 // O(N) approach
14 int mex(vector<int> const& A) {
15     static bool used[MAX_N+1] = { 0 };
16
17     // mark the given numbers
18     for (int x : A) {
19         if (x <= MAX_N)
20             used[x] = true;
21     }
22
23     // find the mex
24     int result = 0;
25     while (used[result])
26         ++result;
27
28     // clear the array again
29     for (int x : A) {
30         if (x <= MAX_N)
31             used[x] = false;
32     }
33
34     return result;
35 }

```

3.2 Josephus

```

1 // Josephus problem
2 // Time complexity: O(N)
3 // Memory complexity: O(1)
4
5 // Recursive (1 indexing)
6 int memo[MAX_N];
7
8 int josephus(int n, int k) {
9     if (n == 1) return 1;

```

```

10     if (memo[n]) return memo[n];
11     return memo[n] = (josephus(n-1, k) + k - 1) % n +
12         1;
13 }
14 // Non-Recursive
15 int josephus(int n, int k) {
16     int res = 0;
17     for (int i = 1; i <= n; ++i)
18         res = (res + k) % i;
19     return res + 1;
20 }

```

4 String

4.1 Kmp

```

1 // Find all occurrences of a pattern in a given text
2 // using the Knuth-Morris-Pratt (KMP) algorithm
3 // Time complexity: O(n + m) where n is the length of
4 // the text and m is the length of the pattern
5
6 vector<int> LPS(const string& pattern) {
7     int m = pattern.size();
8     vector<int> lps(m, 0);
9     int len = 0; // length of the previous longest
10    prefix suffix
11    int i = 1;
12
13    while (i < m) {
14        if (pattern[i] == pattern[len]) {
15            len++;
16            lps[i] = len;
17            i++;
18        } else {
19            if (len != 0) {
20                len = lps[len - 1];
21            } else {
22                lps[i] = 0;
23                i++;
24            }
25        }
26    }
27    return lps;
28 }
29
30 vector<int> KMP(const string& text, const string&
31    pattern) {
32     vector<int> lps = LPS(pattern);
33     vector<int> occurrences;
34     int n = text.size();
35     int m = pattern.size();
36     int i = 0; // index for text
37     int j = 0; // index for pattern
38
39     while (i < n) {
40         if (text[i] == pattern[j]) {
41             i++;
42             j++;
43         }
44         if (j == m) {
45             occurrences.push_back(i - j); // Pattern
46             found at index (i - j)
47             j = lps[j - 1]; // Continue to search for
48             the next match
49         } else if (i < n && text[i] != pattern[j]) {
50             if (j != 0) {
51                 j = lps[j - 1];
52             } else {
53                 i++;
54             }
55         }
56     }
57 }

```

```

50     }
51     return occurrences;
52 }

```

4.2 Duval

```

1 // Duval algorithm for factorizing strings in
  lexicographical order
2 // Time complexity: O(n)
3 // Memory complexity: O(n)
4
5 vector<string> duval(string const& s) {
6     int n = s.size();
7     int i = 0;
8     vector<string> factorization;
9     while (i < n) {
10         int j = i + 1, k = i;
11         while (j < n && s[k] <= s[j]) {
12             if (s[k] < s[j])
13                 k = i;
14             else
15                 k++;
16             j++;
17         }
18         while (i <= k) {
19             factorization.push_back(s.substr(i, j - k
20             i += j - k;
21         }
22     }
23     return factorization;
24 }

```

5 Math

5.1 Sieve Of Eratosthenes

```

1 // Find all prime numbers up to a given limit using
  the Sieve of Eratosthenes algorithm
2 // Time complexity: O(n log log n) where n is the
  limit
3
4 vector<int> findPrimes(int limit) {
5     vector<bool> isPrime(limit + 1, true);
6     isPrime[0] = isPrime[1] = false;
7
8     for (int i = 2; i * i <= limit; i++) {
9         if (isPrime[i]) {
10             for (int j = i * i; j <= limit; j += i) {
11                 isPrime[j] = false;
12             }
13         }
14     }
15
16     vector<int> primes;
17     for (int i = 2; i <= limit; i++) {
18         if (isPrime[i]) {
19             primes.push_back(i);
20         }
21     }
22     return primes;
23 }

```

5.2 Matrix Fibonacci

```

1 // Calculate the Nth Fibonacci number using matrix
  exponentiation.
2 // Time Complexity: O(log N)
3 // Space Complexity: O(1)
4

```

```

5 void matrixExponentiation(vector<vector<long long>>&
  matrix, long long power) {
6     int n = matrix.size();
7     vector<vector<long long>> result(n, vector<long
  long>(n, 0));
8
9     // Initialize result as the identity matrix
10    for (int i = 0; i < n; i++) {
11        result[i][i] = 1;
12    }
13
14    while (power) {
15        if (power % 2 == 1) {
16            result = matrixMultiplication(result,
  matrix);
17        }
18        matrix = matrixMultiplication(matrix, matrix);
19        power /= 2;
20    }
21
22    matrix = result;
23 }

```

5.3 Matrix Multiplication

```

1 // Multiply two matrices A and B, and return the
  result in matrix C.
2 // Time Complexity: O(n^3)
3 // Space Complexity: O(n^2)
4
5 vector<vector<long long>> matrixMultiplication(const
  vector<vector<long long>>& A, const vector<vector
  <long long>>& B) {
6     int n = A.size();
7     vector<vector<long long>> C(n, vector<long long>(
  n, 0));
8
9     for (int i = 0; i < n; i++) {
10        for (int j = 0; j < n; j++) {
11            for (int k = 0; k < n; k++) {
12                C[i][j] += A[i][k] * B[k][j];
13            }
14        }
15    }
16    return C;
17 }

```

5.4 Solve Linear System

```

1 // Solve a system of linear equations using LU
  decomposition with partial pivoting
2 // Time complexity: O(n^3) for decomposition, O(n^2)
  for forward and backward substitution
3
4 void luDecomposition(const vector<vector<double>>& A,
  vector<vector<double>>& L, vector<vector<double
  >>& U, vector<int>& perm) {
5     int n = A.size();
6     U = A;
7     L.assign(n, vector<double>(n, 0));
8     perm.resize(n);
9     iota(perm.begin(), perm.end(), 0);
10
11    for (int i = 0; i < n; i++) {
12        int maxRow = i;
13        for (int k = i + 1; k < n; k++)
14            if (abs(U[k][i]) > abs(U[maxRow][i]))
15                maxRow = k;
16        swap(U[i], U[maxRow]);
17        swap(perm[i], perm[maxRow]);
18        for (int k = 0; k < i; k++) swap(L[i][k], L[
  maxRow][k]);
19    }

```

```

18         L[i][i] = 1;
19         for (int j = i + 1; j < n; j++) {
20             L[j][i] = U[j][i] / U[i][i];
21             for (int k = i; k < n; k++)
22                 U[j][k] -= L[j][i] * U[i][k];
23         }
24     }
25 }
26 }
27
28 // perm is the permutation vector returned by
29 // luDecomposition
30 void forwardSubstitution(const vector<vector<double>>& L, const vector<double>& b, const vector<int>& perm, vector<double>& y) {
31     int n = L.size();
32     for (int i = 0; i < n; i++) {
33         y[i] = b[perm[i]];
34         for (int j = 0; j < i; j++)
35             y[i] -= L[i][j] * y[j];
36     }
37 }
38 void backwardSubstitution(const vector<vector<double>>& U, const vector<double>& y, vector<double>& x) {
39     int n = U.size();
40     for (int i = n - 1; i >= 0; i--) {
41         x[i] = y[i];
42         for (int j = i + 1; j < n; j++)
43             x[i] -= U[i][j] * x[j];
44         x[i] /= U[i][i];
45     }
46 }

```

5.5 Modular Exponentiation

```

1 // Calculates (x^n) % MOD
2 // Time Complexity: O(log n)
3 // Space Complexity: O(1)
4
5 long long powMod(long long x, long long n, long long MOD){
6     long long res = 1;
7     x %= MOD;
8
9     while(n >= 1){
10         if(n & 1){
11             res = (res * x) % MOD;
12         }
13         x = (x * x) % MOD;
14         n /= 2;
15     }
16     return res;
17 }

```

5.6 Spf

```

1 // SPF sieve implementation for finding the smallest
2 // prime factor of each number up to a given limit.
3 // Time complexity: O(n log log n) for the sieve
4 // construction, O(log n) for factorization of each
5 // number.
6
7 #define MAXN 1000000 // Maximum limit for the sieve
8 std::vector<int> spf(MAXN + 1);
9
10 void sieve() {
11     for (int i = 1; i <= MAXN; i++) {
12         spf[i] = i;
13     }
14     for (int i = 2; i * i <= MAXN; i++) {

```

```

12         if (spf[i] == i) {
13             for (int j = i * i; j <= MAXN; j += i) {
14                 if (spf[j] == j) {
15                     spf[j] = i;
16                 }
17             }
18         }
19     }
20 }

```

5.7 Gcd

```

1 // Calculates the Greatest Common Divisor (GCD) of
2 // two integers using Euclidean algorithm
3 // Time Complexity: O(log(min(a, b)))
4 // Space Complexity: O(log(min(a, b)))
5 int gcd(int a, int b){
6     if (a == 0) return b;
7     return gcd(b % a, a);
8 }

```

5.8 Extended Euclidean Algorithm

```

1 // Extended Euclidean Algorithm
2 // Returns (gcd(a, b), x, y) such that a*x + b*y =
3 // gcd(a, b)
4 int extendedEuclidean(int a, int b, int& x, int& y){
5     if(a == 0){
6         x = 0;
7         y = 1;
8         return b;
9     }
10    int x1, y1;
11    int gcd = extendedEuclidean(b % a, a, x1, y1);
12    x = y1 - (b / a) * x1;
13    y = x1;
14    return gcd;
15 }

```

5.9 Factorial

```

1 // Precompute factorials and inverse factorials
2 // modulo a prime MOD using DP
3 // Requires: powMod (modular_exponentiation.cpp)
4 // MOD must be prime (uses Fermat's little theorem: a
5 // ^{-1} = a^{MOD-2} mod MOD)
6 // Time complexity: O(N) for precomputation, O(1) per
7 // query
8 // Space complexity: O(N)
9
10 const int MAXN = 1e6 + 5;
11 const long long MOD = 1e9 + 7;
12
13 long long fact[MAXN], inv_fact[MAXN];
14
15 void precompute(int n) {
16     fact[0] = 1;
17     for (int i = 1; i <= n; i++)
18         fact[i] = fact[i - 1] * i % MOD;
19
20     inv_fact[n] = powMod(fact[n], MOD - 2, MOD);
21     for (int i = n - 1; i >= 0; i--)
22         inv_fact[i] = inv_fact[i + 1] * (i + 1) % MOD;
23 }
24
25 // C(n, k) = n! / (k! * (n-k)!) mod MOD
26 long long C(int n, int k) {
27     if (k < 0 || k > n) return 0;

```

```

25     return fact[n] % MOD * inv_fact[k] % MOD *
    inv_fact[n - k] % MOD;
26 }

```

6 Graph

6.1 Bellman-ford

```

1 // Find the shortest path from a source vertex to all
  other vertices in a graph with negative weight
  edges and detect negative weight cycles.
2 // Time Complexity: O(V * E)
3 // Space Complexity: O(V)
4
5 struct Edge { int u, v, weight; };
6
7 void bellmanFord(int V, const vector<Edge>& edges,
  int src) {
8     vector<int> dist(V, INT_MAX);
9     dist[src] = 0;
10
11     for (int i = 1; i <= V - 1; i++) {
12         for (const auto& edge : edges) {
13             if (dist[edge.u] != INT_MAX && dist[edge.
14 u] + edge.weight < dist[edge.v]) {
15                 dist[edge.v] = dist[edge.u] + edge.
16 weight;
17             }
18         }
19     }
20
21     // Check for negative weight cycles
22     for (const auto& edge : edges) {
23         if (dist[edge.u] != INT_MAX && dist[edge.u] +
24 edge.weight < dist[edge.v]) {
25             cout << "Graph contains negative weight
26 cycle" << endl;
27             return;
28         }
29     }
30 }

```

6.2 Floyd-warshall

```

1 // Find the shortest paths in a weighted graph with
  positive or negative edge weights (but with no
  negative cycles).
2 // Time Complexity: O(V^3)
3 // Space Complexity: O(V^2)
4
5 void floydWarshall(vector<vector<int>>& dist) {
6     int V = dist.size();
7     int INF = 1e8;
8
9     for (int k = 0; k < V; k++) {
10
11         for (int i = 0; i < V; i++) {
12             for (int j = 0; j < V; j++) {
13                 if (dist[i][k] != INF && dist[k][j] !=
14 INF )
15                     dist[i][j] = min(dist[i][j],
16                                     dist[i][k] +
17                                     dist[k][j]);
18             }
19         }
20     }
21 }

```

6.3 Ford-fulkerson

```

1 // Find maximum flow in graph

```

```

2 // Time complexity: O(|V| * E^2)
3 // Space complexity: O(V)
4 bool bfs(int residual[V][V], int start, int target,
  vi& parent) {
5     vector<bool> visited(V, false);
6     queue<int> q;
7     q.push(start);
8     visited[start] = true;
9     parent[start] = -1;
10
11     while(!q.empty()){
12         int u = q.front();
13         q.pop();
14
15         for(int v = 0 ; v < V ; v++){
16             if(!visited[v] and residual[u][v] > 0){
17                 if(v == target){
18                     parent[v] = u;
19                     return true;
20                 }
21                 q.push(v);
22                 parent[v] = u;
23                 visited[v] = true;
24             }
25         }
26     }
27     return false;
28 }
29
30 int fordFulkerson(int g[V][V], int start, int target)
  {
31     int u, v;
32     int residual[V][V];
33
34     for(u = 0 ; u < V ; u++){
35         for(v = 0 ; v < V ; v++){
36             residual[u][v] = g[u][v];
37         }
38     }
39     vi parent(V);
40     int maxFlow = 0;
41
42     while(bfs(residual, start, target, parent)){
43         int pathFlow = INT_MAX;
44         for(v = target ; v != start ; v = parent[v]){
45             u = parent[v];
46             pathFlow = min(pathFlow, residual[u][v]);
47         }
48
49         for(v = target ; v != start ; v = parent[v]){
50             u = parent[v];
51             residual[u][v] -= pathFlow;
52             residual[v][u] += pathFlow;
53         }
54         maxFlow += pathFlow;
55     }
56     return maxFlow;
57 }

```

6.4 Mst Prim

```

1 // Prim's algorithm for finding the Minimum Spanning
  Tree
2 // Time complexity: O(E log V) where E is the number
  of edges and V is the number of vertices
3
4 struct Edge {
5     int u, v, weight;
6     bool operator<(const Edge& other) const {
7         return weight > other.weight; // Min-heap
8     }
9 };
10

```



```

11 vector<Edge> primMST(const vector<vector<int>>& graph) {
12     int n = graph.size();
13     vector<bool> visited(n, false);
14     vector<Edge> mst;
15     priority_queue<Edge> pq;
16
17     // Start with the first vertex
18     visited[0] = true;
19     for (int i = 0; i < n; ++i) {
20         if (graph[0][i] != 0) {
21             pq.push({0, i, graph[0][i]});
22         }
23     }
24
25     while (!pq.empty()) {
26         Edge current = pq.top();
27         pq.pop();
28
29         if (visited[current.v]) continue;
30
31         visited[current.v] = true;
32         mst.push_back(current);
33
34         for (int i = 0; i < n; ++i) {
35             if (!visited[i] && graph[current.v][i] !=
36                 0) {
37                 pq.push({current.v, i, graph[current.
38                     v][i]});
39             }
40         }
41     }
42     return mst;

```

6.5 Dfs

```

1 // Depth First Search (DFS)
2 // Time Complexity: O(V + E)
3 // Space Complexity: O(V)
4
5 // Recursive DFS
6 void dfs(const Graph& graph, int vertex, vector<bool>
7     & visited) {
8     visited[vertex] = true;
9
10    for (int neighbor : graph[vertex]) {
11        if (!visited[neighbor]) {
12            dfs(graph, neighbor, visited);
13        }
14    }
15
16    // Iterative DFS
17    void dfsIterative(const Graph& graph, int start) {
18        int V = graph.size();
19        vector<bool> visited(V, false);
20        stack<int> s;
21        s.push(start);
22
23        while (!s.empty()) {
24            int vertex = s.top();
25            s.pop();
26
27            if (!visited[vertex]) {
28                visited[vertex] = true;
29
30                for (int neighbor : graph[vertex]) {
31                    if (!visited[neighbor]) {
32                        s.push(neighbor);
33                    }
34                }

```

6.6 Bfs

```

1 // Breadth First Search (BFS)
2 // Time Complexity: O(V + E)
3 // Space Complexity: O(V)
4 void bfs(const Graph& graph, int start) {
5     int V = graph.size();
6     vector<bool> visited(V, false);
7     queue<int> q;
8
9     visited[start] = true;
10    q.push(start);
11
12    while (!q.empty()) {
13        int vertex = q.front();
14        q.pop();
15        cout << vertex << " ";
16
17        for (int neighbor : graph[vertex]) {
18            if (!visited[neighbor]) {
19                visited[neighbor] = true;
20                q.push(neighbor);
21            }
22        }
23    }
24 }

```

6.7 Reverse Graph

```

1 // Reverse the edges of a directed graph
2 // Time Complexity: O(V + E)
3 // Space Complexity: O(V + E)
4
5 Graph reverseGraph(const Graph& graph) {
6     int V = graph.size();
7     Graph reversedGraph(V);
8
9     for (int u = 0; u < V; u++) {
10        for (int v : graph[u]) {
11            reversedGraph[v].push_back(u);
12        }
13    }
14
15    return reversedGraph;
16 }

```

6.8 Eulerian Path

```

1 // Find the Eulerian path in a graph using Hierholzer
2 // Time complexity: O(E) where E is the number of
3 // edges in the graph
4 void findEulerianPath(vector<vector<int>> graph, int
5     start, vector<int>& path) {
6     stack<int> s;
7     s.push(start);
8
9     while (!s.empty()) {
10        int v = s.top();
11        if (graph[v].empty()) {
12            path.push_back(v);
13            s.pop();
14        } else {
15            int u = graph[v].back();
16            graph[v].pop_back(); // Remove the edge
17            // from v to u
18            s.push(u);

```

```

18     }
19 }

```

6.9 Dijkstra

```

1 // Find shortest path from a source vertex to all
  other vertices in a graph with non-negative edge
  weights
2 // Time Complexity:  $O((V + E) \log V)$ 
3 // Space Complexity:  $O(V)$ 
4
5 void dijkstra(const Graph& graph, int src) {
6     int V = graph.size();
7     vector<int> dist(V, INT_MAX);
8     dist[src] = 0;
9
10    priority_queue<pair<int, int>, vector<pair<int,
      int>>, greater<pair<int, int>>> pq; // Min-heap
      priority queue
11    pq.push({0, src});
12
13    while (!pq.empty()) {
14        int d = pq.top().first;
15        int u = pq.top().second;
16        pq.pop();
17
18        if (d > dist[u]) continue;
19
20        for (const auto& adj : graph[u]) {
21            int v = adj.first;
22            int weight = adj.second;
23
24            if (dist[u] != INT_MAX && dist[u] +
      weight < dist[v]) {
25                dist[v] = dist[u] + weight;
26                pq.push({dist[v], v});
27            }
28        }
29    }
30 }

```

7 DP

7.1 Binary Lifting

```

1 // Binary lifting to find lower common ancestor in a
  binary tree
2 // Time complexity:  $O(\log N)$  for queries and  $O(N \log
  N)$  for pre-processing
3 // Memory complexity:  $O(N)$ 
4 struct BinaryLifting{
5     int n, l, timer; // n = size, l = max jump
6     vector<int> tin, tout;
7     vector<vector<int>> up;
8
9     //Constructor
10    BinaryLifting(int n, int root, const vector<vector
      <int>>& adj) : n(n), timer(0) {
11        l = n <= 1 ? 0 : __lg(n) + 1;
12        tin.resize(n);
13        tout.resize(n);
14        up.assign(n, vector<int>(l+1));
15
16        dfs(root, root, adj);
17    }
18
19    void dfs(int v, int p, const vector<vector<int>>&
      adj){
20        tin[v] = ++timer;
21        up[v][0] = p;
22

```

```

23        for(int i = 1 ; i <= l ; i++) up[v][i] = up[
      up[v][i-1]][i-1];
24
25        for(auto& u : adj[v]) if(u != p) dfs(u, v,
      adj);
26        tout[v] = ++timer;
27    }
28
29    bool isAncestor(int u, int v){ return tin[u] <=
      tin[v] and tout[u] >= tout[v]; }
30
31    int lca(int u, int v){
32        if(isAncestor(u, v)) return u;
33        if(isAncestor(v, u)) return v;
34
35        for(int i = l ; i >= 0 ; i--){
36            if(!isAncestor(up[u][i], v)) u = up[u][i
      ];
37        }
38        return up[u][0];
39    }
40 };

```

7.2 Knapsack

```

1 // Knapsack problem implementation using dynamic
  programming
2 // Time complexity:  $O(n*w)$ , where n is the number of
  items and w is the maximum weight
3 // Space complexity:  $O(n*w)$  for the dp table
4
5 int knapsack(int w, vector<ii>& items){
6     int n = items.size();
7     vector<vi> dp(n+1, vi(w+1, 0));
8
9     for(int i = 1 ; i <= n ; i++){
10        for(int j = 0 ; j <= w ; j++){
11            if(items[i-1].first > j) dp[i][j] = dp[i
      -1][j];
12            else dp[i][j] = max(dp[i-1][j], dp[i-1][j
      -items[i-1].first] + items[i-1].second);
13        }
14    }
15
16    return dp[n][w];
17 }

```

7.3 Coins Change

```

1 // Find the minimum number of coins needed to make a
  given amount using a set of coin denominations
2 // Time complexity:  $O(n * m)$  where n is the amount
  and m is the number of coin denominations
3
4 int coinChange(const vector<int>& coins, int amount)
  {
5     vector<int> dp(amount + 1, INT_MAX);
6     dp[0] = 0;
7
8     for (int i = 1; i <= amount; i++) {
9         for (const int& coin : coins) {
10             if (coin <= i && dp[i - coin] != INT_MAX)
11                 dp[i] = min(dp[i], dp[i - coin] + 1);
12         }
13     }
14
15     return dp[amount] == INT_MAX ? -1 : dp[amount];
16 }
17 }

```

7.4 Longest Increasing Subsequence

```

1 // Find the length of the longest increasing
  subsequence in a given array
2 // Time complexity:  $O(n \log n)$  where  $n$  is the length
  of the input array
3
4 int lis(vector<int>& arr) {
5     vector<int> dp;
6     for (int num : arr) {
7         auto it = lower_bound(dp.begin(), dp.end(),
8                               num);
9         if (it == dp.end()) {
10             dp.push_back(num);
11         } else {
12             *it = num;
13         }
14     }
15     return dp.size();
16 }

```

7.5 Kadane Algorithm

```

1 // Find maximum subarray sum using Kadane's algorithm
2 // Time complexity:  $O(n)$  where  $n$  is the length of the
  input array
3
4 int maxSubArraySum(const vector<int>& arr) {
5     int maxSum = arr[0];
6     int maxLocal = arr[0];
7
8     for (int i = 1; i < (int)arr.size(); i++) {
9         maxLocal = max(arr[i], maxLocal + arr[i]);
10        maxSum = max(maxSum, maxLocal);
11    }
12
13    return maxSum;
14 }

```