

Python IP Class Notebook

Nebhrajani A. V.

Contents

1	Preamble	2
1.1	Notebook Conventions	2
1.2	Hardware and Software Used	2
1.3	Acknowledgements	2
2	NumPy	3
2.1	Worksheet 2020-07-26	3
3	Pandas	8
3.1	Series	8
3.2	Dataframe	14

1 Preamble

1.1 Notebook Conventions

All code in this notebook is in Python unless specified otherwise. All code is syntax-highlighted, placed in boxes, and is line numbered. The output of the interpreter on `stdout` is printed directly below it, *verbatim*, thus.

```
1  # Print Hello world!
2  print("Hello world!")
```

Hello world!

It is recommended that you navigate using the hyperlinked TOC or the Adobe Bookmarks tree.

1.2 Hardware and Software Used

This notebook is written in an `org-mode` file and exported to PDF via \LaTeX , Org version 9.3.6 on GNU Emacs 25.2.2 (x86_64-pc-linux-gnu, GTK+ Version 3.22.21) of 2017-09-23, modified by Debian, on a Foxconn Core i7 NanoPC running Linux Mint 19.3 XFCE 64-bit. Python 2.7.17 of 2020-04-15 is used throughout unless specified otherwise. For the Org or \LaTeX source, contact aditya.v.nebhrajani@gmail.com.

1.3 Acknowledgements

I am grateful to the FSF, the GNU Project, the Linux foundation, the Emacs, StackExchange and FLOSS communities, and my father, who taught me that a world outside commercialized technology does exist and thrive.

2 NumPy

2.1 Worksheet 2020-07-26

1. Create an ndarray with values ranging from 10 to 49 each spaced with a difference of 3.

```
1 import numpy as np
2 arr=np.arange(10,50,3,dtype=int)
3 print(arr)
```

[10 13 16 19 22 25 28 31 34 37 40 43 46 49]

2. Find the output of the following Python code:

```
1 x="hello world"
2 print(x[:2],x[:-2],x[-2:])
```

('he', 'hello wor', 'ld')

3. Predict the output of the following code fragments:

```
1 import numpy as np
2 x=np.array([1,2,3])
3 y=np.array([3,2,1])
4 z=np.concatenate([x,y])
5 print(z)
```

[1 2 3 3 2 1]

4. Consider following two arrays: Array1= array([0,1,2],[3,4,5],[6,7,8]) and Array2= array([10,11,12],[13,14,15],[16,17,18]). Write NumPy command to concatenate Array1 and Array2:

(a) Row wise

```
1 import numpy as np
2 Array1= np.array([[0,1,2],[3,4,5],[6,7,8]])
3 Array2= np.array([[10,11,12],[13,14,15],[16,17,18]])
4 rarr=np.concatenate([Array1,Array2],axis=1)
5 print(rarr)
```

```
[[ 0  1  2 10 11 12]
 [ 3  4  5 13 14 15]
 [ 6  7  8 16 17 18]]
```

(b) Column wise

```
1  import numpy as np
2  Array1= np.array([[0,1,2],[3,4,5],[6,7,8]])
3  Array2= np.array([[10,11,12],[13,14,15],[16,17,18]])
4  carr=np.concatenate([Array1,Array2],axis=0)
5  print(carr)
```

```
[[ 0  1  2]
 [ 3  4  5]
 [ 6  7  8]
 [10 11 12]
 [13 14 15]
 [16 17 18]]
```

5. To create sequences of numbers, NumPy provides a function (a)arange analogous to range that returns arrays instead of lists.
6. Find the output of following program.

```
1  import numpy as np
2  a=np.array([30,60,70,30,10,86,45])
3  print(a[-2:6])
```

[86]

7. Write a NumPy program to create a 2d array with 1 on the border and 0 inside.

```
1  import numpy as np
2  x = np.ones((5,5))
3  print("Original array:")
4  print(x)
5  print("1 on the border and 0 inside in the array")
6  x[1:-1,1:-1] = 0
7  print(x)
```

Original array:

```
[[1. 1. 1. 1. 1.]
 [1. 1. 1. 1. 1.]
 [1. 1. 1. 1. 1.]
 [1. 1. 1. 1. 1.]
 [1. 1. 1. 1. 1.]
```

```

[1. 1. 1. 1. 1.]
1 on the border and 0 inside in the array
[[1. 1. 1. 1. 1.]
 [1. 0. 0. 0. 1.]
 [1. 0. 0. 0. 1.]
 [1. 0. 0. 0. 1.]
 [1. 1. 1. 1. 1.]]

```

8. Given following ndarray A: ([[2, 4, 6], [7, 8, 9], [1, 2, 3]]) Write the python statements to perform the array slices in the way so as to extract first row and second column.

```

1  import numpy as np
2  A = np.array([[2,4,6],[7,8,9],[1,2,3]])
3  print(A[0,:])
4  print(A[:,1])

```

```

[2 4 6]
[4 8 2]

```

9. Write python statement to create a two- dimensional array of 4 rows and 3 columns. The array should be filled with ones.

```

1  import numpy as np
2  x = np.ones((4,3))
3  print(x)

```

```

[[1. 1. 1.]
 [1. 1. 1.]
 [1. 1. 1.]
 [1. 1. 1.]]

```

10. Find the output of following program.

```

1  import numpy as np
2  d = np.array([10,20,30,40,50,60,70])
3  print(d[-5:])

```

```

[30 40 50 60 70]

```

11. State at least two differences between a NumPy array and a list

NumPy Array	List
By default, numpy arrays are homogeneous	They can have elements of different data types
Element-wise operations are possible	Element-wise operations don't work on lists
They take up less space	They take up more space

12. Find the output of following program.

```
1 import numpy as np
2 d=np.array([10,20,30,40,50,60,70])
3 print(d[-1:-4:-1])
```

[70 60 50]

13. Write the output of the following code.

```
1 import numpy as np
2 a=[[1,2,3,4],[5,6,7,8]]
3 b=[[1,2,3,4],[5,6,7,8]]
4 n=np.concatenate((a, b), axis=0)
5 print(n[1])
6 print(n[1][1])
```

[5 6 7 8]

6

14. Which of the following is contained in NumPy library?

- (a) **N-Dimensional Array Object**
- (b) Series
- (c) DataFrame
- (d) Plot

15. Point out the correct statement:

- (a) NumPy main object is the homogeneous multidimensional array
- (b) In Numpy, dimensions are called axes
- (c) NumPy array class is called ndarray
- (d) **All of the above**

16. When the fromiter() is preferred over array()? **A:** Fromiter() is preferred over array() for creating non-numeric sequences like strings and dictionaries.

17. What is the purpose of order argument in empty(). What do 'C' and 'F' stands for? What is the default value of order argument? **A:** The "order" argument arranges the elements of the array row-wise or column-wise. C order arranges elements column wise and means "c"-like, whereas F order arranges elements row wise and means "fortran"-like. Default value of order argument is C.

18. Differentiate `split()` from `hsplit()` and `vsplit()`. **A:** `Split()` function is a general function which can be used to split an array in numpy both horizontally and vertically by providing an axis. If the axis is 0 it is the same as `hsplit()` and if the axis is 1 it behaves as `vsplit()`. The difference between `split()` and `hsplit()`, `vsplit()` is that `split()` allows you to specify the axis that you wish, and `hsplit()` and `vsplit()` are for specific axes.

19. Find the output:

```
(a) import numpy as np
2    a = np.linspace(2.5,5,6)
3    print(a)
```

```
[2.5 3.   3.5 4.   4.5 5. ]
```

```
(b) import numpy as np
2    a=np.array([[0,2,4,6],[8,10,12,14],[16,18,20,22],[24,26,28,30]])
3    print(a)
4    print(a[:3,3:])
5    print(a[1::2,:3])
6    print(a[-3:-1,-4::2])
7    print(a[::-1,::-1])
```

```
[[ 0  2  4  6]
 [ 8 10 12 14]
 [16 18 20 22]
 [24 26 28 30]]
[[ 6]
 [14]
 [22]]
[[ 8 10 12]
 [24 26 28]]
[[ 8 12]
 [16 20]]
[[30 28 26 24]
 [22 20 18 16]
 [14 12 10  8]
 [ 6  4  2  0]]
```

3 Pandas

3.1 Series

```
1  # Import numpy and pandas
2  import pandas as pd
3  import numpy as np
4
5  # Create an empty series
6  s = pd.Series()
7  print(s)
8
9  # Series from ndarray
10 data = np.array(['a', 'b', 'c', 'd'])
11
12 ## Without index
13 s = pd.Series(data)
14 print(s)
15 ## With index
16 s = pd.Series(data, index = [100, 101, 102, 103])
17 print(s)
18
19 # Scalar series
20 s = pd.Series(5, index = [0, 1, 2, 3])
21 print(s)
22
23 # Series from dictionary
24 data = {'a' : 0., 'b' : 1., 'c' : 2.}
25
26 ## Without index
27 s = pd.Series(data)
28 print(s)
29 ## With index
30 s = pd.Series(data, index = ['b', 'c', 'd', 'a'])
31 print(s)
32
33 # Another dictionary example
34 f_dict = {'apples': 500, 'kiwi': 20, 'oranges': 100, 'cherries': 6000}
35 print(f_dict)
36
37 arr = pd.Series(f_dict)
38 print('\nArray Items')
39 print(arr)
```

```
Series([], dtype: float64)
```

```
0    a
1    b
2    c
```



```

3    d
dtype: object
100   a
101   b
102   c
103   d
dtype: object
0    5
1    5
2    5
3    5
dtype: int64
a    0.0
b    1.0
c    2.0
dtype: float64
b    1.0
c    2.0
d    NaN
a    0.0
dtype: float64
{'kiwi': 20, 'cherries': 6000, 'apples': 500, 'oranges': 100}

```

```

Array Items
apples      500
cherries    6000
kiwi        20
oranges     100
dtype: int64

```

```

1  # Indexing
2  import pandas as pd
3  from pandas import Series
4  arr = Series([22, 44, 66, 88, 108])
5  print(arr[[1, 3, 0, 4]])

```

```

1    44
3    88
0    22
4   108
dtype: int64

```

```

1  # Series operations
2  import pandas as pd
3  ds1 = pd.Series([2, 4, 6, 8, 10])
4  ds2 = pd.Series([1, 3, 5, 7, 9])
5  print(ds1)

```

```

6 | print(ds2)
7 | ds = ds1 + ds2
8 | print("Add two Series:")
9 | print(ds)
10 | print("Subtract two Series:")
11 | ds = ds1 - ds2
12 | print(ds)
13 | print("Multiply two Series:")
14 | ds = ds1 * ds2
15 | print(ds)
16 | print("Divide Series1 by Series2:")
17 | ds = ds1 / ds2
18 | print(ds)

```

```

0    2
1    4
2    6
3    8
4   10
dtype: int64
0    1
1    3
2    5
3    7
4    9
dtype: int64
Add two Series:
0    3
1    7
2   11
3   15
4   19
dtype: int64
Subtract two Series:
0    1
1    1
2    1
3    1
4    1
dtype: int64
Multiply two Series:
0    2
1   12
2   30
3   56
4   90
dtype: int64
Divide Series1 by Series2:

```

```
0    2.000000
1    1.333333
2    1.200000
3    1.142857
4    1.111111
dtype: float64
```

```
1  # Series to array
2  import pandas as pd
3  import numpy as np
4  s1 = pd.Series(['100', '200', '300', 'python'])
5  print("Original data series")
6  print(s1)
7  print("Series to array")
8  a = np.array(s1.values.tolist())
9  print(a)
```

Original data series

```
0    100
1    200
2    300
3    python
dtype: object
Series to array
['100' '200' '300' 'python']
```

```
1  # Heads and tails
2  import pandas as pd
3  import math
4  s = pd.Series(data = [math.sqrt(x) for x in range(1,10)],
5                  index = [x for x in range(1,10)])
6  print(s)
7  print(s.head(6))
8  print(s.tail(7))
9  print(s.head())
10 print(s.tail())
```

```
1    1.000000
2    1.414214
3    1.732051
4    2.000000
5    2.236068
6    2.449490
7    2.645751
8    2.828427
9    3.000000
```

```

dtype: float64
1    1.000000
2    1.414214
3    1.732051
4    2.000000
5    2.236068
6    2.449490
dtype: float64
3    1.732051
4    2.000000
5    2.236068
6    2.449490
7    2.645751
8    2.828427
9    3.000000
dtype: float64
1    1.000000
2    1.414214
3    1.732051
4    2.000000
5    2.236068
dtype: float64
5    2.236068
6    2.449490
7    2.645751
8    2.828427
9    3.000000
dtype: float64

```

```

1  # Sorting pandas series
2  import pandas as pd
3  s = pd.Series(['100', '200', 'python', '300.12', '400'])
4  print("Original data series:")
5  print(s)
6  asc_s = pd.Series(s).sort_values()
7  print(asc_s)
8  dsc_s = pd.Series(s).sort_values(ascending=False)
9  print(dsc_s)
10
11 # Appending
12 new_s = s.append(pd.Series(['500', 'php']))
13 print(new_s)

```

```

Original data series:
0    100
1    200
2  python

```

```

3      300.12
4        400
dtype: object
0        100
1        200
3      300.12
4        400
2      python
dtype: object
2      python
4        400
3      300.12
1        200
0        100
dtype: object
0        100
1        200
2      python
3      300.12
4        400
0        500
1        php
dtype: object

```

```

1  # Mean and median
2  import pandas as pd
3  s = pd.Series(data = [1,2,3,4,5,6,7,8,9,5,3])
4  print("Original data series:")
5  print(s)
6  print("Mean:")
7  print(s.mean())
8  print("Standard deviation:")
9  print(s.std())

```

Original data series:

```

0      1
1      2
2      3
3      4
4      5
5      6
6      7
7      8
8      9
9      5
10     3
dtype: int64

```

Mean:

4.818181818181818

Standard deviation:

2.522624895547565

```
1  # Isin function
2  import numpy as np
3  import pandas as pd
4
5  s = pd.Series(['dog', 'cow', 'dog', 'cat', 'lion'], name='animal')
6
7  r = s.isin(['dog', 'cat'])
8  print(r)
```

```
0    True
1   False
2     True
3     True
4   False
Name: animal, dtype: bool
```

```
1  # Appending and concatenation
2  import numpy as np
3  import pandas as pd
4
5  # Input
6  ser1 = pd.Series(range(5))
7  ser2 = pd.Series(list('abcde'))
8
9  # Vertical
10 ser3 = ser1.append(ser2)
11 print(ser3)
12
13 # Or using Pandas concatenate along axis 0
14 ser3 = pd.concat([ser1, ser2], axis = 0)
15 print(ser3)
16
17 # Horizontal (into a dataframe)
18 ser3 = pd.concat([ser1, ser2], axis = 1)
19 print(ser3)
```

3.2 Dataframe

```
1  # Empty dataframe
2  import pandas as pd
3
```

```

4 data = pd.DataFrame()
5 print(data)

```

Empty DataFrame

Columns: []

Index: []

```

1 # Dataframe from list
2 import pandas as pd
3
4 table = [1, 2, 3, 4, 5]
5 data = pd.DataFrame(table)
6 print(data)

```

```

      0
0 1
1 2
2 3
3 4
4 5

```

```

1 # Dataframe from mixed list
2 import pandas as pd
3
4 table = [[1, 'Nebhrajani'], [2, 'Python'], [3, 'Hello']]
5 data = pd.DataFrame(table)
6 print(data)

```

```

      0      1
0 1  Nebhrajani
1 2      Python
2 3      Hello

```

```

1 # Column labels
2 import pandas as pd
3
4 table = [[1, 'Nebhrajani'], [2, 'Python'], [3, 'Hello']]
5 data = pd.DataFrame(table, columns = ['S.No', 'Name'])
6 print(data)

```

```

      S.No      Name
0      1  Nebhrajani
1      2      Python
2      3      Hello

```

```

1  # Random numbers dataframe
2  import numpy as np
3  import pandas as pd
4
5  d_frame = pd.DataFrame(np.random.randn(8, 4))
6  print(d_frame)

```

	0	1	2	3
0	-1.067210	-0.641223	-0.365953	-0.142540
1	-0.592651	0.469174	0.890560	0.319794
2	1.184533	-0.933480	-1.382302	-0.469527
3	1.412379	-0.864983	-0.422046	0.937044
4	-0.713212	1.483705	0.628708	-0.435091
5	-0.793572	1.826652	-0.778544	-0.059586
6	-0.272879	1.586516	-0.663512	1.368802
7	-0.240090	0.531833	-0.314350	0.363192

```

1  # Dataframe from dict
2  import pandas as pd
3
4  table = {'name': ['Aditya', 'Aryan', 'Nebhrajani', 'Sahej'],
5           'Salary': [1000000, 1200000, 900000, 1100000]}
6
7  data = pd.DataFrame(table)
8  print(data)

```

	Salary	name
0	1000000	Aditya
1	1200000	Aryan
2	900000	Nebhrajani
3	1100000	Sahej

```

1  # Dataframe from some given dictionary data
2  import pandas as pd
3  import numpy as np
4
5  exam_data = {'name': ['Anastasia', 'Dima', 'Katherine', 'James',
6                        'Emily', 'Michael', 'Matthew', 'Laura', 'Kevin', 'Jonas'],
7               'score': [12.5, 9, 16.5, np.nan, 9, 20, 14.5, np.nan, 8, 19],
8               'attempts': [1, 3, 2, 3, 2, 3, 1, 1, 2, 1],
9               'qualify': ['yes', 'no', 'yes', 'no', 'no', 'yes', 'yes',
10                           'no', 'no', 'yes']}
11 labels = ['a', 'b', 'c', 'd', 'e', 'f', 'g', 'h', 'i', 'j']
12

```



```

13 df = pd.DataFrame(exam_data , index=labels)
14 print(df)

```

	attempts	name	qualify	score
a	1	Anastasia	yes	12.5
b	3	Dima	no	9.0
c	2	Katherine	yes	16.5
d	3	James	no	NaN
e	2	Emily	no	9.0
f	3	Michael	yes	20.0
g	1	Matthew	yes	14.5
h	1	Laura	no	NaN
i	2	Kevin	no	8.0
j	1	Jonas	yes	19.0

```

1  # Messing with columns
2  import pandas as pd
3
4  table = {'name': ['Aditya', 'Aryan', 'Nebhrajani', 'Sahej'],
5           'Age': [25, 32, 30, 26],
6           'Profession': ['Developer', 'Analyst', 'Admin', 'HR'],
7           'Salary': [1000000, 1200000, 900000, 1100000]}
8
9
10 data1 = pd.DataFrame(table)
11 print(data1)
12
13 print('\n___ After Changing the Column Order___')
14 data2 = pd.DataFrame(table, columns = ['name', 'Profession', 'Salary',
15                                       'Age'])
16 print(data2)
17 print('\n___ Using Wrong Column ___')
18 data3 = pd.DataFrame(table, columns = ['name', 'Qualification', 'Salary',
19                                       'Age'])
20 print(data3)

```

	Age	Profession	Salary	name
0	25	Developer	1000000	Aditya
1	32	Analyst	1200000	Aryan
2	30	Admin	900000	Nebhrajani
3	26	HR	1100000	Sahej

```

___ After Changing the Column Order___
      name Profession  Salary  Age
0  Aditya  Developer  1000000   25
1   Aryan   Analyst  1200000   32

```

2	Nebhrajani	Admin	900000	30
3	Sahej	HR	1100000	26

--- Using Wrong Column ---

	name	Qualification	Salary	Age
0	Aditya	NaN	1000000	25
1	Aryan	NaN	1200000	32
2	Nebhrajani	NaN	900000	30
3	Sahej	NaN	1100000	26

```

1  # Dataframe indexing
2  import pandas as pd
3
4  table = {'name': ['Aditya', 'Aryan', 'Nebhrajani', 'Sahej'],
5           'Age': [25, 32, 30, 26],
6           'Profession': ['Developer', 'Analyst', 'Admin', 'HR'],
7           'Salary': [1000000, 1200000, 900000, 1100000]}
8
9  data = pd.DataFrame(table)
10 print(data)
11
12 print('\n___Setting name as an index___')
13 new_data = data.set_index('name')
14 print(new_data)
15
16 print('\n___Return Index Aditya Details___')
17 print(new_data.loc['Aditya'])

```

	Age	Profession	Salary	name
0	25	Developer	1000000	Aditya
1	32	Analyst	1200000	Aryan
2	30	Admin	900000	Nebhrajani
3	26	HR	1100000	Sahej

___Setting name as an index___

	Age	Profession	Salary
name			
Aditya	25	Developer	1000000
Aryan	32	Analyst	1200000
Nebhrajani	30	Admin	900000
Sahej	26	HR	1100000

___Return Index Aditya Details___

Age	25
Profession	Developer
Salary	1000000

Name: Aditya, dtype: object

```

1  import pandas as pd
2
3  table = {'name': ['Aditya', 'Aryan', 'Nebhrajani', 'Sahej'],
4           'Age': [25, 31, 35, 26],
5           'Salary': [100000, 120000, 700000, 110000]
6           }
7
8  data = pd.DataFrame(table)
9  print(data)
10 print('\n___Shape and Size of a DataFrame___')
11 print(data.shape)
12 data2 = pd.DataFrame(table, columns = ['name', 'Profession', 'Salary',
13                                       'Age'])
14 data3 = pd.DataFrame(table, columns = ['name', 'Qualification', 'Salary',
15                                       'Age'])
16 print('___Data2 Values___ ')
17 print(data2.values)
18 print('\n___Data3 Values___ ')
19 print(data3.values)
20 data1 = pd.DataFrame(table)
21 table = {'Age': [25, 32, 30, 26],
22          'Salary': [1000000, 1200000, 900000, 1100000]
23          }
24 data4 = pd.DataFrame(table)
25 data1.index.name = 'Emp No'
26 print(data1)
27 print()
28 data4.index.name = 'Cust No'
29 print(data4)
30 data1.columns.name = 'Employee Details'
31 print(data1)
32 data4.columns.name = 'Customers Information'
33 print(data4)
34 data1 = pd.DataFrame(table)
35 print(data1)
36 print('\n___describe function result___')
37 print(data1.describe())

```

	Age	Salary	name
0	25	100000	Aditya
1	31	120000	Aryan
2	35	700000	Nebhrajani
3	26	110000	Sahej

```

___Shape and Size of a DataFrame___
(4, 3)

```

___Data2 Values___

```
[['Aditya' nan 100000 25]
 ['Aryan' nan 120000 31]
 ['Nebhrajani' nan 700000 35]
 ['Sahej' nan 110000 26]]
```

___Data3 Values___

```
[['Aditya' nan 100000 25]
 ['Aryan' nan 120000 31]
 ['Nebhrajani' nan 700000 35]
 ['Sahej' nan 110000 26]]
```

	Age	Salary	name
Emp No			
0	25	100000	Aditya
1	31	120000	Aryan
2	35	700000	Nebhrajani
3	26	110000	Sahej

()

	Age	Salary
Cust No		
0	25	1000000
1	32	1200000
2	30	900000
3	26	1100000

Employee Details	Age	Salary	name
Emp No			
0	25	100000	Aditya
1	31	120000	Aryan
2	35	700000	Nebhrajani
3	26	110000	Sahej

Customers Information	Age	Salary
Cust No		
0	25	1000000
1	32	1200000
2	30	900000
3	26	1100000

	Age	Salary
0	25	1000000
1	32	1200000
2	30	900000
3	26	1100000

___describe function result___

	Age	Salary
count	4.000000	4.000000e+00
mean	28.250000	1.050000e+06
std	3.304038	1.290994e+05
min	25.000000	9.000000e+05

25%	25.750000	9.750000e+05
50%	28.000000	1.050000e+06
75%	30.500000	1.125000e+06
max	32.000000	1.200000e+06