




Lnr	Mrk	Qty	Description	Width × Height
005	W001-N-O	1	<p>ND NTech Villa Fixed frame w/sash NOBB 51260035 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,79W/m²K Weight 97 kg</p> <p>Without ventilator Outward opening topswing reversible sash Toughened LowE w/Lam 33.2 LowE WES/Ar Construction 4ES#+16G+4+16G+ES6,76 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black glass spacer RAL9004 Max pallet width 80 cm</p> <p>Details (sash): a.: Black Line Powdercoated hinge arms: Black Black handles</p> <p>Bar: 62 = Solid transom/mullion</p>	1108 × 2200mm




Lnr	Mrk	Qty	Description	Width × Height
010	W002- N-O	1	<p>ND NTech Villa Fixed frame w/sash NOBB 51260035 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,79W/m²K Weight 97 kg</p> <p>Without ventilator Outward opening topswing reversible sash Toughened LowE w/Lam 33.2 LowE WES/Ar Construction 4ES#+16G+4+16G+ES6,76 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black glass spacer RAL9004 Max pallet width 80 cm</p> <p>Details (sash): a.: Black Line Powdercoated hinge arms: Black Black handles</p> <p>Bar: 62 = Solid transom/mullion</p>	1108 × 2200mm





Lnr	Mrk	Qty	Description	Width× Height
015	W003- 5-NF	3	<p>ND NTech Villa Fixed frame NOBB 47543466 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,66W/m²K Weight 168 kg</p> <p>Without ventilator Lam 33.1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Max pallet width 80 cm</p>	1227 ×3210mm



Lnr	Mrk	Qty	Description	Width× Height
017	W0-06-E-F	1	<p>ND NTech Villa Fixed frame NOBB 47543466 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,74W/m²K Weight 65 kg</p> <p>Without ventilator Lam 33.1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Max pallet width 80 cm</p>	708 ×2100mm





Lnr	Mrk	Qty	Description	Width × Height
020	W0-07- N-O	1	<p>ND NTech Villa Sideswing reversible NOBB 47546985 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,81W/m²K Weight 60 kg</p> <p>Left hinge Without ventilator Outward opening sideswing reversible sash Lam 33,1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Black handles Max pallet width 80 cm</p>	<p>908 × 1500mm</p> 

Lnr	Mrk	Qty	Description	Width × Height
025	W0-08- N-O	1	<p>ND NTech Villa Sideswing reversible NOBB 47546985 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,81W/m²K Weight 60 kg</p> <p>Right hinge Without ventilator Outward opening sideswing reversible sash Lam 33,1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Black handles Max pallet width 80 cm</p>	<p>908 × 1500mm</p> 


All drawings viewed externally


Lnr	Mrk	Qty	Description	Width× Height
030	W0-09- W-F	1	<p>ND NTech Villa Fixed frame NOBB 47543466 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,76W/m²K Weight 37 kg</p> <p>Without ventilator Lam 33.1 LowE/Toughened Matelux/Toughened LowE MTECH/Ar Construction 6,38ES+16G+4#+16G+#ES6 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Max pallet width 80 cm</p>	708 ×1200mm



Lnr	Mrk	Qty	Description	Width × Height
035	D0-02-W	1	<p>ND NTech Villa Balcony door (security)</p> <p>NOBB 47547057</p> <p>Construction 105/80, 113 mm frame incl. 8 mm alum.</p> <p>U-value product: 0,82W/m²K</p> <p>Weight 104 kg</p> <p>Right hinge</p> <p>Without ventilator</p> <p>Outward opening sidehinged door leaf</p> <p>Lam 33,1 Low E 2s WES/Ar</p> <p>Construction 6,38ES+16G+4+16G+ES6,38</p> <p>Safety gl. externally & internally</p> <p>Threshold 25 mm</p> <p>Panel height 136 mm</p> <p>Aluminium cladded</p> <p>Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing</p> <p>Product RAL 7033 Cement grey</p> <p>Details:</p> <p>Wallside frame finished</p> <p>No sub frame groove</p> <p>No fixing holes</p> <p>Classic profile, internally</p> <p>Handle int. thumbturn cylinder / ext. without hole for cylinder</p> <p>Max pallet width 80 cm</p> <p>Black Line</p> <p>Black glass spacer RAL9004</p> <p>Black hinges</p> <p>Black handles</p>	<p>1108 × 2200mm</p> 


Lnr	Mrk	Qty	Description	Width × Height
040	D0-03-W	1	<p>ND NTech Villa Balcony door (security)</p> <p>NOBB 47547057</p> <p>Construction 105/80, 113 mm frame incl. 8 mm alum.</p> <p>U-value product: 1,2W/m²K</p> <p>Weight 81 kg</p> <p>Right hinge</p> <p>With ventilator</p> <p>Outward opening sidehinged door leaf</p> <p>Toughened w/Lam 33.1 LowE WES/Ar</p> <p>Construction 4#+16G+ES6,38</p> <p>Safety gl. externally & internally</p> <p>Threshold 25 mm</p> <p>Panel height 136 mm</p> <p>Aluminium clad</p> <p>Product Standard RAL colour, Powder coated</p> <p>Surface finishing</p> <p>Product NCS S0502Y Std White</p> <p>Details:</p> <p>Wallside frame finished</p> <p>No sub frame groove</p> <p>No fixing holes</p> <p>Classic profile, internally</p> <p>Handle int. thumbturn cylinder / ext. without hole for cylinder</p> <p>Max pallet width 80 cm</p> <p>Black Line</p> <p>Black glass spacer RAL9004</p> <p>Black hinges</p> <p>Black handles</p>	1188 × 2188mm



Lnr	Mrk	Qty	Description	Width× Height
045	W0-10- W-F	1	<p>ND NTech Villa Fixed frame NOBB 47543466 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,68W/m²K Weight 105 kg</p> <p>Without ventilator Lam 33.1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Max pallet width 80 cm</p>	<p>1108 ×2200mm</p> 

Lnr	Mrk	Qty	Description
050	D0-04-S	1	ND NTech Villa Double Balcony door (security) NOBB 53289320 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,81W/m²K Weight 198 kg

Width× Height
2088 ×2200mm



Right door leaf primary
Without ventilator
Inward opening sidehinged door leaf
Lam 33,1 Low E 2s WES/Ar
Construction 6,38ES+16G+4+16G+ES6,38
Safety gl. externally & internally
Threshold 25 mm

Panel height 136 mm

Aluminium cladded

Product RAL 7033 matt Cement grey, Powder coated, gloss 30

Surface finishing

Product RAL 7033 Cement grey

Details:

Wallside frame finished
No sub frame groove
No fixing holes
Classic profile, internally
Black Line
Black glass spacer RAL9004
Black hinges
Max pallet width 80 cm

Details (sash):

a.: Handle int. thumbturn cylinder / ext. without hole for cylinder
Black handles

Note (only for customer):

MAX WIDTH 2088MM



0,81



198

All drawings viewed externally

Lnr	Mrk	Qty	Description	Width× Height
055	W0-11-S-F	1	<p>ND NTech Villa Fixed frame NOBB 47543466 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,67W/m²K Weight 123 kg</p> <p>Without ventilator Lam 33.1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Max pallet width 80 cm</p>	1308 ×2200mm




All drawings viewed externally

Lnr	Mrk	Qty	Description	Width × Height
060	W0-12-S-F	1	<p>ND NTech Villa Fixed frame NOBB 47543466 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,68W/m²K Weight 100 kg</p> <p>Without ventilator Lam 33.1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Max pallet width 80 cm</p>	1800 × 1300mm




Lnr	Mrk	Qty	Description
065	D0-05-S	1	<p>ND NTech Villa Double Balcony door (security)</p> <p>NOBB 53289320</p> <p>Construction 105/80, 113 mm frame incl. 8 mm alum.</p> <p>U-value product: 0,81W/m²K</p> <p>Weight 198 kg</p> <p>Right door leaf primary</p> <p>Without ventilator</p> <p>Inward opening sidehinged door leaf</p> <p>Lam 33,1 Low E 2s WES/Ar</p> <p>Construction 6,38ES+16G+4+16G+ES6,38</p> <p>Safety gl. externally & internally</p> <p>Threshold 25 mm</p> <p>Panel height 136 mm</p> <p>Aluminium cladded</p> <p>Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing</p> <p>Product RAL 7033 Cement grey</p> <p>Details:</p> <p>Wallside frame finished</p> <p>No sub frame groove</p> <p>No fixing holes</p> <p>Classic profile, internally</p> <p>Black Line</p> <p>Black glass spacer RAL9004</p> <p>Black hinges</p> <p>Max pallet width 80 cm</p> <p>Details (sash):</p> <p>a.: Handle int. thumbturn cylinder / ext. without hole for cylinder</p> <p>Black handles</p> <p>Note (only for customer):</p> <p>MAX WIDTH 2088mm</p>


Width× Height
2088 ×2200mm





All drawings viewed externally

Lnr	Mrk	Qty	Description	Width × Height
070	W0-13-S-F	1	<p>ND NTech Villa Fixed frame NOBB 47543466 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,77W/m²K Weight 41 kg</p> <p>Without ventilator Lam 33.1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Max pallet width 80 cm</p>	708 × 1300mm



Lnr	Mrk	Qty	Description	Width × Height
071	W0-14-E-F	1	<p>ND NTech Villa Fixed frame NOBB 47543466 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,74W/m²K Weight 45 kg</p> <p>Without ventilator Lam 33.1 LowE/Toughened Matelux/Toughened LowE MTECH/Ar Construction 6,38ES+16G+4#+16G+#ES6 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Max pallet width 80 cm</p>	<p>696 × 1488mm</p> 

Lnr	Mrk	Qty	Description	Width × Height
075	W0-15- E-O	1	<p>ND NTech Villa Topswing reversible NOBB 47546974 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,79W/m²K Weight 73 kg</p> <p>Without ventilator Outward opening topswing reversible sash Lam 33.1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Powdercoated hinge arms: Black Black handles Max pallet width 80 cm</p>	<p>1108 × 1500mm</p> 


Lnr	Mrk	Qty	Description	Width × Height
080	W1-01- N-O	1	<p>ND NTech Villa Topswing reversible NOBB 47546974 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,79W/m²K Weight 73 kg</p> <p>Without ventilator Outward opening topswing reversible sash Lam 33.1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Powdercoated hinge arms: Black Black handles Max pallet width 80 cm</p>	<p>1108 × 1500mm</p> 


Lnr	Mrk	Qty	Description	Width× Height
085	W1-02- N-F	1	<p>ND NTech Villa Fixed frame NOBB 47543466 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,69W/m²K Weight 92 kg</p> <p>Without ventilator Lam 33.1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Max pallet width 80 cm</p>	1227 ×1735mm




Lnr	Mrk	Qty	Description	Width× Height
090	W1-03- N-F	1	<p>ND NTech Villa Fixed frame NOBB 47543466 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,69W/m²K Weight 92 kg</p> <p>Without ventilator Lam 33.1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Max pallet width 80 cm</p>	1227 ×1735mm



Lnr	Mrk	Qty	Description	Width× Height
095	W1-04- N-F	1	<p>ND NTech Villa Fixed frame NOBB 47543466 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,69W/m²K Weight 92 kg</p> <p>Without ventilator Lam 33.1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Max pallet width 80 cm</p>	<p>1227 ×1735mm</p> 


Lnr	Mrk	Qty	Description	Width × Height
100	W1-05- W-O	1	<p>ND NTech Villa Topswing reversible NOBB 47546974 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,79W/m²K Weight 73 kg</p> <p>Without ventilator Outward opening topswing reversible sash Lam 33.1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Powdercoated hinge arms: Black Black handles Max pallet width 80 cm</p>	<p>1108 × 1500mm</p> 

All drawings viewed externally


Lnr	Mrk	Qty	Description	Width × Height
105	W1-06-S-F	1	<p>ND NTech Villa Fixed frame NOBB 47543466 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,80W/m²K Weight 33 kg</p> <p>Without ventilator Lam 33.1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Max pallet width 80 cm</p>	<p>1108 × 675mm</p> 

All drawings viewed externally


Lnr	Mrk	Qty	Description	Width× Height
110	W1-07-S-F	1	<p>ND NTech Villa Fixed frame NOBB 47543466 Construction 105/80, 113 mm frame incl. 8 mm alum. U-value product: 0,74W/m²K Weight 106 kg</p> <p>Without ventilator Lam 33.1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Drip-nose (NOR) Black Line Black glass spacer RAL9004 Max pallet width 80 cm</p>	3600 ×675mm



Lnr	Mrk	Qty	Description	Width × Height
115	D0-06-S	1	<p>ND NTech Patio door NOBB 47547076 Construction 172 mm frame incl. 8 mm alum. U-value product: 0,80W/m²K Weight 292 kg</p> <p>Right door leaf primary Without ventilator Lifting sliding door leaf Lam 33,1 Low E 2s WES/Ar Construction 6,38ES+16G+4+16G+ES6,38 Safety gl. externally & internally Threshold 25 mm</p> <p>Panel height 136 mm</p> <p>Aluminium cladded Product RAL 7033 matt Cement grey, Powder coated, gloss 30</p> <p>Surface finishing Product RAL 7033 Cement grey</p> <p>Details: Wallside frame finished No sub frame groove No fixing holes Classic profile, internally Max pallet width 80 cm Black glass spacer RAL9004</p> <p>Details (sash): b.: Handle int. thumbturn / ext. without hole for cyl. Black handles Black Line</p>	2850 × 2200mm



All drawings viewed externally

Lnr	Mrk	Qty	Description	Width × Height
120	D0-01-E	1	ND External door HomeGuard HG-104 NOBB 53289365 Construction 105 mm frame U-value product: ~1,0W/m²K Weight 55 kg Right hinge Inward opening sidehinged door leaf Groove (decor), only outside Surface finishing Product RAL 7033 Cement grey Details: No fixing holes No sub frame groove Wallside frame finished Winkhaus STV-F 2070/65 3-point lock (3 striking plates) Hoppe Atlanta Handle PAS24 (F1), delivered in the box External Cylinder/Internal thumbturn Euro Black Line Black glass spacer RAL9004 Black hinges Max pallet width 80 cm	1000 × 2105mm 

All drawings viewed externally

Lnr	Mrk	Qty	Description	Width× Height
991		1	Non standard stain colour NOBB 26924910	
992		1	Non standard finishing NOBB 26924910	

Averaged U-value: ~0,77W/m²K

Calculation of U-value in accordance to NS-EN ISO 10077-1, 10077-2 and the programme "Therm".
Centre U-value of glass is calculated in accordance to NS-EN 673.
The calculation methodology is independently quality assured by SINTEF Building and Infrastructure.

Reservation regarding the ongoing war situation and sanctions

In the event an Order(s) – or parts thereof – is delayed due to a war situation and/or subsequent sanctions; NorDan disclaims all responsibilities for any financial loss and/or other liabilities attributable to such delay.

Risk of colour deviation

NorDan's products are coated using standard coating systems intended for normal UV exposure and UK/Ireland/Scandinavian climate conditions. NorDan have no liability for any discrepancies related to matching of colours with other products which are not coated by NorDan. This includes, but is not limited to, other products and/or facade elements.

Be aware about possible significant/noticeable colour deviations for different manufacturers of paint, applicators and described parameters:

- Significant - differences in special finish colours: pearl, mica, metallic
- Noticeable - connected elements with different gloss finishes
- Noticeable - difference between color batches
- Noticeable - various base material and surface structure smooth to rough and difference in thickness

General: Comparison and assessment of coated surfaces is carried out according to EN ISO 3668

Aluminum: Difference in shades for Standard Colors meets CEPE regulations.

Colours can be verified by customer by ordering a sample from NorDan

Important information

Glass must be pressure equalized due to the difference in air pressure in the lowlands in relation to the air pressure at altitudes above 800m. It is the customer's responsibility to inform if the windows are to be used above this height before ordering. NorDan products may not be modified without the written consent of NorDan.

Thermal breakage can occur due to critical temperature differences on the glass surface. Glass can crack if it is partially covered by, for example, large cushions/sofa or curtains/blinds/plisse that hang closely against the glass. Breakage caused by improper use is not eligible for warranty claims. For more information, visit www.nordan.no/info.

Goods liability

Important information regarding goods liability:

NorDan's responsibility for the goods ends upon delivery in accordance with the order's agreed-upon delivery terms. All handling and treatment of goods after takeover is the buyer's responsibility.

NB! It is always the receiver's responsibility that the goods are handled and moved in a safe and approved manner. When handling goods, the receiver must have approved certificates in accordance with the operation to be performed. When lifting, a safety zone must be created, and straps must be attached so that goods cannot fall should an accident occur.