Harkin Internorm 25 Canal Walk Park West Industrial Estate Dublin 12

davin@harkin.ie 087 608 5514 01-524 1265



Customer number: 9

Offer number: 20240005

Clerk in charge: Larkin Davin Telephone No.: 01 524 1265 EMail: davin@harkin.ie

Date: 19.01.2024

Offer Mr.Nial Douglas - Co.Cork

AT540 ALUMINIUM ENTRANCE DOOR

Internorm

CHARACTERISTICS

Construction depth93 mm

Colour inside Traffic white RAL 9016 matt (M916)
External colour Anthracite grey RAL 7016 matt (HM716)

Locking Multi-point lock (MV)
Cylinder Standard cylinder AZ

Handle inside GD15 lever handle stainless steel

(GD15)

Handle outside Bar handle vertical straight (EGS01)

Designer panel Designer element PG



Symbolic photo

Spacer Coating

ISO spacer black

ECLAZ® (high insulation value with high light transmission)

Glazing Triple 48mm coated obscured glass 33b.2#(laminated)/15Ar/4/15Ar/b33.2#(laminated) (0.6W/m²K,

38dB, 3GN-IS)

- Perfect material: Aluminium stands for longevity, weather-resistance and has an easy-to-care-for surface.
- Flush design: The design of this door is absolutely flush and completely smooth both inside and out.
- **Permanent innovation & quality:** Consistent advancement of in-house product development guarantees premium products at the cutting edge of technology.
- Optimally hidden: A concealed door hinge as standard in the series.
- Outstanding break-in protection: Various different security systems up to RC2 ensure reliable break-in protection.
- Optimised heat insulation & sealing properties: 3-chamber frame profile, foam insulated core, and thermally separated threshold as well as 3 surrounding seals ensure superior heat and sound insulation.

Deviations to this information are listed in the positions descriptions!



Offer number: 20240005

Pos.	Quantity	Description	Price per unit EUR	Total price EUR	
100	1,00 Pcs.	NR, Frame system in side light: DR, Obscure glass: Matt foil Satinato whit Installation for sash: Inward-oper Designer element PG1: Decorative element glass: Quadruple 33b.2#(laminated)/20Ar/5/20/5/20A 39dB, 4DK-IS_) operation: Cylinder ring PR20, Key GR10, AZ profile 60/40 keyed to differ (ZA1 accessories: 30 mm connection be Pre-drilled screw hardware 3-sided (Element width: 2000mm, Element height: 2400mm, Frame system: NR, Frame system in side light: DR, Vertical division: 1100/900, Obscure glass: Matt foil Satinato white, Installation for sash: Inward-opening, Opening direction: DIN left, Designer element PG1: Decorative element glass: Quadruple 84mm coated obscured glass 33b.2#(laminated)/20Ar/5/20/5/20Ar/b33.2#(laminated) (0.5W/m²K, 39dB, 4DK-IS_) operation: Cylinder ring PR20, Key hole cover plate stainless steel		
		Sub total Discount VAT		7.587,23 -10% +23%	
		SUM total	===:	€8,399.06 ======	

Please direct all sales enquiries to davin@harkin.ie

Please direct all technical enquiries to james@harkin.ie

Thank you for your business and we look forward to working with you and your team.

The Harkin Team