

SUB: Design Pattern And Framework

TOPIC: JAVASCRIPT

Java Script Operators

What is an Operator?

Let us take a simple expression **4 + 5 is equal to 9**. Here 4 and 5 are called **operands** and '+' is called the **operator**. JavaScript supports the following types of operators.

- Arithmetic Operators
- Comparison Operators
- Logical (or Relational) Operators
- Assignment Operators
- Conditional (or ternary) Operators
- 'typeof' Operator

Arithmetic Operator

Operator	Description
+	Addition
-	Subtraction
*	Multiplication
**	Exponentiation (ES2016)
/	Division
%	Modulus (Remainder)
++	Increment
--	Decrement

Java Script Operator

The following code shows how to use arithmetic operators in JavaScript.

```
<html>
<body>

<script type="text/javascript">
<!--
var a = 33;
var b = 10;
var c = "Test";
var linebreak = "<br />";

document.write("a + b = ");
result = a + b;
document.write(result);
document.write(linebreak);
```

Assignment Operator

Operator	Example	Same As
=	<code>x = y</code>	<code>x = y</code>
+=	<code>x += y</code>	<code>x = x + y</code>
-=	<code>x -= y</code>	<code>x = x - y</code>
*=	<code>x *= y</code>	<code>x = x * y</code>
/=	<code>x /= y</code>	<code>x = x / y</code>
%=	<code>x %= y</code>	<code>x = x % y</code>
**=	<code>x **= y</code>	<code>x = x ** y</code>

Comparison Operator

Operator	Description
----------	-------------

==	equal to
----	----------

===	equal value and equal type
-----	----------------------------

!=	not equal
----	-----------

!==	not equal value or not equal type
-----	-----------------------------------

>	greater than
---	--------------

<	less than
---	-----------

>=	greater than or equal to
----	--------------------------

<=	less than or equal to
----	-----------------------

?	ternary operator
---	------------------

Java Script Operator

Example

Try the following code to understand how the Conditional Operator works in JavaScript.

```
<html>
<body>

<script type="text/javascript">
<!--
var a = 10;
var b = 20;
var linebreak = "<br />";

document.write ("((a > b) ? 100 : 200) => ");
result = (a > b) ? 100 : 200;
document.write(result);
document.write(linebreak);
```

Java Script Operator

typeof Operator

The **typeof** operator is a unary operator that is placed before its single operand, which can be of any type. Its value is a string indicating the data type of the operand.

The *typeof* operator evaluates to "number", "string", or "boolean" if its operand is a number, string, or boolean value and returns true or false based on the evaluation.

```
<script type="text/javascript">
<!--
var a = 10;
var b = "String";
var linebreak = "<br />";

result = (typeof b == "string" ? "B is String" : "B is Numeric");
document.write("Result => ");
document.write(result);
```

Bitwise Operator

Operator	Description	Example	Same as	Result	Decimal
&	AND	5 & 1	0101 & 0001	0001	1
	OR	5 1	0101 0001	0101	5
~	NOT	~ 5	~0101	1010	10
^	XOR	5 ^ 1	0101 ^ 0001	0100	4
<<	left shift	5 << 1	0101 << 1	1010	10
>>	right shift	5 >> 1	0101 >> 1	0010	2
>>>	unsigned right shift	5 >>> 1	0101 >>> 1	0010	2

Java Script Function

Like any other advanced programming language, JavaScript also supports all the features necessary to write modular code using functions. You must have seen functions like **alert()** and **write()** in the earlier chapters. We were using these functions again and again, but they had been written in core JavaScript only once.

Function Definition

Before we use a function, we need to define it. The most common way to define a function in JavaScript is by using the **function** keyword, followed by a unique function name, a list of parameters (that might be empty), and a statement block surrounded by curly braces.

Java Script Function

```
<script type="text/javascript">  
<!--  
function functionname(parameter-list)  
{  
    statements  
}  
//-->  
</script>
```

Java Script Function

```
<html>
<head>
<script type="text/javascript">
function sayHello()
{
    document.write ("Hello there!");
}
</script>
</head>
<body>
<p>Click the following button to call the function</p>
<form>
<input type="button" onclick="sayHello()" value="Say Hello">
</form>
<p>Use different text in write method and then try...</p>
</body>
```

Java Script Function Parameters

```
<html>
<head>
<script type="text/javascript">
function sayHello(name, age)
{
    document.write (name + " is " + age + " years old.");
}
</script>
</head>
<body>
<p>Click the following button to call the function</p>
<form>
<input type="button" onclick="sayHello('Zara', 7)" value="Say Hello">
</form>
</body>
</html>
```

Java Script Function Return Statement

The return Statement

A JavaScript function can have an optional **return** statement. This is required if you want to return a value from a function. This statement should be the last statement in a function.

For example, you can pass two numbers in a function and then you can expect the function to return their multiplication in your calling program.

Java Script Function – Return Statement

```
<html>
<head>
<script type="text/javascript">
function concatenate(first, last)
{
    var full;
    full = first + last;
    return full;
}
function secondFunction()
{
    var result;
    result = concatenate('Zara', 'Ali');
    document.write (result );
} </script> </head>
```

LECTURE-3 JAVASCRIPT.pptx - PowerPoint (Product Activation Failed)

Java Script Function Return Statement

```
<body>
```

```
<p>Click the following button to call the function</p>
```

```
<form>
```

```
<input type="button" onclick="secondFunction()" value="Call Function">
```

```
</form>
```

```
<p>Use different parameters inside the function and then try...</p>
```

```
</body>
```

```
</html>
```


Java Script Function – Nested Function

```
<html>
<head>
<script type="text/javascript">
<!--
function hypotenuse(a, b) {
    function square(x) { return x*x; }
    return Math.sqrt(square(a) + square(b));
}
function secondFunction(){
    var result;
    result = hypotenuse(1,2);
    document.write ( result );
}
//-->
</script>
```

Java Script Function – Nested Function

```
<body>
```

```
<p>Click the following button to call the function</p>
```

```
<form>
```

```
<input type="button" onclick="secondFunction()" value="Call Function"
```

```
</form>
```

```
<p>Use different parameters inside the function and then try...</p>
```

```
</body>
```

```
</html>
```

Java Script Function - Constructor

The *function* statement is not the only way to define a new function; you can define your function dynamically using **Function()** constructor along with the **new** operator.

```
<script type="text/javascript">  
<!--  
var variablename = new Function(Arg1, Arg2..., "Function Body");  
//-->  
</script>
```

The **Function()** constructor expects any number of string arguments. The last argument is the body of the function – it can contain arbitrary JavaScript statements, separated from each other by semicolons.

Notice that the **Function()** constructor is not passed any argument that specifies a name for the function it creates. The **unnamed** functions created with the **Function()** constructor are called **anonymous** functions.

Java Script Function - Constructor

```
<html>
<head>
<script type="text/javascript">
<!--
var func = new Function("x", "y", "return x*y;");

function secondFunction(){
    var result;

    result = func(10,20);
    document.write ( result );
}
//-->
</script>
```

Java Script Function - Constructor

```
<body>
```

```
<p>Click the following button to call the function</p>
```

```
<form>
```

```
<input type="button" onclick="secondFunction()" value="Call Function
```

```
</form>
```

```
<p>Use different parameters inside the function and then try...</p>
```

```
</body>
```

```
</html>
```

Java Script Function – Literal Function

Function Literals

JavaScript 1.2 introduces the concept of **function literals** which is another new way of defining functions. A function literal is an expression that defines an unnamed function.

```
<script type="text/javascript">  
<!--  
var variablename = function FunctionName(Argument List){  
    Function Body  
};  
//-->  
</script>
```

JavaScript Function –Literal Function

```
<html>
<head>
<script type="text/javascript">
<!--
var func = function(x,y){ return x*y };
function secondFunction(){
    var result;
    result = func(10,20);
    document.write ( result );
}
//-->
</script>
</head>
```

Java Script Function – Literal Function

```
<body>
<p>Click the following button to call the function</p>
<form>
<input type="button" onclick="secondFunction()" value="Call Function">
</form>
<p>Use different parameters inside the function and then try...</p>
</body>
</html>
```