# **Exploring the Frontier of Vision-Language Models: A Survey of Current Methodologies and Future Directions**

Akash Ghosh<sup>1</sup>, Arkadeep Acharya <sup>1</sup>, Sriparna Saha<sup>1</sup>, Vinija Jain<sup>2,3\*</sup>, Aman Chadha<sup>2,3\*</sup>

<sup>1</sup>Department of Computer Science And Engineering, Indian Institute of Technology Patna <sup>2</sup>Stanford University, <sup>3</sup>Amazon AI

{akash\_2321cs219, arkadeep\_2101ai41, sriparna}@iitp.ac.in, hi@vinija.ai, hi@aman.ai

### **Abstract**

The advent of Large Language Models (LLMs) has significantly reshaped the trajectory of the AI revolution. Nevertheless, these LLMs exhibit a notable limitation, as they are primarily adept at processing textual information. To address this constraint, researchers have endeavored to integrate visual capabilities with LLMs, resulting in the emergence of Vision-Language Models (VLMs). These advanced models are instrumental in tackling more intricate tasks such as image captioning and visual question answering. In our comprehensive survey paper, we delve into the key advancements within the realm of VLMs. Our classification organizes VLMs into three distinct categories: models dedicated to vision-language understanding, models that process multimodal inputs to generate unimodal (textual) outputs and models that both accept and produce multimodal inputs and outputs. This classification is based on their respective capabilities and functionalities in processing and generating various modalities of data. We meticulously dissect each model, offering an extensive analysis of its foundational architecture, training data sources, as well as its strengths and limitations wherever possible, providing readers with a comprehensive understanding of its essential components. We also analyzed the performance of VLMs in various benchmark datasets. By doing so, we aim to offer a nuanced understanding of the diverse landscape of VLMs. Additionally, we underscore potential avenues for future research in this dynamic domain, anticipating further breakthroughs and advancements.

## 1 Introduction

The advent of Large Language Models (LLMs) has marked the onset of a transformative era in Artificial Intelligence, reshaping the entire landscape. Research labs, spanning both academia and industry, are actively engaged in a competitive race to advance the capabilities of LLMs. Yet, a notable limitation has come to the forefront – these models are confined to processing a singular modality of data, specifically text. This constraint underscores a pivotal challenge in the ongoing pursuit of refining LLMs to operate seamlessly across multiple modalities, marking a crucial avenue for further innovation in the realm of AI.

Natural intelligence excels in processing information across multiple modalities, encompassing written and spoken language, visual interpretation of images, and comprehension of videos. This innate ability to seamlessly integrate diverse sensory inputs enables humans to navigate the complexities of the real world. For artificial intelligence to emulate human-like cognitive functions, it must similarly embrace multimodal data processing. This imperative is not merely technological but essential for providing AI systems with contextual awareness and adaptability in real-world scenarios.

In response to these limitations, researchers have pioneered a cutting-edge class of neural models known as Vision-Language Models (VLMs). These models intricately combine visual and textual information, showcasing a remarkable proficiency in comprehending and generating content that involves both images and text. Designed to excel in tasks such as image captioning, responding to visual queries, and generating images based on textual descriptions, VLMs exhibit a versatile capability. Their seamless integration of visual and linguistic modalities positions them at the forefront of technological advancements, allowing them to navigate the intricate interplay between images and text with unparalleled finesse.

In recent times, major research labs have been consistently introducing innovative VLMs, including DeepMind's Flamingo, Salesforce's BLIP, and OpenAI's CLIP. Examples like GPT-4 (V) and Gemini showcase how chatbots are evolving within the realm of VLMs. Notably, not all multimodal models are VLMs; for instance, text-to-image models like Midjourney and DALL-E [Ramesh *et al.*, 2021] lack a language generation component, underscoring the diverse landscape of multimodal AI landscape. The general architecture of a VLM consists of an image and text encoder to generate the embeddings which are then fused in an image-text fusion layer and this fused vector is passed through an LLM to generate the final visually aware generated text. The working of a VLM is shown in Figure-2

In this survey paper, we have categorized VLMs based on their input processing and output generation capabilities into three distinct groups: Vision-Language Understanding Mod-

<sup>\*</sup>Work does not relate to position at Amazon.

els, Multimodal Input Text Generation models, and the most advanced Multimodal Input-Multimodal Output Models. The subsequent sections delve into comprehensive explanations of each category, elucidating the nuanced functionalities and capabilities of these diverse VLM frameworks.

Recent surveys in this area like [Wang et al., 2023b] mostly explore various pre-trained techniques and datasets used for developing multimodal models, [Yin et al., 2023] explores various key techniques in training various multimodal language models. [Wu et al., 2023a] provides practical applications and guidance in using multimodal language models. The most recent one by [Zhang et al., 2024] covers around 26 most recent VLMs in depth. In contrast to previous surveys, none have systematically classified Vision-Language Models (VLMs) based on their input-processing and output-generation capabilities. Our survey addresses this gap by providing a thorough categorization of VLMs, shedding light on the intricacies of their functionalities. We extensively analyze the performance of different VLMs across benchmark datasets, notably including the latest MME benchmark, providing comprehensive insights. Our survey represents the most comprehensive and current compilation of VLMs to date, encompassing approximately 70 models. It serves as the ultimate guide for users navigating the evolving realm of vision-language models, offering the most current and comprehensive insights in this pioneering field of research.

# 2 Vision-Language Model (VLMs)

In this section, we conduct a comprehensive examination of VLMs, categorizing them into three overarching classifications:

- Vision-Language Understanding (VLU): This category encompasses models specifically designed for the interpretation and comprehension of visual information in conjunction with language.
- Text Generation with Multimodal Input: Within this classification, we explore models that excel in generating textual content while leveraging multimodal inputs, thereby incorporating diverse forms of information.
- Multimodal Output with Multimodal Input: This category delves into models that exhibit proficiency in generating multimodal outputs by processing multimodal inputs. This involves the synthesis of diverse modalities, such as visual and textual elements, to produce comprehensive and coherent results. We have shown this broad classification in the figure-1.

Comparative Analysis We have conducted an extensive analysis of several Vision-and-Language Models (VLMs) across ten widely recognized benchmark datasets, spanning tasks such as Visual Question Answering (VQA) and image captioning. The results of this analysis are presented in Table 1. Additionally, we have evaluated the perception and cognition capabilities of these VLMs using the Multimodal Model Evaluation (MME) benchmark, with findings summarized in Table 2. Furthermore,

a comparative examination of various VLMs on video question-answering datasets is detailed in Table 3.

## 2.1 Vision-Language Understanding

**CLIP** [Radford *et al.*, 2021]: CLIP, introduced by OpenAI, is a neural network proficient in grasping visual concepts through natural language guidance. It seamlessly identifies visual categories on diverse benchmarks, mirroring the "zeroshot" capabilities seen in GPT-powered models. By scaling a basic contrastive pre-training task, it achieved competitive zero-shot performance on diverse image classification datasets. CLIP gives a much more robust performance than the finetuned deep learning vision models in general for classification tasks. Though CLIP excels at common object recognition but struggles with abstract tasks, fine-grained classification, generalization, and wording sensitivity.

**AlphaCLIP** [Sun *et al.*, 2023b]: The model is an upgraded version of CLIP, incorporating an alpha channel for attentive region indication, enhancing awareness. Alpha-CLIP focuses on specific areas while maintaining CLIP's recognition accuracy using an extended pipeline. It serves as a vision backbone for various applications, excelling in focused region attention but facing challenges with multiple objects and attention amplitude specification.

**MetaCLIP** [Xu *et al.*, 2023b]: CLIP's success lies in its data not just the model or pre-training objective. To address limited data transparency MetaCLIP was introduced which refines a raw data pool using metadata from CLIP's concepts, outperforming CLIP on benchmarks with 400M image-text pairs from CommonCrawl.

**GLIP** [Li *et al.*, 2022a]: Inspired by CLIP, GLIP employs contrastive pre-training for language-image representations, emphasizing object-level alignment through phrase grounding. It redefines object detection as a vision-language task, utilizing deep fusion for improved representations. GLIP's scalable pre-training on semantic-rich data enables automatic grounding box generation and robust zero/few-shot transferability to outperform baselines like CLIP on image captioning tasks and compete with a fully supervised dynamic head in downstream object detection tasks.

**VLMO** [Bao *et al.*, 2022]: Vlmo concurrently learns a dual encoder and a fusion encoder utilizing a modular Transformer network. The model adopts a Mixture-of-Modality-Experts (MOME) Transformer, comprising modality-specific experts and a shared self-attention layer in each block, providing notable modeling flexibility. Vlmo can be adeptly fine-tuned as a fusion encoder for vision-language classification tasks or employed as a dual encoder for efficient image-text retrieval, highlighting its versatility. The proposed stage-wise pre-training strategy maximizes the utilization of large-scale image-only and text-only data alongside image-text pairs, yielding state-of-the-art performance on diverse vision-language tasks such as visual question answering(VQA) and image retrieval.

**ImageBind** [Girdhar *et al.*, 2023]: The model learns a shared representation space by aligning various modalities' embeddings to image embeddings, utilizing diverse paired data sources. It enables zero-shot recognition across modalities, leveraging web-scale image-text data and large-scale vision-language models like CLIP. This approach requires minimal

<sup>&</sup>lt;sup>1</sup>We have shown the most well-known VLMs in this taxonomy due to space constraints.





Figure 1: Taxonomy of Visual Language Models highlighting the input and output formats that the models are capable of handling.



Component	Trainable	Frozen
LLM	MiniGPT-V2	Fuyu [Bavishi
Decoder	[Chen et al.,	et al., 2023],
	2023d]	Qwen-VL [Bai
		et al., 2023b]
Image	Qwen-VL [Bai	MiniGPT-V2
Encoder	et al., 2023b]	[Chen et al.,
		2023d]

#### **Image-Text Fusion:**

Some prominent examples are:

• **Qformer:** BLIP-2 [Li et al., 2023d]

Perceiver Resampler: Flamingo [Alayrac *et al.*, 2022]
Full Connected Layers (MLP): Llava [Liu *et al.*, 2023c]

Figure 2: A high-level overview of the architecture of VLMs highlighting various design choices with corresponding examples.

training for application across different tasks and modalities. ImageBind utilizes large-scale image-text pairs and naturally paired self-supervised data across diverse modalities (audio, depth, thermal, IMU) to achieve strong emergent zero-shot classification and retrieval performance. It outperforms specialist models on audio benchmarks and demonstrates versatility in compositional tasks. Further enhancements include richer alignment data and adapting embeddings for specific tasks.

VideoCLIP [Xu et al., 2021]: VideoCLIP focuses on pretraining a unified model for zero-shot video and text understanding without relying on labels for downstream tasks. It employs a contrastive learning framework with hard-retrieved negatives and overlapping positives for video-text pre-training. Key innovations include loosely temporally overlapping positive pairs and a retrieval-based sampling technique for negative pairs. The method utilizes contrastive loss and incorporates overlapped video-text clips for improved association. It is evaluated on various end tasks, showcasing state-of-the-art performance on video language datasets like Youcook2[Zhou et al., 2018]. The approach demonstrates significant advancements in zero-shot video-text understanding, outperforming previous work and even supervised approaches in some cases.

**VideoMAE** [Tong *et al.*, 2022]: VideoMAE is a self-supervised video pre-training method challenging the need for large-scale datasets. It adapts the masked autoencoder framework with a unique video tube masking strategy, achieving data efficiency on small datasets (3k-4k videos). It employs a Vision Transformer with joint space-time attention, demonstrating superior efficiency and effectiveness compared to traditional methods. VideoMAE outperforms in downstream tasks like action detection and holds potential for improvements through dataset expansion and integration of additional data streams. The paper acknowledges energy consumption concerns during pre-training but emphasizes VideoMAE's practical value in scenarios with limited data availability.

## 2.2 Text generation with Multimodal Input

**GPT-4V** [OpenAI, 2023]: GPT-4V marks a significant advancement, allowing users to instruct GPT-4 to analyze image inputs. OpenAI conducted extensive safety evaluations and

preparations for GPT-4V, building on the safety work done for GPT-4. The training process involved predicting the next word in a document, utilizing a vast dataset of text and image data. GPT-4V inherits both text and vision capabilities, presenting novel features at their intersection. The system card outlines OpenAI's preparation, early access period, safety evaluations, red team assessments, and implemented mitigations before broad release.

**LLaVA** [Liu *et al.*, 2023a]: The passage describes LLaVA, an open-source multimodal framework designed to enhance LLMs for understanding both language and images. It utilizes language-only GPT-4 to generate data for instruction-following tasks in a multimodal context. LLaVA integrates a vision encoder from CLIP with the LLM, enabling it to process visual information alongside language. The model undergoes pre-training on image-text pairs and fine-tuning for end-to-end multimodal understanding, resulting in a versatile multimodal chatbot. Early experiments show LLaVA's impressive performance, achieving an 85.1% relative score compared to GPT-4 on a synthetic instruction-following dataset and setting a new state-of-the-art accuracy of 92.53% on Science QA tasks when combined with GPT-4.

Flamingo [Alayrac et al., 2022]: Flamingo introduces novel architectural features to seamlessly integrate vision-only and language-only models. By incorporating interleaved crossattention layers with frozen language-only self-attention layers, Flamingo excels in handling sequences of intermixed visual and textual data. It adopts a Perceiver-based architecture to convert input sequence data, like videos, into a fixed set of visual tokens. Leveraging large-scale multimodal web corpora with interleaved text and images, Flamingo demonstrates remarkable few-shot learning capabilities across various benchmarks, surpassing models fine-tuned on significantly more task-specific data. This showcases its adaptability and efficiency in rapidly adapting to diverse image and video understanding tasks with limited examples. OpenFlamingo is an ongoing initiative aiming to create an open-source version of DeepMind's Flamingo models. Across seven visionlanguage datasets, OpenFlamingo models consistently achieve performance levels ranging from 80% to 89% of their counterparts in the Flamingo models. Med-Flamingo [Moor et al.,

Model	Science-QA	VizWiz	Flickr30K	POPE	VQA <sup>v2</sup>	GQA	LlavaBench	Chart-QA	MM-Vet	ViSiTBench
LLaVA	90.92	-	-	50.37 R/A	-	41.3	81.9	-	23.8 <sup>7B</sup>	1091 <sup>13B</sup>
LaVIN 13B	90.83	-	-	-	-	-	-	-	-	-
LaVIN 7B	89.41	-	-		-	-	-	-	-	-
BLIP-2	61 <sup>img</sup>	19.6	71.6	85.3 <sup>V13B</sup>	41	41	38.1 <sup>w</sup>	-	22.4	-
InstructBLIP <sup>V13B</sup>	63.1	34.5	82.8	88.57 R/A	=	49.5	58.2 <sup>w</sup>	=	25.6	-
InstructBLIP <sup>V7B</sup>	60.5	-	-	-	-	49.2	60.9 <sup>w</sup>	-	26.2	964
MetaCLIP	68.77	-	-	-	-	-	-	-	-	-
MiniGPT4	58.7	=	-	79.67 R/A	=	30.8	-	=	24.4	900
Qwen-VL	67.1 <sup>img</sup>	35.2	81	-	78.8	59.3	-	=	=	-
Owen-VL-Chat	68.2 <sup>img</sup>	38.9	85.8	-	78.2	57.5	-	-	-	-
GPT-4V	85	23	15.2(S)	-	0 <sup>VQAS</sup>	10 <sup>EM</sup>	-	78.5	_	1349
LLaVa 1.5 V7B	66.8	50	-	85.9	78.5	62	63.4 <sup>w</sup>	-	_	-
LLaVa 1.5 <sup>V13B</sup>	71.6	53.6	_	85.9	80	63.3	70.7	-	_	-
BakLLaVa-1	66.7	-	-	86.6	-	-	-	-	-	-
LLaMa-VID <sup>V13B</sup>	70	54.3	-	86	80	65	-	-	-	-
LLaMa-VID V7B	68.3	54.2	-	86	79.3	64.3	-	-	_	-
Sphinx	-	-	-	-	-	-	-	-	-	-
Gemini	-	-	-	-	-	-	-	80.8 <sup>u</sup>	-	-
IDEFICS-9B	-	35.5	-	-	50.9	38.4	-	-	-	997
IDEFICS-80B	-	36	-	-	60	45.2	-	-	-	-
Flamingo-9B	-	28.8	61.5	-	51.8	-	-	-	-	-
TinyGPT	-	33.4	-	-	-	33.6	-	-	-	-
Flamingo-80B	-	31.6	-	ı	56.3	-	-	ı	-	-
KOSMOS-1	-	29.2	65.2	-	51	-	-	-	-	-
Ferret-7B	-	-	80.39	90.24 R/A	1	-	86.7	-	-	-
Ferret-13B	-	-	81.13	-	-	-	87.5	-	-	-
mPLUG-Owl	-	-	-	53.97 R/A	1	-	-	-	-	1025
KOSMOS-2	-	-	80.5	-	51.1	-	70	-	-	-
Fuyu-8B	-	-	-	74.1	-	-	-	42.1	-	-
LLaMa-Adapter-v2-7b	-	-	-	-	=	-	-	=	31.4	1066
PaLM-E <sup>12B</sup>	-	-	-	-	76.2	-	-	-	-	-
PaLM-E <sup>562B</sup>	-	-	-	1	80	-	-	-	-	-
Frozen	-	-	-	-	29.5	-	-	-	-	-
Emu2 <sup>37B</sup>	-	-	-	-	33.3	-	-	-	-	-
Emu2-Chat	-	54.9	-	-	84.9	65.1	-	-	-	-
Lyrics <sup>V13B</sup>	71.1 <sup>img</sup>	37.6	8534	-	81.2	62.4	-	-	-	-

Table 1: Table showing the comparative analysis of multiple Visual Language Models on 10 benchmark datasets: Science-QA [Lu *et al.*, 2022], VizWiz [Danna *et al.*, 2018], Flickr30K [A *et al.*, 2016], POPE [Fan *et al.*, 2023], VQA<sup>v2</sup> [Goyal *et al.*, 2017], GQA [Hudson and Manning, 2019], LLaVaBench [Liu *et al.*, 2023c], Chart-QA [Masry *et al.*, 2022], MM-Vet [Yu *et al.*, 2023], ViSiTBench [Bitton *et al.*, 2023]. Vicuna, , <sup>img</sup>: only image, <sup>R/A</sup>: Random and Accuracy has been reported, <sup>VQAS</sup>: VQA Score, <sup>EM</sup>: EM Accuracy, <sup>w</sup>: in-the-wild version, <sup>u</sup>: Ultra version. <sup>XB</sup>: The model is of X billion parameters.

2023], a medical-focused multimodal few-shot learner based on OpenFlamingo-9B, achieves up to a 20% improvement in generative medical Visual Question Answering. It pioneers human evaluation in this context, involving clinicians in an interactive assessment, and enables applications like rationale generation.

PALM-E [Driess et al., 2023]: PALM-E emerges as an innovative Embodied Multimodal Language Model, meticulously crafted to navigate real-world scenarios by fusing language comprehension with continuous sensor inputs. This model is the result of a collaborative endeavor between TU Berlin and Google Research, signifying a pivotal advancement in the realm of multimodal AI. It incorporates real-world continuous sensor modalities into language models, training multi-modal sentences end-to-end with a pre-trained large language model. The model successfully tackles multiple embodied tasks, including robotic manipulation planning, visual question answering, and captioning. PaLM-E, the largest model with 562B parameters, demonstrates state-of-the-art performance in both embodied reasoning tasks and visuallanguage domains like OK-VQA. The model operates on multimodal sentences, showcasing positive transfer of knowledge from visual-language domains to embodied reasoning tasks, emphasizing its versatility and scalability. PaLM-E faces limitations in relying on low-level language-conditioned policies

for robotic tasks, prompting the proposal of self-supervised entity-centric labeling to enhance guidance in intricate tasks.

**BLIP** [Li *et al.*, 2023a]: BLIP is a novel Vision-Language Pre-training (VLP) framework, that surpasses existing models, excelling in both understanding and generation tasks, addressing noisy training limitations.BLIP introduces the Multimodal Mixture of Encoder-Decoder (MED) architecture, utilizing Image-Text Contrastive (ITC), Image-Text Matching (ITM), and Language Modeling (LM) objectives for pre-training. Captioning and Filtering (CapFilt) enhances data quality, improving downstream task performance.BLIP, implemented in PyTorch and pre-trained on a diverse 14 million image dataset, demonstrated notable improvements in downstream tasks like image-text retrieval and captioning. Leveraging nucleus sampling and effective parameter sharing, BLIP outperformed existing models on standard datasets.

**BLIP-2** [Li *et al.*, 2023a]: It introduces a cost-effective vision-language pre-training strategy with frozen image encoders and large language models. The Querying Transformer achieves state-of-the-art performance in vision-language tasks with fewer parameters, addressing interoperability challenges between different modality embeddings. BLIP-2 introduced a fresh component known as the Querying Transformer (Q-Former), serving as a trainable bridge between a static image encoder and a static LLM. Illustrated in Figure[3], the Q-

Former undergoes a two-stage pre-training regimen. Initially, the focus lies on vision-language representation learning, compelling the Q-Former to grasp visual elements most pertinent to the accompanying text. Subsequently, the emphasis shifts to vision-to-language generative learning, linking the Q-Former's output to a fixed LLM and refining its capabilities so that the visual representations it produces can be effectively interpreted by the LLM.

**InstructBLIP** [Dai *et al.*, 2023]: InstructBLIP employs instruction-aware visual feature extraction, enhancing its ability to extract informative features tailored to provided instructions. Achieving state-of-the-art zero-shot performance across 13 held-out datasets, InstructBLIP outperforms BLIP-2 and larger models like Flamingo. The models also excel in downstream tasks, demonstrating a 90.7% accuracy on ScienceQA IMG [Lu *et al.*, 2022], and showcase qualitative advantages over concurrent multimodal models in diverse capabilities such as visual scene understanding, knowledge-grounded image description, and multi-turn visual conversation.

KOSMOS-1 [Huang et al., 2023]: KOSMOS-1 is a VLM from Microsoft. Trained on a web-scale multimodal corpus, KOSMOS-1 excels in language understanding and generation, OCR-free NLP, and various perception-language tasks, showcasing its capabilities in image captioning and visual question answering. Using a Transformer-based architecture, KOSMOS-1 aligns vision with large language models. Its training involves diverse multimodal corpora, including The Pile and Common Crawl, with language-only instruction tuning. Additionally, the model excels in chain-of-thought prompting, generating rationales before addressing complex question-answering tasks. Overall, KOSMOS-1 represents a significant advancement in the field of Multimodal Large Language Models, offering robust performance across a wide range of tasks.

KOSMOS-2 [Peng et al., 2023]: KOSMOS-2 again from Microsoft Research, advances traditional models by introducing capabilities for perceiving object descriptions, such as bounding boxes, and grounding text in the visual world. Utilizing a unique representation format for referring expressions, KOSMOS-2 links text spans to spatial locations in images. Employing a sophisticated image processing approach, the model combines vision encodings with location tokens to understand and relate specific image areas to textual descriptions. Built on the KOSMOS-1 architecture, this Transformer-based causal language model represents a substantial step towards Embodiment AI and the convergence of language, multimodal perception, action, and world modeling, showcasing its potential for advancing artificial general intelligence.

MultiInstruct [Xu et al., 2022]: MultiInstruct presents a benchmark dataset for multimodal instruction tuning, featuring 62 tasks across 10 categories. Utilizing the OFA pre-trained multimodal language model, the study focuses on enhancing zero-shot performance on diverse tasks through large-scale text-only instruction datasets like Natural Instructions. Results show strong zero-shot performance and reduced model sensitivity to instruction variations. Comparative analysis of transfer learning strategies indicates improved robustness across multimodal tasks. Increasing task clusters during training enhances overall performance, supporting the effectiveness of

MultiInstruct.

**IDEFICS** [Laurençon *et al.*, 2023]: IDEFICS, an openaccess reproduction of the closed-source vision-language model Flamingo by DeepMind, boasts 80 billion parameters and is available on HuggingFace. It performs well in imagetext benchmarks, such as visual question answering and image captioning, utilizing in-context few-shot learning. IDEFICS has two versions – an 80 billion parameters model and a 9 billion parameters model.

**PaLI** [Chen *et al.*, 2022]: PALI, or Pathways Language and Image model, from Google Research, leverages large pre-trained encoder-decoder language models and vision transformers for joint language and vision modeling. The model achieves state-of-the-art results in various vision and language tasks across 100+ languages by utilizing a diverse multilingual dataset containing 10B images and texts. With a simple, modular, and scalable design, PaLI highlights the importance of joint scaling in vision and language components for effective training and performance.

Frozen [Tsimpoukelli et al., 2021]: Frozen, a multimodal few-shot learning approach developed by DeepMind, leveraging a pre-trained, frozen language model and a vision encoder trained on aligned image and caption data to enable rapid learning of new tasks with just a few examples, demonstrating its effectiveness in tasks such as learning words for new objects, visual question-answering, and incorporating outside knowledge across various benchmarks. The approach utilizes gradients through a frozen language model's self-attention layers to train the vision encoder. The system's notable limitation lies in its suboptimal performance on tasks learned with few shots compared to state-of-the-art models using full training sets, highlighting the potential for enhanced zero-shot and few-shot generalization through further improvements in accuracy and reduced seed requirements.

**Qwen-VL** [Bai et al., 2023a]: The Qwen-VL series, introduced as large-scale vision-language models, encompasses Owen-VL and Owen-VL-Chat, demonstrating exceptional performance in tasks such as image captioning, question answering, visual localization, and versatile interactions. Qwen-VLs demonstrate outstanding performance across various visioncentric tasks, surpassing counterparts of similar scale. Their exceptional accuracy extends beyond traditional benchmarks like captioning and question-answering to include recent dialogue benchmarks. Trained on multilingual image-text data, with a significant portion in English and Chinese, Qwen-VLs naturally support multiple languages. They handle multiple images concurrently during training, enabling Qwen-Chat-VL to contextualize and analyze complex scenarios. With higher-resolution inputs and fine-grained training data, Qwen-VLs excel in fine-grained visual understanding, outperforming existing vision-language models in grounding, text comprehension, question answering, and dialogue tasks.

**Fuyu-8B** [Bavishi *et al.*, 2023]: Fuyu-8B, a multi-modal text and image transformer developed by Adept AI, offers a simplified yet powerful solution tailored for digital agents. Its straightforward architecture and training process enhance comprehension, scalability, and deployment, making it ideal for various applications. Specifically designed for digital agents, Fuyu-8B seamlessly handles arbitrary image resolutions and

excels in tasks like graph and diagram comprehension, UI-based queries, and rapid processing of large images within 100 milliseconds. Despite its optimization for Adept's use case, Fuyu-8B delivers impressive performance in standard image understanding benchmarks such as visual question-answering and natural image captioning. Architecturally, Fuyu adopts a vanilla decoder-only transformer, efficiently processing image patches by linear projection into the first layer. Its versatility in supporting diverse image resolutions is achieved by treating image tokens like text tokens, utilizing raster-scan order, and signaling line breaks for adaptability.

Sphinx [Lin et al., 2023a]: SPHINX is a versatile VLM that integrates model weights, tuning tasks, and visual embeddings to enhance its capabilities. It unfreezes the large language model during pre-training to strengthen vision-language alignment and efficiently mixes weights from LLMs trained on real-world and synthetic data for robust understanding. By incorporating diverse tasks like region-level understanding and human pose estimation, SPHINX achieves mutual enhancement across different scenarios. It also extracts comprehensive visual embeddings from various sources, enriching language models with robust image representations. SPHINX demonstrates superior multi-modal understanding across applications and introduces an efficient strategy for capturing fine-grained details in high-resolution images, excelling in visual parsing and reasoning tasks.

Mirasol [Piergiovanni et al., 2023]: Mirasol, from Google DeepMind and Google Research, is a multimodal autoregressive model designed to handle both time-aligned modalities (audio, video) and non-aligned modality (text). The architecture involves segmenting long video-audio sequences into manageable chunks, passing them through respective encoders, and using a Combiner to fuse video and audio features. Autoregressive training predicts sequential features, with a separate Transformer block integrating textual prompts through crossmodal attention. This enables enriched contextual understanding, showcasing a comprehensive approach to multimodal learning and generation. Pretrained on 12% of VTP, the model uniformly weighed losses in pretraining, with a tenfold emphasis on unaligned text loss during fine-tuning. Ablation studies underscore its ability to maintain content consistency and adapt to dynamic changes in video-audio sequence

MiniGPT-4 [Zhu et al., 2023a]: MiniGPT-4 combines a frozen visual encoder (ViT + Q-Former from BLIP-2) with LLM using a single trainable projection layer. Pretrained on aligned image-text pairs and fine-tuned on detailed image descriptions, MiniGPT-4 exhibits GPT-4-like capabilities without training vision or language modules separately. The finetuning process enhances language outputs, demonstrating diverse skills like meme interpretation, recipe generation, and poem composition. The model's architecture involves a vision encoder, linear projection layer, and large language model.

MiniGPT-v2 [Chen et al., 2023d]: The model architecture of MiniGPT-v2 consists of a ViT visual backbone, a linear projection layer, and a large language model like LLaMA-2 [Touvron et al., 2023]. The ViT backbone is frozen during training, and four adjacent visual output tokens are concatenated and projected into LLaMA-2 space. Task-specific identifiers are incorporated during training using a three-stage

strategy with weakly labeled image-text datasets and multimodal instructional datasets. The model demonstrates superior performance in visual question-answering and visual grounding, outperforming other generalist models. The use of task identifier tokens enhances efficiency in multi-task learning, contributing to its state-of-the-art performance. Challenges include occasional hallucinations, emphasizing the need for more high-quality image-text-aligned data.

LLaVA-Plus [Liu et al., 2023e]: LLaVA-Plus, is a general-purpose multimodal assistant designed to enhance LMMs through visual instruction tuning. The model maintains a skill repository with diverse vision and vision-language pre-trained models, activating relevant tools in response to user inputs for various tasks. Trained on multimodal instruction-following data, LLaVA-Plus covers tool usage in visual understanding, generation, and external knowledge retrieval, surpassing its predecessor, LLaVA, in both existing and new capabilities. The training approach involves using GPT-4 to generate instruction data and integrating new tools through instruction tuning, enabling continuous enhancement. LLaVA-Plus demonstrates state-of-the-art performance on VisiT-Bench, a real-life multimodal task benchmark, excelling in tool use compared to other tool-augmented LLMs.

**BakLLaVA** [Bitton *et al.*, 2023]: It is a VLM developed by LAION, Ontocord, and Skunkworks AI. BakLLaVA uses a Mistral 7B base augmented with the LLaVA 1.5 architecture. Used in combination with llama.cpp. BakLLaVA is a faster and less resource-intensive alternative to GPT-4 with Vision.

**LLaVa-1.5** [Liu *et al.*, 2023a]: It is a refined version of the LLaVA, focusing on visual instruction tuning to enhance multimodal models. The paper outlines modifications to LLaVA, such as using CLIP-ViT-L-336px with an MLP projection and incorporating academic-task-oriented Visual Question Answering (VQA) data. Despite its advancements, limitations are acknowledged, such as prolonged training iterations due to the use of full image patches and challenges in processing multiple images and certain domain-specific tasks.

CogVLM [Wang et al., 2023a]: CogVLM is an open-source vision-language foundation model developed by researchers from Tsinghua University. Its architecture comprises a Vision Transformer (ViT) encoder (e.g., EVA2-CLIP-E) for image processing, with output mapped into the text feature space using an MLP adapter. The model includes a pre-trained GPTstyle language model and a visual expert module added to each layer, consisting of a QKV matrix and an MLP. CogVLM adopts a deep fusion approach, integrating visual and language features at multiple layers through the visual expert module, surpassing traditional shallow alignment methods. Alignment techniques involve pretraining on a vast dataset of 1.5 billion image-text pairs, employing image captioning loss and Referring Expression Comprehension (REC). Fine-tuning on various tasks, with a focus on free-form instructions, leads to the creation of a variant known as CogVLM-Chat.

**FERRET** [You *et al.*, 2023]: FERRET is designed for spatial referring and grounding in images at different shapes and granularities. Ferret's distinct features include a Hybrid Region Representation, blending discrete coordinates and continuous visual features for diverse region inputs. It uses a Spatial-Aware Visual Sampler to handle various region shapes

effectively and is trained on the Ground-and-Refer Instruction-Tuning (GRIT) dataset, which includes hierarchical spatial knowledge and hard negative samples. The architecture includes an image encoder, a spatial-aware visual sampler, and a Language Model. Ferret utilizes a pre-trained visual encoder (CLIP-ViT-L/14) and a Language Model's tokenizer for image and text embeddings. Training occurs on the GRIT dataset for three epochs, with the model randomly choosing between center points or bounding boxes to represent regions. In multimodal chatting tasks, Ferret significantly enhances performance by integrating refer-and-ground capabilities. Notably, Ferret mitigates the issue of object hallucination, a common challenge in multimodal models.

BARD[Google, 2023]: BARD from Google utilizes a reinforcement learning framework to automate machine learning model design, architecture search, and hyperparameter tuning, making it accessible to users without extensive AI expertise. The system is positioned as a standalone experiment, with a focus on productivity, creativity, and curiosity enhancement. Users engage BARD for tasks such as writing resumes, creating workout routines, and planning itineraries. The model is pre-trained on diverse data sources, and responses are generated by considering context, classified against safety parameters, and re-ranked based on quality. Human feedback and evaluation, including fine-tuning and reinforcement learning on human feedback, are used to improve BARD. Limitations include potential inaccuracies, biases, persona attribution, false positives/negatives, and vulnerability to adversarial prompting. Google is committed to addressing these limitations and improving BARD responsibly over time.

LLaMA-VID [Li et al., 2023c]: LLaMA-VID introduces a novel dual-token strategy, incorporating context and content tokens, to efficiently encode each video frame. This approach enables the model to handle hour-long videos while mitigating computational complexity. LLaMA-VID employs a hybrid architecture, incorporating pre-trained models like Vicuna for text processing and a Vision Transformer for image embeddings in videos. The Q-Former introduces the contextattention token (Et) by computing attention between querygenerated text embeddings (Q) and visual tokens (X). Et encapsulates relevant visual features. A content token (Ev) is obtained through mean pooling on visual tokens. Both tokens are integrated into the V decoder for generating text responses. LLaMA-VID's dual-token generation strategy, comprising context and content tokens, ensures adaptability to various settings, optimizing efficiency for videos while preserving detail for single images.LLaMA-VID is a video and image understanding model designed for efficiency, completing training in two days on 8xA100 GPUs. It uses EVA-G for visual encoding and QFormer for text decoding. The training set includes image and video caption pairs, with evaluations on diverse benchmarks. LLaMA-VID excels in zero-shot video QA benchmarks, achieving high accuracy with only two tokens per frame.

**CoVLM** [Li *et al.*, 2023b]: CoVLM introduces a novel approach to enhance large language models' compositional reasoning by integrating vision-language communicative decoding. Utilizing communication tokens, the model dynamically composes visual entities and relationships, improving

language generation through iterative communication with vision encoders and detection networks. Trained on a large-scale dataset, CoVLM outperforms baseline vision-language models in compositional reasoning tasks, and exhibits competitive performance in tasks such as referring expression comprehension and visual question answering. The model represents a noteworthy advancement in integrating vision and language models, with acknowledgment of potential future improvements in compositionality.

**Emu2:** [Sun *et al.*, 2023a]: Emu2 is a 37 billion-parameter generative multimodal model, that achieves remarkable incontext learning on diverse multimodal sequences, setting new records in few-shot understanding tasks. Employing a unified autoregressive objective, Emu2 seamlessly integrates visual embeddings and textual tokens. Its architecture includes a visual encoder, multimodal modeling, and visual decoder, allowing coherent outputs across different modalities. Emu2 excels in vision-language tasks, instruction tuning, and controllable visual generation, showcasing state-of-the-art performance in image question answering, subject-driven generation, and zero-shot text-to-image generation. The paper acknowledges broader impact considerations and limitations, emphasizing responsible deployment in light of challenges such as hallucination, biases, and question-answering capabilities.

Video-LLaMA [Zhang et al., 2023c]: Video-LLaMA is designed to understand both visual and auditory content in videos. The model integrates pre-trained visual and audio encoders with frozen LLMs, addressing challenges in capturing temporal changes in visual scenes and integrating audio-visual signals. Utilizing a Video Q-former for temporal information and an Audio Q-former for audio encoding, the framework aligns audio-visual data with textual information. Experimental results demonstrate Video-LaMA's effectiveness in comprehending video content and generating meaningful responses in audio and video-grounded conversations. However, the paper acknowledges limitations such as restricted perception capacities and challenges with long videos. Despite these, Video-LLaMA represents a notable advancement in audiovisual AI assistants, with the authors providing open-sourced resources for further development.

Video-ChatGPT [Maaz et al., 2023]: It is, a novel multimodal model enhancing video understanding by integrating a video-adapted visual encoder with a Large Language Model. The architecture leverages the CLIP ViT-L/14 visual encoder for spatiotemporal video representations and the V-v1.1 language model for comprehensive understanding. Notably, a dataset of 100,000 video-instruction pairs is created to fine-tune the model, focusing on temporal relationships and contextual understanding. The model exhibits competitive performance in correctness, detail orientation, contextual and temporal understanding, and consistency, surpassing contemporary models in zero-shot question-answering tasks. Qualitatively, Video-ChatGPT demonstrates proficiency in various video-based tasks but faces challenges in subtle temporal relationships and small visual details, indicating avenues for future improvement.

**LAVIN** [Luo *et al.*, 2023]: LAVIN is utilizing Mixture-of-Modality Adaptation (MMA) for cost-effective adaptation of LLMs to vision-language tasks. LaVIN, with lightweight

adapters, achieves competitive performance and superior training efficiency in multimodal tasks like science question answering and dialogue. Remarkably, LaVIN requires only 1.4 training hours and 3.8M trainable parameters. Experimental results on the ScienceQA dataset demonstrate efficiency with comparable performance and reduced training time and storage costs. LAVIN represents a breakthrough in cost-effective adaptation but has limitations, including the potential for incorrect responses and challenges in identifying fine-grained details in images.

**BEiT-3** [Wang *et al.*, 2022]: BEiT-3 is, a multimodal foundation model showcasing a significant convergence in language, vision, and multimodal pretraining. BEiT-3 excels in transfer performance for both vision and vision-language tasks, advancing convergence through innovations in backbone architecture, pretraining tasks, and scalable model design. Employing Multiway Transformers, the model features a modular architecture enabling deep fusion and modality-specific encoding. Utilizing a shared backbone, BEiT-3 conducts unified masked "language" modeling on images, texts (English), and image-text pairs ("parallel sentences"). Experimental results demonstrate BEIT-3 achieving state-of-the-art performance across various tasks, including object detection, semantic segmentation, image classification, visual reasoning, visual question answering, image captioning, and cross-modal retrieval.

mPLUG-2 [Xu et al., 2023a]: Departing from prevalent approaches reliant on sequence-to-sequence generation or encoder-centric instance discrimination, mPLUG-2 introduces a multi-module composition network. This innovative design fosters modality collaboration while effectively addressing modality entanglement. The flexibility inherent in mPLUG-2 allows for the selective use of diverse modules across text, image, and video modalities for various understanding and generation tasks. Empirical evaluations demonstrate mPLUG-2's prowess, achieving state-of-the-art or competitive results across an extensive range of over 30 downstream tasks. From challenging multi-modal endeavors like image-text and videotext understanding to uni-modal tasks spanning text-only, image-only, and video-only domains, mPLUG-2 exhibits its versatility. Particularly noteworthy is its achievement of new state-of-the-art performance with a 48.0 top-1 accuracy and 80.3 CIDEr on video QA and video caption tasks, all achieved with a notably smaller model size and data scale. Additionally, mPLUG-2 showcases robust zero-shot transferability in visionlanguage and video-language tasks, solidifying its position at the forefront of multimodal pretraining advancements.

 $X^2$ -VLM [Zeng et al., 2023]:  $X^2$ -VLM is a versatile model with a flexible modular architecture that integrates image-text and video-text pre-training into a unified framework. It excels in image-text and video-text tasks across different scales, balancing performance and model scale.  $X^2$ -VLM's modular design enhances transferability, allowing seamless use in various languages or domains. By substituting the text encoder, it outperforms state-of-the-art multilingual multimodal pre-trained models, demonstrating superior performance without requiring specific multilingual pre-training. This adaptability positions  $X^2$ -VLM as a promising model in the field of multimodal pre-training.

Lyrics [Lu et al., 2023]: Lyrics, an innovative paradigm

in multi-modal pre-training and instruction fine-tuning that revolutionizes vision-language alignment through fine-grained cross-modal collaboration. Evolving from the robust foundation of BLIP-2, Lyrics incorporates local visual features extracted from a sophisticated visual refiner, encompassing image tagging, object detection, and semantic segmentation modules. In the Querying Transformer, these visual features seamlessly integrate with language inputs, enriched by boundary boxes and tags derived from the visual refiner. The two-stage training approach is a key highlight, addressing the modality gap by establishing explicit and comprehensive visionlanguage alignment targets during pre-training. Subsequently, in the instruction fine-tuning stage, we introduce semanticaware visual feature extraction, a pivotal method empowering the model to glean informative features from tangible visual objects. The efficacy of the approach is underscored by its robust performance across 13 held-out datasets spanning diverse vision-language tasks.

X-FM [Zhang et al., 2023b]: XFM, a novel general foundation model equipped with one language encoder, one vision encoder, and one fusion encoder, featuring a unique training method. The proposed method incorporates two innovative techniques: halting gradients from vision-language training during language-encoder learning and leveraging visionlanguage training to guide vision-encoder learning. Extensive experiments on benchmark datasets demonstrate that X-FM outperforms existing general foundation models and performs competitively with or surpasses models tailored specifically for language, vision, or vision-language understanding. The paper acknowledges limitations, including substantial computational requirements, and aims to explore techniques for efficiency improvement and reduced environmental impact. The authors highlight their commitment to addressing efficiency challenges and reducing the carbon footprint in line with "green" deep learning initiatives. However, due to computational constraints, the study did not explore super-large models or pre-train large-sized models on extensive datasets, emphasizing scalability as an essential consideration for foundation models.

VALOR [Chen et al., 2023a]: VALOR is a unified vision-audio-language crossmodality pretraining model designed for trimodality understanding and generation. VALOR employs two pretraining tasks, Multimodal Grouping Alignment and Multimodal Grouping Captioning, showcasing good versatility and scalability. Two datasets, VALOR-1M and VALOR-32K, are proposed for tri-modality pretraining research and benchmarking audiovisual-language retrieval and captioning. Trained on VALOR-1M and other vision-language datasets, VALOR achieves new state-of-the-art performances in downstream tasks like vision/audio/audiovisual retrieval, captioning, and question answering. The paper outlines plans for future work, including scaling the VALOR-1M dataset through unsupervised methods and introducing vision and audio generation modeling into the VALOR framework.

**Prismer** [Liu *et al.*, 2023b]: Prismer is a data- and parameter-efficient vision-language model that utilizes a frozen ensemble of domain experts, minimizing the need for extensive training data. By inheriting weights from pre-trained domain experts across various domains and keeping them

frozen during training, Prismer efficiently adapts to different vision-language reasoning tasks. Despite its small-scale language model foundation, Prismer demonstrates competitive fine-tuned and few-shot learning performance, requiring significantly less training data than current state-of-the-art models. However, it lacks the ability for zero-shot in-context generalization and shows limitations in adapting to new experts or partial expert ensembles during inference, leading to performance drops. The paper discusses these limitations, including the absence of few-shot in-context prompting, challenges in adapting to new experts, and potential improvements in representing expert knowledge for enhanced reasoning performance in future iterations.

MMReact [Yang et al., 2023b]: MM-REACT introduces a novel textual prompt design enabling language models to process multimodal information, including text descriptions, spatial coordinates, and file names for dense visual signals. The approach demonstrates its effectiveness in zero-shot experiments, showcasing its potential for advanced visual understanding across various scenarios. However, the paper identifies limitations, such as challenges in systematically evaluating performance due to the absence of annotated benchmarks for recognition capability in the wild. The integrated vision experts may introduce errors, and the system's success depends on the availability of necessary experts. Additionally, the number of experts is constrained by the context window of ChatGPT, and the conversion of visual signals to text words may not be optimal for certain tasks. Manual prompt engineering is required, and the authors suggest future research to automate this process for increased system development ease.

**PICa** [Jin *et al.*, 2021]: PICa is a method utilizing image captions to prompt GPT-3 for knowledge-based Visual Question Answering (VQA). Leveraging GPT-3's knowledge retrieval and question-answering capabilities, the approach treats GPT-3 as an implicit and unstructured knowledge base, converting images into captions or tags for GPT-3 understanding. By adapting GPT-3 for VQA through a few-shot learning approach with in-context examples, PICa achieves notable performance, surpassing the supervised state of the art on the OK-VQA dataset with just 16 examples. The method is the first to use GPT-3 for multimodal tasks. However, a limitation is noted, as the image is abstracted as text, and captions may provide only a partial description, potentially missing crucial visual details necessary for detailed question answering, such as queries on specific visual attributes.

PNP-VQA [Tiong et al., 2022]: Plug-and-Play VQA (PNP-VQA) is a modular framework designed for zero-shot Visual Question Answering (VQA). Unlike existing approaches that demand extensive adaptation of pre-trained language models (PLMs) for vision, PNP-VQA eliminates the need for additional training of PLMs. Instead, it employs natural language and network interpretation as an intermediate representation to connect pre-trained models. The framework generates question-guided informative image captions, utilizing them as context for PLMs during question answering. PNP-VQA surpasses end-to-end trained baselines and achieves state-of-the-art results on zero-shot VQAv2 and GQA datasets. With 11B parameters, it outperforms an 80B-parameter model on VQAv2 and exhibits a 9.1% improvement over a comparable

model on GQA, showcasing its efficacy with different PLM parameter sizes.

Img2LLM [Guo et al., 2023]: Img2LLM is designed for LLMs that facilitates zero-shot VQA without necessitating end-to-end training. The approach involves developing LLMagnostic models that articulate image content through exemplar question-answer pairs, proving to be effective prompts for LLMs. Img2LLM boasts several advantages, achieving performance on par with or surpassing end-to-end trained methods, such as outperforming Flamingo by 5.6% on VQAv2 and exhibiting notable superiority on the challenging A-OKVQA dataset. Additionally, the flexibility of Img2LLM allows seamless integration with various LLMs for VQA tasks, eliminating the need for specialized, costly end-to-end fine-tuning. One caveat is the additional inference overhead incurred during image caption and question-answer pair generation, contributing to a 24.4% increase in computational time. However, this overhead can be mitigated by shortening prompts, trading a fraction of accuracy for speed, while Img2LLM avoids the resource-intensive end-to-end multimodal representation alignment seen in comparable models like Flamingo.

SimVLM [Wang et al., 2021]: SimVLM is a streamlined pretraining framework that embraces a minimalist approach. Unlike previous methods, SimVLM simplifies training complexities by leveraging large-scale weak supervision, and undergoing end-to-end training with a singular prefix language modeling objective. Remarkably, without resorting to additional data or task-specific tailoring, the resultant model surpasses its predecessors like OSCAR, VILLA etc establishing new benchmarks in various vision-language tasks. Additionally, SimVLM demonstrates robust generalization and transfer capabilities, showcasing zero-shot behavior in tasks such as open-ended visual question answering and cross-modality transfer.

VideoCOCA [Yan et al., 2022]: VideoCoCa is an adaptation of the Contrastive Captioners CoCa [Yan et al., 2022] model for video-text tasks. Utilizing CoCa's generative and contrastive attentional pooling layers, VideoCoCa achieves state-of-the-art results in zero-shot video classification and text-to-video retrieval with minimal additional training. The model processes uniformly sampled frames through CoCa's image encoder, creating a tensor representing the entire video sequence. This tensor undergoes attention-pooling layers for both generative and contrastive modeling tasks. Video-CoCa demonstrates proficiency in various video-based tasks, including video reasoning and action recognition, but faces challenges in subtle temporal relationships. Various adaptation strategies and lightweight finetuning approaches were explored, with the attentional pooler method proving most effective. The model was tested on multiple datasets, exhibiting significant improvements over the CoCa baseline. VideoCoCa consistently outperforms CoCa across various scales and tasks, showcasing its robust performance in video-text modeling.

**TinyGPT-V** [Yuan *et al.*, 2023a]: TinyGPT-V addresses the challenges posed by closed-source and computationally demanding multimodal models like GPT-4V. This model achieves high performance with lower computational requirements, utilizing a 24G GPU for training and an 8G GPU or CPU for inference. Integrating Phi-2 and pre-trained vision

modules from BLIP-2 or CLIP, TinyGPT-V excels in benchmarks such as visual question-answering and referring expression comprehension, showcasing competitive performance against larger models like LLAVA in various benchmarks. The model's compact and efficient design, combining a small backbone with large model capabilities, marks a significant step towards practical, high-performance multimodal language models for diverse applications.

ChatBridge [Zhao et al., 2023b]: ChatBridge is a multimodal language model aiming to create versatile AI models capable of understanding diverse real-world modalities. Using language as a bridge, the model leverages language-paired two-modality data to connect different modalities. ChatBridge extends the zero-shot capabilities of large language models, undergoing a two-stage training process aligning each modality with language and fine-tuning with a new multimodal instruction dataset (MULTIS). The model demonstrates strong results on zero-shot multimodal tasks, encompassing text, image, video, and audio. However, limitations include challenges in understanding long-range videos and audio, suggesting a need for a more precise temporal modeling approach. The framework can be extended to include additional modalities like sketch and point cloud. While frozen modules alleviate the computational burden, they may lead to insufficient performance and introduce biases from pre-trained models.

Macaw LLM [Lyu et al., 2023]: Macaw-LLM is a novel multi-modal large language model that integrates visual, audio, and textual information. It comprises a modality module for encoding multi-modal data, a cognitive module utilizing pretrained LLMs, and an alignment module harmonizing diverse representations. The alignment module bridges multi-modal features to textual features, simplifying adaptation. A large-scale multi-modal instruction dataset is created for multi-turn dialogue. The paper acknowledges limitations, including concerns about the evaluation accurately reflecting Macaw-LLM's capabilities. The model is not optimized for multi-turn dialogues, and potential issues like hallucination, toxicity, and fairness are not evaluated due to the unavailability of suitable evaluation suites.

**GPT4Tools** [Yang *et al.*, 2023a]: GPT4Tools, aiming to enable open-source LLMs, such as LLaMA and OPT, to efficiently use multimodal tools. It addresses challenges posed by proprietary LLMs like ChatGPT and GPT-4, which often rely on inaccessible data and high computational costs. GPT4Tools employs self-instruction to generate an instruction-following dataset, allowing open-source LLMs to solve visual problems through Low-Rank Adaptation (LoRA) optimization. The approach significantly improves tool invocation accuracy and enables zero-shot capacity for unseen tools. However, the explicit and fixed prompt approach reduces computational efficiency, prompting the exploration of implicit tool invocation methods. Despite limitations, GPT4Tools is considered a viable approach for equipping language models with multimodal tools.

**PandaGPT** [Su *et al.*, 2023]: PandaGPT is an approach enhancing large language models with visual and auditory instruction-following capabilities. PandaGPT excels in tasks like image description, video-inspired story writing, and answering audio-related questions. It seamlessly handles

multimodal inputs, connecting visual and auditory information. By combining ImageBind's multimodal encoders and Vicuna's large language models, PandaGPT requires only aligned image-text pairs for training and exhibits emergent cross-modal behaviors for various data modalities. The paper suggests improvements, including using additional alignment data, exploring fine-grained feature extraction, generating richer multimedia content, creating new benchmarks, and addressing common language model deficiencies. Despite these considerations, PandaGPT represents a promising step toward building Artificial General Intelligence for holistic perception across diverse modalities.

mPLUG-Owl [Ye et al., 2023a]: mPLUG-Owl is a training paradigm equipping LLMs with multi-modal abilities through modularized learning of a foundation LLM, a visual knowledge module, and a visual abstractor module. The two-stage training method aligns image and text, leveraging LLM assistance while maintaining generation abilities. Experimental results demonstrate mPLUG-Owl's superior performance in instruction and visual understanding, multi-turn conversation, and knowledge reasoning. The model exhibits unexpected abilities like multi-image correlation and multilingual understanding but has limitations, including challenges in multiimage correlation, limited multilingual training, and mixed performance in OCR of complex scenes. The model also shows potential in vision-only document comprehension, with strengths in tasks like movie review writing and code generation but limitations in other applications, indicating further exploration opportunities in document understanding and downstream applications.

**Ying-VLM** [Li *et al.*, 2023e]: Ying-VLM is trained on M³IT dataset. Models trained with M³IT show success in following human instructions, providing engaging responses, and achieving strong generalization on unseen video and Chinese tasks. The analysis indicates that increasing task numbers improves performance, and instruction diversity influences results.M³IT comprises 2.4 million instances and 400 manually written task instructions across 40 tasks.

**BLIVA** [Hu *et al.*, 2023]: BLIVA is a novel multimodal Language Learning Model designed to handle text-rich visual questions, integrating query and patch embeddings. It outperforms existing VLMs like GPT-4 and Flamingo, showing significant improvements in OCR-VQA and Visual Spatial Reasoning benchmarks. BLIVA's architecture includes a Q-Former for instruction-aware visual features and a fully connected projection layer for additional visual information. It demonstrates a 17.72% overall improvement in the multimodal LLM benchmark (MME) compared to baseline InstructBLIP and performs well in real-world scenarios like processing YouTube thumbnail question-answer pairs.

**LLAVA-phi** [?]: LLaVA-Phi is a highly efficient multimodal assistant powered by the compact language model, Phi-2. This model demonstrates significant progress in compact multi-modal systems, showing that even smaller models with 2.7B parameters can effectively engage in complex dialogues blending text and visuals, given proper training. LLaVA-Phi excels in various benchmarks covering visual comprehension, reasoning, and knowledge-based perception, suggesting its suitability for real-time interaction scenarios like embodied

Models	Overall	Perception										Cognition			
Would Overall	Exist.	Count	Pos.	Color	Poster	Cele.	Scene	Land	Art	OCR	Com.	Cal.	Trans.	Code	
Sphinx	1870.2	195	160	153.3	160	164.3	177.9	160	168.1	134	87.5	130	55	75	50
GPT-4V	1926.6	190	160	95	150	192.2	0	151	138.3	148	185	142.1	130	75	170
Gemini	1933.4	175	131.7	90	163.3	165	147.4	144.8	158.8	135.8	185	129.3	77.5	145	85
LLaVa	-	50	50	50	55	50	48.82	50	50	49	50	57.14	50	57.5	50
MiniGPT-4	-	68.33	55	43.33	75	41.84	54.41	71.75	54	60.5	57.5	59.29	45	0	40
LaVIN	-	185	88.33	63.33	75	79.79	47.35	136.75	93.5	87.25	107.5	87.14	65	47.5	50
InstructBLIP	-	185	143.33	66.67	153.33	123.81	101.18	153	79.75	134.25	72.5	129.29	40	65	57.5
BLIP-2	-	160	135	73.33	148.33	141.84	105.59	145.25	138	136.5	110	110	40	65	75
mPLUG-OWL	-	120	50	50	55	136.05	100.29	135.5	159.25	96.25	65	78.57	60	80	57.5
Qwen-VL-Chat	1487.5	-	-	-	-	-	-	-	-	-	-	-	-	-	-
LLaVa-1.5 <sup>V7B</sup>	1510.7	-	-	-	-	-	-	-	-	-	-	-	-	-	-
LLaVa-1.5 <sup>V13B</sup>	1531.3	-	-	-	-	-	-	-	-	-	-	-	-	-	-
LLaMA-VID <sup>V13B</sup>	1542.3	-	-	-	-	-	-	-	-	-	-	-	-	-	-
LLaMA-VID <sup>V7B</sup>	1521.4	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Table 2: Table showing a comparative analysis of various VLMs on the MME Benchmark [Fu et al., 2023]. The model is of X billion parameters.

agents. Notably, it underscores the potential of smaller language models to achieve sophisticated levels of understanding and interaction while maintaining resource efficiency. The training process involves two stages: (1) feature alignment, where a pretrained vision encoder is connected to a language model using a subset of the LAION-CC-SBU dataset, and (2) visual instruction tuning, using a combination of GPT-generated multimodal instruction-following data and VQA data to teach the model to follow multimodal instructions.

MoE-LLaVA [Lin et al., 2024]: MoE-LLaVA is a novel training strategy for Large Vision-Language Models developed by researchers from Peking University, Sun Yat-sen University, FarReel Ai Lab, Tencent Data Platform, and Peng Cheng Laboratory. This strategy, called MoE-tuning, efficiently handles performance degradation in multi-modal learning and model sparsity by activating only the top-k experts through routers during deployment. With 3 billion sparsely activated parameters, MoE-LLaVA achieves comparable or superior performance to state-of-the-art models while reducing hallucinations in model outputs. The architecture involves a vision encoder, visual projection layer (MLP), word embedding layer, stacked LLM blocks, and MoE blocks. MoE-tuning comprises three stages: MLP training, parameter training excluding the Vision Encoder, and initializing experts in MoE followed by training only MoE layers. Evaluation on various visual understanding datasets demonstrates MoE-LLaVA's efficiency and effectiveness, with extensive ablation studies and visualizations illustrating its effectiveness and offering insights for future research in multi-modal learning systems.

Yi-VL [Chen et al., 2023c]: Yi Vision Language (Yi-VL) is an open-source multimodal model based on the Yi Large Language Model series, excelling in content comprehension, recognition, and multi-round conversations about images. It leads in recent benchmarks, including English and Chinese. Key features include multi-round text-image conversations, bilingual support, strong image comprehension, and finegrained resolution at 448 × 448. Yi-VL utilizes the LLaVA architecture, comprising a vision transformer, projection module, and large language model. However, it has limitations such as supporting only visual question answering, accepting a single image input, and potential content generation issues and object identification inaccuracies in complex scenes. Additionally, it operates at a fixed resolution of 448x448, which

may result in information loss for low-resolution images and a lack of additional knowledge for higher resolutions.

Moondream [vikhyatk, 2024]: Moondream is a 1.6 billion parameter model, meticulously crafted by Vikhyatk, emerges from the fusion of SigLIP, Phi-1.5, and the expansive LLaVa training dataset. Representing a significant milestone in AI research, this model is purposefully unveiled for scholarly exploration, underlining its exclusivity for non-commercial endeavors. This amalgamation of cutting-edge techniques and robust data sets underscores a commitment to advancing the frontiers of artificial intelligence, setting a new benchmark for computational prowess and innovation in the field.

Shikra [Chen et al., 2023e]: Shikra is a Multimodal Large Language Model designed to bridge the gap in human-like referential abilities within dialogue. Shikra can handle spatial coordinate inputs and outputs in natural language, featuring a simple architecture comprising a vision encoder, alignment layer, and LLM. It eliminates the need for extra vocabularies or external plugin models, allowing seamless integration of referential dialogue tasks with various vision-language tasks. Shikra demonstrates promising performance in tasks like REC, PointQA, Image Captioning, and VQA, enabling applications such as providing object coordinates and comparing userpointed regions. However, it currently supports only English and lacks user-friendliness for non-English speakers. Future work aims to make Shikra multilingual and explore improved coordinate representations for dense object detection and segmentation tasks. Additionally, like most LLMs, Shikra may generate harmful or counterfactual responses.

**BuboGPT** [Zhao *et al.*, 2023c]: BuboGPT is a VLM with visual grounding capabilities, designed to enhance cross-modal interaction between vision, audio, and language. It provides a fine-grained understanding of visual objects and other modalities, enabling specific object localization in images during response generation. BuboGPT incorporates an off-the-shelf visual grounding module based on SAM for entity extraction and mask correspondence in images, alongside a two-stage training scheme and instruction dataset for comprehensive text-image-audio understanding. Despite limitations such as language hallucination and insufficient capacities in Grounding QA, BuboGPT demonstrates impressive multi-modality understanding and visual grounding abilities, promising advancements in multi-modal LLMs.

ChatSpot: [Zhao et al., 2023a]: ChatSpot has been introduced as a unified end-to-end multimodal large language model designed to enhance human-AI interaction. It supports diverse interactive forms such as mouse clicks, drag-and-drop, and drawing boxes, providing users with a flexible and seamless interactive experience. The model is built on precise referring instructions, utilizing various reference representations like points and boxes to focus on specific regions of interest. Additionally, a multi-grained vision-language instructionfollowing dataset is created for training ChatSpot. Experimental results demonstrate its robustness in region referring, showing minimal instances of region referring hallucination even in the presence of box noises. This highlights ChatSpot's capability for precise region referencing and its potential to improve interactive accuracy and efficiency in multimodal large language models.

MiniGPT5 [Zheng et al., 2023]: MiniGPT-5 introduces an innovative interleaved vision-and-language generation technique, utilizing "generative vokens" to harmonize image-text outputs. Its distinctive two-staged training strategy focuses on description-free multimodal generation, eliminating the need for comprehensive image descriptions. MiniGPT-5 enhances model integrity with classifier-free guidance, resulting in substantial improvements over baseline models like Divter on the MMDialog dataset. It consistently delivers superior or comparable multimodal outputs in human evaluations on the VIST dataset, demonstrating its efficacy across diverse benchmarks.

**DRESS** [Chen *et al.*, 2023b]: DRESS is a large vision language model that leverages Natural Language Feedback from Large Language Models to enhance its alignment and interactions, addressing key limitations in existing LVLMs. It introduces a novel categorization of NLF into critique and refinement types to better align with human preferences and improve interaction ability in multi-turn conversations. Critique NLF identifies strengths and weaknesses, aligning LVLMs with human preferences, while refinement NLF offers concrete improvement suggestions for refining responses. To address the non-differentiable nature of NLF, conditional reinforcement learning is generalized for training. Experimental results show that DRESS generates more helpful, honest, and harmless responses, and effectively learns from feedback during multi-turn interactions compared to state-of-the-art LVLMs.

**X-InstructBLIP** [Panagopoulou *et al.*, 2023]: InstructBLIP is a cross-modality framework built upon frozen large language models that integrates various modalities without extensive customization. High-quality instruction tuning data is collected automatically, enabling fine-tuning for different modalities. The model performs comparably to leading-edge counterparts without extensive pre-training or customization. A novel evaluation task, Discriminative Crossmodal Reasoning (DisCRn), has been introduced to assess the model's cross-modal abilities across disparate input modalities. X-InstructBLIP demonstrates emergent cross-modal reasoning despite separate optimization of each modality and outperforms strong captioning baselines across all examined modalities in DisCRn. However, complexities and unanswered questions within each modality highlight challenges and opportunities for future exploration both across and within modalities.

VILA [Lin et al., 2023b]: VILA, a Visual Language model family, emerges from an enhanced pre-training recipe that systematically augments LLMs towards VLMs. VILA consistently outperforms state-of-the-art models like LLaVA1.5 across main benchmarks, showcasing its superior performance without additional complexities. Notably, VILA's multi-modal pre-training unveils compelling properties such as multi-image reasoning, enhanced in-context learning, and improved world knowledge, marking significant advancements in visual language modeling.

# 2.3 Multimodal Output with Multimodal Input

The Composable Diffusion (CoDi): CoDi [Tang et al., 2023a] model adopts a multimodal approach using Latent Diffusion Models for text, image, video, and audio. Text processing involves a variational encoder (VAE) with BERT and GPT-2, image tasks use a latent diffusion model (LDM) with a VAE, and audio tasks utilize an LDM with a VAE encoder-decoder for mel-spectrogram representation. CoDi creates a shared multimodal space through cross-modal generation with Joint Multimodal Generation and cross-attention modules. Training involves individual diffusion models with aligned prompt encoders, and CoDi achieves any-to-any generation with a linear number of training objectives.

CoDi-2 [Tang et al., 2023b]: CoDi-2 employs a multimodal encoder, ImageBind, with aligned encoders and a multilayer perceptron for modalities projection. It integrates diffusion models (DMs) into the multimodal latent language model (MLLM) for detailed, modality-interleaved generation. The fusion strategy involves projecting multimodal data into a feature sequence, processed by the MLLM, and utilizing DMs for improved generation quality. The alignment method leverages projections from aligned multimodal encoders to enable the MLLM to understand modality-interleaved input sequences, facilitating in-context learning and supporting multi-round interactive conversations.

Google Gemini [Google et al., 2023]: Gemini models feature a transformative architecture with deep fusion capabilities, excelling in integrating text, image, audio, and video modalities. They surpass GPT-4 in 30 out of 32 benchmarks and are trained on Google's TPU v4 and v5e accelerators for efficient scaling. The multimodal and multilingual training dataset prioritizes quality and safety, with models undergoing Reinforcement Learning from Human Feedback (RLHF). While specific details remain undisclosed, safety evaluations for bias and toxicity are a central part of Gemini's development, involving collaboration with external experts.

**NExT-GPT** [Wu *et al.*, 2023b]: NExT-GPT features three stages: Multimodal Encoding, LLM Understanding and Reasoning, and Multimodal Generation. It uses models like ImageBind for encoding and Transformer-based layers for generation. In inference, modal encoders transform inputs, LLM decides on content, and diffusion decoders use signal tokens for synthesis. The system employs Multimodal Alignment Learning to align features and Modality-switching Instruction Tuning (MosIT) for improved LLM capabilities by aligning modal signal tokens with gold captions. The diverse MosIT dataset enhances the model's ability to handle various user

Models	MSV	D-QA	MSRT	T-QA	ActivityNet-QA		
	Accu.	Score	Accu.	Score	Accu.	Score	
VideoLLaMa <sup>V7B</sup>	51.6	2.5	29.6	1.8	12.4	1.1	
LLaMa-Adapter <sup>L7B</sup>	54.9	3.1	43.8	2.7	34.2	2.7	
VideoChat <sup>V7B</sup>	56.3	2.8	45	2.5	26.5	2.2	
Video-ChatGPT <sup>V7B</sup>	64.9	3.3	49.3	2.8	35.2	2.7	
LLaMa-VID <sup>V7B</sup>	69.7	3.7	57.7	3.2	47.4	3.3	
LLaMa-VID <sup>V13B</sup>	70	3.7	58.9	3.3	47.5	3.3	

Table 3: Comparative analysis of leading models on 4 zero-shot video QA datasets from [Li et al., 2023c]. Results are reported with two tokens for each frame.

interactions effectively.

VideoPoet [Wu et al., 2023b]: VideoPoet is a language model designed for high-quality video synthesis with matching audio. The model employs a decoder-only transformer architecture, processing multimodal inputs like images, videos, text, and audio. Utilizing a two-stage training protocol, VideoPoet showcases state-of-the-art capabilities in zero-shot video generation and excels in tasks such as text-to-video and video stylization. Notable features include a Large Language Model backbone, custom spatial super-resolution, and scalability with model size. Human evaluations highlight VideoPoet's superiority in text fidelity, video quality, and motion interestingness. Responsible AI analysis underscores considerations for fairness, emphasizing the model's capabilities in zero-shot editing, task chaining, and maintaining quality across multiple stages in video generation.

### 3 Future Directions

**Tradeoff between pre-training and modular structure:** A Lot of research is going on to increase the understanding, control, and faithfulness capacities of VLMs by introducing modularity in place of black box pretraining. **Incorporating other modalities:** Works are going on for incorporating more finer modalities like gaze/gestures inspired by [Cheng *et al.*, 2022] which is very important for the educational sector.

**Fine-grained Evaluation of VLMs:** Works are going on for more fine-grained evaluation of VLMs on parameters like bias, fairness etc. DALL-Eval [Cho *et al.*, 2023a] and VP-Eval [Cho *et al.*, 2023b] are a few works in this direction.

Causality and Counterfactual Capabilities in VLMs: A lot of work is done to understand the causal and counterfactual capabilities of LLM, which inspired researchers to explore the same in the realm of VLMs. Cm3 [Aghajanyan *et al.*, 2022] is one of the earliest works in this domain and there is a lot of buzz in this topic.

Continual Learning/Unlearning: A trend is there on efficiently learning continuously without training it from scratch in the VLM space. VQACL [Zhang et al., 2023a] and Decouple before Interact [Qian et al., 2023] are some of the earliest works in this domain. Inspired by the concept of knowledge unlearning observed in LLMs [Si et al., 2023], researchers are also delving into similar approaches within the realm of VLMs.

**Efficieny in training:** Efforts are concentrated on developing efficient multimodal models, with notable advancements

such as BLIP-2 showing promise. It surpasses Flamingo-80B by 8.7% in zero-shot VQA-v2, while utilizing significantly fewer trainable parameters (54 times fewer).

Multilingual grounding of VLMs: Following the recent surge in multilingual LLMs such as OpenHathi [sarvam.ai, 2023] and BharatGPT [corovor.ai, 2023], there is a growing momentum towards the development of multilingual vision-language models (VLMs).

More Domain specific VLMs: Various domain-specific VLMs, exemplified by projects like MedFlamingo [Moor *et al.*, 2023] and SkinGPT [Zhou *et al.*, 2023], have paved the way in their specialized fields. Further endeavors are in progress to craft VLMs specifically tailored for sectors like education and agriculture.

### 4 Conclusion

This paper provides a comprehensive survey of the latest developments in the space of VLMs. We categorize VLMs according to their use cases and output-generation capabilities, offering concise insights into the architecture, strengths, and limitations of each model. Additionally, we highlight future directions in the field, informed by recent trends, to provide a roadmap for further exploration in this domain. We trust that this paper will serve as a valuable resource, offering guidance to researchers in the realms of Computer Vision and Natural Language Processing who are actively involved in interesting areas of multimodal learning.

## References

[A et al., 2016] Bryan A, Plummer, and et al. Flickr30k entities: Collecting region-to-phrase correspondences for richer image-to-sentence models, 2016.

[Aghajanyan *et al.*, 2022] Aghajanyan, Armen, and et al. Cm3: A causal masked multimodal model of the internet. *arXiv preprint arXiv:2201.07520*, 2022.

[Alayrac *et al.*, 2022] Alayrac, Jean-Baptiste, and et al. Flamingo: a visual language model for few-shot learning. *Neurips*, 35:23716–23736, 2022.

[Bai *et al.*, 2023a] Bai, Jinze, and et al. Qwen-vl: A frontier large vision-language model with versatile abilities. *arXiv* preprint arXiv:2308.12966, 2023.

[Bai *et al.*, 2023b] Jinze Bai, Shuai Bai, and et al. Qwenvl: A versatile vision-language model for understanding, localization, text reading, and beyond, 2023.

- [Bain *et al.*, 2021] Bain, Max, and et al. Frozen in time: A joint video and image encoder for end-to-end retrieval. In *ICCV*, pages 1728–1738, 2021.
- [Bao *et al.*, 2022] Bao, Hangbo, and el al. Vlmo: Unified vision-language pre-training with mixture-of-modality-experts, 2022.
- [Bavishi *et al.*, 2023] Bavishi, Rohan, and et al. Introducing our multimodal models, 2023.
- [Bitton *et al.*, 2023] Bitton, Yonatan, and et al. Visit-bench: A benchmark for vision-language instruction following inspired by real-world use. *arXiv preprint arXiv:2308.06595*, 2023.
- [Chen et al., 2022] Chen, Xi, and et al. Pali: A jointly-scaled multilingual language-image model. arXiv preprint arXiv:2209.06794, 2022.
- [Chen et al., 2023a] Chen, Sihan, and et al. Valor: Visionaudio-language omni-perception pretraining model and dataset. arXiv preprint arXiv:2304.08345, 2023.
- [Chen *et al.*, 2023b] Chen, Yangyi, and et al. Dress: Instructing large vision-language models to align and interact with humans via natural language feedback. *arXiv preprint arXiv:2311.10081*, 2023.
- [Chen *et al.*, 2023c] Bei Chen, y, and et al. Better bilingual multimodal model, 2023.
- [Chen *et al.*, 2023d] Jun Chen, Deyao Zhu, and et al. Minigpt-v2: large language model as a unified interface for vision-language multi-task learning, 2023.
- [Chen et al., 2023e] Keqin Chen, Zhao Zhang, Weili Zeng, Richong Zhang, Feng Zhu, and Rui Zhao. Shikra: Unleashing multimodal llm's referential dialogue magic. arXiv preprint arXiv:2306.15195, 2023.
- [Chen et al., 2023f] Xi Chen, Xiao Wang, and et al. Pali: A jointly-scaled multilingual language-image model, 2023.
- [Cheng *et al.*, 2022] Cheng, Yihua, and Feng Lu. Gaze estimation using transformer. In *ICPR*, pages 3341–3347. IEEE, 2022.
- [Cho *et al.*, 2023a] Cho, Jaemin, and et al. Dall-eval: Probing the reasoning skills and social biases of text-to-image generation models. In *ICCV*, pages 3043–3054, 2023.
- [Cho *et al.*, 2023b] Cho, Jaemin, and et al. Visual programming for text-to-image generation and evaluation. *arXiv* preprint arXiv:2305.15328, 2023.
- [corovor.ai, 2023] corovor.ai. Bharatgpt. 2023. https://corover.ai/bharatgpt/.
- [Dai and et al., 2023] Wenliang Dai and et al. Instructblip: Towards general-purpose vision-language models with instruction tuning, 2023.
- [Dai *et al.*, 2023] Wenliang Dai, Junnan Li, and et al. Instructblip: Towards general-purpose vision-language models with instruction tuning. arxiv 2023. *arXiv preprint arXiv:2305.06500*, 2023.
- [Danna *et al.*, 2018] Danna, Gurari, and et al. Vizwiz grand challenge: Answering visual questions from blind people, 2018.

- [Driess and et al, 2023] Danny Driess and et al. Palm-e: An embodied multimodal language model, 2023.
- [Driess *et al.*, 2023] Driess, Danny, and et al. Palm-e: An embodied multimodal language model. *arXiv preprint arXiv:2303.03378*, 2023.
- [Fan *et al.*, 2023] Fan, Zhiwen, and et al. Pope: 6-dof promptable pose estimation of any object, in any scene, with one reference, 2023.
- [Fu et al., 2023] Fu, Chaoyou, and et al. Mme: A comprehensive evaluation benchmark for multimodal large language models, 2023.
- [Girdhar *et al.*, 2023] Girdhar, Rohit, and et al. Imagebind: One embedding space to bind them all. In *CVPR*, pages 15180–15190, 2023.
- [Google *et al.*, 2023] Google, team, and et al. Gemini: a family of highly capable multimodal models. *arXiv* preprint *arXiv*:2312.11805, 2023.
- [Google, 2023] Google. Google bard. 2023. https://ai.google/static/documents/google-about-bard.pdf.
- [Goyal *et al.*, 2017] Yash Goyal, Tejas Khot, and et al. Making the v in vqa matter: Elevating the role of image understanding in visual question answering, 2017.
- [Guo *et al.*, 2023] Guo, Jiaxian, and et al. From images to textual prompts: Zero-shot visual question answering with frozen large language models. In *CVPR*, pages 10867–10877, 2023.
- [Hu et al., 2023] Wenbo Hu, Yifan Xu, Yi Li, Weiyue Li, Zeyuan Chen, and Zhuowen Tu. Bliva: A simple multimodal llm for better handling of text-rich visual questions. arXiv preprint arXiv:2308.09936, 2023.
- [Huang *et al.*, 2023] Huang, Shaohan, and et al. Language is not all you need: Aligning perception with language models. *arXiv preprint arXiv:2302.14045*, 2023.
- [Hudson and Manning, 2019] Drew A. Hudson and Christopher D. Manning. Gqa: A new dataset for real-world visual reasoning and compositional question answering, 2019.
- [Jin et al., 2021] Jin, Woojeong, and et al. A good prompt is worth millions of parameters: Low-resource prompt-based learning for vision-language models. arXiv preprint arXiv:2110.08484, 2021.
- [Kondratyuk *et al.*, 2023] Kondratyuk, Dan, and et al. Videopoet: A large language model for zero-shot video generation. *arXiv preprint arXiv:2312.14125*, 2023.
- [Laurençon *et al.*, 2023] Laurençon, Hugo, and et al. Obelisc: An open web-scale filtered dataset of interleaved image-text documents. *arXiv preprint arXiv:2306.16527*, 2023.
- [Laurençon *et al.*, 2023] Hugo Laurençon, Lucile Saulnier, and et al. Obelics: An open web-scale filtered dataset of interleaved image-text documents, 2023.
- [Li et al., 2022a] Li, Liunian Harold, and et al. Grounded language-image pre-training. In CVPR, pages 10965– 10975, 2022.

- [Li *et al.*, 2022b] Junnan Li, Dongxu Li, and et al. Blip: Bootstrapping language-image pre-training for unified vision-language understanding and generation, 2022.
- [Li *et al.*, 2023a] Li, Junnan, and et al. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. *arXiv preprint arXiv:2301.12597*, 2023.
- [Li et al., 2023b] Li, Junyan, and et al. Covlm: Composing visual entities and relationships in large language models via communicative decoding. arXiv preprint arXiv:2311.03354, 2023.
- [Li *et al.*, 2023c] Li, Yanwei, and et al. Llama-vid: An image is worth 2 tokens in large language models, 2023.
- [Li *et al.*, 2023d] Junnan Li, Dongxu Li, and et al. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models, 2023.
- [Li *et al.*, 2023e] Lei Li, Yuwei Yin, and et al. M<sup>3</sup>it: A large-scale dataset towards multi-modal multilingual instruction tuning, 2023.
- [Lin et al., 2023a] Lin, Ziyi, and et al. Sphinx: The joint mixing of weights, tasks, and visual embeddings for multi-modal large language models. arXiv preprint arXiv:2311.07575, 2023.
- [Lin et al., 2023b] Ji Lin, Hongxu Yin, Wei Ping, Yao Lu, Pavlo Molchanov, Andrew Tao, Huizi Mao, Jan Kautz, Mohammad Shoeybi, and Song Han. Vila: On pre-training for visual language models. arXiv preprint arXiv:2312.07533, 2023.
- [Lin et al., 2024] Bin Lin, Zhenyu Tang, Yang Ye, Jiaxi Cui, Bin Zhu, Peng Jin, Junwu Zhang, Munan Ning, and Li Yuan. Moe-llava: Mixture of experts for large vision-language models. arXiv preprint arXiv:2401.15947, 2024.
- [Liu *et al.*, 2023a] Liu, Haotian, and et al. Visual instruction tuning. *arXiv preprint arXiv:2304.08485*, 2023.
- [Liu *et al.*, 2023b] Liu, Shikun, and et al. Prismer: A vision-language model with an ensemble of experts. *arXiv preprint arXiv:2303.02506*, 2023.
- [Liu *et al.*, 2023c] Liu, Shilong, and et al. Llava-plus: Learning to use tools for creating multimodal agents. *arXiv* preprint arXiv:2311.05437, 2023.
- [Liu *et al.*, 2023d] Haotian Liu, Chunyuan Li, and et al. Improved baselines with visual instruction tuning, 2023.
- [Liu *et al.*, 2023e] Shilong Liu, Hao Cheng, and et al. Llavaplus: Learning to use tools for creating multimodal agents, 2023.
- [Lu *et al.*, 2022] Lu, Pan, and et al. Learn to explain: Multimodal reasoning via thought chains for science question answering. *Neurips*, 35:2507–2521, 2022.
- [Lu *et al.*, 2023] Lu, Junyu, and et al. Lyrics: Boosting fine-grained language-vision alignment and comprehension via semantic-aware visual objects. *ArXiv*, abs/2312.05278, 2023.

- [Luo *et al.*, 2023] Luo, Gen, and et al. Cheap and quick: Efficient vision-language instruction tuning for large language models. *arXiv preprint arXiv:2305.15023*, 2023.
- [Lyu *et al.*, 2023] Lyu, Chenyang, and et al. Macaw-llm: Multi-modal language modeling with image, audio, video, and text integration. *arXiv preprint arXiv:2306.09093*, 2023.
- [Maaz et al., 2023] Muhammad Maaz, Hanoona Rasheed, and et al. Video-chatgpt: Towards detailed video understanding via large vision and language models, 2023.
- [Masry *et al.*, 2022] Masry, Ahmed, and et al. Chartqa: A benchmark for question answering about charts with visual and logical reasoning, 2022.
- [Moor *et al.*, 2023] Moor, Michael, and et al. Med-flamingo: a multimodal medical few-shot learner. In *ML4H*, pages 353–367. PMLR, 2023.
- [OpenAI, 2023] OpenAI. Gpt4. 2023. https://openai.com/research/gpt-4.
- [Panagopoulou *et al.*, 2023] Panagopoulou, Artemis, and et al. X-instructblip: A framework for aligning x-modal instruction-aware representations to llms and emergent cross-modal reasoning. *arXiv preprint arXiv:2311.18799*, 2023.
- [Peng et al., 2023] Zhiliang Peng, Wenhui Wang, Li Dong, Yaru Hao, Shaohan Huang, Shuming Ma, and Furu Wei. Kosmos-2: Grounding multimodal large language models to the world. arXiv preprint arXiv:2306.14824, 2023.
- [Piergiovanni *et al.*, 2023] Piergiovanni, AJ, and et al. Mirasol3b: A multimodal autoregressive model for timealigned and contextual modalities. *arXiv preprint arXiv:2311.05698*, 2023.
- [Qian *et al.*, 2023] Qian, Zi, and et al. Decouple before interact: Multi-modal prompt learning for continual visual question answering. In *ICCV*, pages 2953–2962, 2023.
- [Radford *et al.*, 2021] Radford, Alec, and et al. Learning transferable visual models from natural language supervision. In *ICML*, pages 8748–8763. PMLR, 2021.
- [Ramesh *et al.*, 2021] Ramesh, Aditya, and et al. Zero-shot text-to-image generation. In *ICML*, pages 8821–8831. PMLR, 2021.
- [sarvam.ai, 2023] sarvam.ai. openhathi. 2023. https://www.sarvam.ai/blog/announcing-openhathi-series.
- [Si *et al.*, 2023] Nianwen Si, Hao Zhang, Heyu Chang, Wenlin Zhang, Dan Qu, and Weiqiang Zhang. Knowledge unlearning for llms: Tasks, methods, and challenges. *arXiv* preprint arXiv:2311.15766, 2023.
- [Su *et al.*, 2023] Su, Yixuan, and et al. Pandagpt: One model to instruction-follow them all. *arXiv preprint arXiv:2305.16355*, 2023.
- [Sun *et al.*, 2023a] Sun, Quan, and et al. Generative multimodal models are in-context learners. *arXiv preprint arXiv:2312.13286*, 2023.

- [Sun *et al.*, 2023b] Sun, Zeyi, and et al. Alpha-clip: A clip model focusing on wherever you want. *arXiv e-prints*, pages arXiv–2312, 2023.
- [Tang *et al.*, 2023a] Zineng Tang, Ziyi Yang, and et al. Anyto-any generation via composable diffusion, 2023.
- [Tang et al., 2023b] Zineng Tang, Ziyi Yang, and et al. Codi-2: In-context, interleaved, and interactive any-to-any generation, 2023.
- [Tiong et al., 2022] Tiong, Anthony Meng Huat, and et al. Plug-and-play vqa: Zero-shot vqa by conjoining large pretrained models with zero training. arXiv preprint arXiv:2210.08773, 2022.
- [Tong *et al.*, 2022] Tong, Zhan, and et al. Videomae: Masked autoencoders are data-efficient learners for self-supervised video pre-training. *Neurips*, 35:10078–10093, 2022.
- [Touvron *et al.*, 2023] Touvron, Hugo, and et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023.
- [Tsimpoukelli *et al.*, 2021] Tsimpoukelli, Maria, and et al. Multimodal few-shot learning with frozen language models. *Neurips*, 34:200–212, 2021.
- [vikhyatk, 2024] vikhyatk. Moondream1. 2024. https://huggingface.co/vikhyatk.
- [Wang et al., 2021] Wang, Zirui, and et al. Simvlm: Simple visual language model pretraining with weak supervision. arXiv preprint arXiv:2108.10904, 2021.
- [Wang et al., 2022] Wang, Wenhui, and et al. Image as a foreign language: Beit pretraining for all vision and vision-language tasks. arXiv preprint arXiv:2208.10442, 2022.
- [Wang *et al.*, 2023a] Wang, Weihan, and et al. Cogvlm: Visual expert for pretrained language models. *arXiv preprint arXiv:2311.03079*, 2023.
- [Wang *et al.*, 2023b] Wang, Xiao, and et al. Large-scale multi-modal pre-trained models: A comprehensive survey. *Machine Intelligence Research*, pages 1–36, 2023.
- [Wu et al., 2023a] Wu, Jiayang, and et al. Multimodal large language models: A survey. arXiv preprint arXiv:2311.13165, 2023.
- [Wu et al., 2023b] Wu, Shengqiong, and et al. Next-gpt: Anyto-any multimodal llm. arXiv preprint arXiv:2309.05519, 2023.
- [Wu *et al.*, 2023c] Shengqiong Wu, Hao Fei, and et al. Next-gpt: Any-to-any multimodal llm, 2023.
- [Xu et al., 2021] Xu, Hu, and et al. Videoclip: Contrastive pre-training for zero-shot video-text understanding. arXiv preprint arXiv:2109.14084, 2021.
- [Xu et al., 2022] Xu, Zhiyang, and et al. Multiinstruct: Improving multi-modal zero-shot learning via instruction tuning. arXiv preprint arXiv:2212.10773, 2022.
- [Xu *et al.*, 2023a] Xu, Haiyang, and et al. mplug-2: A modularized multi-modal foundation model across text, image and video. *arXiv preprint arXiv:2302.00402*, 2023.

- [Xu et al., 2023b] Xu, Hu, and et al. Demystifying clip data. arXiv preprint arXiv:2309.16671, 2023.
- [Yan *et al.*, 2022] Yan, Shen, and et al. Video-text modeling with zero-shot transfer from contrastive captioners. *arXiv* preprint arXiv:2212.04979, 2022.
- [Yan *et al.*, 2023] Shen Yan, Tao Zhu, and et al. Videococa: Video-text modeling with zero-shot transfer from contrastive captioners, 2023.
- [Yang et al., 2022] Zhengyuan Yang, Zhe Gan, and et al. An empirical study of gpt-3 for few-shot knowledge-based vqa, 2022.
- [Yang *et al.*, 2023a] Yang, Rui, and et al. Gpt4tools: Teaching large language model to use tools via self-instruction. *arXiv preprint arXiv:2305.18752*, 2023.
- [Yang et al., 2023b] Yang, Zhengyuan, and et al. Mm-react: Prompting chatgpt for multimodal reasoning and action. arXiv preprint arXiv:2303.11381, 2023.
- [Ye et al., 2023a] Ye, Qinghao, and et al. mplug-owl: Modularization empowers large language models with multi-modality. arXiv preprint arXiv:2304.14178, 2023.
- [Ye *et al.*, 2023b] Qinghao Ye, Haiyang Xu, and et al. mplugowl: Modularization empowers large language models with multimodality, 2023.
- [Yin et al., 2023] Yin, Shukang, and et al. A survey on multimodal large language models. arXiv preprint arXiv:2306.13549, 2023.
- [You *et al.*, 2023] You, Haoxuan, and et al. Ferret: Refer and ground anything anywhere at any granularity. *arXiv* preprint arXiv:2310.07704, 2023.
- [Yu et al., 2023] Yu, Weihao, and et al. Mm-vet: Evaluating large multimodal models for integrated capabilities, 2023.
- [Yuan et al., 2023a] Yuan, Zhengqing, and et al. Tinygptv: Efficient multimodal large language model via small backbones. arXiv preprint arXiv:2312.16862, 2023.
- [Yuan *et al.*, 2023b] Zhengqing Yuan, Zhaoxu Li, and Lichao Sun. Tinygpt-v: Efficient multimodal large language model via small backbones, 2023.
- [Zeng *et al.*, 2023] Zeng, Yan, and et al. X<sup>2</sup>-vlm: All-in-one pre-trained model for vision-language tasks, 2023.
- [Zhang *et al.*, 2023a] Zhang, Xi, and et al. Vqacl: A novel visual question answering continual learning setting. In *CVPR*, pages 19102–19112, 2023.
- [Zhang *et al.*, 2023b] Zhang, Xinsong, and et al. Toward building general foundation models for language, vision, and vision-language understanding tasks. *arXiv preprint arXiv:2301.05065*, 2023.
- [Zhang *et al.*, 2023c] Hang Zhang, Xin Li, and Lidong Bing. Video-llama: An instruction-tuned audio-visual language model for video understanding, 2023.
- [Zhang *et al.*, 2024] Duzhen Zhang, Yahan Yu, Chenxing Li, Jiahua Dong, Dan Su, Chenhui Chu, and Dong Yu. Mmllms: Recent advances in multimodal large language models. *arXiv preprint arXiv:2401.13601*, 2024.

- [Zhao *et al.*, 2023a] Zhao, Liang, and et al. Chatspot: Bootstrapping multimodal llms via precise referring instruction tuning. *arXiv preprint arXiv:2307.09474*, 2023.
- [Zhao *et al.*, 2023b] Zhao, Zijia, and et al. Chatbridge: Bridging modalities with large language model as a language catalyst. *arXiv preprint arXiv:2305.16103*, 2023.
- [Zhao *et al.*, 2023c] Yang Zhao, Zhijie Lin, Daquan Zhou, Zilong Huang, Jiashi Feng, and Bingyi Kang. Bubogpt: Enabling visual grounding in multi-modal llms. *arXiv* preprint arXiv:2307.08581, 2023.
- [Zheng *et al.*, 2023] Zheng, Kaizhi, and et al. Minigpt-5: Interleaved vision-and-language generation via generative vokens. *arXiv preprint arXiv:2310.02239*, 2023.
- [Zhou *et al.*, 2018] Zhou, Luowei, and et al. Towards automatic learning of procedures from web instructional videos. In *AAAI*, volume 32, 2018.
- [Zhou *et al.*, 2023] Zhou, Juexiao, and et al. Skingpt: A dermatology diagnostic system with vision large language model. *arXiv preprint arXiv:2304.10691*, 2023.
- [Zhu *et al.*, 2023a] Zhu, Deyao, and et al. Minigpt-4: Enhancing vision-language understanding with advanced large language models. *arXiv preprint arXiv:2304.10592*, 2023.
- [Zhu *et al.*, 2023b] Deyao Zhu, Jun Chen, and et al. Minigpt-4: Enhancing vision-language understanding with advanced large language models, 2023.