

Contact Center API Integration Guide

This guide is written for integration teams who need a quick and clear reference for the Contact Center call APIs.

Base URL

```
https://qa-app.beconversive.com/contact-center/v1
```

Authentication

Use the same authentication headers used for other protected Contact Center APIs.

Common Notes

- `call_id` is the main reference for all follow-up call operations.
- Phone numbers should be sent in E.164 format, for example `+919876543210`.
- `use_agent_phone=false` means browser-based calling.
- `use_agent_phone=true` means the system calls the agent's phone first and then bridges the customer.
- `POST /calls/webhook` is for internal LiveKit webhook delivery.
- `POST /calls/{call_id}/status` currently reads `call_id` from the request body.

Typical Integration Flow

1. Call `POST /calls/initiate`.
2. Save `call_id` and `room_name`.
3. If `agent_join_via_phone=false`, use `token` and `livekit_url` to join from browser.
4. Use `POST /calls/{call_id}/action` for hold, mute, unmute, or hangup.
5. Use `POST /calls/{call_id}/status` to check latest call state.
6. Use `GET /calls/{call_id}/recording-url` after the call ends if recording is needed.

1. Initiate Call

Endpoint

```
POST /calls/initiate
```

Purpose

Start a new outbound call.

Request Body

```
{  "phone_number": "+919580440262",    "from_number": "+912264237758",
"contact_name": "John Doe",    "use_agent_phone": false }
```

Request Fields

Field	Type	Required	Description
phone_number	string	Yes	Customer number to dial.
from_number	string	Yes	Business number used as caller ID.
contact_name	string	No	Contact name for reference.
use_agent_phone	boolean	No	false for browser calling, true for phone bridge calling. Default is false .

Success Response

Browser-based call:

```
{    "call_id": "550e8400-e29b-41d4-a716-446655440000",    "room_name":  
"cc_outbound_550e8400-e29b-41d4-a716-446655440000",    "token":  
"eyJhbGciOiJIUzI1NiIsInR5cCI6..."}    "livekit_url": "wss://your-livekit-host",  
    "agent_join_via_phone": false }
```

Phone bridge call:

```
{  "call_id": "550e8400-e29b-41d4-a716-446655440000",    "room_name":
"cc_outbound_550e8400-e29b-41d4-a716-446655440000",    "token": null,
"livekit_url": null,    "agent_join_via_phone": true }
```

Response Fields

Field	Type	Description
<code>call_id</code>	string	Unique ID of the created call.
<code>room_name</code>	string	LiveKit room name created for the call.
<code>token</code>	string or null	Browser join token. Returned only for browser flow.
<code>livekit_url</code>	string or null	LiveKit server URL. Returned only for browser flow.
<code>agent_join_via_phone</code>	boolean	Indicates whether the agent joins by phone.

Important Notes

- If `use_agent_phone=true`, the logged-in agent must have a valid phone number configured.
- `from_number` must belong to the authenticated account/user context.
- If browser flow is used, the client should connect immediately using the returned token.

Common Error Cases

HTTP Status	Meaning
<code>400</code>	Invalid account/user context, invalid <code>from_number</code> , or missing agent phone configuration.
<code>401</code>	Unauthorized.
<code>500</code>	Call setup failed.

2. Disconnect Call

Endpoint

POST /calls/disconnect

Purpose

End an active or recent call.

Request Body

You can disconnect using either `call_id` or `phone_number`.

Using `call_id`:

```
{  "call_id": "550e8400-e29b-41d4-a716-446655440000" }
```

Using `phone_number`:

```
{  "phone_number": "+919580440262" }
```

Request Fields

Field	Type	Required	Description
<code>call_id</code>	string	Conditional	Recommended when available. Use this or <code>phone_number</code> .
<code>phone_number</code>	string	Conditional	Can be used when <code>call_id</code> is not available.

Success Response

```
{  "msg": "completed" }
```

Response Notes

- `msg` usually contains the saved final or latest call status.
- Typical values include `completed` and `cancelled`.

Common Error Cases

HTTP Status	Meaning
-------------	---------

404	Call not found.
-----	-----------------

3. Call Action

Endpoint

POST /calls/{call_id}/action

Purpose

Perform a live call control action.

Path Parameter

Parameter	Type	Required	Description
call_id	string	Yes	Call UUID.

Request Body

```
{  "action": "hold",  "room_name": "cc_outbound_550e8400-e29b-41d4-a716-446655440000" }
```

Request Fields

Field	Type	Required	Description
action	string	Yes	Action to perform.
room_name	string	Yes	LiveKit room name for the call.

Supported Actions

Action	Description
mute	Mute the agent audio track.
unmute	Unmute the agent audio track.
hold	Put the call on hold.
unhold	Resume a held call.

hangup	Disconnect call participants.
--------	-------------------------------

Success Response

```
{  "msg": "hold done" }
```

Common Error Cases

HTTP Status	Meaning
400	Missing <code>room_name</code> , invalid action, or LiveKit operation failed.

4. Webhook

Endpoint

POST `/calls/webhook`

Purpose

Receive LiveKit webhook events and update call lifecycle data.

Intended Caller

This endpoint should be called by LiveKit or internal platform services only.

What It Handles

- Call lifecycle updates
- Participant join and leave events
- Inbound and outbound state transitions
- Recording-related updates

Response

Usually returns HTTP `200` .

Integration Note

External integration partners normally do not need to call this API directly.

5. Get Call Token

Endpoint

```
GET /calls/{call_id}/token
```

Purpose

Get a LiveKit token and room details.

Path Parameter

Parameter	Type	Required	Description
<code>call_id</code>	string	Yes	Call identifier.

Success Response

```
{ "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IHR5cGU6ImFudGljYyJ9", "livekit_url":  
"wss://your-livekit-host", "room_name": "room_123" }
```

Response Fields

Field	Type	Description
token	string	LiveKit access token.
livekit_url	string	LiveKit server URL.
room_name	string	Room name mapped for token join.

Integration Note

This endpoint returns room naming in the format `room_{call_id}`. If your integration depends on room naming, align it with the values returned by the API response instead of hardcoding assumptions.

6. List Calls

Endpoint

```
GET /calls
```

Purpose

Fetch paginated call history for the authenticated account.

Query Parameters

Parameter	Type	Required	Description
page	integer	No	Page number. Default is 1.
page_size	integer	No	Records per page. Default is 20, maximum is 100.

Example

```
GET /calls?page=1&page_size=20
```

Success Response

```
{  "page": 1,  "page_size": 20,  "total": 2,  "items": [    {      "call_id": "550e8400-e29b-41d4-a716-446655440000",      "account_id": "152",      "external_call_id": null,      "direction": "outbound",      "call_mode": "human",      "call_type": "browser",      "outgoing_number": "+912264237758",      "agent_number": null,      "customer_number": "+919580440262",      "status": "completed",      "disconnect_reason": "call completed",      "started_at": "2026-04-28T10:30:00",      "answered_at": "2026-04-28T10:30:10",      "ended_at": "2026-04-28T10:35:00",      "recording_link": "recordings/file.mp3",      "duration_seconds": 290,      "transcription": null,      "transcription_status": null,      "created_at": "2026-04-28T10:30:00",      "updated_at": "2026-04-28T10:35:00"    }  ] }
```

Main Response Fields

Field	Type	Description
page	integer	Current page number.
page_size	integer	Number of records requested.

<code>total</code>	integer	Total number of calls available.
<code>items</code>	array	List of call records.

Important Call Item Fields

Field	Type	Description
<code>call_id</code>	string	Unique call ID.
<code>direction</code>	string	<code>inbound</code> or <code>outbound</code> .
<code>call_mode</code>	string	<code>human</code> , <code>ai</code> , <code>ivr</code> , <code>campaign</code> , or <code>mixed</code> .
<code>call_type</code>	string	Example: <code>browser</code> or <code>phone</code> .
<code>status</code>	string	Latest call status.
<code>disconnect_reason</code>	string or null	Final or current disconnect reason.
<code>recording_link</code>	string or null	Internal recording reference.
<code>duration_seconds</code>	integer or null	Call duration in seconds.

Common Error Cases

HTTP Status	Meaning
<code>401</code>	Unauthorized.

7. Get Call Status

Endpoint

POST `/calls/{call_id}/status`

Purpose

Get the latest saved status for a call.

Important Behavior

Even though `call_id` appears in the URL, the API currently validates and reads `call_id` from the request body.

Request Body

```
{  "call_id": "550e8400-e29b-41d4-a716-446655440000" }
```

Request Fields

Field	Type	Required	Description
<code>call_id</code>	string	Yes	Call UUID.

Success Response

```
{  "call_id": "550e8400-e29b-41d4-a716-446655440000",  "status": "active" }
```

Response Fields

Field	Type	Description
<code>call_id</code>	string	Call UUID.
<code>status</code>	string	Latest saved call status.

Possible Status Values

Status	Meaning
<code>initiated</code>	Call record created.
<code>ringing</code>	A participant is being dialed.
<code>active</code>	Both parties are connected.
<code>completed</code>	Call connected and ended normally.
<code>failed</code>	Technical or carrier failure.

cancelled	Call ended before connect.
no_answer	The call rang but was not answered.
busy	Destination was busy.

Common Error Cases

HTTP Status	Meaning
400	Invalid <code>call_id</code> format.
403	Call does not belong to authenticated account.
404	Call not found.

8. Get Recording URL

Endpoint

GET `/calls/{call_id}/recording-url`

Purpose

Get a pre-signed URL for the call recording.

Path Parameter

Parameter	Type	Required	Description
<code>call_id</code>	string	Yes	Call UUID.

Success Response

```
{  "url": "https://s3.amazonaws.com/bucket/recording?X-Amz-Signature=..." }
```

If Recording Is Not Available

```
{  "error": "Recording not found" }
```

Response Notes

- This API returns a temporary pre-signed URL.
- The URL should be used promptly because it may expire.

Summary For Integrators

- `POST /calls/initiate` is the starting point for outbound calls.
- Save `call_id` from the initiate response and reuse it everywhere.
- For browser calling, `token` and `livekit_url` are needed immediately after initiation.
- For live controls, `room_name` is required in the action API.
- For call progress checks, use the status API.
- For recordings, call the recording URL API after the call has ended.