PRACTICAL 06 / BEGINNER LAB

Use a different recipient

Name: _____ Date: _____

Aim. Bridge 0.25 GLD to a second public address on Sepolia.

Before you start. Create or choose a second account you control. Copy only its public address. The original owner signs and pays gas; the recipient does not need to sign to receive.

Commands

```
$Recipient = 'REPLACE_WITH_SECOND_PUBLIC_ADDRESS'
$A = @(
  '--origin','bsctestnet','--destination','sepolia',
  '--amount','250000000000000000',
  '--recipient',$Recipient,'--relay'
)
npm.cmd run warp:send -- @A
# After delivery, check recipient on Sepolia explorer.
npm.cmd run verify
```

Expected result

The second address receives 0.25 GLD. The verification helper still reports the original owner balance, so check the recipient balance in its wallet or explorer. Total backing still matches. Returning those tokens later requires the recipient account and Sepolia gas; it is not part of this sheet.

Record your observations

Origin / destination: _____
Amount or setting: _____
Dispatch hash or verification time: _____
Message ID / result: _____

Quick questions

- Why does ownerGLD not increase on Sepolia here?
- Can you receive tokens without sharing your private key?

Use testnets only. Run from the selected kit project folder. Use npm.cmd. Amounts are in smallest units. Never record a private key or recovery phrase on this sheet.