PRACTICAL 08 / BEGINNER LAB

Inspect and retry delivery

Name: _____ Date: _____

Aim. Track an existing message without sending more tokens.

Before you start. Use a dispatch transaction hash from an earlier practical. The example is Sepolia-origin; change it to bsctestnet for a BSC-origin dispatch.

Commands

```
$Tx = 'REPLACE_WITH_EXISTING_DISPATCH_TX_HASH'
$A = @('--origin','sepolia','--dispatchTx',$Tx)
npm.cmd run status -- @A
# ONLY if not delivered, after checkpoint availability:
npm.cmd run status -- @A --relay
# After confirmed delivery:
npm.cmd run verify
```

Expected result

An already delivered message reports its delivery transaction, and you stop. A pending message can be retried when metadata is ready. You are relaying the existing dispatch, not issuing another token transfer. Do not deliberately break security settings to simulate an outage.

Record your observations

Origin / destination: _____
Amount or setting: _____
Dispatch hash or verification time: _____
Message ID / result: _____

Quick questions

- Which hash is needed: approval, dispatch, or delivery?
- Why can validator metadata take time to become available?

Use testnets only. Run from the selected kit project folder. Use npm.cmd. Amounts are in smallest units. Never record a private key or recovery phrase on this sheet.