



Problem Solving With C - UE24CS151B

Strings in C

Prof. Sindhu R Pai

PSWC Theory Anchor, Feb-May, 2025

Department of Computer Science and Engineering

PROBLEM SOLVING WITH C

Strings in C



1. Introduction
2. Declaration
3. Initialization
4. Demo of C Code
5. String v/s Pointer


PROBLEM SOLVING WITH C

Strings in C



Introduction

- An array of characters and terminated with a special character '\0' or NULL. ASCII value of NULL character is 0.
- String constants are always enclosed in double quotes. It occupies one byte more to store the null character.
- Example: **"X"** is a **String constant**



PROBLEM SOLVING WITH C


Strings in C



Declaration

Syntax: **char variable_name[size];** //Size is compulsory

char a1[10]; // valid declaration
char a1[]; // invalid declaration



PROBLEM SOLVING WITH C

Strings in C




Initialization


Syntax: `char variable_name[size] = {Elements separated by comma};`

Version 1:

- `char a1[] = {'a', 't', 'm', 'a', '\0'};`
- Shorthand notation: `char a1[] = "atma";`




Version 2: `char a2[] = {'a', 't', 'm', 'a'};`



Version 3: Partial initialization

- `char a3[10] = {'a', 't', 'm', 'a'};`




PROBLEM SOLVING WITH C

Strings in C

Initialization continued..


Version 4: Partial initialization

- `char a4[10] = {'a','t','m','a', '\0'};`
- `char a4[10] = "atma";`




Version 5: `char a5[] = {'a','t','m','a', '\0', 't','r','i','s','h','a', '\0'};`


Version 6: `char a6[] = "atma\0";`



Version 7: `char a7[] = "atma\\0";`



Version 8: `char a8[] = "at\0ma";`



PROBLEM SOLVING WITH C

Strings in C



Demo of C Code

- To read and display a string in C
- Points to note:
 - If the string is hard coded, it is programmer's responsibility to end the string with '\0' character.
 - scanf terminates when white space is given in the user input.
 - scanf with %s will introduce '\0' character at the end of the string. printf with %s requires the address and will display the characters until '\0' character is encountered
 - If you want to store the entire input from the user until user presses new line in one character array variable, use [^\n] with %s in scanf

PROBLEM SOLVING WITH C

Strings in C



String v/s Pointer

- `char x[] = "pes";` // x is an array of 4 characters with 'p', 'e', 's', '\0'
Stored in the Stack segment of memory
- Can change the elements of x. `x[0] = 'P';`
- Can not increment x as it is an array name. x is a constant pointer.

- `char *y = "pes";`
y is stored at stack. "pes" is stored at code segment of memory. It is read only.
- `y[0] = 'P';` // undefined behaviour
- Can increment y . y is a pointer variable.



THANK YOU

Department of Computer Science and Engineering

Dr. Shylaja S S, Director, CCBD & CDSAML, PESU
Prof. Sindhu R Pai - sindhurpai@pes.edu