

5. Git commands —

> used to save and manage diff. versions of files. #

> Remote repositories

checking git version

> git --version

⇒ Terms —

> Repo : track changes.

> Clone : makes a copy of remote repo. on comp.

> Stage : we need to tell what changes we want to save.

> Commit:

> Branch : work on various versions ^{at} same time

> Merge : combine changes of diff branches.

> Pull — Get the latest changes from remote repo.

> Push — send changes to remote repo.

config. — git should know who we are (n)

> git config --global user.name "Neeraja"

> git config --global user.email "n.g@triniti.com"

// global — set value for every repo. on our comp.

local — set it only for current repo.

> git config --list.

> git config user.name (specific).

// to unset any variables —

> git config --global --unset user.name.

// changing branch name —

> git config --global init.defaultBranch Neer

⇒ config levels —

1. System (for all users) — > git config --system

2. Global (current user) — > git config --global

3. Local (current repo) — > git config --local.

> git config --local user.email = "python"

> git config --global user.email = "python"

6. Git — start —

> mkdir NEW

> cd NEW

> git init. → initialize empty git folder

// to see all hidden files (include hidden files)

> ls -a

// to open file & edit

> nano abc.html

// to ~~edit~~ ^{open} file too

> touch abc.html

> ls -a

> code. →

// status

> git status

> git add.html

> git status

Tracked file. &

> Git is watching changes

untracked file

> ~~Git~~ is not yet tracking

> explorer.exe abc.html.

// Reset changes - unstage file without commit

> git reset abc.html → // untracked.

> git add -A or --all

> git status → // saved process

⇒ Commit - save point of file at certain time & msg. describing what changed (happened)

- we can always go back to previous commit.

∴ every time we commit → we need to add.

> git commit -m "hello" ✓

> git status

> git log

→ then change log = html(m) file
↓
write a commit in (source control changes)

msg + commit)

in graph we can Graph

> git add -A abc.html

(or) change add html
git add -A
commit
log