Frameset in HTML:

Index.html file

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width,
initial-scale=1.0">
  <title>Document</title>
</head>
<frameset cols="15%,*">

  <frame src="MenuBar.html" noresize>
    <frame src="" name="destinationPage">
</frameset>
</html>
```

Login.html page

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
```

```
    <meta name="viewport" content="width=device-width,
initial-scale=1.0" />
    <title>Document</title>
  </head>
  <body>
    <h2>Its login Page!!</h2>
    <form action="">
      <table>
        <tr>
          <td>User Name:</td>
          <td>
            <input type="text" name="uname" />
          </td>
        </tr>
        <tr>
          <td>Password:</td>
          <td>
            <input type="password" name="pass" />
          </td>
        </tr>
        <tr>
          <td></td>
```

```
        <td>
          <input type="submit" value="Login Here" />
        </td>
        <td>
          <a href="signup.html">Not a member Yet? Click Here
to Sign Up</a>
        </td>
      </tr>
    </table>
  </form>
 </body>
</html>
```

Signup.html page

```
<!DOCTYPE html>
<html lang="en">
 <head>
  <meta charset="UTF-8" />
  <meta name="viewport" content="width=device-width,
initial-scale=1.0" />
  <title>Document</title>
 </head>
 <body>
```

```
<form action="" method="post">
 <table bgcolor="cyan" align="center">
 <caption>
 <h2>Registration Form</h2>
 </caption>
 <tr>
 <td>
 <label for="fname">First Name</label>

 </td>
 <td>
 <input type="text" name="fname" id="fname"
 />
 </td>
 </tr>
 <tr>
 <td>
 <label for="lname">Last Name</label>
 </td>
 <td>
 <input type="text" name="lname" id="lname"
```

```
/>
</td>
</tr>
<tr>
<td>
<label for="email">Email</label>
</td>
<td>

<input type="email" name="email" id="email"
/>
</td>
</tr>
<tr>
<td>
<label for="pass">Password</label>
</td>
<td>
<input type="password" name="pass"
id="pass" />
</td>
</tr>
```

```
<tr>
<td><label for="gender">Gender</label></td>
<td>
<input type="radio" value="Male" name="gen"
id="male" />
<label for="male">Male</label>
<input type="radio" value="FeMale" name="gen"
id="female" />

<label for="female">FeMale</label>
</td>
</tr>
<tr>
<td>
<label for="skill">Skills</label>
</td>
<td>
<input type="checkbox" name="skill" id="java"
value="Java" />
<label for="java">Java</label>
<input type="checkbox" name="skill" id="Python"
value="Python" />
<label for="Python">Python</label>
```

```
    <input type="checkbox" name="skill" id="Php"
value="Php" />
    <label for="Php">PHp</label>
    </td>
    </tr>
    <tr>
    <td>

    <label for="Comment">Comments</label>
    </td>
    <td>
    <textarea name="comment"
id="Comment"></textarea>
    </td>
    </tr>
    <tr>
    <td>
    <label for="date">DOB</label>
    </td>
    <td>
    <input type="date" name="dob" id="date" />
    </td>
```

```
</tr>
<tr>
<td>
<label for="resume">Upload</label>
</td>
<td>

<input type="file" name="resume" id="resume" />
</td>
</tr>
<tr>
<td>
<label for="city">City</label>
</td>
<td>
<select name="city" id="city">
<option value="Pune">Pune</option>
<option value="Mumbai">Mumbai</option>
<option value="Delhi">Delhi</option>
<option value="Kolkata">Kolkata</option>
</select>
</td>
```

```
</tr>
<tr>
<td></td>
<td>

<input type="submit" value="Register" />
<input type="reset" value="Cancel" />
</td>
</tr>
</table>


<br /><br />
</form>
</body>
</html>


 </body>
</html>
```

Home.html page

```
<!DOCTYPE html>
```

```
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width,
initial-scale=1.0" />
    <title>Document</title>
  </head>
  <body>
    <h2>Its home Page!!</h2>
  </body>
</html>
```

Menubar.html page

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width,
initial-scale=1.0" />
    <title>Document</title>
  </head>
  <body>
```

```
   <a href="home.html"
target="destinationPage">HOMEPage</a><br /><br />
   <a href="login.html"
target="destinationPage">LoginPage</a><br /><br />
   <a href="signup.html"
target="destinationPage">SignUpPage</a><br /><br />
  </body>
</html>
```

Index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width,
initial-scale=1.0">
  <title>Document</title>
</head>
<frameset cols="15%,*">

  <frame src="MenuBar.html" noresize>
   <frame src="" name="destinationPage">
</frameset>
</html>
```