
	DRAWING REVISION INFORMATION					
REV	DESCRIPTION	DRAWN BY	ISSUE DATE			
1	PROTO/QUOTE	JLB	4/23/15			



FOR QUOTE ONLY

## 材料:

尺寸:inch[mm]

- 1.6262-T8/T9或6061-T6
- 2.表面處理:硬陽厚度.0008+/-.0004[0.02+/-0.01]

依照規範MIL-A-8625, TYPE 3, 等級2

- 3.尺寸為皆為陽極後
- 4. 不允許銳角
- 5.無指定的半徑邊緣倒角MAX.02[0.5]
- 6. 允許中心鑽MAX Ø . 06[1.5]
- 7. 允許在這個直徑或表面有接觸點
- 8.去毛邊

## NOTES:

- 1. MATERIAL, 6262-T8/T9 OR 6061-T6 ALUMINUM
- 2. HARD ANODIZE TO YIELD .0008  $\pm$  .0004 [0.02  $\pm$  0.01] BUILD-UP PER SURFACE, PER MIL-A-8625, TYPE III, CLASS 2
- 3. ALL DIMENSIONS APPLY AFTER ANODIZING
- 4. SHARP EDGES WILL NOT BE TOLERATED
- 5. BREAK/RADIUS UNSPECIFIED EDGES/CORNERS, .02 [0.5] MAX
- 6. CENTER DRILL PERMISSIBLE, Ø.06 [1.5]
- 7. CONTACT POINTS PERMITTED ON THIS DIAMETER OR SURFACE.
- 8. REMOVE BURRS

DETAIL A	
SCALE 8:	

(2X) .025[ 0.64 ]

UNLESS OTHERWISE DESIGNATED BY WAY OF SYMBOLS, KEY CHARACTERISTIC	UNLESS OTHERWISE SPECIFIE
REQUIREMENTS SHALL BE GOVERNED BY	DRAFTING PER ASME Y14.5M-1994 DIMENSIONS ARE IN INCHES [MILLIMETE
SON-ENG-GL-02	.xx [x.x] ± .015 [0.38]
SON-ENG-GL-02	.xxx [x.xx] ± .005 [0.13]
	ANGLES ± 5°
KEY CHARACTERISTIC SYMBOLS	SURFACE FINISH 125 [3.2]
	V
Cr) (Ma) CRITICAL MAJOR	THIRD ANGLE PROJECTION

CURRENT ISSUE	DATE							
DRAWN								
JLB	4/23/15							
CHECKED		VALVE						
ETD	4/24/15							
MFG ENG								
-	-							
APPROVED		SIZE			DWG NO.			REV
DGP	-	В			225740-01			
ISSUED								
_	_	SCALE	4:1	EST. WT.	0.05 LBS	SHEET	1 OF 1	

Friday, April 24, 2015

(2X) .020 0.51