

DETAIL B SCALE 4:1

(8X) .025[0.64] →

(8X) .020[0.51]

.04[1.0] 45°±5° -.36[9.1] -.403[10.24]

DETAIL C SCALE 4:1 DETAIL D SCALE 4:1

NOTES:

REV

- 1. MATERIAL, 6262-T8/T9 OR 6061-T6 ALUMINUM
- 2. HARD ANODIZE TO YIELD .0008 [0.020] ± .0004 [0.010] BUILD UP PER SURFACE, PER MIL-A-8625, TYPE III, CLASS 2
- 3. ALL DIMENSIONS APPLY AFTER ANODIZING
- 4. SHARP EDGES WILL NOT BE TOLERATED
- 5. UNSPECIFIED FILLETS & RADII .005/.015 [0.12/0.38]
- 6. CONTACT POINTS PERMISSIBLE ON DIAMETER
- ↑. CENTERS PERMISSABLE, .060 [1.52] MAX

UNLESS OTHERWISE DESIGNATED BY WAY OF SYMBOLS, KEY CHARACTERISTIC REQUIREMENTS SHALL REPORT REPORT

材料:

尺寸:inch[mm]

4.不允許銳角

1.6262-T8/T9或6061-T6

6. 允許在此尺寸有接觸點

7. 允許有中心點MAX.060[1.52]

3.尺寸為皆為陽極後

2.表面處理:硬陽厚度.0008[0.020]+/-.004[0.010]

依照規範MIL-A-8625, TYPE 3, 等級2

5.無指定的圓角及半徑.005/.015[0.12/0.38]

CURRENT ISSUE	DATE							
DRAWN								
TVM	04/24/15							
CHECKED		TITLE						
JLB	04/28/15	VALVE						
MFG ENG					VALVE			
-	-							
APPROVED		SIZE			DWG NO.			RE\
DGP	-	C			22	225740-02		
ISSUED					0.051.00		4 0 = 4	
PRJ	-	SCALE	2:1	EST. WT.	0.05 LBS	SHEET	1 OF 1	

-(5X) .025[0.64]