




DRAWING REVISION INFORMATION			
REV	DESCRIPTION	DRAWN BY	ISSUE DATE
1	PROTO/QUOTE	ETD	-






NOTES:

1. MATERIAL: 6262-T8/T9 OR 6061-T6 ALUMINUM
2. HARD ANODIZE TO YIELD .0008±.0004 [0.02±0.01] BUILD-UP PER SURFACE, PER MIL-A-8625, TYPE III, CLASS 2
3. ALL DIMENSIONS APPLY AFTER ANODIZE
4. BREAK/RADIUS UNSPECIFIED SHARP EDGES/FILLETS, .02 [0.5] MAX
5. REMOVE BURRS
6. SHARP EDGES WILL NOT BE TOLERATED
7. CONTACT POINTS PERMITTED ON THIS DIAMETER
8. 60° CENTERS PERMISSIBLE ON BOTH ENDS TO Ø.160 MAX. CENTER MARKS PERMISSIBLE ON SLOT TO OAL



ISOMETRIC VIEW  
SCALE 2:1

- |   |   |
|---|---|
| 1. 材料：6061-T8/T9或是6061-T6鋁<br>2. 硬陽，厚度.0008+/- .0004[0.02+/-0.01]，依照規範MIL-A-8625，TYPE III，CLASS 2<br>3. 所有尺寸都是陽極之後<br>4. 除銳角，未指定R角.02[0.5]MAX<br>5. 去毛邊<br>6. 不允有銳角<br>7. 允許在此尺寸有接觸點<br>8. 允許有兩端有60度中心點 Ø.160 MAX | UNLESS OTHERWISE SPECIFIED<br>DRAFTING PER ASME Y14.5M-1994<br>DIMENSIONS ARE IN INCHES [MILLIMETERS] |
|---|---|

	UNLESS OTHERWISE SPECIFIED DRAFTING PER ASME Y14.5M-1994 DIMENSIONS ARE IN INCHES [MILLIMETERS]  XX [X.X] ± .015 [0.38] XXX [X.XX] ± .005 [0.13] ANGLES ± 1°  SURFACE FINISH 125 [3.2]✓	CURRENT ISSUE		DATE		TITLE  VALVE																	
		DRAWN		ETD								04/17/14											
		CHECKED		TVM								04/25/14											
		MFG ENG		-		-		SIZE		B		DWG NO.		124740-18		REV		1					
		APPROVED		DGP		-		ISSUED		PRJ		-		SCALE		4:1		EST. WT.		0.01 LBS		SHEET	
KEY CHARACTERISTIC SYMBOLS		THIRD ANGLE PROJECTION								CRITICAL		MAJOR											

# PROTO/QUOTE