
	DRAWING REVISION INFORMATION				
RE	DESCRIPTION	DRAWN BY	ISSUE DATE		
-	ORIGINAL ISSUE	PAK	03/26/13		



SECTION A-A SCALE 4:1

NOTES:

SUPPLY ENOUGH TRANSJEL TO SECURLY HOLD PARTS TOGETHER AS ILLUSTRATED

- 2. THE CLEARANCE BETWEEN THE VALVE AND SLEEVE SPOOL DIAMETERS SHOULD BE .0004/.0014 [0.01/0.036]
- 1.用足夠凝膠保證像圖面那樣撐住零件
- 2.VALVE和SLEEVE的中間必須被清空, 兩者之間的直徑必須是

0.0004/0.0014[0.01/0.036]

	UNLESS OTHERWISE SPECIFIED				
	DRAFTING PER ASME Y14.5M-1994 DIMENSIONS ARE IN INCHES [MILLIMETERS]				
	.XX [X.X] ±	.015 [0.38]			
	.XXX [X.XX] ±	.005 [0.13]			
	ANGLES ±	1°			
KEY CHARACTERISTIC SYMBOLS	SURFACE FINISH	125 [3.2]			
Cr) (Ma) CRITICAL MAJOR	THIRD ANGLE PROJECTION	(b)			

3	1.	31295	-	TRANSJEL			
2	1	104740-20	-	SLEEVE			
1	1	104740-19	-	VALVE			
ITEM	QTY	PART NUMBER	REV	DESCRIPTION (REF)			
DARTOLIOT							

	PARTS LIST								
	CURRENT ISSUE	DATE							
Ī	DRAWN								
	PAK	02/01/13							
Ī	CHECKED		TITLE ACCEMBLY AEL VALVE/CLEEVE						
	DGP	02/04/13							
Ī	MFG ENG			ASSEMBLY, AFL VALVE/SLEEVE					
	-	-							
	APPROVED		SIZE	SIZE DWG NO.				REV	
+	SCJ	03/26/13	В			104740ASSY19			-
	ISSUED			0.4		0.001.00		4.05.4	
	PRJ	03/26/13	SCALE	2:1	EST. WT.	0.02 LBS	SHEET	1 OF 1	

APPROVED