





- 1.材料：4032-T6/T651/T86
2.除非特別指定， 內部R角0.005/0.015(0.13/0.38)MAX
3.除銳角 0.010(0.25)MAX
4.穿過孔洞之間無角度關係
5.穿過孔洞之間無角度關係
6.除毛邊

DRAWING REVISION INFORMATION			
REV	DESCRIPTION	DRAWN BY	ISSUE DATE
-	ORIGINAL ISSUE	DGP	07/06/09
A	.447 [11.34] WAS .410 [10.40], 686 [17.42] WAS .645 [16.38], .920 [23.37] WAS .876 [22.24], .08 [2.0] WAS .04 [1.0], ADDED DIM .539 [13.69], 1.680 [42.67] DIM CHANGED TO REF. DIM., (3) SLOTS WAS (6X) HOLES, (3) SLOTS (2) PLACES WAS (6X) HOLES, 3 PLACES; REV'D NOTES 4 & 5; REF ECN05250	DGP	03/04/10



- NOTES:
- MATERIAL: 4032-T6/T651/T86 ALUMINUM
 - UNLESS OTHERWISE SPECIFIED, RADIUS INSIDE CORNERS R.005/.015 [0.13/0.38] MAX;
 - BREAK SHARP EDGES .010 [0.25] MAX.
 - NO ANGULAR RELATIONSHIP TO CROSS SLOTS
 - NO ANGULAR RELATIONSHIP TO CROSS SLOTS OR CROSS HOLES
 - REMOVE BURRS.

UNLESS OTHERWISE SPECIFIED		CURRENT ISSUE	DATE	TITLE			
DRAFTING PER ASME Y14.5M-1994 DIMENSIONS ARE IN INCHES [MILLIMETERS]		DRAWN DGP	01/16/09	SLEEVE, K2 CLUTCH CONTROL			
.XX [X.X] ± .010 [0.25] .XXX [X.XX] ± .005 [0.13] ANGLES ± 5°		CHECKED MMC	01/21/09				
SURFACE FINISH 63 [1.8]		MFG ENG -	-				
KEY CHARACTERISTIC SYMBOLS Cr (CRITICAL) Ma (MAJOR)		APPROVED SCJ	03/04/10	SIZE C	DWG NO. 15741-06	REV A	
THIRD ANGLE PROJECTION		ISSUED PRJ	03/04/10	SCALE 2:1	EST. WT. 0.01 LBS	SHEET 1 OF 1	

APPROVED