

AEROKLER C



OIL & GAS

Oil and petroleum
Aircraft fueling



APPLICATIONS

Aircraft ground refuelling with kerosene or petroleum fuel, aromatic content $\leq 50\%$.

Fuel discharge under pressure.

ADVANTAGES

- † Recognized by the major oil companies.
- † Highly resistant non fuel contaminating tube.
- † Light weight, flexible and abrasion resistant hose.
- † Available in 30 and 40m long as standard stock.

TECHNICAL DESCRIPTION

Inner tube: kerosene resistant NBR, black, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant CR, black, fabric impression.

Temperature range: -30°C to $+100^{\circ}\text{C}$.

Electrical properties: semi-conductive cover,
 $10^3\Omega/\text{lg} < R < 10^6\Omega/\text{lg}$.

STANDARD/APPROVAL

EI 1529:2014 type C.

EI

ISO 1825:2017 type C.

ISO

COMPLEMENTARY INFORMATION

Supplied upon request, the hose assemblies are ready fitted with tin plated brass couplings secured by drop forged aluminum safety clamps.

Hose assemblies are individually tested and supplied with a test certificate.

Max vacuum 0.15bar: hose retains 80% of its original internal diameter according to EI 1529/C and ISO 1825:2017.



and embossed: TRELLEBORG - AEROKLER C - AIRCRAFT FUELING HOSE - EI 1529:2014 - ISO 1825:2017 - 2/Ω - ND - WP 20BAR (300PSI) - quarter/year - batch number

Luminescent spiralled marking on request:



 OIL & GAS			AEROKLER C							
ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (1) or min. order m
19.0	6 ±0.7	31.0 ±1.0	20	80	0.15	90	0.55	30	5500067	1
19.0	6 ±0.7	31.0 ±1.0	20	80	0.15	90	0.55	40	0060578	1
25.0	6.25 ±0.7	37.5 ±1.0	20	80	0.15	115	0.75	40	0060593	1
32.0	6.25 ±0.7	44.5 ±1.0	20	80	0.15	140	0.87	30	0060594	1
32.0	6.25 ±0.7	44.5 ±1.0	20	80	0.15	140	0.87	40	0060595	1
38.0	6.5 ±0.7	51.0 ±1.0	20	80	0.15	180	1.04	40	0060597	1
38.0	6.5 ±0.7	51.0 ±1.0	20	80	0.15	180	1.04	30	0060596	1
50.0	8 ±0.9	66.0 ±1.0	20	80	0.15	215	1.77	30	0060610	1
50.0	8 ±0.9	66.0 ±1.0	20	80	0.15	215	1.77	40	0060611	1
63.0	8.5 ±1.15	80.0 ±1.5	20	80	0.15	230	2.18	40	0060601	1
75.0	8 ±1.15	91.0 ±1.5	20	80	-	230	2.52	30	0060602	1
75.0	8 ±1.15	91.0 ±1.5	20	80	-	230	2.52	40	0060603	1
100.0	9 ±1.6	118.0 ±2.0	20	80	-	345	3.62	40	5513522	1
Tolerance on length: ±1% (ISO 1307 Standard).										

Digital version

