

25-01-2026

Agenda:

- String methods ●
- while loop ●
- Functions ●
- Function arguments ●

String methods

"Hello". strip()
 . lstrip()
 . rstrip()

far :

far :

ba

"Mona!"

0 1 2 3 4

→

M	I	na!
↓	↓	↓
0	-1/4	2
-5		

→
←
-|→ not found

developer $\rightarrow$ standar $\rightarrow$ find (M) $\rightarrow$ $\begin{matrix} 0 \\ -5 \end{matrix}$

loop:

for

→ iterate over a sequence of elements → 3 iterations

ex. for i in $[1, 2, 3]$:

→ we already know how many iteration loop, is going to take.

while

→ repeat a block of code until
certain condition is true

ex. while condition:

condition $\rightarrow$ understand python

while condition :

jump to next
topic



Syntax: while condition: ^{True}
do something

Example:

count = 0

keep adding +1 to the count until it is smaller than
or equal to 5.


count <= 5



hello != hello -> false

```

user_input = ""
while user_input != "hello":
    user_input = input("Enter your input")
    print(user_input)
print("after while loop")
  
```



Control flow:

for condition: 100 values ¹⁰⁰⁰⁰

-> 100 times

if 'a' == 'mango' !
Continue

- something
- something
- something

- break $\rightarrow$ Terminate the loop
- continue $\rightarrow$ Skip the current iteration

'a' == 'mona' → run below
'b' == 'mona' → — " —
'mona' == 'mona/' → True
↓
break
↓
come out of loop

examples : $\overset{\text{named}}{\downarrow}$ `print()`
 : `type()`
 $\downarrow$
 pre-defined
 function

`print()` $\equiv$ } reusable
`print()`
 $\downarrow$
 prints the output in terminal / screen.

User-defined function:

Syntax:

```
def name-of-function():  
    do something
```

print X

paranthesis

```
def name-of-function():
```



do something

def print():

_____ → predefined function


function — our_custom_string_cleaner — doing some job
 ↓
 print — clean version of string
 ↓
 ⇒ cleaning the string inside it

p.) we want to get cleaned string.



print(3) → OS → 3
 a = 3
 a += 1
 print(a) → 4 } see the output

Terminar)



$l = [200, 100, 2, 3]$


$\text{sorted}(l) \rightarrow$ sort the given list & store the new sorted list in a variable

$\rightarrow$ ~~return the new variable.~~

$l = [200, 100, 2, 3]$

$l = \text{sorted}(l)$ None



$l = [2, 3, 100, 200]$



```
def add_dummy():
    name = input("Enter your name : ")
    print("hello", name, ", Greeting from krish naik academy.")
```

$\rightarrow$ $\text{return_value} = \text{add_dummy}()$ $\rightarrow$ input $\leftarrow$ "hello" $\dots$ $\leftarrow$ l
 $\text{print}(\text{return_value})$

return value $\leftarrow$ None $\leftarrow$ $\text{add_dummy}()$



$\text{lol.split}() \rightarrow$ not

function $\rightarrow$ return something $\rightarrow$ nothing $\rightarrow$ None
 $\rightarrow$ value $\rightarrow$

p.1

we want to create reusable code that will
take input from user as a number &
subtract. Once calculate return that value.
 $\downarrow$
Throw

```
def subtract():  
    a = float(input())  
    b = float(input())  
    c = a - b
```

val = subtract() $\rightarrow$ $a=1, b=2$
None $c=1-2=-1$

```
def subtract():  
    a = float(input())  
    b = float(input())  
    c = a - b  
    return c
```

val = subtract() $\rightarrow$ $a=1, b=2$
-1 $c=1-2=-1$
 $\rightarrow$ return c
subtract()

top to
bottom

left to right $\rightarrow$

subtract()
 $\downarrow$
 $a=2$
 $b=2$
 $c=2-2$ $\rightarrow 0$

0





$\rightarrow$

(+)

Substrac()
 $\downarrow$
 $a=4$
 $b=2$

$c=4-2$
 $c=2$
return 2

+ 2



default-arg
 add(a=0,b) →
 add(a, b=0)

add(a=0, b) add(a, b=0)
 ↓ ↓
 add(1) add(1)