Project Documentation

MicroGoals

1. Introduction

- **Project Title: MicroGoals**
- **Team ID: NM2025TMID37003**

Team Leader:

Neha P
nehapattabiraman@gmail.com @gmail.com

Team Members:

Name & Mail ID

Nanditha bharathi B
Nandithabharathi67@gmail.com

Nidanam Sharon Y
yovan9600@gmail.com

Yogapriya K
ypkumar2727@gmail.com

Project Overview

MicroGoals is a secure backend RESTful API developed using Node.js, Express.js, and MongoDB. It enables users to register, log in, and manage their personal goals through CRUD operations. The system uses JWT authentication and middleware to ensure data security and user-specific access control.

The system includes:

- User Registration & Login

- JWT-based Authentication
- CRUD Operations for Goals
- Protected Routes
- Centralized Error Handling

The main objective is to provide a secure and scalable backend system for digital goal management.

Project Instruction

- The project follows REST API principles.
- Authentication is handled using JWT.
- MongoDB is used as the database.
- APIs are tested using Thunder Client.
- The project follows MVC architecture.

Pre-requisites

Before running the project, the following tools are required:

- Node.js (v18 or higher)
- Express.js
- MongoDB (Local / Atlas)
- VS Code
- Thunder Client (Extension)

- Basic knowledge of JavaScript & REST APIs

Project Architecture Image (Text Representation)



PROJECT ARCHITECTURE

TECHNICAL ARCHITECTURE

- Runtime: Node.js

- Framework: Express.js
- Database: MongoDB
- Authentication: JWT
- Architecture Pattern: MVC

ER DIAGRAM

Entities:

1. User
    - _id
    - name
    - email
    - password
2. Goal
    - _id
    - title
    - completed
    - userId (Reference to User)

Relationship:

One User → Many Goals



FEATURES

- User Registration
- Secure Login with JWT
- Create Goal
- Update Goal
- Delete Goal
- View User-specific Goals
- Protected Routes
- Centralized Error Handling

ROLES AND RESPONSIBILITIES

Role	Responsibility
User	Register, Login, Manage Goals
Developer	API Development & Testing

USERS FLOW

1. User registers
2. User logs in
3. JWT token generated
4. User sends token in header
5. Access protected routes
6. Perform CRUD operations

PROJECT SETUP AND CONFIGURATION

Folder Structure

```
MicroGoals/
├── middleware/
│   ├── authMiddleware.js
│   └── errorMiddleware.js
├──Schema/
├──User.js
├──GoalSchema.js
├── models/
│   ├── userModel.js
│   └── goalModel.js
│
├── routes/
│   ├── authRoutes.js
│   └── goalRoutes.js
│
├── .env
├── Index.js
└── package.json
```



Project Setup

1. npm init -y

2. Install dependencies:

```
npm install express mongoose jsonwebtoken bcryptjs dotenv
```

0. Start server:

```
node server.js
```

BACKEND DEVELOPMENT

- Created Express Server

An Express server was set up to handle API requests, connect routes, and enable JSON parsing for backend operations

```
.env        index.js ×
myfinal-main > index.js > ...
1   require("dotenv").config();
2   const express = require("express");
3   const app = express();
4   const mongoose = require("mongoose");
5   const cors = require("cors");
6   app.use(cors());
7   const errormiddleware = require("./Middlewares/errormiddleware");
8   app.use(express.urlencoded({ extended: true }));
9   const bodyParser = require("body-parser");
10  app.use(express.json());
11  const PORT = process.env.PORT;
12  const Mongo_Url = process.env.MONGO_URL;
13  const authRoute = require("./Router/AuthRouter");
14  const GoalRouter = require("./Router/GoalRouter");
15
16  //mongoDB connection
17  mongoose
18    .connect(Mongo_Url)
19    .then(() => console.log("MongoDB Connected"))
20    .catch((err) => console.log(err));
21
22  //route
23  app.use("/", authRoute);
24  app.use("/", GoalRouter);
25
26  app.use(errormiddleware);
27  app.listen(PORT, () => {
28    console.log("Server running on port 8000");
29  });
30
31
```

- Connected MongoDB

For Connection with MongoDB:-

```
//mongoDB connection
mongoose
  .connect(Mongo_Url)
  .then(() => console.log("MongoDB Connected"))
  .catch((err) => console.log(err));
```

- Implemented Authentication APIs

User registration and login APIs were created with password hashing and JWT token generation for secure authentication.

- Implemented Goal CRUD APIs

Goal CRUD APIs were implemented to allow authenticated users to perform full Create, Read, Update, and Delete operations on their personal goals. These APIs follow RESTful architecture principles and are designed to ensure secure and structured data management.

The Create API enables users to add new goals to the database. Each goal is associated with a specific user using a userId reference, ensuring user-specific data isolation.

The Read API allows authenticated users to retrieve only their own goals from the database. Data filtering is applied using the authenticated user's ID to prevent unauthorized data access.

The Update API enables users to modify existing goals. Proper validation checks ensure that only the owner of the goal can update it.

The Delete API allows users to permanently remove their goals from the system. Secure route protection ensures that users cannot delete goals belonging to others.

All CRUD routes are protected using Authentication Middleware, which verifies the JWT token before granting access. If the token is missing or invalid, the system returns a 401 Unauthorized error.

Additionally, Error Middleware is implemented to handle runtime and validation errors centrally. It captures exceptions from CRUD operations and returns consistent JSON responses with appropriate HTTP status codes such as 200, 201, 400, 401, and 404.

This structured implementation ensures secure data handling, proper authorization, and reliable API behavior across all goal management operations.

```
const express = require("express");
const router = express.Router();
const goalModel = require("../Model/GoalModel");
const authmiddleware = require("../Middlewares/authMiddleware");

router.post("/create", authmiddleware, async (req, res, next) => {
  try {
    const { title } = req.body;
    const goal = new goalModel({
      title: title,
      user: req.user,
    });
    await goal.save();
    res.status(200).json({
      success: true,
      data: goal,
    });
  } catch (err) {
    return next(err);
```

```
  }
});

router.get("/:id", authmiddleware, async (req, res, next) => {
  try {
    const id = req.params.id;
    const data = await goalModel.findOne({
      _id: id,
      user: req.user,
    });
    res.status(200).json({
      success: true,
      data: data,
    });
  } catch (error) {
    return next(error);
  }
});

router.put("/:id", authmiddleware, async (req, res, next) => {
  try {
    const goal = await goalModel.findOneAndUpdate(
      { _id: req.params.id, user: req.user },
      { completed: req.body.completed },
      { new: true },
    );
    res.status(200).json({
      success: true,
      message: "the goal is completed",
    });
  } catch (error) {
    return next(error);
  }
});

router.delete("/:id", authmiddleware, async (req, res, next) => {
  try {
    await goalModel.findOneAndDelete({
      _id: req.params.id,
    });

    res.status(200).json({ message: "Goal deleted" });
  } catch (error) {
    next(error);
  }
});

module.exports = router;
```

- Added Auth Middleware
- Auth middleware was implemented to verify JWT tokens and secure protected routes from unauthorized access.

```
.env        authMiddleware.js ×
myfinal-main > Middlewares > authMiddleware.js > ...
1  const jwt = require("jsonwebtoken");
2  require("dotenv").config();
3
4  const authmiddleware = (req, res, next) => {
5    try {
6      const header = req.headers.authorization;
7
8      if (!header) {
9        return res.status(401).json({ message: "No token" });
10     }
11
12     const token = header.split(" ")[1];
13
14     const decoded = jwt.verify(token, process.env.JWT_SECRET);
15
16     req.user = decoded.userId;
17
18     next();
19   } catch (error) {
20     return res.status(401).json({ message: "Invalid token" });
21   }
22 };
23 module.exports = authmiddleware;
24
```

- Added Error Middleware

An error middleware was added to handle application errors centrally and return proper status codes and messages.

```
.env        errormiddleware.js ×
myfinal-main > Middlewares > errormiddleware.js > ...
1  const errormiddleware = (err, req, res, next) => {
2    console.log(err);
3    const status = err.status|| 500;
4    const message = err.message || "server error";
5    res.status(status).json({
6      success: false,
7      message: message,
8    });
9  };
10
11 module.exports = errormiddleware;
```

DATABASE DEVELOPMENT

CONFIGURE MongoDB

- Use MongoDB Atlas or Local MongoDB

- Store connection string in `.env`

CREATE DATABASE CONNECTION

Index.js file:

- Use mongoose.connect()

```
//mongoDB connection
mongoose
  .connect(Mongo_Url)
  .then(() => console.log("MongoDB Connected"))
  .catch((err) => console.log(err));
```

- Handle connection errors

CREATE SCHEMA AND MODELS

User Schema

The User Schema defines the user data structure with name, email (unique), and hashed password fields.

Goal Schema (with userId reference)

The Goal Schema stores goal details and includes a userId reference to associate each goal with a specific user.

PROJECT EXECUTION

Project Execution Steps

1. Start MongoDB
2. Run server
3. Test APIs in Thunder Client
4. Register User
5. Login and get JWT
6. Perform CRUD operations

Project Output Screenshots

- Successful User Registration(Signup/Login)
- In this Api call the user register or login and token was genrated



- JWT Token Response

After successful login user the api generate the token and these token was sent with every request to every api

- Goal Created Successfully
- After the login and token is generated the user give post request to api for creating there goals and goal was save in MongoDB which was the database



- Protected Route Working
- If the user does not have token which was generated by backend api then he cannot access the api so Route are protectedZ





Project Demo Video

Record video showing:

- Registration
- Login
- Token usage
- CRUD operations
- Error handling

video:https://drive.google.com/file/d/1aIo-oucbgugp4pECEViOgHWbPFokgLxW/view?usp=drivesdk

Drive:https://github.com/neha872025/MicroGoal.git