Online C Compiler - Programiz

programiz.com/c-programming/online-compiler/

Gmail YouTube Maps

Programiz
C Online Compiler

Programiz PRO
Never struggle with DSA again. Learn with interactive visuals
Try Now

main.c

Share Run

```c
#include <stdio.h>
#include <stdlib.h>

struct Node
{
    int data;              // corrected here
    struct Node *next;
};

int main()
{
    struct Node *head, *first, *second;

    head = (struct Node*)malloc(sizeof(struct Node));
    first = (struct Node*)malloc(sizeof(struct Node));
    second = (struct Node*)malloc(sizeof(struct Node));

    head->data = 10;
    head->next = first;

    first->data = 20;
    first->next = second;

    second->data = 30;
```

Output

```
5 -> 10 -> 20 -> 30 -> NULL

=== Code Execution Successful ===
```

programiz.com/c-programming/online-compiler/

Gmail YouTube Maps

Programiz
C Online Compiler

Programiz PRO
Never struggle with DSA again.
Learn with interactive visuals
Try Now

main.c

Share Run

```c
    first->data = 20;
    first->next = second;

    second->data = 30;
    second->next = NULL;

    // Insert at beginning
    struct Node *newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = 5;
    newNode->next = head;
    head = newNode;

    // Print linked list
    struct Node *temp = head;
    while (temp != NULL)
    {
        printf("%d -> ", temp->data);
        temp = temp->next;
    }
    printf("NULL");

    return 0;

}
```

Output

```
5 -> 10 -> 20 -> 30 -> NULL

=== Code Execution Successful ===
```

26°C
Partly cloudy

Search

4.
```
#include<stdio.h>
#include(stdib.h)
struct Node
{
 int data;
 struct Node * next;
};
int main()
{
 struct Node *head, *first, *second;

head = (struct Node*) malloc(sizeof(struct Node));
first = (struct Node*) malloc(sizeof(struct Node));
second = (struct Node*) malloc(sizeof(struct Node));

head -> data = 10;
head -> next = first;

first -> data = 20;
first -> next = second;

second -> data = 30;
second -> next = NULL;
~~head~~

struct Node * newNode = (struct Node*) malloc(sizeof
                        (struct Node));
newNode -> data = 5;
newNode -> next = head;
head = newNode;
```

```
struct Node *temp = head;
while (temp != NULL)
{
printf ("%d -> ", temp->data);
temp = temp -> next;
}
printf ("NULL");
return 0;
}
```