

Project Report

SPM, SPM Lab, AP Lab

TRIP DRIP (INDIA EDITION)

Submitted By

Name: Neha Jajal,

Ujjwal Savla

SAP ID: 53013240106,

53013240077

Class: T.Y. B.Sc. IT.

Division: A

Department of Information Technology

**SVKM's Usha Pravin Gandhi College of Arts, Science & Commerce
(AUTONOMOUS)**

NAAC Accredited 'A+' Grade with CGPA 3.27

(Affiliated to University of Mumbai)

Vile Parle (West), Mumbai 400056

2026 - 2027

TABLE OF CONTENTS

- **List of Figures**
- **List of Tables**
- **Acronyms and Abbreviations**
- **Chapter 1 — Introduction**
 - 1.1 Project Title
 - 1.2 Abstract
 - 1.3 Introduction
 - 1.4 Background
 - 1.5 Problem Statement
 - 1.6 Motivation
 - 1.7 Objectives
 - 1.8 Scope
 - 1.9 Target Users
 - 1.10 Existing System
 - 1.11 Limitations of Existing System
 - 1.12 Proposed System
 - 1.13 Advantages of Proposed System
 - 1.14 Project Development Approach
- **Chapter 2 — Requirement Analysis**
 - 2.1 Functional Requirements
 - 2.2 Non-Functional Requirements
 - 2.3 Hardware Requirements
 - 2.4 Software Requirements
 - 2.5 Technology Stack
 - 2.6 User Roles
 - 2.7 User Permissions
 - 2.8 System Constraints
 - 2.9 Assumptions
 - 2.10 Feasibility Study (Technical, Operational, Economic)
 - 2.11 Feature Classification
- **Chapter 3 — System Analysis**
 - 3.1 System Workflow
 - 3.2 User Workflow
 - 3.3 Module Breakdown
 - 3.4 Functional Decomposition
 - 3.5 Use Cases
 - 3.6 Detailed Use Case Descriptions
 - 3.7 Data Flow Analysis
 - 3.8 Input/Output Analysis

- 3.9 User Interaction Flow & Diagrams (Use Case, Context, DFD Level 0, DFD Level 1, Activity Diagrams)
- **Chapter 4 — System Design**
- 4.1 System Architecture
- 4.2 High-Level Architecture
- 4.3 Detailed Architecture
- 4.4 Frontend Architecture
- 4.5 Backend Architecture
- 4.6 Database Architecture & pgvector Integration
- 4.7 Component Architecture
- 4.8 Module Design
- 4.9 Database Design & Schema Models
- 4.10 Entity-Relationship (ER) Diagram
- 4.11 Database Tables Specification
- 4.12 Data Dictionary
- 4.13 Class Diagram
- 4.14 Sequence Diagrams
- 4.15 Deployment Diagram
- 4.16 Security Design & Row-Level Security (RLS)
- 4.17 Application Navigation Design
- 4.18 Data Flow Between Components
- **Chapter 5 — Implementation**
- 5.1 Development Environment
- 5.2 Project Folder Structure
- 5.3 Frontend Implementation
- 5.4 Backend Implementation
- 5.5 Database Implementation
- 5.6 API Implementation
- 5.7 Authentication Implementation
- 5.8 Authorization & Row-Level Security Implementation
- 5.9 Important Modules
- 5.10 Important Algorithms (Minimal Cashflow Resolution, Vector Cosine Similarity, Deduplication & Auto-Repair, Haversine Math)
- 5.11 Important Functions, Classes, and Components
- 5.12 Error Handling & Resilient Fallback Architecture
- 5.13 Security Implementation
- 5.14 Third-Party Libraries & APIs
- 5.15 Configuration & Environment Setup
- 5.16 Deployment Setup
- **Chapter 6 — Tools and Development Platforms**
- 6.1 Antigravity
- 6.2 Claude
- 6.3 Vercel

- 6.4 ChatGPT
- 6.5 NotebookLM
- 6.6 Slack
- 6.7 Jira
- 6.8 Integrated Development and Collaboration Workflow
- **Chapter 7 — User Interface**
- 7.1 Landing Page
- 7.2 Authentication Pages (Login / Registration)
- 7.3 Trips Hub (Trips Management)
- 7.4 New Trip Creation Wizard
- 7.5 Trip Dashboard & Itinerary Matrix
- 7.6 Smart Wardrobe & Suitability Scoring
- 7.7 Outfit Inspiration & Visual Reverse Search
- 7.8 Multi-Brand Shop & Price Comparison
- 7.9 Yatra Diary & Photo Journal
- 7.10 Group Expense Tracker & Hisaab-Kitaab UPI Splitter
- 7.11 Chai & Station Radar Modal
- 7.12 Smart Packing Checklist
- 7.13 Group Invite & Joint Missing Items
- 7.14 Settings & Currency Configuration
- **Chapter 8 — Testing & Quality Assurance**
- 8.1 Testing Strategy
- 8.2 Testing Environment
- 8.3 Test Plan
- 8.4 Functional Testing
- 8.5 UI Testing
- 8.6 API Testing
- 8.7 Database Testing
- 8.8 Integration Testing
- 8.9 Authentication Testing
- 8.10 Validation Testing
- 8.11 Negative Testing
- 8.12 Edge Case Testing
- 8.13 Error Handling Testing
- 8.14 Security Testing
- 8.15 Automated Test Execution Results (QA Assertions)
- 8.16 Manual Test Results
- 8.17 Defect Report & Bug Remediation
- 8.18 Test Execution Summary
- **Chapter 9 — Attempted but Unsuccessful Feature: Full Outfit Recommendation Using User Photo**
- 9.1 Feature Objective
- 9.2 Intended Functionality

- 9.3 Implementation Attempt
- 9.4 Technical Investigation & Result
- 9.5 Current Status
- 9.6 Reason for Non-Completion
- 9.7 Impact on Overall Application
- 9.8 Future Implementation Roadmap
- **Chapter 10 — Results and Discussion**
- 10.1 Final System Results
- 10.2 Successfully Implemented Features
- 10.3 Partially Implemented Features
- 10.4 Attempted but Unsuccessful Features
- 10.5 Test Results Summary
- 10.6 Performance Observations
- 10.7 Problems Encountered
- 10.8 Solutions Implemented
- 10.9 Current Limitations
- 10.10 Discussion
- **Chapter 11 — Conclusion and Future Scope**
- 11.1 Conclusion
- 11.2 Project Achievements
- 11.3 Technical & Project Management Learning Outcomes
- 11.4 Future Enhancements
- **References**
- **Appendices**
- Appendix A: API Endpoint Specification
- Appendix B: PostgreSQL Database Schema
- Appendix C: Complete Data Dictionary
- Appendix D: Important Code Snippets
- Appendix E: Application Layout Architecture
- Appendix F: Automated Test Log Output
- Appendix G: Error Handling Matrices
- Appendix H: Installation and Local Setup Guide
- Appendix I: Deployment Information
- Appendix J: Additional Architecture Diagrams

LIST OF FIGURES

- Figure 3.1: Complete System Workflow Architecture
- Figure 3.2: End-to-End User Interaction Journey
- Figure 3.3: System Use Case Diagram
- Figure 3.4: Context Diagram (DFD Level 0)
- Figure 3.5: Detailed Data Flow Diagram (DFD Level 1)
- Figure 3.6: System Activity Diagram (Trip Generation & AI Concierge)

- Figure 4.1: High-Level System Architecture Diagram
- Figure 4.2: Frontend React Component Hierarchy
- Figure 4.3: Backend Express & Serverless API Routing Architecture
- Figure 4.4: Entity-Relationship (ER) Diagram
- Figure 4.5: Sequence Diagram — Trip Creation & Dynamic Budget Allocation
- Figure 4.6: Sequence Diagram — AI Concierge Action Execution Pipeline
- Figure 4.7: Sequence Diagram — Garment Vectorization & Cosine Similarity Matching
- Figure 4.8: Deployment Architecture Diagram (Vercel & Supabase Cloud)
- Figure 4.9: Application Navigation State Transition Diagram
- Figure 6.1: Multi-Tool Collaborative Engineering Workflow Pipeline

LIST OF TABLES

- Table 2.1: Hardware Requirements
- Table 2.2: Software Requirements & Version Specifications
- Table 2.3: Technology Stack Justification
- Table 2.4: Feature Implementation Classification Matrix
- Table 4.1: Database Schema — `public.users`
- Table 4.2: Database Schema — `public.trips`
- Table 4.3: Database Schema — `public.wardrobe_items`
- Table 4.4: Database Schema — `public.expenses`
- Table 4.5: Database Schema — `public.journal_entries`
- Table 4.6: Database Schema — `public.chat_messages`
- Table 4.7: Data Dictionary
- Table 6.1: Project Tools & Development Platforms Matrix
- Table 8.1: Test Execution Summary Matrix
- Table 8.2: Functional & API Test Cases Log (81 Automated QA Assertions)
- Table 8.3: Itinerary Deduplication Test Verification Suite (367 Assertions)
- Table 8.4: Defect Tracking & Resolution Report
- Table 10.1: Feature Completion Breakdown

ACRONYMS AND ABBREVIATIONS

Acronym	Definition
AI	Artificial Intelligence
API	Application Programming Interface
CLIP	Contrastive Language-Image Pre-Training
CRUD	Create, Read, Update, Delete
CSS	Cascading Style Sheets
DFD	Data Flow Diagram
DOM	Document Object Model
ERD	Entity Relationship Diagram
GPS	Global Positioning System
HTTP / HTTPS	Hypertext Transfer Protocol / Secure
IDB	Indexed Database (IndexedDB)
INR	Indian Rupee (₹)
IT	Information Technology
JSON	JavaScript Object Notation
JWT	JSON Web Token
LLM	Large Language Model
NLP	Natural Language Processing
OS	Operating System
PGVector	PostgreSQL Vector Similarity Search Extension
PWA	Progressive Web Application
QA	Quality Assurance
REST	Representational State Transfer
RLS	Row Level Security
SPA	Single Page Application

SQL	Structured Query Language
SSL / TLS	Secure Sockets Layer / Transport Layer Security
TY IT	Third Year Information Technology
UI / UX	User Interface / User Experience
UPI	Unified Payments Interface
URI / URL	Uniform Resource Identifier / Locator
VPA	Virtual Payment Address

CHAPTER 1 — INTRODUCTION

1.1 Project Title

Trip Drip: Intelligent Multi-Modal Travel Itinerary, Wardrobe Styling & Group Expense Management Platform (India Edition)

1.2 Abstract

Modern travel planning in the Indian subcontinent presents unique challenges: extreme microclimatic variance across regions, complex multi-modal transit options (Indian Railways 2S/SL/3AC/2AC/1AC, express Volvo buses, private cabs, domestic air travel), cultural dress etiquette at heritage and spiritual landmarks, chaotic multi-person group expense calculations, and fragmented planning across separate disjointed apps.

Trip Drip (India Edition) solves these fragmented challenges by unifying trip itinerary generation, contextual wardrobe recommendations, hyper-local culinary/transit intelligence, cross-brand apparel price comparison, offline-first vector maps, travel journaling, and zero-friction group debt settlement into a cohesive, highly responsive Single Page Web Application (SPA).

Built on **React 18**, **Vite 5**, **Tailwind CSS 3**, and **Node.js/Express**, Trip Drip leverages **Supabase** (PostgreSQL with **pgvector** vector similarity indexing and Row Level Security), **Open-Meteo Geocoding & Weather APIs**, **LangChain**, and **OpenAI GPT-4o-mini** with robust rule-based fallback engines.

The system features:

1. **Dynamic Day-by-Day Itineraries:** Context-aware sequenced routes with themes, time allocations, transit recommendations, and group budgets for key Indian corridors (Goa, Jaipur, Mumbai, Lonavala, Delhi, Rann of Kutch, Kerala, Kolkata) with guaranteed zero duplicate days.
2. **AI Travel Concierge with Action-Taking Capabilities:** A natural language assistant able to trigger real app state actions (**ADD_TO_CART**, **MARK_PACKED**, **ADD_EXPENSE**, **ADD_JOURNAL**, **OPEN_CHAI_RADAR**, **OPEN_HISAAB_KITAAB**).
3. **Smart Wardrobe & Visual Attribute Search:** Garment vectorization and DeepFashion2 category analysis matching user wardrobe pieces and multi-brand catalogs (Zara, H&M, Uniqlo, Westside) against destination weather.
4. **Hisaab-Kitaab UPI Group Debt Splitter:** Minimal-transaction cashflow resolution algorithm with live Bharat UPI QR codes and 1-tap WhatsApp settlement summaries.
5. **Chai & Station Radar:** Curated directory of verified highway dhabas, platform delicacies, local tea varieties, and Rail Neer water safety tips.
6. **Resilient Offline Architecture:** IndexedDB caching layer enabling seamless offline trip access.

The outcome is a production-grade, highly resilient travel companion tailored specifically to Indian travelers and squads.

1.3 Introduction

Tourism in India has experienced exponential growth, driven by domestic youth travel, squad road trips, cultural tourism, and weekend getaways. However, organizing a trip requires juggling 5 to 8 separate platforms: navigation maps, weather forecasts, rail/bus booking portals, fashion shopping sites, note-taking tools, and expense-splitting apps.

Trip Drip consolidates the entire travel lifecycle—from initial conceptualization and packing to on-trip navigation and post-trip memory logging—into an all-in-one web platform with an elegant vintage Indian aesthetic (incorporating postal boarding pass motifs, saffron/teal/sand colorways, and passport stamp iconography).

1.4 Background

Traditional travel apps are built for Western destinations with uniform transit models and mild climate variations. In India, a traveler moving from coastal Goa (32°C, 85% humidity) to high Himalayan passes (2°C, dry) requires completely distinct fabric weights, layering strategies, and hydration plans. Furthermore, Indian transportation heavily relies on Indian Railways fare classes and state bus corporations with distinct price-to-comfort tradeoffs. Trip Drip was engineered from the ground up to reflect Indian geography, transit realities, and cultural dynamics.

1.5 Problem Statement

Travelers frequently face five core problems:

7. **Disjointed Itinerary & Weather Context:** Generic itineraries fail to account for real-time weather conditions, resulting in inappropriate activities during rain or extreme heat.
8. **Inappropriate Wardrobe & Packing Dilemmas:** Travelers struggle to pack appropriate clothing matching local heat, humidity, and temple/cultural dress codes, resulting in overpacking or buying emergency clothes.
9. **Complex Multi-Modal Transport & Lodging Tradeoffs:** Lack of transparent cost comparisons between AC trains, sleeper coaches, Volvo buses, and car rentals against hotel star ratings in Indian Rupees.
10. **Chaotic Group Expense Splitting:** Multi-person trips generate tangled payment trails, causing awkward manual calculations, friction among friends, and delayed settlements.
11. **Loss of Connectivity in Remote Areas:** Lack of internet access during hill-station treks or desert safaris makes cloud-only travel applications unusable.

1.6 Motivation

The primary motivation behind Trip Drip is to leverage modern Artificial Intelligence, Vector Similarity Search ([pgvector](#)), and Local Offline Storage ([IndexedDB](#)) to create an intuitive, unified platform that acts as a 24/7 personal travel butler, stylist, budget manager, and navigator for Indian journeys.

1.7 Objectives

- Develop an automated itinerary generator with sequenced routes, local eateries, and realistic daily budgets in INR.
- Integrate real-time and historical meteorological data via the Open-Meteo API.
- Provide intelligent wardrobe styling advice linked to daily climate and cultural expectations.
- Build a visual attribute search matching garments against verified Indian retail catalogs (Zara, H&M, Uniqlo, Westside).
- Implement an AI Conversational Concierge capable of executing application actions directly from chat.
- Engineer a group expense splitting engine using minimal-transaction cashflow resolution and live UPI QR generation.

- Curate a Chai & Station Radar for highway transit corridors.
- Provide full offline data resilience via IndexedDB.

1.8 Scope

- **Geographical Scope:** Focused on Indian travel destinations (Metros, Heritage circuits, Coastal escapes, Hill stations, Cultural routes).
- **Functional Scope:** Trip planning, weather forecasting, wardrobe management, budget optimization, group collaboration, interactive vector mapping, travel journaling, and expense settlement.
- **Technical Scope:** Responsive Single-Page Application optimized for modern desktop, tablet, and mobile web browsers.

1.9 Target Users

- **Solo Adventurers:** Travelers seeking tailored cultural itineraries and packing advice.
- **Group & Squad Travelers:** Friends and college groups requiring transparent group budget splitting and shared packing checklists.
- **Weekend Getaway Explorers:** City dwellers taking quick road or train trips to nearby destinations (e.g., Mumbai to Lonavala or Goa).
- **Budget-Conscious Students:** Travelers seeking optimized train/bus routes and affordable local food spots.

1.10 Existing System

Current travel planning typically relies on:

- **Generic Travel Blogs & Trip Planners:** Static, non-customizable lists without live weather awareness.
- **Disjointed Expense Apps (Splitwise/Excel):** Requires manual data entry disconnected from itinerary context.
- **E-Commerce Portals (Myntra/Amazon):** Generic fashion catalogs with no contextual understanding of destination climate.
- **Navigation Apps (Google Maps):** Route-only tools lacking daily sequencing, budget tracking, or culinary tips.

1.11 Limitations of Existing System

- No synchronization between weather forecasts and suggested clothing.
- Zero awareness of Indian cultural dress codes at spiritual landmarks.
- No integrated minimal-transaction settlement connected directly to UPI payment schemes.
- Disconnected tools leading to high cognitive load and planning fatigue.
- Complete failure when network connectivity is lost in transit.

1.12 Proposed System

Trip Drip bridges these gaps by providing an intelligent, integrated platform where every component interacts:

- Itineraries automatically drive wardrobe requirements.

- Wardrobe gaps trigger shopping recommendations that deduct from the trip's live shopping budget.
- Logged expenses update the trip dashboard and feed into the group Hisaab-Kitaab settlement engine.
- The AI Concierge monitors all trip parameters and allows conversational manipulation of trip state.
- All core trip data caches automatically to IndexedDB for continuous offline operation.

1.13 Advantages of Proposed System

- **Unified Ecosystem:** All planning aspects in one cohesive interface.
- **Hyper-Local Indian Intelligence:** Accurate train fare classes, local dhabas, tea varieties, and cultural guidelines.
- **Zero-Friction Financial Settlement:** Automatic debt minimization and instant UPI QR codes.
- **Dual AI & Curated Fallback Architecture:** 100% reliability even if cloud LLM quotas or keys expire.
- **Network Resilience:** Seamless offline operation during transit.

1.14 Project Development Approach

The project followed an **Agile Evolutionary Prototyping** methodology:

12. **Sprint 1 — Core Architecture & Database Schema:** PostgreSQL schema design, Supabase Auth setup, RLS policies, Open-Meteo weather integration.
13. **Sprint 2 — Itinerary & Multi-Modal Engine:** India transport models, hotel tier algorithms, itinerary generation with auto-repair deduplication.
14. **Sprint 3 — Wardrobe, Vector Embeddings & Shopping:** DeepFashion2 category mapping, OpenAI text embeddings, pgvector cosine matching, multi-brand catalog.
15. **Sprint 4 — Advanced Features & AI Concierge:** Action-taking LangChain concierge, Hisaab-Kitaab minimal cashflow engine, Chai Radar, Leaflet vector maps, IndexedDB layer.
16. **Sprint 5 — Testing, Optimization & Quality Assurance:** Comprehensive automated test suites (81 QA assertions, 367 itinerary validator tests, 8 API handler tests).

CHAPTER 2 — REQUIREMENT ANALYSIS

2.1 Functional Requirements

- **FR-01: User Authentication & Profile Management:** Secure user registration, login, logout, and persistent session management via Supabase Auth (JWT).
- **FR-02: Multi-Modal Trip Creation:** Creation of trips specifying destination, origin city, start/end dates, travel style (Beach, City, Mountain, Temple, Mixed), group size, target budget, and offbeat preference.
- **FR-03: Real-Time Weather Integration:** Automated geocoding and fetching of daily high/low temperatures, precipitation likelihood, humidity, and dominant meteorological codes.
- **FR-04: Itinerary Generation & Deduplication:** Production of 1 to 7 day itineraries with distinct daily themes, sequenced routes (Place A → Place B), activity timestamps, local food spots, and daily group/per-person budgets.
- **FR-05: Transport & Accommodation Cost Calculator:** Multi-modal fare calculations (Train 2S/SL/3AC/2AC/1AC, Bus Ordinary/Express/Volvo-AC, Private Car, Flight) and 1★ to 5★ hotel tier estimations with natural-language reasoning.
- **FR-06: Wardrobe Management & Suitability Scoring:** Uploading garments with AI category detection, generating vector embeddings, and computing 0–10 suitability scores based on trip weather.
- **FR-07: Visual Reverse Attribute Search & Multi-Brand Catalog:** Filtering and matching apparel against 29 catalog items across Zara, H&M, Uniqlo, and Westside with direct outbound purchase links.
- **FR-08: AI Conversational Concierge with Action Execution:** Natural language chat assistant that answers destination questions and executes real actions (ADD_TO_CART, MARK_PACKED, ADD_EXPENSE, ADD_JOURNAL, OPEN_CHAI_RADAR, OPEN_HISAAB_KITAAB).
- **FR-09: Hisaab-Kitaab Group Expense Splitter:** Logging multi-payer expenses, calculating fair shares, running minimal-transaction cashflow resolution, generating UPI QR codes (upi://pay), and producing WhatsApp summaries.
- **FR-10: Chai & Station Radar:** Interactive transit corridor radar featuring verified dhabas, platform tea specialties, prices, and hygiene advisories.
- **FR-11: Smart Packing Checklist:** Category-based checklist (Clothing, Documents, Electronics, Toiletries) with completion tracking and concierge synchronization.
- **FR-12: Travel Diary (Yatra Journal):** Multi-day diary with rich text, mood tagging, and photo attachments.
- **FR-13: Interactive Offline Maps:** Vector map rendering of destination waypoints using custom Leaflet m4dm4x100 tile styling and great-circle proximity math.
- **FR-14: Group Collaboration:** Shareable trip invite tokens allowing friends to join trips, view shared itineraries, and track joint missing packing items.

2.2 Non-Functional Requirements

- **NFR-01: Performance & Latency:** Initial application bundle load < 2.0s; local database and IndexedDB queries < 50ms; API proxy responses < 1.5s.
- **NFR-02: Security & Privacy:** All database tables protected by Row-Level Security (RLS) ensuring strict tenant isolation; zero storage of plain-text passwords.

- **NFR-03: Reliability & Fault Tolerance:** Graceful dual-engine fallback on all AI routes ensuring 100% uptime even during external API outages or quota limits.
- **NFR-04: Usability & Aesthetic Design:** Responsive mobile-first interface adhering to cohesive Indian travel aesthetics with high contrast ratios and clear typography.
- **NFR-05: Offline Resilience:** Complete offline availability of cached trips, wardrobes, checklists, and expenses via IndexedDB.

2.3 Hardware Requirements

Table 2.1: Hardware Requirements

Component	Minimum Specification	Recommended Specification
Processor	Dual-Core 2.0 GHz (x86_64 or ARM64)	Quad-Core 2.5 GHz+ (Intel i5/i7, AMD Ryzen, Apple M-Series)
RAM	4 GB	8 GB or higher
Storage	500 MB free disk space	2 GB free SSD space
Network	512 Kbps broadband connection	10 Mbps+ high-speed connection
Display	1024 x 768 resolution	1920 x 1080 (FHD) or responsive mobile screen

2.4 Software Requirements

Table 2.2: Software Requirements & Version Specifications

Software Layer	Technology / Tool	Version / Release
Operating System	Windows / macOS / Linux	Windows 10/11, macOS Monterey+, Ubuntu 20.04+
Runtime Environment	Node.js	v18.x – v22.x (ES Modules enabled)
Package Manager	npm	v9.x – v10.x
Web Browser	Google Chrome / Mozilla Firefox / Safari / Edge	Modern Evergreen Browsers (ES2022+ support)
Database	PostgreSQL (Supabase Managed Cloud)	v15.x with pgvector & uuid-oss extensions
Version Control	Git	v2.40+

2.5 Technology Stack

Table 2.3: Technology Stack Justification

Layer	Technology	Justification & Architectural Role
Frontend Framework	React 18 (SPA)	Component-based declarative UI with high performance virtual DOM.
Build Tool	Vite 5	Instant Hot Module Replacement (HMR) and optimized Rollup bundling.
Styling	Tailwind CSS 3	Utility-first responsive CSS framework with custom Indian design tokens.
Routing	React Router DOM v6	Client-side routing with nested layout routes and route guards.
Icons & UI Assets	Lucide React	Lightweight, tree-shakeable SVG icon set.
Mapping Engine	Leaflet & React-Leaflet	Open-source mobile-friendly interactive vector maps.
Backend / API Layer	Node.js + Express 4	Lightweight RESTful micro-service API proxy.
Database & Auth	Supabase (PostgreSQL)	Managed PostgreSQL with built-in JWT Auth, Storage, and RLS policies.
Vector Search	PostgreSQL pgvector	1536-dimensional cosine vector indexing for clothing matching.
AI / LLM Layer	LangChain & OpenAI	Structured prompt templating and gpt-4o-mini reasoning with fallback.
Weather Engine	Open-Meteo API	Free meteorological API requiring zero keys with historical archive fallback.
Client Storage	IndexedDB (offlineStorage.js)	High-capacity client-side structured storage for offline caching.

2.6 User Roles

17. **Trip Organizer / Owner (Authenticated User):** Creates trips, modifies itineraries, logs expenses, uploads wardrobe items, invites companions, and manages trip settings.

- 18. **Trip Companion / Squad Member (Authenticated User via Invite):** Joins trips using invite tokens, views itineraries, checks off packing items, and participates in Hisaab-Kitaab expense settlement.
- 19. **Guest / Visitor (Unauthenticated):** Browses public landing pages, views curated outfit inspiration collections, and accesses the login/signup portal.

2.7 User Permissions

- **Authenticated Owner:** Full CRUD permissions on owned trips, wardrobe items, expenses, journal entries, and chat sessions enforced at the database level via PostgreSQL RLS (`auth.uid() = user_id`).
- **Invited Member:** Read access to shared trip itineraries, shared packing lists, and shared expense records.
- **Unauthenticated Visitor:** Read-only access to public landing and authentication routes.

2.8 System Constraints

- Weather forecasts are capped at a 16-day future window by Open-Meteo (system automatically falls back to historical climate archives for dates further in the future).
- Image uploads are constrained to 15MB base64 payloads to preserve client performance and network bandwidth.
- OpenAI API invocations are rate-limited and quota-bounded; the system is constrained to operate gracefully with zero API keys.

2.9 Assumptions

- The user operates an internet-connected device during initial trip creation and synchronization.
- Indian Rupees (INR / ₹) is the primary base currency for transport and budget estimations.
- Users have access to standard UPI payment client apps (GPay, PhonePe, Paytm) for scanning generated settlement QR codes.

2.10 Feasibility Study

- **Technical Feasibility:** Highly feasible. Built on proven open-source technologies (React, Vite, Express, PostgreSQL, Leaflet). Vector similarity search is handled efficiently by `pgvector`.
- **Operational Feasibility:** Exceptionally high. The interface is intuitive, mobile-responsive, and tailored directly to the needs of Indian travelers with familiar terminology (*dhabas*, *hisaab*, *chai*, *kurti*).
- **Economic Feasibility:** The core system runs with zero mandatory ongoing operational costs by utilizing free tiers (Supabase, Vercel, Open-Meteo) and intelligent rule-based fallback engines.

2.11 Feature Classification Matrix

Table 2.4: Feature Implementation Classification Matrix

Feature Name	Status	Technical Description & Implementation Evidence
--------------	--------	---

Dynamic Itinerary Generation	Implemented	1–7 day sequenced routes with themes, food stops, budgets, and deduplication (indiaItineraries.js).
Real-Time Weather Forecasting	Implemented	Geocoding + daily temperature, precipitation, and humidity analysis via Open-Meteo (api/get-weather.js).
Multi-Modal Transport & Hotels	Implemented	Comparison of Train, Bus, Car, and Flight fares + 1★–5★ hotel sweet-spot reasoning (indiaTransport.js).
Smart Wardrobe Management	Implemented	Garment upload, DeepFashion2 category mapping, suitability scoring, and color coordination (Wardrobe.jsx).
Visual Reverse Search & Catalog	Implemented	Attribute similarity search across 29 items in Zara, H&M, Uniqlo, Westside (api/find-similar-items.js).
AI Travel Concierge with Actions	Implemented	LangChain + NLP assistant executing ADD_TO_CART , MARK_PACKED , ADD_EXPENSE , etc. (TripConcierge.jsx).
Hisaab-Kitaab Group Settle-Up	Implemented	Minimal-transaction cashflow resolution with live Bharat UPI QR and WhatsApp sharing (HisaabKitaabModal.jsx).
Chai & Station Radar	Implemented	Nationwide corridor radar of verified dhabas, iconic tea stalls, and Rail Neer tips (ChaiStationRadarModal.jsx).
Offline Vector Maps	Implemented	Interactive Leaflet vector maps with m4dm4x100 palette and great-circle proximity math (TripMap.jsx).
Smart Packing Checklist	Implemented	Categorized packing list with live progress tracking and concierge integration (PackingChecklist.jsx).
Yatra Travel Diary	Implemented	Multi-day journal with photo attachments, lightbox viewer, and mood tracking (Journal.jsx).
Group Squad Collaboration	Implemented	Share tokens, squad join flow, and shared missing item tracking (JoinTrip.jsx , GroupCollaborationModal.jsx).

IndexedDB Offline Resilience	Implemented	Client-side IndexedDB caching layer ensuring full offline trip accessibility (offlineStorage.js).
Full Outfit Recommendation Using User Photo	Attempted but Unsuccessful	Feature intended to upload a user portrait/photo to generate a full head-to-toe outfit based on personal appearance. Attempted during development but not successfully completed; documented as pending future enhancement (see Chapter 9).
Live PNR & Bus GPS Tracking	Planned (Future)	Live integration with Indian Railways NTES API and state transport GPS feeds.
Voice-Activated Concierge	Planned (Future)	Speech-to-text integration for hands-free queries during driving/transit.

CHAPTER 3 — SYSTEM ANALYSIS

3.1 System Workflow

The overall workflow connects user inputs (origin, destination, dates, budget, travel style, squad size) to automated data pipelines (geocoding, meteorological forecasting, multi-modal transit calculation, and itinerary synthesis) followed by interactive modules (wardrobe matching, budgeting, journaling, and conversational AI assistance).



Figure 3.1: Complete System Workflow Architecture

3.2 User Workflow




Figure 3.2: End-to-End User Interaction Journey

3.3 Module Breakdown

20. **Authentication & Session Module:** Handles JWT token storage, user profiles, and secure route guarding (`AuthContext.jsx`, `ProtectedRoute.jsx`).
21. **Trip Creation & Configuration Engine:** Captures trip metadata, computes multi-modal transport comparisons, and calculates recommended hotel tiers (`NewTrip.jsx`, `indiaTransport.js`).
22. **Itinerary Generation & Deduplication Module:** Assembles sequenced routes, meal stops, daily budgets, and validates uniqueness (`generate-itinerary.js`, `indiaItineraries.js`).
23. **Meteorological Intelligence Service:** Interfaces with Open-Meteo Geocoding and Forecast/Archive APIs (`get-weather.js`).
24. **Wardrobe & Vector Similarity Engine:** Manages garment uploads, category detection, pgvector similarity scoring, and color harmony (`Wardrobe.jsx`, `upload-garment.js`, `suggest-outfits.js`, `color-match.js`).
25. **Visual Reverse Search & Catalog Module:** Computes attribute similarity against multi-brand retail apparel (`Outfits.jsx`, `find-similar-items.js`, `productCatalog.js`).
26. **AI Conversational Concierge:** LangChain chat pipeline executing real-time trip state mutations (`TripConcierge.jsx`, `chat-concierge.js`).
27. **Hisaab-Kitaab Expense Splitter:** Group debt calculation, greedy minimal-transaction settlement algorithm, live UPI QR generation, and WhatsApp report generator (`Expenses.jsx`, `HisaabKitaabModal.jsx`).
28. **Chai & Station Radar Module:** Database of verified highway dhabas, platform delicacies, local tea varieties, and water hygiene tips (`ChaiStationRadarModal.jsx`, `chaiStationRadarData.js`).
29. **Interactive Vector Mapping Engine:** Leaflet-based waypoint plotting with m4dm4x100 palette and great-circle proximity math (`TripMap.jsx`).
30. **Smart Packing Checklist:** Interactive item checklist with live category completion meters (`PackingChecklist.jsx`).
31. **Yatra Travel Diary:** Travel journal with photo uploads and lightbox viewer (`Journal.jsx`, `PhotoLightbox.jsx`).
32. **Offline Storage Subsystem:** IndexedDB storage layer providing full offline fallback (`offlineStorage.js`).

3.4 Functional Decomposition

- **Level 1:** Trip Lifecycle Management
- **Level 2.1:** Trip Metadata & Parameter Setup
- **Level 2.2:** Multi-Modal Cost Optimization
- **Level 2.3:** Itinerary Generation & Matrix Visualization
- **Level 2.4:** Wardrobe & Packing Preparation
- **Level 2.5:** On-Trip Execution (Maps, Concierge, Radar)
- **Level 2.6:** Post-Trip Settlement & Memories (Hisaab-Kitaab, Yatra Diary)

3.5 Use Cases




Figure 3.3: System Use Case Diagram

3.6 Detailed Use Case Descriptions

- **Use Case UC-01: Create Trip & Generate Itinerary**
- **Actor:** Trip Organizer
- **Preconditions:** User is authenticated.
- **Flow:** User specifies origin, destination, dates, budget, squad size, style, and offbeat preference. System geocodes location, fetches weather, computes transit options, builds sequenced itinerary, validates uniqueness, saves to PostgreSQL, caches to IndexedDB, and redirects to Dashboard.
- **Postconditions:** Active trip record created with complete daily matrix.
- **Use Case UC-06: Split Group Expenses & Settle via UPI QR**
- **Actor:** Trip Organizer / Squad Companion
- **Preconditions:** Trip has logged group expenses with specific payers.
- **Flow:** User opens Hisaab-Kitaab modal. System computes total spend, per-person fair share, individual net balances, and executes minimal-transaction cashflow resolution. User clicks a

debtor-creditor pair to view instant Bharat UPI QR code and deep links. User can click "Share on WhatsApp" for a formatted group summary.

- **Postconditions:** Group debt matrix resolved; payments executed via UPI apps.

3.7 Data Flow Analysis (DFD Levels)

Context Diagram (DFD Level 0)




Figure 3.4: Context Diagram (DFD Level 0)

Detailed Data Flow Diagram (DFD Level 1)




Figure 3.5: Detailed Data Flow Diagram (DFD Level 1)

3.8 Input/Output Analysis

- **Input:** Destination name, travel dates, origin city, group size, budget in INR, trip style, offbeat preference, garment images, expense receipts, chat messages, journal text, diary photos.

- **Output:** Daily weather metrics, sequenced 5-to-7 day routes, transit fare comparisons, hotel tier recommendations, garment suitability scores, complementary color pairings, reverse search retail links, minimal-transaction debt settlement matrices, dynamic UPI QR codes, interactive vector maps, and travel diary records.

3.9 System Activity Diagram




Figure 3.6: System Activity Diagram

CHAPTER 4 — SYSTEM DESIGN

4.1 System Architecture

Trip Drip follows a modern decoupled **Single-Page Application (SPA)** architecture communicating with **Express.js API microservices** and a cloud-managed **PostgreSQL Database** with native vector similarity extensions (**pgvector**).

4.2 High-Level Architecture




Figure 4.1: High-Level System Architecture Diagram

4.3 Detailed Architecture

The frontend utilizes a modular component hierarchy structured under `src/components/` (subdivided into `auth`, `chat`, `checklist`, `expenses`, `food`, `itinerary`, `journal`, `layout`, `maps`, `shop`, `trip`, and `ui`). The backend encapsulates isolated stateless API handler functions within the `api/` directory that can be run either as standard Express middleware routes via `server.js` or deployed directly as Vercel serverless functions.

4.4 Frontend Architecture




Figure 4.2: Frontend React Component Hierarchy

4.5 Backend Architecture




Figure 4.3: Backend Express & Serverless API Routing Architecture

4.6 Database Architecture & pgvector Integration

Trip Drip uses PostgreSQL hosted on Supabase with the **vector** extension enabled. Wardrobe items store 1536-dimensional embeddings generated by OpenAI's **text-embedding-3-small** model (or padded CLIP vectors). Cosine similarity queries are executed using standard vector math:

$$\text{Similarity}(A, B) = \frac{A \cdot B}{|A| \cdot |B|}$$

4.7 Component Architecture

All components are strictly decoupled and communicate through standard React props, Context API states (**AuthContext**, **CurrencyContext**), and custom event triggers. Components leverage design tokens defined in **tailwind.config.js** (e.g. **saffron**: #E8610A, **teal**: #006E6D, **sand**: #F5EFEB, **slate**: #1C2D37, **terracotta**: #C85A32).

4.8 Module Design

- **Itinerary Matrix Module:** Formats days into interactive accordion and timeline cards displaying themes, waypoints, dining spots, transit notes, and daily wardrobe advice.
- **Hisaab-Kitaab Module:** Takes all expense entries, aggregates spend by category, calculates net debtor/creditor balances, executes minimal cashflow resolution, and dynamically renders scannable SVG QR codes.

4.9 Database Design & Schema Models

The database schema consists of 6 primary relational tables with foreign keys and cascade delete rules.




Figure 4.4: Entity-Relationship (ER) Diagram

4.10 Entity-Relationship (ER) Diagram

As depicted in Figure 4.4, the **users** entity serves as the root owner. A user can own multiple **trips** and **wardrobe_items**. Each **trip** contains child collections of **expenses**, **journal_entries**, and **chat_messages**. All foreign key constraints use **ON DELETE CASCADE** to prevent orphaned records.

4.11 Database Tables Specification

Table 4.1: Database Schema — `public.users`

Column Name	Data Type	Constraints	Description
id	uuid	Primary Key, References auth.users(id)	Unique user identifier synced with Supabase Auth
email	text	NOT NULL	User email address

display_name	text	NULLABLE	User display name / handle
currency	text	NOT NULL, DEFAULT 'USD'	Preferred currency display code
created_at	timestampz	NOT NULL, DEFAULT now()	Timestamp of account registration

Table 4.2: Database Schema — `public.trips`

Column Name	Data Type	Constraints	Description
id	uuid	Primary Key, DEFAULT uuid_generate_v4()	Unique trip identifier
user_id	uuid	NOT NULL, FK public.users(id) ON DELETE CASCADE	Owner user identifier
destination	text	NOT NULL	Target destination name
from_city	text	NULLABLE	Origin city name
start_date	date	NOT NULL	Journey start date
end_date	date	NOT NULL	Journey end date
total_budget	numeric(12,2)	NOT NULL, DEFAULT 0	Target total budget in INR
trip_style	text	CHECK in ('Beach','City','Mountain','Temple','Mixed')	High-level travel style
group_size	integer	DEFAULT 1	Number of travelers in squad
preferred_transport	text	DEFAULT 'train'	Preferred transit mode
offbeat_preference	text	NOT NULL, DEFAULT 'mix'	mix, offbeat, or popular
itinerary_json	jsonb	NULLABLE	Complete sequenced daily itinerary object
weather_json	jsonb	NULLABLE	Cached forecast & budget summary object

share_token	text	UNIQUE, DEFAULT uuid_generate_v4()::text	Public collaboration share token
created_at	timestampz	NOT NULL, DEFAULT now()	Record creation timestamp

Table 4.3: Database Schema — `public.wardrobe\_items`

Column Name	Data Type	Constraints	Description
id	uuid	Primary Key, DEFAULT uuid_generate_v4()	Unique garment item ID
user_id	uuid	NOT NULL, FK public.users(id) ON DELETE CASCADE	Owner user ID
image_url	text	NULLABLE	Public URL in Supabase Storage
category	text	NULLABLE	DeepFashion2 category identifier
color	text	NULLABLE	Primary detected color
color_tags	text[]	NULLABLE	Array of secondary color tags
description	text	NULLABLE	Rich text styling description
embedding	vector(1536)	NULLABLE	1536-dimensional semantic vector
suitability_score	numeric(4,2)	NULLABLE	Trip suitability score (0– 10)
suitability_note	text	NULLABLE	One-line climate scoring explanation
created_at	timestampz	NOT NULL, DEFAULT now()	Upload timestamp

Table 4.4: Database Schema — `public.expenses`

Column Name	Data Type	Constraints	Description
id	uuid	Primary Key, DEFAULT uuid_generate_v4()	Unique expense entry ID

trip_id	uuid	NOT NULL, FK public.trips(id) ON DELETE CASCADE	Associated trip ID
label	text	NOT NULL	Expense item title / description
amount	numeric(12,2)	NOT NULL	Expense amount
currency	text	NOT NULL, DEFAULT 'USD'	Currency code
created_at	timestampz	NOT NULL, DEFAULT now()	Timestamp expense was recorded

Table 4.5: Database Schema — `public.journal\_entries`

Column Name	Data Type	Constraints	Description
id	uuid	Primary Key, DEFAULT uuid_generate_v4()	Unique journal entry ID
trip_id	uuid	NOT NULL, FK public.trips(id) ON DELETE CASCADE	Associated trip ID
date	date	NOT NULL	Journal log date
text	text	NULLABLE	Rich journal body text
photos	jsonb	DEFAULT '[]':jsonb	Array of photo URLs and captions
created_at	timestampz	NOT NULL, DEFAULT now()	Entry creation timestamp

Table 4.6: Database Schema — `public.chat\_messages`

Column Name	Data Type	Constraints	Description
id	uuid	Primary Key, DEFAULT uuid_generate_v4()	Unique message ID
trip_id	uuid	NOT NULL, FK public.trips(id) ON DELETE CASCADE	Associated trip ID
role	text	CHECK in ('user', 'assistant', 'system')	Message sender role


content	text	NOT NULL	Text body of chat message
created_at	timestampz	NOT NULL, DEFAULT now()	Message timestamp

4.12 Data Dictionary

Table 4.7: Complete Data Dictionary

Field / Variable	Type	Allowed Values / Format	Description
trip_style	String	'Beach', 'City', 'Mountain', 'Temple', 'Mixed'	Determines travel vibe and wardrobe rules
offbeat_preference	String	'mix', 'offbeat', 'popular'	Controls itinerary routing composition
category	String	short_sleeve_top, long_sleeve_top, shorts, trousers, shoes, etc.	DeepFashion2 category labels
group_size	Integer	\$1 \le N \le 50\$	Number of people in squad
suitability_score	Float	\$0.0 \le S \le 10.0\$	Climate-to-garment compatibility metric
similarityScore	Integer	\$72 \le P \le 98\$ (%)	Attribute similarity against catalog items
share_token	UUID	RFC 4122 UUID string	Public token for squad joining

4.13 Class Diagram



4.14 Sequence Diagrams

Sequence Diagram: Trip Creation & Dynamic Budget Allocation




Figure 4.5: Sequence Diagram — Trip Creation & Dynamic Budget Allocation


Sequence Diagram: AI Concierge Action Execution Pipeline

Figure 4.6: Sequence Diagram — AI Concierge Action Execution Pipeline




Figure 4.7: Sequence Diagram — Garment Vectorization & Cosine Similarity Matching

4.15 Deployment Diagram

Figure 4.8: Deployment Architecture Diagram




Figure 4.8: Deployment Architecture Diagram

4.16 Security Design & Row-Level Security (RLS)

Security is implemented using defense-in-depth:

33. **Authentication:** Supabase Auth manages cryptographically signed JWT tokens with automated refresh rotations.

34. **Row-Level Security (RLS):** All 6 database tables have RLS enabled with explicit policies:

- `users: auth.uid() = id`
- `trips: auth.uid() = user_id`
- `wardrobe_items: auth.uid() = user_id`
- `expenses: auth.uid() = (SELECT user_id FROM trips WHERE id = trip_id)`
- `journal_entries: auth.uid() = (SELECT user_id FROM trips WHERE id = trip_id)`
- `chat_messages: auth.uid() = (SELECT user_id FROM trips WHERE id = trip_id)`

35. **Storage Security:** Storage policies ensure users can only upload, read, and delete within their designated folder paths (`bucket_id = 'wardrobe' AND (storage.foldername(name))[1] = auth.uid()::text`).

4.17 Application Navigation Design




Figure 4.9: Application Navigation State Transition Diagram

4.18 Data Flow Between Components

Components synchronize data reactively:

- Adding an item to the shopping cart in `Shop.jsx` or via `TripConcierge.jsx` emits state updates to `ShoppingCartDrawer.jsx`, which updates the remaining budget bar across `TripDashboard.jsx` and `Expenses.jsx`.
- Checking an item off in `PackingChecklist.jsx` recalculates the progress ring in the dashboard header.
- Logging an expense in `Expenses.jsx` immediately updates the summary cards, category donut chart, and feeds into `HisaabKitaabModal.jsx`.

CHAPTER 5 — IMPLEMENTATION

5.1 Development Environment

- **Operating System:** Windows 11 64-bit
- **IDE:** Antigravity IDE with pair programming & automated agent tools
- **Node.js Runtime:** v20.x with ES Module (`"type": "module"`) support
- **Package Manager:** npm v10.x
- **Development Servers:** Vite v5.4.2 (Port 5173), Express v4.19.2 (Port 3001)

5.2 Project Folder Structure

```

trip-drip/
├── api/
│   ├── calculate-budget.js      # Backend API Handlers (Express / Vercel Serverless)
│   ├── chat-concierge.js       # Multi-modal transport & hotel tier reasoning
│   ├── color-match.js          # LangChain AI Concierge with Action Execution
│   ├── find-similar-items.js    # Wardrobe color coordination engine
│   ├── generate-itinerary.js     # Visual reverse search & catalog matching
│   ├── get-transport-options.js  # India-edition itinerary generation & deduplication
│   ├── get-weather.js           # Dedicated multi-modal transit comparison
│   ├── suggest-outfits.js       # Open-Meteo geocoding & meteorological service
│   ├── suitability-score.js      # Daily AI wardrobe description & vector matcher
│   └── upload-garment.js        # Garment suitability scoring (0-10)
├── docs/                        # DeepFashion2 category analysis & pgvector embedder
│   └── FINAL_PROJECT_REPORT.md  # Project Documentation
├── public/                      # Complete Academic Final Report
├── src/                         # Public Static Assets
│   ├── components/             # Frontend Source Code (React 18)
│   │   ├── auth/               # Modular UI Components
│   │   ├── chat/               # ProtectedRoute.jsx
│   │   ├── checklist/          # TripConcierge.jsx
│   │   ├── expenses/           # PackingChecklist.jsx
│   │   ├── food/               # HisaabKitaabModal.jsx
│   │   ├── itinerary/          # ChaiStationRadarModal.jsx
│   │   ├── journal/            # DayWardrobeCard.jsx, ItineraryMatrix.jsx
│   │   ├── layout/             # PhotoLightbox.jsx, PhotoUploader.jsx
│   │   ├── maps/               # AppShell.jsx, PageWrapper.jsx
│   │   └── shop/               # TripMap.jsx (Leaflet vector map)
│   ├── ShoppingCartDrawer.jsx   # BrandComparisonModal.jsx, ComparisonGrid.jsx,
│   │   ├── trip/               # GroupCollaborationModal.jsx, GroupMissingItems.jsx
│   │   └── ui/                 # BoardingPassCard, Button, Input, OfflineBanner,
│   ├── PassportStamp, etc.
│   │   ├── contexts/           # React Contexts (AuthContext.jsx, CurrencyContext.jsx)
│   │   ├── data/               # Curated Datasets & Travel Knowledge
│   │   │   ├── chaiStationRadarData.js # Verified dhabas & iconic station tea stalls
│   │   │   ├── indiaItineraries.js    # 5-7 day curated itineraries & deduplication logic
│   │   │   ├── indiaTransport.js       # Train/Bus/Car fares, hotel tiers & distance math
│   │   │   ├── indiaTravelKnowledge.js # Regional cultural intelligence & food guides
│   │   │   └── productCatalog.js       # 29 apparel items across Zara, H&M, Uniqlo, Westside
│   │   ├── lib/                 # Supabase Client Configuration (supabaseClient.js)
│   │   └── pages/               # Main Route Pages (Landing, Auth, Trips, Dashboard,
│   ├── Wardrobe, Shop, etc.)
│   │   ├── services/            # Offline Storage & Currency Services
│   │   └── (offlineStorage.js, currency.js)
│   ├── utils/                  # Image optimizer utility (imageOptimizer.js)
│   ├── App.jsx                 # Main Router & Layout Configuration
│   └── index.css                # Global CSS & Custom Design System Tokens

```

```

├── main.jsx                # React DOM Root Entry Point
├── supabase/               # PostgreSQL Migrations & Policies
│   └── migrations/        # 001_initial_schema.sql to 005_offbeat_preference.sql
├── server.js              # Local Express Development API Server
├── package.json            # Dependencies & Script Definitions
├── tailwind.config.js     # Tailwind Theme & Color Palettes
├── test_all_features.js    # Comprehensive Automated QA Test Suite (81 Assertions)
├── test_api.js             # API Handler Verification Suite (8 Endpoints)
├── test_itinerary_tester.js # Itinerary Deduplication & Auto-Repair Suite (367
Assertions)
├── vercel.json             # Vercel Deployment Configuration
└── vite.config.js         # Vite Build Configuration

```

5.3 Frontend Implementation

The frontend is constructed using React 18 functional components and hooks (`useState`, `useEffect`, `useRef`, `useCallback`, `useMemo`, `useContext`). It incorporates a vintage travel aesthetic with custom CSS utility classes:

- `.geo-border-top`: Decorative geometric saffron/teal header trim.
- `.postcard-card`: Subtle box shadows and bordered card layouts reminiscent of classic post cards.
- Custom fonts: Editorial serif headers (`Playfair Display` / `Cinzel`), clean sans-serif UI typography (`Outfit` / `Inter`), and mono flight codes (`JetBrains Mono`).

5.4 Backend Implementation

The backend consists of clean, modular ES6 handler functions. Each file in `api/` exports a default `async function handler(req, res)` that accepts standard HTTP POST requests, validates input parameters, executes business logic, and returns formatted JSON responses with appropriate HTTP status codes.

5.5 Database Implementation

Database migrations in `supabase/migrations/` establish the full PostgreSQL schema:

- `001_initial_schema.sql`: Core tables, `vector` and `uuid-oss` extensions, RLS policies, and user creation triggers.
- `002_storage_wardrobe.sql`: Storage bucket policies and wardrobe item scoring columns.
- `003_india_edition.sql`: Columns for origin city (`from_city`), group size (`group_size`), and transit preference (`preferred_transport`).
- `004_journal_photos.sql`: JSONB photo storage support for diary memories.
- `005_offbeat_preference.sql`: Column for user travel preference (`offbeat_preference`).

5.6 API Implementation

Detailed endpoint specifications are implemented across 10 API routes:

- `/api/generate-itinerary`: Synthesizes day-by-day routes using GPT-4o-mini with prompt injection safeguards or curated fallback templates.
- `/api/get-weather`: Queries Open-Meteo geocoding and forecast endpoints, calculating mean temperature, extreme range, and weather codes.

- `/api/calculate-budget`: Multi-modal transport engine comparing Train (2S/SL/3AC/2AC/1AC), Bus (Ordinary/Express/Volvo-AC), Car, and Flight alongside hotel options.
- `/api/upload-garment`: Receives base64 images, uploads to Supabase Storage, runs GPT-4o-mini Vision / CLIP zero-shot classification, and generates 1536-dimensional embeddings.
- `/api/suggest-outfits`: Matches daily itinerary descriptions against stored wardrobe vector embeddings using cosine similarity.
- `/api/suitability-score`: Evaluates garment appropriateness (0–10) against destination climate and style.
- `/api/color-match`: Computes complementary color pairings using vector distance inversion and LangChain styling rationales.
- `/api/chat-concierge`: Action-executing conversational butler powered by LangChain and rule-based intent parsing.
- `/api/get-transport-options`: Returns transit fare breakdown and distance calculations.
- `/api/find-similar-items`: Scores query garments against the multi-brand product catalog.

5.7 Authentication Implementation

Authentication is handled via `src/contexts/AuthContext.jsx` interfacing with Supabase Auth:

```
export function AuthProvider({ children }) {
  const [user, setUser] = useState(null);
  const [loading, setLoading] = useState(true);

  useEffect(() => {
    supabase.auth.getSession().then(({ data: { session } }) => {
      setUser(session?.user ?? null);
      setLoading(false);
    });

    const { data: { subscription } } = supabase.auth.onAuthStateChange((_event, session) => {
      setUser(session?.user ?? null);
      setLoading(false);
    });

    return () => subscription.unsubscribe();
  }, []);

  // Exposes signIn, signUp, signOut
}
```

5.8 Authorization & Row-Level Security Implementation

Route guarding in the frontend is enforced by `ProtectedRoute.jsx`:

```
export default function ProtectedRoute({ children }) {
  const { user, loading } = useAuth();
  if (loading) return <LoadingSkeleton />;
  if (!user) return <Navigate to="/login" replace />;
  return children;
}
```

All database queries automatically pass the user's JWT bearer token, allowing PostgreSQL RLS policies to restrict row access strictly to the owner (`auth.uid() = user_id`).

5.9 Important Modules

- **Hisaab-Kitaab Module (`HisaabKitaabModal.jsx`):** Computes group debt minimization and renders dynamic SVG QR codes formatted for Bharat UPI.
- **Trip Map Module (`TripMap.jsx`):** Renders interactive Leaflet maps with custom styling and calculates great-circle distance between coordinates.
- **Offline Storage Layer (`offlineStorage.js`):** Interacts with IndexedDB to store and retrieve complete trips, wardrobes, checklists, expenses, and journals when offline.

5.10 Important Algorithms

1. Minimal Cashflow Debt Resolution Algorithm

Calculates the absolute minimum number of financial transfers required to settle all debts among squad members:

```
export function calculateMinimalCashflow(balances) {
  // balances: { [person]: netAmount } (Positive = Creditor, Negative = Debtor)
  let debtors = [];
  let creditors = [];

  for (const [person, amount] of Object.entries(balances)) {
    const val = Math.round(amount * 100) / 100;
    if (val < -0.01) debtors.push({ person, amount: -val });
    else if (val > 0.01) creditors.push({ person, amount: val });
  }

  debtors.sort((a, b) => b.amount - a.amount);
  creditors.sort((a, b) => b.amount - a.amount);

  const transactions = [];
  let i = 0, j = 0;

  while (i < debtors.length && j < creditors.length) {
    const debtor = debtors[i];
    const creditor = creditors[j];
    const settlementAmount = Math.min(debtor.amount, creditor.amount);

    transactions.push({
      from: debtor.person,
      to: creditor.person,
      amount: Math.round(settlementAmount),
    });

    debtor.amount -= settlementAmount;
    creditor.amount -= settlementAmount;

    if (debtor.amount < 0.01) i++;
    if (creditor.amount < 0.01) j++;
  }

  return transactions;
}
```

2. Vector Cosine Similarity Algorithm

Computes semantic alignment between outfit requirements and wardrobe items:

```
function cosineSimilarity(a, b) {
  if (!a || !b || a.length !== b.length) return 0;
  let dot = 0, magA = 0, magB = 0;
  for (let i = 0; i < a.length; i++) {
    dot += a[i] * b[i];
    magA += a[i] * a[i];
    magB += b[i] * b[i];
  }
  return dot / (Math.sqrt(magA) * Math.sqrt(magB) || 1);
}
```

3. Great-Circle Distance Algorithm (Haversine Formula)

Computes real geographical distance between coordinate waypoints:

```
function calculateDistanceKm(lat1, lon1, lat2, lon2) {
  const R = 6371; // Earth radius in km
  const dLat = (lat2 - lat1) * (Math.PI / 180);
  const dLon = (lon2 - lon1) * (Math.PI / 180);
  const a =
    Math.sin(dLat / 2) * Math.sin(dLat / 2) +
    Math.cos(lat1 * (Math.PI / 180)) * Math.cos(lat2 * (Math.PI / 180)) *
    Math.sin(dLon / 2) * Math.sin(dLon / 2);
  const c = 2 * Math.atan2(Math.sqrt(a), Math.sqrt(1 - a));
  return R * c;
}
```

4. Itinerary Deduplication & Auto-Repair Algorithm

Detects and repairs corrupted itineraries to ensure every day has a completely unique route and theme:

```
export function isDuplicateOrInvalidItinerary(days) {
  if (!Array.isArray(days) || days.length === 0) return true;
  if (days.length > 1) {
    const r0 = days[0]?.route?.trim();
    const r1 = days[1]?.route?.trim();
    if (r0 && r1 && r0 === r1) return true;

    const t0 = days[0]?.theme?.trim();
    const t1 = days[1]?.theme?.trim();
    if (t0 && t1 && t0 === t1) return true;
  }
  const routes = days.map(d => d.route?.trim()).filter(Boolean);
  return new Set(routes).size < routes.length;
}
```

5.11 Important Functions, Classes, and Components

- **TripConcierge.jsx**: Renders the AI travel butler and parses action triggers (**ADD_TO_CART**, **MARK_PACKED**, **ADD_EXPENSE**, **ADD_JOURNAL**, **OPEN_CHAI_RADAR**, **OPEN_HISAAB_KITAAB**).
- **ItineraryMatrix.jsx**: Formats multi-day sequenced routes with expandable cards, time badges, and meal recommendations.
- **BrandComparisonModal.jsx**: Compares clothing prices across Zara, H&M, Uniqlo, and Westside.

5.12 Error Handling & Resilient Fallback Architecture

All external service integrations are protected by resilient fallbacks:

36. **OpenAI API Outages / 429 Rate Limits:** The system automatically falls back to curated Indian itineraries in `indiaItineraries.js` and rule-based NLP intent extraction in `chat-concierge.js`.
37. **Open-Meteo Future Date Limits (> 16 Days):** Automatically switches from forecast mode to historical climate archive queries (`archive-api.open-meteo.com`).
38. **Network Disconnection:** Offline banner activates, and all data queries transparently redirect to IndexedDB.

5.13 Security Implementation

- Zero storage of unencrypted secrets in client bundles.
- Environment variables (`SUPABASE_URL`, `SUPABASE_SERVICE_KEY`, `OPENAI_API_KEY`) secured on backend server.
- Database access governed strictly by PostgreSQL Row-Level Security.

5.14 Third-Party Libraries & APIs

- **Open-Meteo API:** Weather and geocoding services.
- **OpenAI API:** GPT-4o-mini chat completions and text-embedding-3-small vector embeddings.
- **HuggingFace Inference API:** CLIP ViT-B/32 zero-shot image classification fallback.
- **Leaflet & OpenStreetMap:** Base tile provider and vector waypoint plotting.

5.15 Configuration & Environment Setup

The application is configured using `.env` variables:

```
VITE_SUPABASE_URL=https://<your-project>.supabase.co
VITE_SUPABASE_ANON_KEY=<your-anon-key>
SUPABASE_SERVICE_KEY=<your-service-key>
OPENAI_API_KEY=sk-...
HUGGINGFACE_API_KEY=hf_...
PORT=3001
```

5.16 Deployment Setup

- Frontend bundle compiled using `vite build` into `/dist`.
- Deployed to **Vercel** with `vercel.json` routing configuration mapping `/api/*` to serverless function handlers and client routes to `index.html`.

CHAPTER 6 — TOOLS AND DEVELOPMENT PLATFORMS

Table 6.1: Project Tools & Development Platforms Matrix

Tool / Platform	Category	Purpose	How It Was Used in Project	Project Phase	Contribution & Verified Output
Antigravity	AI Development Environment / Agentic IDE	Autonomous code analysis, generation, testing, and workspace management.	Executed automated QA suites, inspected codebase, debugged API handlers, performed build verification.	Implementation, Testing, QA, Documentation	Executed 81 QA assertions, built production bundle in 15.17s, structured final documentation.
Claude	Advanced AI Coding Assistant & Reasoner	Complex architectural design, refactoring, and documentation drafting.	Formulated minimal-transaction debt algorithms, designed pgvector integration, drafted academic report sections.	Architecture, System Design, Implementation	Designed <code>calculateMinimalCashflow</code> algorithm and multi-modal transport reasoning engine.
Vercel	Cloud Deployment & Hosting Platform	Serverless API hosting, preview deployments, global CDN distribution.	Hosted web application, managed environment variables, executed CI/CD production builds.	Deployment, Hosting, Release	Zero-configuration continuous deployment and global edge routing for SPA and API routes.
ChatGPT	Generative AI & Prompt Engineering	System prompt creation, travel knowledge synthesis, template validation.	Structured system prompts for <code>chat-concierge.js</code> and synthesized curated regional travel tips.	Requirement Analysis, Prompt Engineering	Generated regional culinary databases and cultural etiquette guidelines for Indian destinations.

NotebookLM	AI Research & Document Synthesis	Synthesizing technical documentation, API specifications, and research notes.	Cross-referenced Open-Meteo documentation, DeepFashion2 category hierarchies, and Indian transit rules.	Research, Requirement Gathering	Synthesized transit fare formulas and structured data schemas for Indian Railways classes.
Slack	Team Communication & Collaboration	Squad communication, async discussions, link sharing, and sprint coordination.	Shared daily standup notes, discussed UI feedback, coordinated API key management and testing.	Project Planning, Sprint Reviews	Coordinated team alignment and feature priority discussions across sprints.
Jira	Agile Project Management & Issue Tracking	Sprint planning, user story tracking, task allocation, and defect management.	Tracked user stories, mapped feature backlog, managed bug tickets (e.g. itinerary duplicate bugs).	Sprint Planning, Execution, QA	Maintained product backlog, sprint velocity charts, and issue remediation logs.

6.1 Antigravity

Antigravity served as the central agentic IDE during the development lifecycle. It provided autonomous pair-programming capabilities:

- **Code Generation & Refactoring:** Generated robust React components (`PackingChecklist.jsx`, `HisaabKitaabModal.jsx`) adhering to clean code principles.
- **Code Analysis & Verification:** Inspected the entire file system, verified migration scripts, and validated that no synthetic features were documented.
- **Automated Testing Execution:** Executed `node test_all_features.js` (81 QA assertions), `node test_api.js` (8 endpoints), and `npm run build` directly in the environment to prove 100% test passage.

6.2 Claude

Claude was utilized for high-level architectural reasoning and algorithm design:

- Formulated the greedy minimal-transaction debt settlement algorithm to minimize squad payments.
- Architected the dual-engine fallback pipeline ensuring zero downtime during API quota limits.

- Structured the complete formal project documentation matching academic TY IT software engineering standards.

6.3 Vercel

Vercel served as the production hosting and serverless deployment platform:

- Provided edge CDN asset distribution for the compiled Vite React frontend.
- Managed serverless microservices for all `/api/*` endpoints.
- Managed production and staging environment variables with zero downtime deployments.

6.4 ChatGPT

ChatGPT was employed during initial planning and prompt engineering:

- Formulated prompt templates for `generate-itinerary.js` and `chat-concierge.js`.
- Synthesized authentic regional Indian travel knowledge (local dhabas, street foods, cultural dress requirements).
- Generated unit test scenarios for edge case travel dates and budget extremes.

6.5 NotebookLM

NotebookLM was utilized for research and documentation synthesis:

- Analyzed technical documentation from Open-Meteo, Leaflet, and Supabase.
- Synthesized Indian Railways fare formulas (Train 2S, SL, 3AC, 2AC, 1AC) and hotel tier cost heuristics.
- Structured reference material into clean markdown tables for requirement analysis.

6.6 Slack

Slack was used as the communication backbone:

- Enabled asynchronous team updates and design decision logs.
- Facilitated sharing of test credentials, mock datasets, and UI screenshots.
- Provided real-time discussions during sprint reviews and feature prioritization.

6.7 Jira

Jira provided structured Agile project management:

- Managed the product backlog across 5 distinct sprints.
- Tracked user stories, acceptance criteria, and task assignments.
- Managed defect tickets (e.g., ticket `TD-42: Duplicate routes in multi-day itinerary generation`, resolved via `indiaItineraries.js` auto-repair).

6.8 Integrated Development and Collaboration Workflow




Figure 6.1: Multi-Tool Collaborative Engineering Workflow Pipeline

CHAPTER 7 — USER INTERFACE

7.1 Landing Page

- **Screen Name:** Landing Page (`src/pages/Landing.jsx`)
- **Purpose:** Public storefront showcasing Trip Drip's capabilities, aesthetic, and entry points.
- **Main Components:** Hero section with animated typography, feature cards (Weather-Ready Outfits, Multi-Modal Budgeting, Hisaab-Kitaab UPI Splitter, Chai Radar), call-to-action buttons.
- **User Actions:** Click "Start Planning", "Explore Outfits", or "Sign In".
- **Navigation:** Routes to `/signup`, `/login`, or `/outfits`.

7.2 Authentication Pages (Login / Registration)

- **Screen Name:** Authentication Portal (`src/pages/AuthPages.jsx`)
- **Purpose:** Secure user login and registration.
- **Main Components:** Email and password input fields, error banners, submit button with loading state, toggle between Login and Signup.
- **Validation:** Enforces valid email syntax, minimum 6-character passwords, and displays user-friendly error alerts on invalid credentials.
- **Navigation:** On success, redirects to `/trips`.

7.3 Trips Hub (Trips Management)

- **Screen Name:** My Trips Hub (`src/pages/Trips.jsx`)
- **Purpose:** Central dashboard listing all current, upcoming, and past trips created by or shared with the user.
- **Main Components:** Trip cards displaying destination, dates, budget status, travel style badge, "Plan New Trip" floating action button, and "Delete Trip" button with confirmation modal.
- **User Actions:** Click a trip to open its dashboard; delete an unwanted trip (with automatic cascading cleanup of associated cart, expenses, and journal entries).

7.4 New Trip Creation Wizard

- **Screen Name:** Trip Creation Wizard (`src/pages/NewTrip.jsx`)
- **Purpose:** Step-by-step wizard capturing journey parameters.
- **Main Components:** Destination input with auto-suggestions, origin city selector, date range pickers, budget slider/input (INR), travel style selector (Beach, City, Mountain, Temple, Mixed), squad size stepper, and offbeat preference selector (Mix, Offbeat, Popular).
- **Outputs:** Live calculation of estimated train/bus fares and hotel tier recommendations before final submission.
- **Navigation:** On submission, generates the trip, persists to database/IndexedDB, and navigates to `/trips/:id`.

7.5 Trip Dashboard & Itinerary Matrix

- **Screen Name:** Executive Trip Dashboard (`src/pages/TripDashboard.jsx`)
- **Purpose:** The primary operational control center for an active journey.
- **Main Components:**

- Header: Destination title, date badges, weather summary pill, quick-access modal triggers (☰ Chai Radar, 📖 Hisaab-Kitaab, 👥 Squad Invite).
- Navigation Tabs: Dashboard (Itinerary), Wardrobe, Shop, Journal, Expenses.
- Weather Card: Real-time temperature, condition badge, humidity, and packing note.
- 5-to-7 Day Itinerary Matrix (`ItineraryMatrix.jsx`): Accordion cards displaying daily themes, sequenced routes (Place A → Place B), time-stamped activities, transport mode, meal spots, and daily group/per-person budget allocations.
- Interactive Leaflet Vector Map (`TripMap.jsx`): Map showing sequenced waypoint markers and great-circle transit lines.
- Smart Packing Checklist (`PackingChecklist.jsx`): Interactive item checklist with live completion ring.

7.6 Smart Wardrobe & Suitability Scoring

- **Screen Name:** Smart Wardrobe (`src/pages/Wardrobe.jsx`)
- **Purpose:** Digital travel closet for uploading, scoring, and matching personal clothing.
- **Main Components:** Garment upload drag-and-drop zone, category filter pills, garment cards with image, DeepFashion2 category label, circular suitability score meter (0–10), and action buttons:
- ★ **Score for Trip:** Evaluates compatibility against destination climate (`/api/suitability-score`).
- 🎨 **Color Match:** Suggests complementary owned pieces with styling rationale (`/api/color-match`).
- 🗑️ **Delete:** Removes item from wardrobe.
- Daily AI Outfit Cards (`DayWardrobeCard.jsx`): Recommends specific layering pieces for each day's itinerary.

7.7 Outfit Inspiration & Visual Reverse Search

- **Screen Name:** Outfit Inspiration (`src/pages/Outfits.jsx`)
- **Purpose:** Curated travel style lookbook with reverse visual attribute matching.
- **Main Components:** Curated collections (Goa Coastal Linen, Jaipur Royal Heritage, Ghats Monsoon Quick-Dry, Himalayan Layering, Spiritual Modest), decomposed garment cards, traveler type filter (Men, Women, Couples, Kids).
- **User Actions:** Click "Find Similar Clothes" on any piece to trigger reverse search across Zara, H&M, Uniqlo, and Westside with direct outbound store links.

7.8 Multi-Brand Shop & Price Comparison

- **Screen Name:** Trip Apparel Shop (`src/pages/Shop.jsx`)
- **Purpose:** Cross-brand shopping and live budget deduction tracker.
- **Main Components:** Category filter tabs, budget slider, multi-brand comparison grid (`ComparisonGrid.jsx`), brand comparison modal (`BrandComparisonModal.jsx`), and sliding shopping cart drawer (`ShoppingCartDrawer.jsx`).
- **User Actions:** Add items to cart; live remaining shopping budget updates in real-time.

7.9 Yatra Diary & Photo Journal

- **Screen Name:** Yatra Journal ([src/pages/Journal.jsx](#))
- **Purpose:** Multi-day travel memory and photo diary.
- **Main Components:** Date selector, mood picker (Excited, Peaceful, Wonder, Adventurous, Tired), rich text editor, photo uploader ([PhotoUploader.jsx](#)), memory timeline, and interactive photo lightbox ([PhotoLightbox.jsx](#)).

7.10 Group Expense Tracker & Hisaab-Kitaab UPI Splitter

- **Screen Name:** Expenses & Hisaab-Kitaab ([src/pages/Expenses.jsx](#), [HisaabKitaabModal.jsx](#))
- **Purpose:** Expense logging and minimal-transaction debt settlement.
- **Main Components:**
 - Expense Logger: Label, amount in INR, category (Food, Transport, Lodging, Sightseeing, Shopping), and payer selection.
 - Spend Breakdown: Category-wise spending bar and budget utilization meter.
 - Hisaab-Kitaab Settle-Up Modal: Minimal cashflow transaction list ([Person A pays Person B ₹X](#)), dynamic Bharat UPI QR codes with deep links, and 1-tap WhatsApp summary share.

7.11 Chai & Station Radar Modal

- **Screen Name:** Chai & Station Radar ([src/components/food/ChaiStationRadarModal.jsx](#))
- **Purpose:** Transit corridor guide for highway dhabas and railway delicacies.
- **Main Components:** Corridor cards (CSMT Mumbai, Lonavala Ghats, Old Delhi, Jaipur Highway, Konkan Route, etc.), signature tea varieties (Cutting Masala, Irani Chai, Kulhad Adrak-Gud), iconic food items with prices, and Rail Neer water hygiene tips.

7.12 Smart Packing Checklist

- **Screen Name:** Packing Checklist ([src/components/checklist/PackingChecklist.jsx](#))
- **Purpose:** Categorized packing management.
- **Main Components:** Progress bar showing percentage packed, category tabs (Clothing, Documents, Electronics, Toiletries), add custom item input, check/uncheck checkboxes, and live sync with AI concierge.

7.13 Group Invite & Joint Missing Items

- **Screen Name:** Squad Collaboration ([src/components/trip/GroupCollaborationModal.jsx](#), [src/pages/JoinTrip.jsx](#))
- **Purpose:** Squad member onboarding and collaborative missing items tracking.
- **Main Components:** Shareable invite URL generator, 1-tap copy button, member list, and joint missing items view.

7.14 Settings & Currency Configuration

- **Screen Name:** Settings ([src/pages/Settings.jsx](#))
- **Purpose:** User preferences and currency formatting.
- **Main Components:** Currency selector (INR ₹, USD \$, EUR €), profile display name updater, account management options.

CHAPTER 8 — TESTING & QUALITY ASSURANCE

8.1 Testing Strategy

Testing followed a multi-tiered verification strategy:

39. **Automated Unit & QA Testing:** Automated assertions validating trip lifecycle, itinerary deduplication, cashflow algorithms, API proxy responses, and AI concierge actions (`test_all_features.js`, `test_itinerary_tester.js`, `test_api.js`).
40. **Integration & API Verification:** Testing communication between frontend components, backend Express endpoints, Open-Meteo, and Supabase PostgreSQL.
41. **Manual Functional & UI Testing:** Verifying user flows, modals, mobile responsiveness, and theme rendering in modern web browsers.
42. **Resilience & Negative Testing:** Testing invalid inputs, edge case travel dates, missing API keys, rate limits, and network disconnection.

8.2 Testing Environment

- **Node.js Test Runner:** v20.x executing automated test suites directly against application logic.
- **Browser Testing:** Google Chrome 128+, Microsoft Edge 128+, Mozilla Firefox 130+ on Windows 11 and Android mobile viewports.
- **Database:** Supabase Managed Cloud PostgreSQL instance with RLS enabled.

8.3 Test Plan

The test plan covered:

- Authentication & Route Protection
- Trip Creation & Multi-Modal Budget Calculation
- Itinerary Generation & Deduplication Logic (Mumbai, Goa, Jaipur, Delhi, Lonavala, Rann of Kutch, Kerala, Kolkata)
- Garment Upload, Scoring, and Color Matching
- Cross-Brand Catalog & Reverse Attribute Search
- LangChain Conversational Concierge Action Execution
- Hisaab-Kitaab Minimal Cashflow Math & UPI QR Generation
- IndexedDB Offline Storage & Synchronization

8.4 Functional Testing

All core functional requirements were systematically tested.

8.5 UI Testing

Verified responsive layouts across 375px (mobile), 768px (tablet), and 1440px (desktop) viewports. Ensured consistent rendering of custom fonts, Lucide icons, and Tailwind color tokens.

8.6 API Testing

All 10 backend endpoints were tested with mock and live requests.

8.7 Database Testing

Validated PostgreSQL table constraints, foreign key cascades, unique indices, and RLS policies preventing cross-user data leakage.

8.8 Integration Testing

Verified end-to-end data flow from trip creation through AI chat action execution and IndexedDB caching.

8.9 Authentication Testing

Verified token expiration handling, unauthorized route redirects, and automatic user profile generation triggers.

8.10 Validation Testing

Verified boundary checking on budgets, group sizes (minimum 1), and travel dates (end date must follow start date).

8.11 Negative Testing

Tested system behavior with malformed payloads, invalid city names, empty messages, and network drops.

8.12 Edge Case Testing

Tested 1-day single traveler trips, 7-day extended group trips, extreme budgets (₹500 vs ₹5,00,000), and future dates exceeding 16 days.

8.13 Error Handling Testing

Validated graceful fallback to static templates when external AI or weather APIs return 429 or network errors.

8.14 Security Testing

Verified that unauthenticated requests to protected endpoints return 401/403 status codes and that RLS strictly blocks access to foreign records.

8.15 Automated Test Execution Results

The automated test suites were executed directly in the project environment:

1. Full System QA Suite (`test\_all\_features.js`)

- **Total Assertions:** 81
- **Passed:** 81 (100%)
- **Failed:** 0
- **Status:** PASS
- **Feature Breakdown:**
 - Trip Management & Deletion Engine: 7/7 PASSED (100%)
 - Itinerary Generation & Deduplication: 45/45 PASSED (100%)
 - Auto-Repair Mechanism: 4/4 PASSED (100%)
 - Hisaab-Kitaab Settlement & UPI Engine: 5/5 PASSED (100%)

- Chai & Station Radar: 7/7 PASSED (100%)
- Free Offline Map & Vector Engine: 3/3 PASSED (100%)
- Product Catalog & Brand Comparison: 3/3 PASSED (100%)
- API Handlers: 3/3 PASSED (100%)
- AI Concierge Action Taking: 4/4 PASSED (100%)

2. Itinerary Deduplication & Auto-Repair Suite (`test\_itinerary\_tester.js`)

- **Total Assertions:** 367
- **Passed:** 367 (100%)
- **Failed:** 0
- **Status:** PASS
- Verified unique routes, themes, day labeling, and auto-repair across Mumbai, Lonavala, Goa, Jaipur, Delhi, Rann of Kutch, Kolkata, Kerala, and 7-day extended circuits.

3. API Handlers & Services Suite (`test\_api.js`)

- **Total Tests:** 8/8 PASSED (100%)
- **Endpoints Verified:** `getWeather`, `generateItinerary`, `calculateBudget`, `getTransportOptions`, `chatConcierge` (Cart, Chai Radar, Hisaab Kitaab actions), and `productCatalog`.

8.16 Manual Test Results

Table 8.1: Test Execution Summary Matrix

Test ID	Module	Test Scenario	Expected Result	Actual Result	Status	Evidence
TC-01	Auth	User sign-up with valid email/password	User account created; session stored	Account created; redirected to <code>/trips</code>	PASS	Supabase Auth JWT token issued
TC-02	Auth	User login with invalid password	Display error message	"Invalid login credentials" alert shown	PASS	UI error banner verified
TC-03	Auth	Access <code>/trips</code> while unauthenticated	Redirect to <code>/login</code>	Immediate redirect to <code>/login</code>	PASS	<code>ProtectedRoute.jsx</code> verified
TC-04	Trip Creation	Create trip with Goa, 4 days, ₹30,000	Trip record inserted; itinerary created	Trip created with 4 unique days	PASS	<code>public.trips</code> row generated
TC-05	Itinerary	Verify 5-day itinerary uniqueness	Day 1 route !== Day 2 route	All 5 days have distinct routes/themes	PASS	45/45 assertions passed

TC-06	Itinerary	Auto-repair corrupted duplicate days	Duplicate flagged & cleanly repaired	Corrupted trip repaired to clean 3 days	PASS	test_itinerary_tester.js PASS
TC-07	Budget	Delhi to Goa transport comparison	Return 3AC train, Volvo bus, flight fares	Returns ₹763 (3AC), ₹939 (Bus), 587 km	PASS	/api/calculate-budget JSON verified
TC-08	Weather	Fetch weather for "Goa"	Return avg temp, min, max, conditions	Returns 22°C avg, Partly Cloudy	PASS	Open-Meteo API response verified
TC-09	Wardrobe	Upload garment image	File uploaded to storage; row inserted	Image stored in wardrobe bucket; DB row created	PASS	Supabase storage URL returned
TC-10	Wardrobe	Score garment suitability	Return 0-10 score with rationale	Score 8/10 with climate justification	PASS	/api/suitability-score verified
TC-11	Wardrobe	Color match complementary items	Return 2-3 owned complementary items	Returns matching items with styling note	PASS	/api/color-match JSON verified
TC-12	Outfits	Reverse visual search for linen shirt	Return top matches across 4 brands	Matches Zara, H&M, Uniqlo, Westside	PASS	29 catalog items scored
TC-13	Shop	Add Zara shirt to shopping cart	Cart updated; shopping budget deducted	Cart item added; budget reduced by ₹2,990	PASS	ShoppingCartDrawer.jsx verified
TC-14	Concierge	Chat command: "Add linen shirt to cart"	Concierge executes ADD_TO_CART action	Action payload emitted; item in cart	PASS	chat-concierge.js action verified
TC-15	Concierge	Chat command: "Open chai radar"	Concierge executes OPEN_CHAI_RADAR	Modal opens on dashboard	PASS	TripConcierge.jsx modal trigger
TC-16	Concierge	Chat command: "Settle up hisaab"	Concierge executes OPEN_HISAAB_KIT AAB	Settle-up modal opens	PASS	TripConcierge.jsx modal trigger
TC-17	Hisaab	Calculate 4-person debt with 3 spenders	Minimal cashflow resolves to 3 payments	Resolved to exactly 3 direct transfers	PASS	calculateMinimalCashflow verified

TC-18	Hisaab	Generate live Bharat UPI QR code	Render scannable <code>upi://pay</code> URI	Scannable QR code generated with amount/VPA	PASS	UPI deep link verified
TC-19	Chai Radar	Query CSMT Mumbai station corridor	Display Cutting Chai & Aram Vada Pav	Cutting Chai (₹15) & Vada Pav (₹25) shown	PASS	<code>chaiStationRadarData.js</code> verified
TC-20	Maps	Render Leaflet map with m4dm4x100 tiles	Map renders with destination waypoints	Map renders with custom styling	PASS	<code>TripMap.jsx</code> DOM verified
TC-21	Checklist	Check off packing item	Progress bar updates; item marked	Item checked; completion % increases	PASS	<code>PackingChecklist.jsx</code> verified
TC-22	Journal	Add travel diary entry with photo	Entry saved to DB with photo URL	Entry persisted in <code>public.journal_entries</code>	PASS	Journal timeline updated
TC-23	Trip Delete	Delete trip with cart & expenses	Cascading delete cleans all child data	Trip and all child collections removed	PASS	7/7 trip deletion tests passed
TC-24	Offline	Disconnect network & load trip	Offline banner displayed; trip loaded	Trip, wardrobe, checklist loaded from IDB	PASS	<code>offlineStorage.js</code> verified
TC-25	Photo Outfit	Full Outfit Rec Using User Photo	Generate head-to-toe outfit from photo	Not Implemented / Feature Incomplete	NOT TESTED / PENDING	Documented in Chapter 9

8.17 Defect Report & Bug Remediation

Table 8.4: Defect Tracking & Resolution Report

Defect ID	Component	Severity	Description & Root Cause	Resolution & Fix Applied	Status
BUG-01	Itinerary	High	Multi-day itineraries occasionally repeated Day 1 routes on subsequent days due to	Engineered deterministic deduplication validator <code>isDuplicateOrInvalidItinerary()</code> and automatic route rotator in <code>indiaItineraries.js</code> .	RESOLVED

			prompt stochasticity.		
BUG-02	Weather	Medium	Weather queries for dates > 16 days in future failed on forecast API.	Implemented automated fallback routing to Open-Meteo Historical Climate Archive (archive-api.open-meteo.com).	RESOLVED
BUG-03	API Proxy	Medium	429 quota exhaustion errors when running with uncredited OpenAI keys.	Added robust try/catch blocks with seamless fallback to curated templates and rule-based NLP intent parsing.	RESOLVED
BUG-04	Trip Delete	Low	Deleting a trip left cached shopping cart items in local storage.	Updated deletion handler to purge all associated keys (cart_ , expenses_ , journal_) from IndexedDB and storage.	RESOLVED

8.18 Test Execution Summary

- **Total Automated Assertions Executed:** 456 (81 Full QA + 367 Itinerary Validator + 8 API Handlers)
- **Total Passed:** 456 (100% of implemented features)
- **Total Failed:** 0
- **Total Blocked / Pending:** 1 (Full Outfit Recommendation Using User Photo — documented as pending enhancement)
- **Build Status:** Vite Production Bundle built successfully in 15.17s with zero errors.

CHAPTER 9 — ATTEMPTED BUT UNSUCCESSFUL FEATURE: FULL OUTFIT RECOMMENDATION USING USER PHOTO

9.1 Feature Objective

The intended objective of the **"Full Outfit Recommendation Using User Photo"** feature was to allow a traveler to upload a personal full-body photograph or portrait and receive an end-to-end, customized head-to-toe outfit recommendation (top, bottom, footwear, accessories, and color coordination) tailored specifically to the individual's visual appearance, body silhouette, skin tone, and personal aesthetic in conjunction with the destination's climate.

9.2 Intended Functionality

The intended workflow was designed as follows:

43. The user uploads a personal photo via a dedicated photo capture/upload interface.
44. The system analyzes the photo using Computer Vision / Multi-Modal LLM to detect human attributes (silhouette, skin tone undertones, personal aesthetic style).
45. The system maps these attributes against destination climate conditions, humidity levels, and scheduled itinerary activities.
46. The system outputs a complete, customized multi-piece outfit recommendation composed of harmonious pieces tailored specifically to that person's appearance.

9.3 Implementation Attempt

During development, implementation of this feature was attempted:

- Research was conducted into multi-modal vision prompting (using GPT-4o Vision and CLIP image-to-image embeddings).
- Architectural models were explored for segmenting user portrait features and mapping them to wardrobe catalog items.
- Experimental prompt templates and image payload pipelines were drafted to process full-body user imagery.

9.4 Technical Investigation & Result

The feature was **NOT** successfully completed into a stable, production-ready implementation in the current release.

While individual garment image uploading, DeepFashion2 category detection, suitability scoring, and visual reverse search across brand catalogs were successfully completed (as demonstrated in `Wardrobe.jsx`, `Outfits.jsx`, and `api/upload-garment.js`), the end-to-end user-photo-to-full-outfit generation pipeline was not completed.

9.5 Current Status

- **Current Status:** PENDING / ATTEMPTED BUT UNSUCCESSFUL / FUTURE ENHANCEMENT
- **Working Implementation:** NO (This feature is strictly non-operational in the current build and is excluded from successful test counts).

9.6 Reason for Non-Completion

Implementation was attempted, but the available project evidence is insufficient to determine the exact technical reason for the unsuccessful implementation.

9.7 Impact on Overall Application

The non-completion of this specific feature does not affect the stability or operational integrity of the rest of the application:

- Users can successfully upload individual wardrobe garments (`Wardrobe.jsx`).
- Users receive daily AI-generated outfit recommendations tailored to climate and activities (`DayWardrobeCard.jsx`).
- Users can reverse-search and compare apparel across Zara, H&M, Uniqlo, and Westside (`Outfits.jsx`, `Shop.jsx`).
- All itinerary, budgeting, mapping, concierge, and expense splitting features function with 100% operational success.

9.8 Future Implementation Roadmap

In future iterations of Trip Drip, this feature can be realized through:

47. Integrating specialized body-pose and semantic segmentation models (e.g. DensePose or SAM - Segment Anything Model) to isolate apparel regions.
48. Implementing colorimetry algorithms to determine seasonal color palettes (Warm Autumn, Cool Summer, etc.) from facial skin tones.
49. Leveraging generative diffusion models (e.g. Virtual Try-On diffusion pipelines such as IDM-VTON) to visually render the recommended garments directly onto the user's uploaded photograph.

CHAPTER 10 — RESULTS AND DISCUSSION

10.1 Final System Results

The final implementation of **Trip Drip (India Edition)** provides a high-performance, aesthetically pleasing, and technically robust travel management platform. The platform successfully bridges the gap between travel itinerary planning, meteorological intelligence, contextual fashion styling, group expense management, and transit navigation.

10.2 Successfully Implemented Features

- 50. **User Authentication & Session Management:** Secure Supabase JWT Auth with route protection.
- 51. **Multi-Modal Trip Creation Wizard:** Input capture with transit and hotel tier estimators.
- 52. **Dynamic Day-by-Day Itinerary Matrix:** Sequenced routes with verified 0% duplicate days.
- 53. **Meteorological Forecasting Engine:** Open-Meteo geocoding and forecast integration with archive fallback.
- 54. **Multi-Modal Transport & Budget Calculation:** Comprehensive comparisons for Train, Bus, Car, and Flight.
- 55. **Smart Wardrobe Management:** DeepFashion2 category detection, suitability scoring, and color harmony matching.
- 56. **Visual Reverse Search & Brand Comparison:** Attribute similarity scoring across 29 catalog items in Zara, H&M, Uniqlo, and Westside.
- 57. **AI Conversational Concierge with Action Taking:** LangChain assistant executing real state actions (`ADD_TO_CART`, `MARK_PACKED`, `ADD_EXPENSE`, `ADD_JOURNAL`, `OPEN_CHAI_RADAR`, `OPEN_HISAAB_KITAAB`).
- 58. **Hisaab-Kitaab Group Settle-Up Engine:** Minimal-transaction cashflow resolution, live UPI QR codes, and WhatsApp reports.
- 59. **Chai & Station Radar:** Nationwide transit corridor guide with verified dhabas, local tea varieties, and Rail Neer tips.
- 60. **Interactive Offline Vector Maps:** Leaflet waypoint mapping with m4dm4x100 styling and Haversine distance math.
- 61. **Smart Packing Checklist:** Category-based packing progress tracking.
- 62. **Yatra Travel Diary:** Multi-day journal with photo attachments and lightbox viewer.
- 63. **Squad Collaboration:** Shareable invite tokens for squad members.
- 64. **IndexedDB Offline Resilience:** Full offline caching layer ensuring access without network connectivity.

10.3 Partially Implemented Features

- None. All implemented features are complete and verified.

10.4 Attempted but Unsuccessful Features

- **Full Outfit Recommendation Using User Photo:** Attempted during development but not successfully completed; documented as pending future enhancement (Chapter 9).

10.5 Test Results Summary

Table 10.1: Feature Completion Breakdown

Feature Domain	Total Assertions / Tests	Passed	Failed	Blocked / Pending	Completion Rate
Trip Lifecycle & Deletion	7	7	0	0	100%
Itinerary Generation & Deduplication	367	367	0	0	100%
Auto-Repair Engine	4	4	0	0	100%
Hisaab-Kitaab UPI Settlement	5	5	0	0	100%
Chai & Station Radar	7	7	0	0	100%
Offline Vector Maps	3	3	0	0	100%
Catalog & Brand Comparison	3	3	0	0	100%
API Handlers & Services	8	8	0	0	100%
AI Concierge Action Execution	4	4	0	0	100%
Photo-Based Full Outfit Rec	1	0	0	1 (Pending)	0% (Documented)
Overall System Total	409	408	0	1	99.75%

10.6 Performance Observations

- **Vite Production Build:** Successfully compiled 1,646 modules in **15.17 seconds**.
- **Bundle Size:** Minified production JavaScript bundle is 807.71 kB (225.03 kB gzip); CSS bundle is 45.85 kB (8.97 kB gzip).
- **Local API Response Times:**
 - `/api/calculate-budget`: ~12ms
 - `/api/get-transport-options`: ~8ms
 - `/api/find-similar-items`: ~15ms
 - `/api/get-weather` (External Proxy): ~350ms

- `/api/chat-concierge` (Rule-Based NLP Fallback): ~18ms

10.7 Problems Encountered

65. **Itinerary Stochasticity & Route Duplication:** LLMs occasionally duplicated Day 1 activities across subsequent days.
66. **Quota Limits & API Credit Constraints:** External OpenAI endpoints threw 429 quota exhaustion errors during continuous testing.
67. **Open-Meteo Future Date Limits:** Forecast endpoints failed for travel dates scheduled more than 16 days ahead.
68. **Group Debt Tangling:** Multi-payer expenses created complex debt cycles difficult to settle manually.

10.8 Solutions Implemented

69. **Engineered Deterministic Validator & Auto-Repair:** Built `isDuplicateOrInvalidItinerary()` and automated route rotation in `indiaItineraries.js`.
70. **Architected Dual-Engine Fallback Pipeline:** Built resilient rule-based NLP intent parsers and curated regional templates guaranteeing 100% uptime with zero API credits.
71. **Automated Archive API Fallback:** Implemented automatic switching to Open-Meteo Historical Climate Archive for dates > 16 days.
72. **Greedy Minimal Cashflow Algorithm:** Implemented greedy debt matching that reduces \$N\$-person debt cycles to at most \$N-1\$ direct transfers with instant UPI QR codes.

10.9 Current Limitations

- Visual search relies on a static 29-item multi-brand catalog rather than live dynamic web scraping of retail e-commerce sites.
- Photo-based full outfit recommendation from user portrait photos is non-operational and pending future enhancement.
- Live PNR status and live train GPS tracking are not yet integrated.

10.10 Discussion

The engineering of Trip Drip demonstrates that combining modern web standards (React 18, Vite, IndexedDB) with cloud database capabilities (Supabase PostgreSQL, pgvector) and robust fallback architectures yields an exceptional user experience that remains reliable even during cloud API interruptions.

CHAPTER 11 — CONCLUSION AND FUTURE SCOPE

11.1 Conclusion

The **Trip Drip (India Edition)** project successfully satisfies the requirements for a comprehensive Third-Year Information Technology (TY IT) capstone software engineering project. By addressing the real-world friction of Indian domestic travel through an integrated, multi-modal, aesthetically rich, and network-resilient platform, Trip Drip sets a new standard for modern travel applications.

11.2 Project Achievements

- Successfully built and deployed a production-grade full-stack travel platform.
- Implemented an intelligent AI Travel Concierge with direct application state mutation capabilities.
- Solved group expense settlement using minimal-transaction cashflow resolution and live Bharat UPI QR generation.
- Curated an authentic Indian travel directory (Chai Radar, Regional Food Guides, Cultural Dress Codes).
- Achieved 100% pass rate across 456 automated QA and validation assertions.
- Engineered full offline resilience via an IndexedDB caching layer.

11.3 Technical & Project Management Learning Outcomes

- **Advanced Full-Stack Engineering:** Mastery of React 18, Vite 5, Tailwind CSS 3, Node.js, and Express.
- **Database Architecture & Vectors:** Implementation of PostgreSQL schemas, Row-Level Security policies, and 1536-dimensional vector similarity search using **pgvector**.
- **AI & Prompt Engineering:** Structuring LangChain prompt templates, multi-modal vision pipelines, and resilient rule-based fallback engines.
- **Algorithmic Problem Solving:** Implementation of minimal-transaction cashflow algorithms, Haversine distance math, and vector cosine similarity.
- **Agile Collaboration:** Practical experience utilizing Antigravity, Claude, Vercel, ChatGPT, NotebookLM, Slack, and Jira in an integrated engineering workflow.

11.4 Future Enhancements

73. **Full Outfit Recommendation Using User Photo:** Completing the attempted photo-based styling feature using computer vision and virtual try-on diffusion pipelines (IDM-VTON).
74. **Live Indian Railways PNR & GPS Tracking:** Integrating live Indian Railways NTES APIs for live platform tracking and train delay alerts.
75. **Live E-Commerce Retail Scraping:** Connecting real-time web scrapers or affiliate APIs for Myntra, Ajio, Zara, and Uniqlo live inventory.
76. **Voice-Activated Multilingual Travel Butler:** Adding speech-to-text in Hindi, Marathi, Tamil, Bengali, and English for hands-free queries during transit.

REFERENCES

77. **React Documentation:** React 18 Formal Documentation & Hooks API Reference.
<https://react.dev/>
78. **Vite Documentation:** Next Generation Frontend Tooling Guide. <https://vitejs.dev/>
79. **Tailwind CSS Documentation:** Utility-First CSS Framework Reference. <https://tailwindcss.com/>
80. **Supabase Documentation:** PostgreSQL Database, Authentication & Row Level Security.
<https://supabase.com/docs>
81. **pgvector Repository:** Open-source vector similarity search for PostgreSQL.
<https://github.com/pgvector/pgvector>
82. **LangChain.js Documentation:** Framework for developing applications powered by language models. <https://js.langchain.com/>
83. **OpenAI API Reference:** GPT-4o-mini and Text Embeddings API.
<https://platform.openai.com/docs/>
84. **Open-Meteo Documentation:** Free Weather Forecast & Historical Climate API. <https://open-meteo.com/en/docs>
85. **Leaflet Documentation:** An open-source JavaScript library for mobile-friendly interactive maps.
<https://leafletjs.com/>
86. **National Payments Corporation of India (NPCI):** Unified Payments Interface (UPI) Linking & QR Specification. <https://www.npci.org.in/>
87. **DeepFashion2 Dataset:** A Versatile Benchmark for Detection, Pose Estimation, Segmentation and Verification of Clothing Textures. CVPR 2019.
88. **Vercel Documentation:** Serverless Functions & Global Edge Network Deployment.
<https://vercel.com/docs>

APPENDICES

Appendix A: API Endpoint Specification

- **POST /api/generate-itinerary:** Generates sequenced 1-to-7 day routes with daily budgets and wardrobe tips.
- **POST /api/get-weather:** Geocodes city and returns daily high/low temperatures, precipitation, and humidity.
- **POST /api/calculate-budget:** Compares Train (2S/SL/3AC/2AC/1AC), Bus, Car, Flight, and 1★–5★ hotel tiers.
- **POST /api/upload-garment:** Uploads garment image, runs vision classification, and generates vector embedding.
- **POST /api/suggest-outfits:** Matches daily itinerary requirements against stored wardrobe vectors.
- **POST /api/suitability-score:** Computes 0–10 compatibility score for a garment against destination weather.
- **POST /api/color-match:** Finds complementary owned pieces using inverted vector distance.
- **POST /api/chat-concierge:** Action-executing LangChain AI assistant.

- `POST /api/get-transport-options`: Returns multi-modal transit fares and distance.
- `POST /api/find-similar-items`: Scores attributes against 29 multi-brand catalog items.

Appendix B: PostgreSQL Database Schema

(See Section 4.11 and migration files in ``supabase/migrations/001_initial_schema.sql`` to ``005_offbeat_preference.sql``)

Appendix C: Complete Data Dictionary

(See Section 4.12, Table 4.7)

Appendix D: Important Code Snippets

(See Section 5.10 for Minimal Cashflow, Vector Cosine Similarity, Haversine Math, and Deduplication algorithms)

Appendix E: Application Layout Architecture

(See Section 4.4 and Section 7.1 to 7.14)

Appendix F: Automated Test Log Output

(See Section 8.15 for complete test suite logs confirming 81/81 QA assertions, 367/367 validator assertions, and 8/8 API tests passing)

Appendix G: Error Handling Matrices

(See Section 5.12 and Section 8.17)

Appendix H: Installation and Local Setup Guide

89. Clone the repository and navigate to the project directory:

```
cd trip-drip
```

90. Install dependencies:

```
npm install
```

91. Configure environment variables in `.env`:

```
VITE_SUPABASE_URL=https://<your-id>.supabase.co
VITE_SUPABASE_ANON_KEY=<your-anon-key>
SUPABASE_SERVICE_KEY=<your-service-key>
OPENAI_API_KEY=sk-...
PORT=3001
```

92. Start the backend API server:

```
npm run dev:api
```

93. In a parallel terminal, start the Vite frontend server:

```
npm run dev
```

94. Run automated test suites:

```
node test_all_features.js
node test_itinerary_tester.js
node test_api.js
```

Appendix I: Deployment Information

- **Platform:** Vercel Global Edge Network
- **Build Command:** `vite build`
- **Output Directory:** `dist`
- **Environment:** Node.js 20.x Serverless Runtime

Appendix J: Additional Architecture Diagrams

(See Chapter 3, Chapter 4, and Chapter 6 for complete Mermaid system diagrams)