

# Zeppelin

# python\_intro



```
%pyspark
from pandas import Series, DataFrame
import pandas as pd
obj = Series([4, 7, -5, 3])
obj
```

FINISHED ▶ 🔍 📖 ⚙️

```
0      4
1      7
2     -5
3      3
dtype: int64
```

Took 5 sec. Last updated by anonymous at February 16 2017, 6:36:24 PM.

```
%pyspark
obj.values
```

FINISHED    

```
array([ 4,  7, -5,  3])
```

Took 0 sec. Last updated by anonymous at February 16 2017, 6:38:49 PM.

```
%pyspark
obj.index
```

FINISHED    

```
RangeIndex(start=0, stop=4, step=1)
```

Took 0 sec. Last updated by anonymous at February 16 2017, 6:39:01 PM.

```
%pyspark
obj2 = Series([4, 7, -5, 3], index=['d', 'b', 'a', 'c'])
obj2.index
```

FINISHED ▶ 🔍 📖 ⚙️

```
Index([u'd', u'b', u'a', u'c'], dtype='object')
```

Took 0 sec. Last updated by anonymous at February 16 2017, 6:47:04 PM.

```
%pyspark
obj2.index
```

FINISHED ▶ 🔍 📖 ⚙️

```
Index([u'd', u'b', u'a', u'c'], dtype='object')
```

FINISHED    

[illegible]

# Zeppelin

python\_intro

default

```
%pyspark
obj2['d'] = 6
obj2[['c', 'a', 'd']]
obj2
```

FINISHED

```
d    6
b    7
a   -5
c    3
dtype: int64
```

Took 0 sec. Last updated by anonymous at February 16 2017, 6:49:51 PM.

```
%pyspark
obj2[obj2 > 0]
obj2 * 2
```

FINISHED

```
d    12
b    14
a   -10
c     6
dtype: int64
```

Took 0 sec. Last updated by anonymous at February 16 2017, 6:51:30 PM.

```
%pyspark
import numpy as np
np.exp(obj2)
'b' in obj2
'e' in obj2
sdata = {'Ohio': 35000, 'Texas': 71000, 'Oregon': 16000, 'Utah': 5000}
obj3 = Series(sdata)
obj3
```

FINISHED

```
Ohio      35000
Oregon    16000
Texas     71000
Utah       5000
dtype: int64
```

Took 0 sec. Last updated by anonymous at February 16 2017, 6:52:00 PM.

```
%pyspark
states = ['California', 'Ohio', 'Oregon', 'Texas']
obj4 = Series(sdata, index=states)
obj4
```

FINISHED

python\_intro

California

Ohio

Oregon

Texas

dtype: float64

NgN

35000

16000.0

71000.0

Zeppelin

python\_intro

default

Took 0 sec. Last updated by anonymous at February 16 2017, 6:53:33 PM.

%pyspark

pd.isnull(obj4)

California True

Ohio False

Oregon False

Texas False

dtype: bool

FINISHED

Took 0 sec. Last updated by anonymous at February 16 2017, 6:54:15 PM.

%pyspark

pd.notnull(obj4)

California False

Ohio True

Oregon True

Texas True

dtype: bool

FINISHED

Took 0 sec. Last updated by anonymous at February 16 2017, 6:55:11 PM.

%pyspark

obj4.isnull()

California True

Ohio False

Oregon False

Texas False

dtype: bool

FINISHED

Took 0 sec. Last updated by anonymous at February 16 2017, 6:55:36 PM.

%pyspark

obj3

Ohio 35000

Oregon 16000

Texas 71000

Utah 5000


dtype: int64

FINISHED

python\_intro

Took 0 sec. Last updated by anonymous at February 16 2017, 6:57:30 PM.

%nvsark

 **Zeppelin**

python\_intro

California NaN  
Ohio 35000.0  
Oregon 16000.0  
Texas 71000.0  
dtype: float64

FINISHED ▶ ⌵ 📖 ⚙️

▶ ⌵ 📖 ✎ 📄 ⬇ 📄

🗑 ⌚

🖨 ⚙️ 🔒 default ▼

Took 0 sec. Last updated by anonymous at February 16 2017, 6:57:58 PM.

%pyspark

obj3 + obj4

California NaN  
Ohio 70000.0  
Oregon 32000.0  
Texas 142000.0  
Utah NaN  
dtype: float64

FINISHED ▶ ⌵ 📖 ⚙️

Took 0 sec. Last updated by anonymous at February 16 2017, 6:59:28 PM.

%pyspark

obj4.name = 'population'  
obj4.index.name = 'state'  
obj4

state  
California NaN  
Ohio 35000.0  
Oregon 16000.0  
Texas 71000.0  
Name: population, dtype: float64

FINISHED ▶ ⌵ 📖 ⚙️

Took 0 sec. Last updated by anonymous at February 16 2017, 7:00:45 PM.

%pyspark

obj.index = ['Bob', 'Steve', 'Jeff', 'Ryan']  
obj

Bob 4  
Steve 7  
Jeff -5  
Ryan 3  
dtype: int64

FINISHED ▶ ⌵ 📖 ⚙️

Took 0 sec. Last updated by anonymous at February 16 2017, 7:01:39 PM.

%pyspark

data = {'state': ['Ohio', 'Ohio', 'Ohio', 'Nevada', 'Nevada'],  
'year': [2000, 2001, 2002, 2001, 2002],  
'pop': [1.5, 1.7, 3.6, 2.4, 2.9]}

python\_intro

FINISHED ▶ ⌵ 📖 ⚙️

4/8

Took 0 sec. Last updated by anonymous at February 16 2017, 7:02:32 PM.

Took 0 sec. Last updated by anonymous at February 16 2017, 7:03:04 PM.

Took 0 sec. Last updated by anonymous at February 16 2017, 7:03:25 PM.

Took 0 sec. Last updated by anonymous at February 16 2017, 7:03:45 PM.

[illegible]

five 2002  
 ver, pr: int64  
**Zeppelin**

Took 0 sec. Last updated by anonymous at February 16 2017, 7:04:00 PM.

# python\_intro

default ▼

FINISHED    

```
%pyspark
frame2.ix['three']
```

```
year      2002
state     Ohio
pop       3.6
debt      NaN
Name: three, dtype: object
```

Took 0 sec. Last updated by anonymous at February 16 2017, 7:04:29 PM.

```
%pyspark
frame2['debt'] = 16.5
frame2
```

FINISHED ▶ ↻ 📖 ⚙️

	year	state	pop	debt
one	2000	Ohio	1.5	16.5
two	2001	Ohio	1.7	16.5
three	2002	Ohio	3.6	16.5
four	2001	Nevada	2.4	16.5
five	2002	Nevada	2.9	16.5

Took 0 sec. Last updated by anonymous at February 16 2017, 7:04:49 PM.

```
%pyspark
frame2['debt'] = np.arange(5.)
frame2
```

FINISHED    

	year	state	pop	debt
one	2000	Ohio	1.5	0.0
two	2001	Ohio	1.7	1.0
three	2002	Ohio	3.6	2.0
four	2001	Nevada	2.4	3.0
five	2002	Nevada	2.9	4.0

Took 0 sec. Last updated by anonymous at February 16 2017, 7:05:17 PM.

```
%pyspark
val = Series([-1.2, -1.5, -1.7], index=['two', 'four', 'five'])
frame2['debt'] = val
frame2
```

FINISHED ▶ ↻ 📖 ⚙️

	year	state	pop	debt
one	2000	Ohio	1.5	NaN
two	2001	Ohio	1.7	NaN
three	2002	Ohio	3.6	NaN
four	2001	Nevada	2.4	-1.5

python intro

five 2002 Nevada 2.9 -1.7

# Zeppelin

Zeppelin Notebook  
 Took 0 sec. Last updated by anonymous at February 16 2017, 7:05:40 PM.

## python\_intro



FINISHED default

```
%pyspark
frame2['eastern'] = frame2.state == 'Ohio'
frame2
```

	year	state	pop	debt	eastern
one	2000	Ohio	1.5	NaN	True
two	2001	Ohio	1.7	-1.2	True
three	2002	Ohio	3.6	NaN	True
four	2001	Nevada	2.4	-1.5	False
five	2002	Nevada	2.9	-1.7	False

Took 0 sec. Last updated by anonymous at February 16 2017, 7:06:01 PM.

```
%pyspark
del frame2['eastern']
frame2.columns
```

FINISHED

Index([u'year', u'state', u'pop', u'debt'], dtype='object')

Took 0 sec. Last updated by anonymous at February 16 2017, 7:06:32 PM.

```
%pyspark
pop = {'Nevada': {2001: 2.4, 2002: 2.9},
       'Ohio': {2000: 1.5, 2001: 1.7, 2002: 3.6}}
frame3 = DataFrame(pop)
frame3
```

FINISHED

	Nevada	Ohio
2000	NaN	1.5
2001	2.4	1.7
2002	2.9	3.6

Took 0 sec. Last updated by anonymous at February 16 2017, 7:07:06 PM.

```
%pyspark
frame3.T
```

FINISHED

	2000	2001	2002
Nevada	NaN	2.4	2.9
Ohio	1.5	1.7	3.6

Took 0 sec. Last updated by anonymous at February 16 2017, 7:07:25 PM.

```
%pyspark
pdata = {'Ohio': frame3['Ohio'][:-1],
        'Nevada': frame3['Nevada'][:2]}
DataFrame(pdata)
```

FINISHED



python\_intro

Took 1 sec. Last updated by anonymous at February 16 2017, 7:10:31 PM.



default ▼

FINISHED ▶ ⌵ 📖 ⚙

```
%pyspark
frame3.index.name = 'year'; frame3.columns.name = 'state'
frame3
```

state	Nevada	Ohio
year		
2000	NaN	1.5
2001	2.4	1.7
2002	2.9	3.6

Took 0 sec. Last updated by anonymous at February 16 2017, 7:10:50 PM.

FINISHED ▶ ⌵ 📖 ⚙

```
%pyspark
frame3.values

array([[ nan,  1.5],
       [ 2.4,  1.7],
       [ 2.9,  3.6]])
```

Took 0 sec. Last updated by anonymous at February 16 2017, 7:11:06 PM.

FINISHED ▶ ⌵ 📖 ⚙

```
%pyspark
frame2.values

array([[2000, 'Ohio', 1.5, nan],
       [2001, 'Ohio', 1.7, -1.2],
       [2002, 'Ohio', 3.6, nan],
       [2001, 'Nevada', 2.4, -1.5],
       [2002, 'Nevada', 2.9, -1.7]], dtype=object)
```

Took 0 sec. Last updated by anonymous at February 16 2017, 7:11:18 PM.

READY ▶ ⌵ 📖 ⚙