Computer Science and Engineering Department, SVNIT, Surat B.tech.-III, Semester-V Operating system Lab Assignment 5

 To implement first fit, best fit and worst fit storage allocation algorithms for memory Management. Also, calculate the total External Fragmentation after allocation.

Description

A set of holes, of various sizes is scattered through the memory at any given time. When a process arrives and needs the memory, the system searches for a hole that is large enough for this process. The first-fit, best-fit and worst-fit are strategies used to select a free hole from the set of available holes.

Implementation details

Free space is maintained as a linked list of nodes with each node having the starting byte address and the ending byte address of a free block. Each memory request consists of the process-id and the amount of storage space required in bytes. Allocated memory space is again maintained as a linked list of nodes with each node having the processid, starting byte address and the ending byte address of the allocated space.

When a process finishes (taken as input) the appropriate node from the allocated list should be deleted and this free disk space should be added to the free space list. [Care should be taken to merge contiguous free blocks into one single block. This result in deleting more than one node from the free space list and changing the start and end address in the appropriate node]. For allocation use first fit, worst fit and best fit.

First-Fit

Allocate the first hole that is big enough. Searching can start either at the beginning of the set of holes or where the previous first-fit search ended. You can stop searching as soon as you find a free hole that is large enough.

Best-Fit

Allocate the smallest hole that is big enough. You must search the entire list unless the list is kept ordered by size. The strategy produces the smallest leftover hole.

Worst fit

Allocate the biggest hole.

- 2) Write a program that implements the following Page replacement algorithm.
 - i) LRU (Least Recently Used)
 - ii) Optimal Page Replacement algorithm

Count total numbers of page fault at the end and compare for both of the algorithms.

Description:

The total number of frames, sequence numbers of pages should be asked as input, Take 10 sequence numbers minimum.

And validate that total number of frames given in input are less than highest page no. given in sequence (i.e., given in second input.)

For e.g., If my sequence is 1 2 6 7 5 4 7 2 3 1 2, then Total frames should not be 7 or 8 and it should be less than 7.