# SD13 BUIId02ec

Engine model: Shangchai D6114ZG4B

Rated power: 95.5 kW (130Hp)

Operating weight: 14 t



SHANTUI

(Model shown)May Include optional equipments

# **SD13**



#### **SPECIFICATION**

Blade Type		
Specification	Straight-tilt	Angle
Min.ground clearance(mm)	320	320
Operating weight(t)	14	14.5
Ground pressure(MPa)	0.064	0.064
Gradeability(°)	30	30
Track gauge(mm)	1880	1880



#### **ENGINE**

Model Shangchai D6114ZG4B
TypeWater cooled,in -line,4-cycle,direct injection and turbo charge
Rated revolution(rpm)
Rated Power(kW)
Cylinder Number-Bore × Stroke(mm) 6-114 × 135
Piston displacement(L)
Rated fuel consumption(g/kW⋅h) ≤ 228
Max.Torque(N·m/rpm)



#### POWER TRANSMISSION SYSTEM

Torque converter	3-element,1 stage,1 phase
Transmission	Forced connected, Planetary gear
Main drive	Spiral bevel gear, Splash lubrication
Steering clutch	Wet, Multi-disc, Spring loaded, Hydraulic helping operation,
	Mechanical Separating, Linking steering brake
Steering brake	Wet,Floating,band type Foot stepping
	brake with hydraulic helping
Final drive	2-stage speed reduction of spur gear splash lubrication



#### TRAVEL SPEED

Gear	1st	2nd	3rd
Foward(km/h)	0~3.2	0~5.9	0~9.8
Reverse(km/h)	0~3.9	0~7.1	0~11.9



# **UNDERCARRIAGE SYSTEM**

Type Swing type of sprayed beam, suspend	ed structure of equalizer bar
Carry rollers(each side)	2
Track rollers(each side)	6
Track type	Single grouser.dry type
Width of track shoes(mm)	460
Pitch(mm)	190



# **HYDRAULIC SYSTEM**

Max.pressure(MPa)	14
Pump type	Gear punp
Discharge(L/min)	180
Working cylinder(mm) × No	Ø90 × 2



# BLADE

Blade Type		
Specification	Straight-tilt	Angle
Dozing capacity(m³)	3.7	3.4
Blade width(mm)	3185	3745
Blade height(mm)	1090	915
Max.drop below ground (mm)	590	590
Max.tilt adjustment(mm)	400	400

# P


# RIPPER(OPTIONAL)


Max.digging depth of 3-Shank Ripper(mm)	467
Max.lift above ground(mm)	559
Weight of 3-Shank Ripper(kg)	1421



#### **OVERALL DIMENSIONS**

Straight-tilt blade





Note: Materials and specifications are subject to change without notice.