

```

#include <stdio.h>
#include <stdlib.h>
struct Node {
    int data;
    struct Node*next;
};

struct Queue {
    struct Node*front;
    struct Node*rear;
};

void initQueue(struct Queue*q) {
    q->front=NULL;
    q->rear=NULL;
}

int isEmpty(struct Queue*q) {
    return(q->front==NULL);
}

void enqueue(struct Queue*q, int value) {
    struct Node*newNode=(struct Node*)malloc(sizeof(struct Node));

    if(newNode==NULL) {
        printf("Heap Overflow\n");
        return;
    }
    newNode->data=value;
    newNode->next=NULL;

    if(q->rear==NULL) {
        q->front=q->rear=newNode;
        return;
    }

    q->rear->next=newNode;
    q->rear=newNode;
}

void dequeue(struct Queue*q) {
    if(isEmpty(q)) {
        printf("Queue Underflow\n");
        return;
    }

```

```

    }

    struct Node*temp=q->front;
    printf("Deleted element:%d\n,temp->data");

    q->front=q->front->next;

    if(q->front=NULL) {
        q->rear=NULL;
        free(temp);
    }
}

void peek(struct Queue*q) {
    if(isEmpty(q)) {
        printf("Queue is Empty\n");
        return;
    }
    printf("Front element:%d\n,q->front->data");
}

void display(struct Queue*q) {
    if(isEmpty(q)) {
        printf("Queue is Empty\n");
        return;
    }

    struct Node*temp=q->front;
    printf("Queue elements:");
    while(temp!=NULL) {
        printf("%d->",temp->data);
        temp=temp->next;
    }
    printf("NULL\n");
}

int main() {
    struct Queue q;
    initQueue(&q);
    enqueue(&q,10);
    enqueue(&q,20);
    enqueue(&q,30);
    display(&q);
    dequeue(&q);
    display(&q);
}

```

```
    peek(&q);  
    return 0;  
}
```