

Dec.1.2021 Copyright 2021 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

PCB LAYOUT

PICK AND PLACE CAP

2.5 REF.
PICK AND PLACE AREA

- NOTE
- 1 CO-PLANARITY IS WITHIN 0.08.
 - 2 LOT No. SHALL BE INDICATED AT THE POSITION AS SHOWN.
 - 3 PLATING
CONTACT AREA : GOLD PLATE $0.75\mu\text{m}$ MIN.
LEAD AREA : GOLD PLATE $0.05\mu\text{m}$ MIN.
UNDER PLATING : NICKEL $2\mu\text{m}$ MIN.
 - 4 PACKING
300 PCS PER TRAY.
 - 5 AS FOR PART No. 3, THE PERFORMANCE REMAINS GOOD EVEN IF THERE IS A RUBBING WOUND BY THE ASSEMBLY PROCESS. AND THE PERFORMANCE REMAINS GOOD EVEN IF THERE IS A DIFFERENCE OF THE COLOR OF PLATING WITH THE MANUFACTURING LOT.

2	LCP	BLACK	UL94V-0	5	PS	
1	COPPER ALLOY	3		4	POLYAMIDE RESIN	
NO.	MATERIAL	FINISH .	REMARKS	3	STAINLESS STEEL	UNDER PLATING: NICKEL $0.2\mu\text{m}$ MIN. OVER PLATING : TIN $1\mu\text{m}$ MIN. LUBRICANT
NO.	MATERIAL	FINISH .	REMARKS	NO.	MATERIAL	FINISH .
UNITS mm		SCALE 5 : 1	COUNT 	DESCRIPTION OF REVISIONS		
HIROSE ELECTRIC CO., LTD.			APPROVED : NM. NISHIMATSU	15.10.27	DRAWING NO.	EDC-126723-30-00
			CHECKED : KN. ICHIKAWA	15.10.27	PART NO.	ZX80-B-5P<30>
			DESIGNED : TS. ITO	15.10.27	CODE NO.	CL242-0051-0-30
			DRAWN : AK. AKIYAMA	15.10.27		

Dec.1.2021 Copyright 2021 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

