Scanners

Uniden SDS200
Display

← back

SIMPLE DISPLAY MODE

Conventional and Trunked mode share the same color scheme, but different display items are available for each mode.

F	Option_1	Option_2	Option_3	Option_4	SIG	BAT
SP0	Option_5	Option_6	Option_7	Option_8	KEY	DIR

```
System Name (30 char x 2)
```

System Option		AVOID

```
Dept Name (30 char x 2)
```

Dept Option		AVOID

```
Channel Name (30 char x 2)
```

Channel Option		AVOID

Option A_1		Option B_1	

ICON1	ICON2	ICON3	ICON4	ICON5	ICON6	ICON7	ICON8	ICON9	ICON10

Soft Key 1	SP	Soft Key 2	SP	Soft Key 3

DETAIL DISPLAY MODE

F	Option_1	Option_2	Option_3	Option_4	SIG	BAT
Info area 1			Option_7	Option_8	KEY	DIR
Info area 2		Option C 1				
Info area 3		Option C 2				

```
System Name
```

System Option		AVOID

```
Dept Name   (30)
```

Dept Option		AVOID

```
Channel Name (30)
```

Channel option		AVOID

Option A_1		Option B_1	
Option A_2		Option B_2	
Option A_3		Option B_3	
Option A_4		Option B_4	
Option A_5		Option B_5	

ICON1	ICON2	ICON3	ICON4	ICON5	ICON6	ICON7	ICON8	ICON9	ICON10

Soft Key 1	SP	Soft Key 2	SP	Soft Key 3

SEARCH/TONE-OUT/WEATHER MODE

You can individually set colors for Search/Close Call mode, Weather Mode, and Tone-Out mode, but they share the same general layout. You can only set display option items for Search mode.

F	Option_1	Option_2	Option_3	Option_4	SIG	BAT
Info area 1			Option_7	Option_8	KEY	DIR
Info area 2		Option C 1				
Info area 3		Option C 2				

```
Primary 1 (30 x 1)

Primary 2 (30 x 1)

Primary 3 (30 x 1)
```

Sub Info		Mod	AVOID	HOLD
Detail info				

Option A_1					Option B_1				
Option A_2					Option B_2				
Option A_3					Option B_3				
ICON1	ICON2	ICON3	ICON4	ICON5	ICON6	ICON7	ICON8	ICON9	ICON10
Soft Key 1				Soft Key 2				Soft Key 3	

AVAILABLE ITEMS

The below tables outline what display items are available. Note that not all items are possible for all display fields.

ITEM	SAMPLE	HUGE 22	LARGE 16/14	SHORT 5 CHAR
Favorites List Name		O	O	-
Site Name		O	O	-
Unit ID Name		O	O	-
Frequency	xxxx.xxxxMHz	O	O	-
TGID	TGID:xxxxxxxx	O	O	-
RSSI	RSSI:x.xxV	-	O	-
System type	DMR One Frequency	O	O	-
System/Network ID	Net ID : xxxx	O	O	-
	Sys ID : xxxx			
Site ID	Site ID : xxxx	O	O	-
Unit ID	UID : 12345678	O	O	-
LCN	LCN:4096		O	-
Number Tag	Tag:FF-SS-CC	O	O	-
Volume/Squelch	VOL=15 SQL=15	O	O	-
Volume	V:15	-	-	O
Squelch	S:15	-	-	O
Digital Error count	Err:xx		O	-

ITEM	SAMPLE	HUGE 22	LARGE 16/14	SHORT 5 CHAR
CTCSS/DCS/NAC	DCS031		O	
Latitude	-97.0483		O	
Longitude	104.8292		O	
Noise	282		O	
RF Sub System (RFSS) ID	210h		O	
RSSI Graph	▮		O	
Service Type	Law Talk		O	
Attenuator	G-ATT	-	-	O
Site Name	Simulcast		O	
USB1 vbus voltage	4.982		O	
USB2 vbus voltage	5.002		O	
Volume & Squelch	V:9 S:3		O	
WACN	12		O	
P25 Status	P25-2	-	-	O
Date	mm/dd	-	-	O
Time	xx:xx	-	-	O
Modulation	NFM	-	-	O
Broadcast Screen	SCR			O
Close Call	CC (icon)			O

Digital Status	P25			O
GPS	GPS			O
IF eXchange	IFX			O
P-Channel	**P**			O
Priority Scan	PRI			O
REC	REC			O
Repeater Find	REP			O
TDMA Slot	0		O	O
Volume Offset	V+1			O
WX Priority	WX			O

Icon Area

Item	Sample
Priority Scan	PRI
Close Call	CC (icon)
WX Priority	WX
REC	REC
IF eXchange	IFX
GPS	GPS
Broadcast Screen	SCR
Repeater Find	REF
Volume Offset	V+x
Modulation	NFM
P-Channel	P