

Spec Sheet

PERFORMANCE	
Accuracy Class – %	0.05
Nonlinearity – % range	±0.02
Sample Rate – per channel – samples/	sec 48,000 synchronous
Digital Output Data Rate – values/sec	0.75 to 48,000
Resolution – bit	24
Resolution – noise limited	> 100,000 parts @ 10/s data rate > 20,000 parts @ 2000/s data rate > 9,400 parts @ 12,000/s data rate
Signal Input Filter – (3dB) – Hz	28, 850, 11.4k 1st order, switchable
Digital Onput Filter – (3dB) – Hz Individually configurable for each channel	0.18 to 15K includes high pass, low pass, band pass and band stop
SENSOR INPUTS	
Input Channels	8
Bridge Input Range – mV/V	2.0, 3.5, or 7.0
Bridge Input Impedance – MΩ – (pF)	> 20 (300)
Bridge Excitation Voltage – VDC	8.75, 5, or 2.5
Bridge Excitation Current – mA	mA 135
Bridge Input Type – wire	4 or 6
Bridge Completion – Ω	1/4 and 1/2, 120, 350 or 1000
CMMR – dB – DC – 100 Hz	>120, >100
Analog Input Range – VDC	±10
Analog Input Resistance – MΩ	10
PT1000 thermocouple – Ω	1000
ANALOG OUTPUTS	
Outputs types – V – Ma Individually configurable for each channel	±10, ±5, 0-5, 0-10, 4-20, 0-20
Analog Output Scaling	via software, active scaling capability
Analog Output Resolution – bit	16 over scaled range
Analog Output Update Rate – Hz	Up to 48K
DIGITAL INPUTS/OUTPUTS	
DIOs	16 configurable

USB – 8 channel packets – bit – /sec	16 integer, 48K, raw data 24 integer, 24K, raw data 32 floating point, 9.6K, scaled data 6-axis sensor: 32 floating point, 6K scaled data
ENVIRONMENTAL	
Operating Temperature Range – °F	+32 to +122
Storage Temperature Range – °F	-4 to +158
POWER	
Supply – VDC	12-28
Supply – Watt	< 12
CONNECTION TYPE	
Connection Type	44-pin High Density D-Sub Connector