

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B

1.0 SCOPE

THIS DOCUMENT PROVIDES THE REQUIREMENTS FOR THE PROCUREMENT OF
SODIUM PHOSPHATE, TRIBASIC DODECAHYDRATE

2.0 LIST OF APPLICABLE DOCUMENTS

IF A SUPPLIER QUOTES TO A LATER REVISION OF THE DRAWING (OR CATALOG ITEM) THAN SPECIFIED BELOW, SUBMITTAL OF QUOTE SHALL INCLUDE TWO (2) COPIES OF THE REVISED DOCUMENT AND AN EVALUATION OF THE INTERCHANGEABILITY. THE FOLLOWING DOCUMENTS AND CHANGE DATA ARE APPLICABLE TO THE EXTENT SPECIFIED IN THIS IRPOD, THE DRAWINGS, OR OTHER DOCUMENTS INVOKED BY THIS IRPOD. CONTRACTING AGENCY APPROVAL IS REQUIRED TO USE EARLIER SPECIFICATION VERSIONS THAN THOSE LISTED HEREIN, EXCEPT AS IDENTIFIED BELOW. IF NO DOCUMENT VERSION IS LISTED, THEN ANY VERSION OF THE DOCUMENT MAY BE USED.

RAW MATERIAL REQUIRED HEREIN MAY HAVE BEEN PROCESSED OR TESTED (FOR EXAMPLE, HEAT TREATED OR ULTRASONICALLY TESTED) AS REQUIRED BY THE RAW MATERIAL SPECIFICATION PRIOR TO RECEIPT OF THIS ORDER USING PREVIOUS VERSIONS OF PROCESSING OR TESTING SPECIFICATIONS. THIS PROCESSING AND TESTING NEED NOT BE REPEATED IF:

- 1.IT COMPLIED WITH THE APPLICABLE REQUIREMENTS OF THE
PROCESSING/TESTING SPECIFICATION VERSIONS IN EFFECT AT THE TIME OF
THE ACTUAL PROCESSING OR TESTING AND;
- 2.ALL REQUIREMENTS OF THE RAW MATERIAL SPECIFICATION VERSION LISTED
HEREIN HAVE BEEN SATISFIED.

SECTION 6.0 IDENTIFIES SPECIAL REQUIREMENTS FOR SUBMITTAL OF THE PROCEDURES USED FOR COMPLETED PROCESSING AND TESTING. ALL PROCESSING AND TESTING PERFORMED AFTER RECEIPT OF THIS ORDER SHALL CONFORM TO THE PROCESSING/TESTING SPECIFICATION VERSIONS LISTED HEREIN.

DOCUMENT NUMBER	VERSION	TITLE
-----------------	---------	-------

FEDERAL SPECIFICATIONS

PPP-C-186	C NOTICE 1	CONTAINERS, PACKAGING AND PACKING FOR DRUGS, CHEMICALS, AND PHARMACEUTICALS
PPP-C-2020	A, NOTICE 1	CHEMICALS, LIQUID, DRY, AND PASTE, PACKAGING OF

FEDERAL STANDARDS

FED-STD-313	D, NOTICE 1	MATERIAL SAFETY DATA, TRANSPORTATION SAFETY DATA AND DISPOSAL DATA FOR HAZARDOUS MATERIAL FURNISHED TO GOVERNMENT ACTIVITIES
FED-STD-595	B	COLORS USED IN GOVERNMENT PROCUREMENT

MILITARY STANDARDS

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B

+ MIL-STD-129

R W/CHANGE 2

MARKING FOR SHIPMENT AND STORAGE

PUBLICATIONS

+ AOR-00256-BMPC-17

ORIGINAL

ADDITIONAL ORDERING REQUIREMENTS FOR X2
CHEMICAL ITEMS (U)

DRAWINGS

5577B18

B

BECHTEL BETTIS, INC. METAL CAN FOR
PACKAGING SODIUM PHOSPHATE, TRIBASIC
(1H 6810-00-043-0758X2)

OTHERS

TITLE 29

OCCUPATIONAL SAFETY AND HEALTH
ADMINISTRATION REQUIREMENTS
CODE OF FEDERAL REGULATIONS
CHAPTER XVII

TITLE 49

DEPARTMENT OF TRANSPORTATION CODE OF FEDERAL
REGULATIONS
HAZARDOUS MATERIAL REGULATIONS
PARTS 100 - 199

AMERICAN CHEMICAL

11TH EDITION

REAGENT CHEMICALS, AMERICAN CHEMICAL SOCIETY
SPECIFICATIONS

SOCIETY (ACS)

REAGENT CHEMICALS, AMERICAN CHEMICAL SOCIETY
SPECIFICATIONS

PUBLICATION

REAGENT CHEMICALS, AMERICAN CHEMICAL SOCIETY
SPECIFICATIONS

UNIFORM FREIGHT
CLASSIFICATION

NATIONAL RAILROAD FREIGHT COMMITTEE

NATIONAL CLASSIFICATION
BOARD

NATIONAL MOTOR FREIGHT CLASSIFICATION

+ LATER VERSIONS (IE: REVISIONS, AMENDMENTS, CHANGE NOTICES
AND/OR INTERIM CHANGES) OF DOCUMENTS IDENTIFIED BY THIS SYMBOL
MAY BE USED IN THE PERFORMANCE OF THE CONTRACT. WHICHEVER
VERSION IS USED MUST BE USED IN ITS ENTIRETY. THE LATER
VERSION MAY BE IDENTIFIED AS "MIL-DTL-" OR "MIL-PRF-" AS
APPLICABLE, WHICH IS EQUIVALENT TO "MIL-#-" (WHERE # IS AN
ALPHA CHARACTER).

3.0 TECHNICAL REQUIREMENTS

SODIUM PHOSPHATE TR

8723-0112

NON-DEFINITIVE UNIT OF ISSUE

CONTAINER - 112 OUNCE

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B

3.1 MATERIAL REQUIREMENTS

SODIUM PHOSPHATE TR 8723-0112

THE MATERIAL SHALL CONFORM TO THE REQUIREMENTS FOR SODIUM PHOSPHATE, TRIBASIC, DODECAHYDRATE, OF THE AMERICAN CHEMICAL SOCIETY (ACS) SPECIFICATIONS FOR REAGENT CHEMICALS.

SHELF LIFE OF THIS ITEM IS FORTY-EIGHT MONTHS.

THIS ITEM SHALL BE SUPPLIED WITH AT LEAST 85 PERCENT OF ITS SHELF LIFE REMAINING AT TIME OF SHIPMENT.

3.2 MANUFACTURING AND PROCESS REQUIREMENTS

SODIUM PHOSPHATE TR 8723-0112

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B

A. MERCURY CONTAMINATION

THIS PRODUCT SHALL NOT CONTAIN AND SHALL NOT BE CONTAMINATED BY MERCURY NOR MERCURY COMPOUNDS. DURING THE MANUFACTURING PROCESS, TESTS, AND INSPECTIONS, THE PRODUCT SHALL NOT HAVE COME IN DIRECT CONTACT WITH MERCURY, NOR ANY OF ITS COMPOUNDS, NOR ANY MERCURY CONTAINING DEVICE EMPLOYING A SINGLE BOUNDARY OF CONTAINMENT. THE SPECIFIC LIMIT IS THAT THIS ITEM SHALL CONTAIN LESS THAN OR EQUAL TO 50 PPB MERCURY WHEN TESTED AS SPECIFIED IN SECTION 4.6 OF THIS IRPOD.

B. FOREIGN MATERIAL EXCLUSION

THE SODIUM PHOSPHATE, TRIBASIC, DODECAHYDRATE MATERIAL SHALL BE UNIFORM AND SHALL CONFORM TO THE FOREIGN MATERIAL INSPECTION REQUIREMENTS OF SECTION 4.6 OF THIS IRPOD. EXAMPLES OF FOREIGN MATERIAL INCLUDE, BUT ARE NOT LIMITED TO, RUST, GLASS OR DIRT PARTICLES; PLASTIC, CERAMIC, WOOD OR METAL CHIPS, CARDBOARD FIBERS, CLOTH FIBERS, BRUSH BRISTLES AND PAINT CHIPS. PRODUCTION OPERATIONS AND INSPECTION PROCEDURES SHALL BE CONDUCTED SO AS TO PREVENT THE INTRODUCTION OF FOREIGN MATERIAL.

SUCH OPERATIONS MAY INCLUDE, BUT ARE NOT LIMITED TO, THE FOLLOWING PRECAUTIONS: ENSURING THAT THE CANS ARE FREE FROM FOREIGN MATERIAL PRIOR TO FILL, PROVIDING AN AREA FOR FILL OPERATIONS WHICH IS FREE OF DIRT AND DEBRIS, AND MAINTAINING THE FILL EQUIPMENT IN A CLEAN CONDITION.

INSPECTION FOR FOREIGN MATERIAL SHALL BE CONDUCTED IN ACCORDANCE WITH SECTION 4.6.C OF THIS IRPOD. IN THE EVENT FOREIGN MATERIAL IS DETECTED, THIS FINDING SHALL NOT PRECLUDE CONDUCTING ALL OTHER REQUIRED INSPECTIONS AND TESTS. DISPOSITION OF THE LOT WITH RESPECT TO FOREIGN MATERIAL SHALL BE DETERMINED IN ACCORDANCE WITH THE FOREIGN MATERIAL EXCLUSION REQUIREMENTS OF SECTION 4.6.C.8.

C. CONTAINER REQUIREMENTS

THE CONTAINER SHALL CONFORM TO THE SPECIFICATIONS OF BECHTEL BETTIS, INC. DRAWING 5577B18 WHICH INCLUDES THE FOLLOWING SIGNIFICANT REQUIREMENTS:

1. MATERIAL

THE METAL CONTAINER SHALL CONSIST OF 135 POUND, 0.50 ELECTROLYTIC TINPLATE.

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B

2. CONSTRUCTION

THE METAL CAN SHALL BE A ROUND CORNERED, SQUARE CROSS-SECTION CAN, WITH A SQUARE SLIP COVER AS SHOWN IN BECHTEL BETTIS, INC. DRAWING 5577B18. THE BODY SHALL HAVE A WELDED VERTICAL SEAM AND SHALL BE BEADED JUST BELOW THE COVEREDGE. THE TOP EDGES SHALL BE HEMMED INSIDE. THE BOTTOM SHALL BE DOUBLE SEAMED TO THE BODY. THE SQUARE SLIP COVER SHALL BE TIGHT FITTING WITH HEMMED EDGES.

3. DIMENSIONS

THE WALL THICKNESS OF THE CAN, THE CAN BOTTOM, AND THE SLIP COVER SHALL NOT BE LESS THAN 0.014 INCH THICK. THE INSIDE BODY SHALL BE A NOMINAL 5.0 INCHES BY 5.0 INCHES IN CROSS SECTION BY 10.0 INCHES IN HEIGHT. THE SQUARE SLIP COVER TOP SHALL BE A NOMINAL 0.50 INCH IN HEIGHT.

4. INSIDE COATING

THE INSIDE OF THE CAN AND THE SLIP COVER SHALL BE COATED WITH CLEAR, NON-STICK, MOISTURE RESISTANT LACQUER (E.G., PHENOLIC OR VINYL).

5. OUTSIDE COATING

THE TOP, BOTTOM AND SIDES, INCLUDING THE VERTICAL SEAM AREA SHALL BE PAINTED WITH ONE COLOR OF PAINT THAT SHALL BE RESISTANT TO PEELING AND CHIPPING. THE COLOR OF THE PAINT SHALL BE APPROXIMATELY NUMBER 25109, SEMIGLOSS BLUE OF FEDERAL STANDARD 595. THE PAINT THAT IS USED SHALL BE ACCEPTABLE FOR APPLICATION OF LETTERING BY A SILK SCREENING PROCESS.

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B

6. LETTERING

THE LETTERING SHALL BE STANDARD BLOCK PRINT THAT WILL NOT FADE OR RUB OFF. THE LETTERING MAY BE APPLIED BY A SILK SCREENING PROCESS, OR MAY BE LITHOGRAPHED WHEN THE OUTSIDE COATING IS APPLIED. THE LETTERING SHALL BE IN BLACK EXCEPT THAT THE DESTROY DATE SHALL BE APPROXIMATELY NUMBER 22246 SEMIGLOSS ORANGE OF FEDERAL STANDARD 595. THE LOT OR BATCH NUMBER SHALL BE EITHER BLACK OR ORANGE.

ALL LETTERING SHALL BE SUFFICIENTLY ADHERENT THAT NO SMUDGING OCCURS. THE SIZES AND ARRANGEMENTS OF THE LETTERING AND THE LOCATION OF THE SIDE SEAM OF THE CAN SHALL BE IN ACCORDANCE WITH BECHTEL BETTIS, INC. DRAWING 5577B18 WITH THE LETTERING CENTERED TO THE FULLEST EXTENT PRACTICABLE AND SUCH THAT A MINIMUM 1/8-INCH MARGIN EXISTS BETWEEN EACH EDGE AND ALL TEXT ON THE TOP, BOTTOM, AND SIDES OF THE CAN UNLESS OTHERWISE INDICATED.

7. PACKAGING

THE SODIUM PHOSPHATE, TRIBASIC, DODECAHYDRATE MATERIAL SHALL BE PACKAGED IN A POLYETHYLENE BAG CONFORMING TO GROUP F, CLASS 2 OF FEDERAL SPECIFICATION PPP-C-186 SEALED WITH ARE SEALABLE TWIST TYPE SEALING STRIP. EACH BAG SHALL CONTAIN 7.0 +/- 0.25 POUNDS OF SODIUM PHOSPHATE, TRIBASIC, DODECAHYDRATE MATERIAL. THE POLYETHYLENE BAG SHALL THEN BE CONTAINED IN THE ABOVE DESCRIBED CAN WITH THE LID OF THE CAN SEALED WITH VINYL TAPE.

D. UNIT OF ISSUE

SEVEN (7) POUNDS OF SODIUM PHOSPHATE, TRIBASIC, DODECAHYDRATE, IN A POLYETHYLENE BAG IN A METAL CAN.

E. SHELF LIFE

THE DESIGNATED SHELF LIFE IS FORTY-EIGHT (48) MONTHS. THIS ITEM SHALL BE SUPPLIED WITH AT LEAST EIGHTY-FIVE (85) PERCENT (FORTY-ONE (41) MONTHS) SHELF LIFE REMAINING AT TIME OF SHIPMENT.

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B

F. LOT

ALL SODIUM PHOSPHATE, TRIBASIC, DODECAHYDRATE, PRODUCED AT ONE (1) TIME, BY ONE (1) MANUFACTURER, AT ONE (1) PLANT, FROM THE SAME MATERIALS, AND UNDER ESSENTIALLY THE SAME MANUFACTURING CONDITIONS PROVIDED THE OPERATION IS CONTINUOUS. IN THE EVENT THE PROCESS IS A BATCH OPERATION, EACH BATCH (SEE 3.2.G BELOW) SHALL CONSTITUTE A LOT. EVEN IF A BATCH IS LARGER, EACH LOT PACKAGED FOR DELIVERY SHALL BE LIMITED TO A MAXIMUM OF FIVE HUNDRED (500) CANS OF SODIUM PHOSPHATE, TRIBASIC, DODECAHYDRATE.

G. BATCH

THAT QUANTITY OF MATERIAL WHICH HAS BEEN MANUFACTURED BY SOME UNIT CHEMICAL PROCESS, OR SUBJECTED TO SOME PHYSICAL MIXING OPERATION, INTENDED TO MAKE THE FINAL PRODUCT SUBSTANTIALLY UNIFORM.

4.0 QUALITY ASSURANCE PROVISIONS

SODIUM PHOSPHATE TR 8723-0112

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B

4.1 CONTRACTOR INSPECTION AND TESTING SYSTEM

THE CONTRACTOR SHALL MAINTAIN COMPLETE RECORDS FOR ALL INSPECTIONS AND TESTS PERFORMED ON THE FINAL CONTAINERS AND THEIR CONTENTS. THE RECORDS SHALL BE TRACEABLE BY THE CONTRACTOR'S LOT OR BATCH NUMBER. THE CONTRACTOR SHALL RETAIN THESE RECORDS FOR FOUR (4) YEARS FOLLOWING DELIVERY TO THE GOVERNMENT. THE RECORDS SHALL BE MADE AVAILABLE FOR GOVERNMENT REVIEW UPON WRITTEN REQUEST DURING THIS PERIOD. THESE RECORDS SHALL INDICATE THE NATURE AND NUMBER OF OBSERVATIONS MADE, THE NUMBER AND TYPE OF DEFICIENCIES FOUND, THE QUANTITIES APPROVED AND REJECTED, AND THE SPECIFIC ACTIONS TAKEN TO CORRECT THE DEFICIENCIES. THESE RECORDS SHALL INCLUDE HIGH MAGNIFICATION (AT LEAST 45X) DIGITAL PHOTOGRAPHS OF ANY FOREIGN MATERIAL IDENTIFIED DURING INSPECTION THAT CLEARLY INDICATE THE SIZE OF THE FOREIGN MATERIAL (E.G., A LINEAR SCALE IS INCLUDED IN THE PHOTOGRAPH).

4.2 TEST EQUIPMENT

ALL GAGES, MEASURING AND TEST EQUIPMENT USED IN THE TESTS, INSPECTION AND PROCESSING OF FILLED CANS UNDER THIS IRPOD SHALL BE CALIBRATED TO CERTIFIED STANDARDS THAT HAVE KNOWN, VALID RELATIONSHIPS TO NATIONALLY ACCEPTED INDUSTRY STANDARDS. THE CALIBRATION FREQUENCY FOR EACH DEVICE SHALL BE BASED ON ITS STABILITY, PURPOSE AND USAGE. A POSITIVE MEANS (SUCH AS STICKERS) SHALL BE PROVIDED TO IDENTIFY THE CALIBRATION INTERVAL, LAST DATE OF CALIBRATION AND DATE CALIBRATION IS DUE FOR EACH DEVICE. COMPLETE WRITTEN RECORDS OF CALIBRATION DATA TRACEABLE TO THE INDIVIDUAL TEST DEVICES SHALL BE AVAILABLE FOR GOVERNMENT REVIEW FOR UP TO FOUR (4) YEARS FOLLOWING DELIVERY OF THE CANS TESTED WITH THE CALIBRATED EQUIPMENT.

4.3 RESPONSIBILITIES

THE CONTRACTOR IS RESPONSIBLE FOR THE PERFORMANCE OF ALL INSPECTIONS AND TEST REQUIREMENTS IN SECTIONS 4.4 AND 4.6 OF THIS IRPOD. THE NUMBER OF SAMPLES TO BE TESTED SHALL BE IN ACCORDANCE WITH TABLE 1 OF SECTION 4.4 OF THIS IRPOD. THE CONTRACTOR MAY USE HIS OWN OR ANY OTHER FACILITIES SUITABLE FOR THE PERFORMANCE OF THE REQUIRED INSPECTIONS AND TESTS. THE FINAL PRODUCT SHALL BE MADE AVAILABLE FOR GOVERNMENT TESTING AND INSPECTION. IN ADDITION TO THE SPECIFIED TESTS AND INSPECTIONS IN THIS IRPOD, THE GOVERNMENT RESERVES THE RIGHT TO PERFORM ANY ADDITIONAL

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B

INSPECTIONS AND TESTS DEEMED NECESSARY TO ASSURE SUPPLIES AND SERVICES CONFORM TO PRESCRIBED REQUIREMENTS. THE CONTRACTOR SHALL ALSO PROVIDE THE FOLLOWING:

A. A WRITTEN CERTIFICATION IN ACCORDANCE WITH THE CONTRACT DELIVERY SCHEDULE THAT EACH MANUFACTURER'S LOT OF SODIUM PHOSPHATE, TRIBASIC, DODECAHYDRATE MEETS ALL THE REQUIREMENTS OF THE AMERICAN CHEMICAL SOCIETY SPECIFICATIONS FOR REAGENT CHEMICALS.

IF THE VENDOR FOR THIS CHEMICAL IS NOT THE MANUFACTURER, THE VENDOR SHALL SUBMIT THE CERTIFICATION DOCUMENTATION PROVIDED BY THE ACTUAL MANUFACTURER (DEFINED AS THE ENTITY WHO LAST PROCESSED THE MATERIAL FROM THE LIQUID FORM TO THE FINAL DRY MATERIAL). THE CERTIFICATION SHALL BE TRACEABLE BY LOT NUMBER FROM THE MANUFACTURER TO THE SUPPLIER, AS ADDITIONAL VERIFICATION THAT THIS LOT OF CHEMICALS MEETS THE REQUIREMENTS FOR ACS GRADE CHEMICALS.

B. CERTIFIED TEST RESULTS IN ACCORDANCE WITH THE CONTRACT DELIVERY SCHEDULE SHOWING THAT THE APPROPRIATE NUMBER OF REPRESENTATIVE SAMPLES OF EACH LOT OF FINISHED PRODUCT WERE SELECTED IN ACCORDANCE WITH SECTION 4.4 OF THIS IRPOD AND WERE TESTED AND FOUND TO MEET THE QUANTITATIVE REQUIREMENTS OF SECTION 4.0 OF THIS IRPOD.

C. A WRITTEN CERTIFICATION IN ACCORDANCE WITH THE CONTRACT DELIVERY SCHEDULE THAT THE ITEMS ANALYZED AND OFFERED FOR DELIVERY ARE THE SAME.

4.4 CONTRACTOR INSPECTION AND TESTING IN PREPARATION FOR DELIVERY

SAMPLING FOR INSPECTION OF PREPARATION FOR DELIVERY SHALL BE FROM COMPLETED CANS OFFERED FOR DELIVERY. SAMPLES SHALL BE CHOSEN RANDOMLY AND IN ACCORDANCE WITH TABLE 1.

=====	
TABLE 1	

SAMPLING FOR INSPECTION AND TESTING	

LOT SIZE	NUMBER OF CANS
-----	-----
< OR = 25	4
26 TO 150	6
151 TO 500	10
=====	

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B

EACH SELECTED CAN SHALL BE INSPECTED FOR CONFORMANCE WITH THE REQUIREMENTS SPECIFIED IN SECTION 3.2.C, CONTAINER REQUIREMENTS, SECTION 3.2.B, FOREIGN MATERIAL EXCLUSION, AND SECTION 5.0, PREPARATION FOR DELIVERY, OF THIS IRPOD. FAILURE OF ANY ONE (1) CAN CONSTITUTES FAILURE OF THE ENTIRE LOT. A REJECTED LOT MAY BE RESUBMITTED FOR INSPECTION PROVIDED THE CONTRACTOR HAS CORRECTED ALL NON-CONFORMING ATTRIBUTES.

4.5 GOVERNMENT INSPECTION AND TESTING

FOLLOWING COMPLETION OF SECTION 4.4, THE COGNIZANT DEFENSE CONTRACT MANAGEMENT AGENCY (DCMA) QUALITY ASSURANCE REPRESENTATIVE (QAR) WILL SELECT RANDOM CANS FROM EACH LOT IN ACCORDANCE WITH WITH TABLE 1 OF THIS IRPOD AND ONE (1) ADDITIONAL RANDOM CAN FROM EACH LOT FOR RETENTION AS A LIBRARY SAMPLE AT PSNS&IMF (CAN SHALL NOT BE OPENED BY THE QAR).

EACH SAMPLE CAN SELECTED IN ACCORDANCE WITH TABLE 1 SHALL BE INDIVIDUALLY SUBSAMPLED INTO A ONE (1) POUND SAMPLE CONTAINED IN A SEALED POLYETHYLENE BOTTLE FOR GOVERNMENT LABORATORY TESTING. THE QAR SHALL WITNESS THE SUBSAMPLING AND PACKAGING OF THE SUBSAMPLES. THE VENDOR SHALL PREPARE THE SELECTED SAMPLES FOR DELIVERY IN ACCORDANCE WITH THIS IRPOD AND SHALL SHIP THEM WITH FORM DD-1222, A SAFETY DATA SHEET (SDS), AND A COPY OF THE DATA REQUIRED IN SECTION 4.3 TO THE FOLLOWING ADDRESS:

PUGET SOUND NAVAL SHIPYARD & IMF
CODE 134.4, BUILDING 59
1400 FARRAGUT AVE
BREMERTON, WA 98314-2025

ON EACH UNIT CONTAINER AND EXTERIOR SHIPPING CONTAINER USED TO SHIP SAMPLES FOR GOVERNMENT INSPECTION AND TESTING, THE CONTRACTOR SHALL PLACE A PROMINENT, BRIGHTLY COLORED LABEL THAT READS "PLT SAMPLE FOR PSNS 134.4 LABORATORY USE ONLY." THIS LABEL SHOULD BE APPLIED DIRECTLY TO THE CONTAINER WHERE POSSIBLE OR AFFIXED AS A TAG, IF NECESSARY.

ANY FOREIGN MATERIAL OBSERVED DURING THE SUBSAMPLING PROCESS SHOULD BE REMOVED, RETAINED, AND SHIPPED TO PSNS&IMF WITH THE SELECTED SUBSAMPLES.

THE GOVERNMENT INSPECTION AND TESTING MUST DEMONSTRATE CONFORMANCE WITH THE REQUIREMENTS OF THIS IRPOD BEFORE THE LOT OF MATERIAL WILL BE ACCEPTED. PUGET SOUND NAVAL SHIPYARD SHALL PROVIDE NOTIFICATION TO THE PROCURING CONTRACTING OFFICER, WHO WILL NOTIFY THE CONTRACTOR AND DCMA QAR.

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B

4.6 ACCEPTANCE TESTING

THE CONTRACTOR MAY USE ALTERNATE TEST METHODS TO ENSURE THAT THE DELIVERED PRODUCT CONFORMS TO THE IRPOD REQUIREMENTS. HOWEVER, IN THE EVENT OF A DISAGREEMENT BETWEEN THE CONTRACTOR AND THE GOVERNMENT, THE TEST METHOD IDENTIFIED HERE SHALL BE USED AS THE REFEREE METHOD. ACCEPTANCE TESTING SHALL CONSIST OF THE TESTS DESCRIBED BELOW. 50% OF THE SAMPLES SHALL UNDERGO THE TESTING IN PARAGRAPHS (A) AND (B), BELOW. ALL OF THE SAMPLES SHALL UNDERGO THE TESTING IN PARAGRAPH (C).

A. GOVERNMENT TESTING SHALL CONSIST OF ALL THE TESTS SPECIFIED IN THE AMERICAN CHEMICAL SOCIETY SPECIFICATIONS FOR REAGENT CHEMICALS FOR SODIUM PHOSPHATE, TRIBASIC, DODECAHYDRATE.

B. MERCURY CONTENT

THE MERCURY CONTENT OF THIS CHEMICAL SHALL BE DETERMINED BY ATOMIC ABSORPTION SPECTROMETRY USING ENVIRONMENTAL PROTECTION AGENCY METHOD 7470 FOR LIQUIDS OR METHOD 7471 FOR SOLIDS. FAILURE OF ONE (1) OF THE SUBMITTED ACCEPTANCE SAMPLES TO MEET THE MERCURY SPECIFICATION OF SECTION 3.2.A SHALL BE CAUSE FOR REJECTION OF THE LOT.

C. VISUAL INSPECTION FOR FOREIGN MATERIAL

1. OBTAIN A REPRESENTATIVE SAMPLE OF APPROXIMATELY 250 GRAMS (+5.0/- 0.0 GRAMS) OF MATERIAL.
- A. REDUCE THE SAMPLE SIZE TO OBTAIN THE ABOVE QUANTITY FROM LARGER RECEIVED SAMPLES EMPLOYING GOOD SAMPLING PRACTICES, INCLUDING BUT NOT LIMITED TO CONING AND QUARTERING, ROLLING AND QUARTERING, OR APPLICATION OF A MECHANICAL SAMPLE SPLITTER, DIVIDER, OR RIFFLER.

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B

2. SPREAD THE MATERIAL COMPRISING THE 250 GRAM SAMPLE, A SMALL PORTION AT A TIME, ON A PIECE OF CLEAN, WHITE PAPER.
- A. BREAK UP CLUMPS, IF NECESSARY.

B. THE SAMPLE MAY BE SLOWLY POURED FROM THE CONTAINER TO FORM A LAYER NO MORE THAN SEVERAL GRANULES THICK FOR INSPECTION.

C. SPREAD IN A THIN LAYER SO THAT NONE OF THE GRANULES ARE HIDDEN FROM VIEW.

D. ENSURE THAT FOREIGN MATERIAL IS NOT INTRODUCED (CLOTHING, ENVIRONMENT, UTENSILS) BY THIS INSPECTION PROCEDURE.
3. VIEW THE MATERIAL FROM NORMAL READING DISTANCE (APPROXIMATELY 35 CM) IN A LABORATORY ENVIRONMENT WITH CONVENTIONAL FLUORESCENT OVER-HEAD LIGHTING, AND BY A PERSON WITH NORMAL OR CORRECTED VISUAL ACUITY.
4. VIEW THE MATERIAL AT 90 DEGREES, 180 DEGREES, AND 270 DEGREES RELATIVE TO THE INITIAL VIEWING DIRECTION.
5. CONTINUE VIEWING ALL PORTIONS OF THE SELECTED SAMPLE SIZE BY REPETITION OF STEPS 2 THROUGH 4.
6. REMOVE ANY AND ALL VISIBLE FOREIGN MATERIAL FROM THE OBSERVED SAMPLE SIZE AND DETERMINE THE INDIVIDUAL MASS, TOTAL MASS, AND NUMBER OF FOREIGN PIECES COMPRISING THIS MASS.
- A. ISOLATE FOREIGN MATERIAL FROM CHEMICAL PARTICULATE AND USE A BALANCE WITH RESOLUTION OF 0.1 MG TO DETERMINE THE MASS. IF THE FOREIGN MATERIAL INDIVIDUAL MASS IS TOO SMALL TO MEASURE, NOTE IT AS ~LT~0.1 MG.

B. FOR FOREIGN MATERIAL WITH INDIVIDUAL MASS THAT IS TOO SMALL TO MEASURE, MEASURE A TOTAL MASS AND SPECIFY THE NUMBER OF PIECES COMPRISING THIS MASS.

C. IF POSSIBLE, IN ADDITION TO SIZE, MASS, AND NUMBER, CHARACTERIZE ANY FINDING OF FOREIGN MATERIAL FOUND WITHIN THE 250 GRAM SAMPLE BY TYPE.

D. PRESERVE FOREIGN MATERIAL IN AN APPROPRIATE CONTAINER, FOR FURTHER CHARACTERIZATION.
7. RESULTS FROM MULTIPLE 250 GRAM SAMPLES FOR A SINGLE LOT SHALL BE REPORTED INDIVIDUALLY, AND NOT AVERAGED UNTIL THE

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B

CONCLUSION OF THE INSPECTION PROCESS FOR ALL SAMPLES.

8. BASED ON THE COLLECTIVE FINDING OF FOREIGN MATERIAL IDENTIFIED DURING SUBSAMPLING AND DURING THE DETAILED VISUAL INSPECTION OF THE SUBSAMPLES, INDIVIDUAL LOTS OF POWDERED CHEMICAL ARE ACCEPTABLE IF THE FOLLOWING CRITERIA ARE MET:
- A. THE NUMBER OF PARTICLES AND FIBERS OF FOREIGN MATERIAL DETECTED DURING SUBSAMPLING OF UNIT-OF-ISSUE CONTAINERS AND DURING VISUAL INSPECTION OF THE CORRESPONDING SUBSAMPLES SHALL BE NO MORE THAN AN AVERAGE OF 2.0 PER CONTAINER (E.G., AT MOST A TOTAL OF 20 PIECES OF FOREIGN MATERIAL ARE IDENTIFIED IN TEN (10) CONTAINERS INSPECTED FOR THE LARGEST LOT SIZE);
- B. FROM THE TOTAL QUANTITY OF FOREIGN MATERIAL, THE SINGLE LARGEST PARTICLE SHALL MEASURE NO MORE THAN THREE MILLIMETERS IN MAJOR DIMENSION AND THE REMAINDER OF THE PARTICLES SHALL HAVE A MAJOR DIMENSION OF 1.5 MILLIMETERS OR LESS;
- C. FROM THE TOTAL QUANTITY OF FOREIGN MATERIAL, ANY FIBERS SHALL BE NO LONGER THAN SIX MILLIMETERS AND NO THICKER THAN 50 MICROMETERS.

IF FOREIGN MATERIAL OR OTHER TEST REQUIREMENTS ARE NOT MET, THE LOT SHALL BE REJECTED AND THE DOCUMENTATION FORWARDED TO NAVSUP WSS.

5.0 PREPARATION FOR DELIVERY

SODIUM PHOSPHATE TR 8723-0112

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B

5.1 PACKAGING AND PACKING

PACKAGING AND PACKING SHALL CONFORM TO LEVEL B OF FEDERAL SPECIFICATION PPP-C-2020, AND 49 CFR 100-199. THE PACKING SHALL BE SUFFICIENT TO PREVENT SHIFTING OF CONTENTS, BREAKAGE, DAMAGE, OR SUBSTANTIAL DISTORTION DURING HANDLING, SHIPMENT, AND INTERMEDIATE STORAGE. CONTAINERS SHALL CONFORM TO THE UNIFORM FREIGHT CLASSIFICATION OR REGULATIONS OF OTHER CARRIERS AS APPLICABLE TO THE MODE OF TRANSPORTATION.

A SAFETY DATA SHEET (SDS) PREPARED PER FED-STD-313 SHALL BE PROVIDED WITH EACH UNIT OF ISSUE AND AFFIXED/PACKAGED IN A MANNER FOR EASY ACCESSIBILITY WITHOUT BEING LOST OR DAMAGED DURING SHIPMEN AND STORAGE.

5.2 PRECAUTIONARY LABELS

NOT APPLICABLE

5.3 MARKING

A. MARKING FOR SHIPMENT AND STORAGE

INTERIOR PACKAGES AND EXTERIOR SHIPPING CONTAINERS SHALL BE MARKED IN ACCORDANCE WITH MIL-STD-129, 49 CFR 100-199, AND 29 CFR 1910.1200.BAR CODE MARKING SUITABLE FOR HAND SCANNING IS REQUIRED.

THE BAR CODE SHALL CONTAIN THE NSN, MFR/PN, AND THE CONTRACTOR'S CAGE CODE. THE BAR CODE SHALL BE APPLIED ON THE UNIT AND INTERMEDIATE PACK.

B. SPECIAL MARKING

FOR CHEMICALS PACKAGED IN METAL CANS, THE LABELING INFORMATION PRINTED ON THE CAN WILL BE PRESENTED IN THE MANNER SPECIFIED ON THE ENGINEERING SKETCH FOR THE CAN (LISTED IN SECTION 2.0), WHICH MAY NOT BE IDENTICAL TO THE CONTENTS OF THE FOLLOWING STANDARDIZED TABLE.

- (1) IDENTIFICATION LABEL DATA - EACH UNIT, INTERMEDIATE AND EXTERIOR SHIPPING CONTAINER SHALL BE MARKED WITH THE FOLLOWING INFORMATION IN ACCORDANCE WITH MIL-STD-129:

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT	
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018	
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP	
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B	

=====

= NATIONAL STOCK NUMBER	1H 6810-00-043-0758X2	=
= -----		
= NOMENCLATURE	SODIUM PHOSPHATE, TRIBASIC	=
= -----		
= NAME OF PRIME CONTRACTOR		=
= -----		
= NAME OF MANUFACTURER (IF DIFFERENT)		=
= -----		
= CONTRACT NUMBER		=
= -----		
= LOT NUMBER		=
= -----		
= DATE OF MANUFACTURE	(MONTH/YEAR)	=
= -----		
= SHELF LIFE	48 MONTHS	=
= -----		
= EXPIRATION DATE	(MONTH/YEAR)	=
= -----		
= NET CONTENTS	7 POUNDS	=
= -----		

=====

THE EXPIRATION DATE IS COMPUTED BY ADDING THE SHELF LIFE (48 MONTHS) TO THE DATE OF MANUFACTURE. IF THE CONTRACTOR IS THE MANUFACTURER OR IS PERFORMING STEPS THAT CHANGE THE FINAL FORM OR FORMULATION OF THE MATERIAL, THE DATE OF MANUFACTURE SHALL BE WHEN THE MATERIAL IS PLACED IN ITS END USE CONTAINERS. THIS DATE SHOULD CORRESPOND TO THE TIME AT WHICH THE SODIUM PHOSPHATE, TRIBASIC, DODECAHYDRATE MATERIAL IS TESTED BY THE CONTRACTOR FOR CERTIFICATION IT MEETS PURCHASE SPECIFICATIONS AND THE PROCUREMENT CONTRACT, IF POSSIBLE. IF THE CONTRACTOR AND MANUFACTURER ARE DIFFERENT AND THE CONTRACTOR WILL NOT BE CHANGING THE FORMULATION OF THE MATERIAL, THE DATE OF MANUFACTURE SHALL BE THE ORIGINAL MANUFACTURE DATE STATED BY THE MANUFACTURER, IF KNOWN; OTHERWISE, THE MANUFACTURE DATE SHALL BE THE DATE AT WHICH THE CONTRACTOR FIRST RECEIVED THE MATERIAL.

- (2) SHIPPING CONTAINERS SHALL BE MARKED WITH TAPE IMPRINTED WITH THE WORDS "X2 CHEMICALS". THE TAPE SHALL BE VISIBLE FROM ALL LATERAL DIRECTIONS OF THE SHIPPING CONTAINERS, IF PRACTICAL. THE TAPE SHALL BE WHITE AND APPROXIMATELY 1.25 INCHES WIDE. THE RED BLOCK PRINTING SHALL BE APPROXIMATELY 0.75 INCH TALL. THE RED BORDER SHALL BE APPROXIMATELY 0.2 INCH WIDE. THE TAPE SHALL NOT COVER ANY OTHER IDENTIFICATION MARKINGS ON THE CONTAINER. WHERE THE EXTERIOR CONTAINER IS A BOX OR CARTON, A STRIP OF TAPE SHALL BE

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B

PLACED ON ALL FOUR (4) LATERAL FACES TO ENSURE THAT THE COMPLETE WORDS "X2 CHEMICALS" ARE REPEATED AT LEAST TWICE ON EACH FACE.NOTE: TAPE MAY BE PURCHASED FROM:

NADCO INCORPORATED
ONE WASHINGTON ST
DOVER, NH 03820

(P/N X2CHEM)

PHONE (800) 839-9018

5.4 SHIPPING

SPECIAL REQUIREMENTS FOR SHIPMENT OF CHEMICALS

SHIP ALL MATERIAL IN ACCORDANCE WITH THE APPLICABLE TRANSPORTATION REGULATIONS IN SECTION 2.0, DEPENDING ON THE MODE OF TRANSPORTATION USED AND THE HAZARDS OF THE MATERIAL.

IN ACCORDANCE WITH 29 CFR 1910.1200, ONE (1) COPY OF THE SDS SHALL BE PROVIDED WITH THE BILL OF LADING FOR EACH SHIPMENT OF MATERIAL.

IN ADDITION TO THE EXISTING REQUIREMENTS OF MIL-STD-129, THIS PART SHALL CONTAIN BAR CODES THAT IDENTIFY SHELF LIFE INFORMATION (CURE DATE, SHELF LIFE CODE) ON THE UNIT PACKING ONLY.

6.0 CONTRACT DATA REQUIREMENTS

THE SELLER MUST PROVIDE THE CONTRACTING AGENCY WITH ALL OF THE SUBMITTALS LISTED BELOW. SUBMITTALS WHICH ARE REQUIRED BY A SPECIFICATION, BUT WHICH ARE NOT LISTED BELOW, NEED NOT BE SUBMITTED. ONLY THOSE SUBMITTALS LISTED BELOW ARE REQUIRED.

HOWEVER, IF THE SELLER CONSIDERS A REQUIRED SUBMITTAL INAPPLICABLE TO THIS PROCUREMENT, THE SELLER MUST SUBMIT A STATEMENT JUSTIFYING THE EXCLUSION OF THE REQUIRED SUBMITTAL.

REQUESTS FOR APPROVAL OF PROCEDURES USED PRIOR TO RECEIPT OF THIS ORDER SHALL IDENTIFY THE PROCESSING/TESTING SPECIFICATION VERSION APPLICABLE AND STATE THAT THE PROCESSING AND/OR TESTING WAS PERFORMED PRIOR TO RECEIPT OF THE ORDER. IF THE PROCEDURE THAT WAS USED IS NOT COMPLETE, TEST REPORTS, HEAT TREATMENT RECORDS, OR OTHER DOCUMENTATION SHALL BE SUBMITTED WITH THE PROCEDURES TO SUBSTANTIATE THAT ALL SPECIFICATION REQUIREMENTS WERE MET.

NATIONAL STOCK NUMBER	ITEM NAME	REVISION	TECHNICAL CONTACT
1H 6810-00-043-0758 X2	SODIUM PHOSPHATE TR	20241113111728	A08NAXXX1A0018
DRAWING PREPARER/MANUFACTURER		MANUFACTURER'S PART NO./DRAWING NO.	RSP
NAVSUP WEAPON SYSTEMS SUPPORT		8723-0112	B

6.1 PROCEDURES AND REPORTS

THE SELLER SHALL PROVIDE THE FOLLOWING PROCEDURE(S) AND REPORT(S) TO THE PROCURING ACTIVITY. CONTRACTOR PROCEDURE SUBMITTALS REQUIRED BY MATERIAL AND PROCESS SPECIFICATIONS NEED NOT BE RESUBMITTED FOR APPROVAL EACH TIME AN ORDER IS PLACED FOR THE SAME IRPOD ITEM TO THE SAME VERSION (I.E., REVISION, AMENDMENT, CHANGE NOTICE OR INTERIM CHANGE) OF THE SPECIFICATION OR STANDARD INVOKED. THE SELLER NEED ONLY SUBMIT PROOF OF THE PRIOR APPROVAL FOR THAT ITEM AND SPECIFICATION REVISION. ACCEPTABLE PROOF OF PRIOR APPROVAL WILL CONSIST OF A COORDINATED PROCEDURE REVIEW SYSTEM (CPRS) APPROVAL LETTER. CPRS APPROVAL DOES NOT RELIEVE THE SELLER OF THE RESPONSIBILITY TO COMPLY WITH ALL REQUIREMENTS IMPOSED ON ANY CURRENT AND FUTURE PURCHASE ORDERS.

IF FIRST-TIER MANUFACTURER RETESTING OF MATERIAL IS NECESSARY, USE OF BUYER APPROVED PROCEDURES APPLICABLE TO THE SAME VERSION OF THE SPECIFICATION OR STANDARD INVOKED ON THE IRPOD IS ACCEPTABLE IN LIEU OF OBTAINING THE RAW MATERIAL MANUFACTURER OR MATERIAL INSPECTION AND TEST PROCEDURES FOR APPROVAL.

WHERE ALTERNATIVE SPECIFICATIONS ARE SHOWN FOR A GIVEN ITEM, ONLY THE DATA FOR THE SPECIFICATION USED IS REQUIRED. THE SELLER SHALL SPECIFY THE FOLLOWING ON PROCEDURE(S)/REPORT(S) REQUIRING SUBMITTAL, AS APPLICABLE, IN ORDER THAT THE PROCEDURE/REPORT CAN BE READILY REVIEWED AGAINST THE APPROPRIATE ACCEPTANCE CRITERIA: SPECIFICATION AND REVISION, INCLUDING AMENDMENTS, NOTICES, ETC., APPLICABLE PARAGRAPH OF THE SPECIFICATION, THE NAME OF THE SUBMITTAL, THE MATERIAL CONDITIONS (I.E., MATERIAL GRADE, CLASS, TYPE, SIZE, COMPOSITION, ETC.).

6.1.3 PER CONTRACT DELIVERY SCHEDULE:

SODIUM PHOSPHATE TR 8723-0112

FOR EACH SHIPMENT, THE SELLER SHALL PROVIDE TO THE GOVERNMENT A REPORT DOCUMENTING THE RESULTS OF QUALITY ASSURANCE TESTING AND INSPECTION SPECIFIED IN SECTION 4.3, AS WELL AS ANY ADDITIONAL WRITTEN CERTIFICATIONS REQUIRED BY SECTION 4.3. THESE REPORTS AND CERTIFICATIONS ARE DELIVERABLE IN ACCORDANCE WITH THE CONTRACT DELIVERY SCHEDULE AND SHALL PROVIDE THE QUANTITATIVE RESULTS (NUMERICAL RESULT OR PASS/FAIL AS APPLICABLE) FOR EACH SAMPLE TESTED.

6.2 OTHER CONTRACT DATA REOUIREMENTS

INTENTIONALLY LEFT BLANK