

# ESSAYONS QUALIFICATION CHECKLIST

| PHYSICAL REQUIREMENTS                                                    |     |    |
|--------------------------------------------------------------------------|-----|----|
| Overall:                                                                 | YES | NO |
| Not less than 25 feet of water depth at Mean Low Water Level             |     |    |
| A distance of not less than 380 feet between fore and aft tie off kevels |     |    |

  

|                                                                                                         |     |    |
|---------------------------------------------------------------------------------------------------------|-----|----|
| Dry-dock:                                                                                               | YES | NO |
| Lift capacity of 7,500 long tons                                                                        |     |    |
| Clearance between wing walls of not less than 108'-0" for job orders requiring lowering of drag arms.   |     |    |
| Clearance between wing walls of not less than 78'-0" for job orders NOT requiring lowering of drag arms |     |    |
| Keel block height of not less than 6'-0"                                                                |     |    |

  

|                                                                                                                                                                                                                                                                                                                                          |     |    |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----|
| Facilities:                                                                                                                                                                                                                                                                                                                              | YES | NO |
| 50'-0" x 16'-0" clear dock working area;                                                                                                                                                                                                                                                                                                 |     |    |
| Live load pier capacities not less than those prescribed in AASHTO H15-44 as certified by a Professional Engineer                                                                                                                                                                                                                        |     |    |
| Not less than 1200A, 480V AC, 3-phase, 60 cycle continuous electrical service with GFCI and phase protection                                                                                                                                                                                                                             |     |    |
| Compressed air service that can provide a minimum of 100 psig through a portable air dryer and 1 1/2" hose to the vessel's air connection.                                                                                                                                                                                               |     |    |
| Potable water service capable of providing 90 psi, 50gph at not less than 1200 gallons per day.                                                                                                                                                                                                                                          |     |    |
| Fresh water for ship cooling water. Less than 90 Degrees F at 90 psig and 175 gallons per minute of fresh water. In case of closed loop system supply water must be not less than 25 Degrees F cooler than return water from ship. System must be in place and ready to deliver fresh water within two hours of vessel being dry-docked. |     |    |
| Receiving tank or other suitable service in place to receive effluent from the vessel sewage plant.                                                                                                                                                                                                                                      |     |    |
| Receiving tank or other suitable service in place to receive effluent from the vessel gray water overboard flange connections.                                                                                                                                                                                                           |     |    |
| Fire protection water at 50 psig and 400 gallons per minute. Fresh water is not required for this service.                                                                                                                                                                                                                               |     |    |
| Crane shall be capable of accessing any area above the vessel and have a lift capacity of 10,000 lbs minimum over the entire area.                                                                                                                                                                                                       |     |    |
| A minimum of 600 square feet of temporary office space available for use by the Government within 500 yards of the proposed Berth and Dry-dock facilities                                                                                                                                                                                |     |    |