

YAQUINA QUALIFICATION CHECKLIST

PHYSICAL REQUIREMENTS		
Overall:	YES	NO
Not less than 20 feet of water depth at Mean Low Water Level		
A distance of not less than 250 feet between fore and aft tie off kevels		

Dry-dock:	YES	NO
Lift capacity of 2,001 long tons		
Clearance between wing walls of not less than 85'-0" for job orders requiring lowering of drag arms.		
Clearance between wing walls of not less than 68'-0" for job orders NOT requiring lowering of drag arms		
Keel block height of not less than 6'-0"		

Facilities:	YES	NO
50'-0" x 16'-0" clear dock working area;		
Live load pier capacities not less than those prescribed in AASHTO H15-44 as certified by a Professional Engineer		
Not less than 400A, 480V AC, 3-phase, 60 cycle continuous electrical service with GFCI and phase protection		
Compressed air service that can provide a minimum of 100 psig through a portable air dryer and 1 1/2" hose to the vessel's air connection.		
Potable water service capable of providing 90psi, 50gph at not less than 1000 gallons per day.		
Receiving tank or other suitable service in place to receive effluent from the vessel sewage plant.		
Receiving tank or other suitable service in place to receive effluent from the vessel gray water overboard flange connections.		
Fire protection water at 50 psig and 400 gallons per minute. Fresh water is not required for this service.		
Crane shall be capable of accessing any area above the vessel and have a lift capacity of 8,800 lbs minimum over the entire area.		
A minimum of 600 square feet of temporary office space available for use by the Government within 500 yards of the proposed Berth and Dry-dock facilities		