

The following salient characteristics are required for the matrix intercom system:

- 1) Matrix frame shall have Slots for 2 CPU cards, 7 interface cards and 8 interface modules
- 2) Matrix frame should support up to 448 internal ports
- 3) Matrix frame shall have Dual redundant CPU-HX processors fitted as standard
- 4) Matrix frame shall have Dual redundant power supplies.
- 5) Matrix frame shall be full compatible/integration with Clear-Com Free Speak II and Clear-Com Free Speak Edge wireless belt packs
- 6) Matrix frame shall be fully compatible with Clear-Com V-Series Iris and I-Series panels
- 7) Matrix frame shall be programmed via Clear-Com EHX programming software

The following salient characteristics are required for the intercom panels:

- 1) Fully compatible with Clear-Com HX ecosystem
- 2) Panels shall be free standing desk type and 1RU rack mount
- 3) Panels shall have rotary volume / channel activation and push button talk keys
- 4) Panels shall have 4 pin male XLR headset input on front of panel
- 5) Panels shall have DB-25M connections on the back of the panel
- 6) Panels shall be capable of bi-nural coms where channels can be assigned to either the right or left ear via the matrix frame via programming software.

Installation / sustainment support:

- 1) Support vendor shall have full access to Clear-Com firmware including DOD specific firmware not offered to the public.
- 2) Vendor shall have direct access to Clear-Com engineering and product support.
- 3) The vendor shall have at a minimum Green Badge base access to PSNS & IMF.