

STATEMENT OF WORK

JRM Milestone Secondary Cluster

OVERVIEW:

Joint Region Marianas (JRM) requires the procurement of a Secondary Virtual Machine (VM) Stack that will provide the redundancy infrastructure for the Milestone Recording servers. The Milestone Systems platform is what provides video surveillance services for JRM and all of the tenant commands (Naval Base Guam, Marine Corps Base Camp Blaz, and NCTS). This specialized cluster will be integrated into Joint Region Marianas Platform Enclave (JRM-PE) and provide scalability to accommodate camera requirements for all of JRM and its tenant commands; also this provides reliability for surveillance services and disaster avoidance ensures continuity of operations.

REQUIRED IA CONTROLS FOR COMPLIANCE:

NIST SP 800-53 rev4 - The NIST SP 800-53 rev4 provides a list of controls that is used for the development of Federal Information Systems, specifically its Information Assurance (IA) aspect.

SA-4(7): System and Services Acquisition – refers to “National Information Assurance Partnership” (NIAP) approved; Department of Defense Information Systems Approved Products List (DoDIN APL) listed. Hardware and/or Software being procured must be evaluated against NIAP and included in the DoDIN APL.

The organization:

- (a) Limits the use of commercially provided information assurance (IA) and IA-enabled information technology products to those products that have been successfully evaluated against a National Information Assurance partnership (NIAP)-approved Protection Profile for a specific technology type, if such a profile exists; and
- (b) Requires, if no NIAP-approved Protection Profile exists for a specific technology type but a commercially provided information technology product relies on cryptographic functionality to enforce its security policy, that the cryptographic module is Federal Information Processing Standards (FIPS)-validated.

VENDOR WILL PROVIDE THE FOLLOWING:

A. HARDWARE/SOFTWARE

****Specifications below are the requirements for four (4) nodes – (equal or better)**

Item	Description	Qty
0001	Dell PowerEdge Server Model Number R750 (2RU Rack-mountable server, 2.5” Chassis, All Flash) below are the key specifications:	4
	SAS/SATA Backplane; No Rear Storage	4
	GPU Enablement GPU Ready Configuration Cable Install Kit R750	4
	Dual port 10/25GbE SFP28, Network Interface Card	4
	Dual port 10/25GbE SFP28, Additional Network Interface Card	4
	R750 Motherboard with Broadcom 5720 Dual Port 1Gb On-Board LOM	4
	Dell HBA355i Controller Front	4

	Intel Xeon Gold 5315Y 3.2G, 8C/16T, 11.2GT/s, 12M Cache, Turbo, HT (140W) DDR4- 2933 2 CPU per node	8
	64GB RDIMM, 3200MT/s, Dual Rank	64
	1.92TB SSD SAS ISE Read Intensive 12Gbps 512 2.5in Hot-plug AG Drive, 1 DWPD	12
	800GB SSD SAS ISE Mix Use 12Gbps 512e 2.5in Hot-plug AG Drive, 3 DWPD	4
	Trusted Platform Module 2.0 V3	4
	ReadyRails Sliding Rails	4
	Dual, Hot-Plug,Power Supply Redundant (1+1), 1400W, Mixed Mode	4
	C13 to C14, PDU Style, 12 AMP, 6.5 Feet (2m) Power Cord, North America	8
	PE R7525/ R750 Acceleration Standard Cable	4
	Fan Foam, HDD 2U	4
	BOSS-S2 controller card + with 2 M.2 480GB (RAID 1)	4
	BOSS Cables and Bracket for R750 (Riser 1)	4
	Heatsink for 2 CPU with GPU configuration	4
0002	NVIDIA Ampere A10, PCIe, 150W, 24GB Passive, Single Wide, Full Height GPU Customer Kit	4

B. MAINTENANCE AND SUPPORT

Item	Quantity	Description
1	n/a	24x7 HW/SW Technical Support and Assistance, 3 years (ProDeploy Support)
2	n/a	Vendor Standard Hardware Warranty plus On-Site Service

*ALL items/components must be brand new.

*Must include ALL required hardware and software components for normal operation “out-of-the-box”.

*Vendor must ensure the compatibility of all hardware and software components.

*ALL items/components must be fully interoperable and shall no create and/or develop any issues, bugs, and/or problems with existing Network Transport Infrastructure.

REQUIRED DELIVERY DATE:

- NLT 12SEPT2025

SHIP TO:

(N61128) Naval Base Guam

Santa Rita, GU, Guam - 96915

POC:

[TBD](#)

Draft