

TECHNICAL REQUIREMENTS

Sensor, Accelerometer

The accelerometer is a device that senses motion. The requirements for this purchase order are for accelerometers that sense motion in 3 axes, a tri-axial accelerometer. The sensor converts movement to an electrical signal proportional to the acceleration of the movement. The model requested uses MEMS capacitive technology to achieve a low-end frequency response of zero (0).

Amplitude Range: Tri-axial Model 7603D5: +/- 50 g

Sensitivity: Tri-axial Model 7603D5: 10 mV/g

Minimum Excitation Voltage: 7600 Series Accelerometers: 3 Vdc

Maximum Excitation Voltage: 7600 Series Accelerometers: 11 Vdc

Shock Limit: 5000 g

Frequency Range +/-3db: Tri-axial Model 7603D5: 0-1200 Hz

Operating Temperature Range: Tri-axial Model 7603D5: -67 to 257 deg. F

Weight: Tri-axial Model 7603D5: 38 grams

Construction: Hermetically sealed

Electrical Configuration: Signal/ground isolated

Physical Signal Output Medium: 7600 Series Accelerometers: 9-pin 5/16-32 radial connector

Calibration: Certificate supplied for each sensor

Sensor accessories to be provided for mounting and electrical connection:

Adhesive mounting base made of anodized aluminum with tapped holes.

Cable assembly that is 30 feet long with a 9-pin connector at one end and pigtail at the other.

Quantity Of Items: Accelerometers.

Quantity	Model # / Description
10	7603D5 TRIAXIAL DC ACCELEROMETER, 50g
10	69026 ADHESIVE MOUNTING BASE, 2X 8-32, 1X 10-32 TAPPED HOLES, ALUMINUM ANODIZED ORANGE
10	6964A30 CABLE ASSY, 9 PIN JACK TO PIGTAIL, 30FT

Delivery POC: Michael Barry, [REDACTED]

[REDACTED]

Technical Point of Contact: Michael Barry.

Delivery Date: 60 Days After Contract Award.

Delivery Address: 6850 LANYARD ROAD-BLDG 358

ABERDEEN PROVING GROUND MD 21005