

Purchase Description Procurement of Automated Calibration Machine

The U.S. Army TMDE Activity (USATA) has a requirement to implement a brand name purchase of one (1) UCM-200k Automated Force Calibration Machine with accessories or equivalent that will be a life cycle replacement of an existing model to be used for custom calibration to provide automation capabilities to improve efficiency and lower uncertainty in measurements. The unit shall be delivered to USATA's Army Physical Standards Labs located at Building 5435, Fowler Road Redstone Arsenal. The Automate Force Machine will also include the additional accessories to support USATA's mission as follow:

1.0 Requirements:

Includes the following accessories:

- (1) Jack Compression Block
- (1) Upper Yoke compression Block
- (1) Lower Yoke Compression Block
- (1) Upper Platen Compression Block
- (1) Automation Control Unit

4215-PLUS

Morehouse 4215-Plus..• Single strain gage type input channel..• Peak / valley / hold / peak reset ..• Two shunt resistors /direct analog amplifier output ..• USB communications port..• Up to Fifth order Polynomial calibration profiles

TUZ-225-001-01

CLEVIS PIN SET FOR 225K UCM FOR DILLON EDX-100T; MSI 7300; STRAIGHTPOINT RLP100T/LLP100T

TUZ-225-001-08

CLEVIS PIN SET FOR 225K UCM FOR EILON RON 2000/2501 S100

TU-225-001

Basic 225k Clevis for use with 225K Quick Change Tension member set.

TMA-225-10-2.438

TENSION MEMBER ASSEMBLY FOR 225K UCM

NOTE

Reference Standard Adapters (Below)

CG-15-6.000-4.500-01

4.500 Alignment Ring for use with CG-10-6.000-(0.750-16)-01 6" dia. Hardened Upper Bearing Block

CI-1-2.750-01

CI-1-2.750-01 ISO 376 Type Compression Top Adapter for 1MN with 2.750- UNF-2A thread

CA-1-(2.750-8)-01

2.75"-8 Alignment Plug for LC Adapter Plate. Old Part #600037.35

NOTE

Tension Adapters (Below)

TA-225F(1.250-12)

1.250"-12 Female thread adapter for 225k Quick-Change Tension Members; Capacity: 84.5k lbf

TA-225M(1.250-12)

1.250"-12 Male thread adapter for 225k Quick-Change Tension Members; Capacity: 84.5k lbf

1 TA-225F(1.500-12)

1.500"-12 Female thread adapter for 225k Quick-Change Tension Members; Capacity: 126k lbf

1 TA-225M(1.500-12)

1.500"-12 Male thread adapter for 225k Quick-Change Tension Members; Capacity: 126k lbf

1 TA-225F(1.750-12)

1.750"-12 Female thread adapter for 225k Quick-Change Tension Members; Capacity: 176k lbf

1 TA-225M(1.750-12)

1.750"-12 Male thread adapter for 225k Quick-Change Tension Members; Capacity: 176k lbf

NOTE

Compression Adapters (Below)

1 UC-100-051-01

3/4"-16UNF-2A, 7/8" Ball Seat for 30k+ UCMs, capacity: 100k lbf Old Part # 600006.03

1 UC-100-051-02

3/4"-16UNF-2A, 5/8" Ball Seat for UCM's Capacity: 60k and 100k lbf Old Part # 600006.02

1 CCE-1-(1.250-12)-01

1.25"-12 female Ball Adapter, capacity: 60k lbf, Ball Dia. 5/8"..Old Part # 600082.03

1 CCE-1-(1.500-12)-01

1.5"-12 female Ball Adapter, capacity: 60k lbf, Ball Dia. 5/8"..Old Part # 600082.15

1 CCE-1-(1.750-12)-01

1.75"-12 female Ball Adapter, capacity: 100k lbf, Ball Dia. 7/8"..Old Part # 600082.04

1 CA-1-(1.250-12)-01

1.25"-12 Alignment Plug for LC Adapter Plate..Old Part # 600037.08

CA-1-(1.500-12)-01

1.5"-12 Alignment Plug for LC Adapter Plate..Old Part # 600037.12

1 CA-1-(1.750-12)-01

1.75"-12 Alignment Plug for LC Adapter Plate..Old Part # 600037.09

2.0 Delivery Requirements

Shipping Address: U.S. Army TMDE Activity, Attn: Bradford Suggs, Building 5435, Redstone Arsenal, AL 35898