

SPECIFICATIONS

Project: Equipment for genetics lab expansion

PR Number:

1. Product Features

Name of Item: Sterling VAULT100-PWR5 Ultra-Low Temperature Freezer

Manufacturer: Sterling Ultracold

Model Number: VAULT100-PWR5

Salient Characteristics:

- -100 to -20°C temperature range
- user interface display with onboard predictive analytics and freezer diagnostics
- free-piston engine design
- 28 cu ft storage
- Exterior dimensions 78.6 x 34.3 x 36 in
- 5 adjustable shelves
- Capable of storing 384 100-place hinged plastic storage boxes with accessory racks

Capabilities:

- -100 to -20°C temperature range
- steady-state setpoint adherence of +/-3°C

Name of Item: Side access racks for hinged plastic storage boxes

Manufacturer: Stirling Ultracold

Model Number: 780-RHT-44

Salient Characteristics:

- dimensions of 8.85 in x 27.4 in x 5.5in (hxdxw)
- stainless steel construction

Capabilities:

- Each rack capable of storing 16 (4x4 arrangement) 100-place plastic storage boxes for 2ml tubes

Name of Item: VWR Standard 14CF refrigerator

Manufacturer: VWR

Model Number: 76580-186

Salient Characteristics:

- Microprocessor temperature controller
- Digital temperature display and alarm module
- Audible, visual, sensor error, and power failure alarms
- Alarm validation and alarm mute with ring back
- Keyed door lock
- Natural hydrocarbon refrigerants
- ENERGY STAR certified*

Capabilities:

- 1-10°C temperature range
- 14 of storage volume

Name of Item: VWR FREEZER LAB TOUCHSCREEN 49CF

Manufacturer: VWR

Model Number: 77696-006

Salient Characteristics:

- Variable speed compressors
- Premium touchscreen controllers
- Microprocessor temperature control
- Advanced alarm systems
- Data logging capabilities
- Natural hydrocarbon refrigerants
- Internal dimensions of $49\frac{1}{8}\times 26\frac{1}{2}\times 59$ "
- 49cf of storage volume

Capabilities:

- 10 adjustable shelves
- Maintain temperature stability of $\pm 2.1^{\circ}\text{C}$
- Energy consumption of less than 10 KWh/day

Name of Item: VWR FREEZER SOLID MAN DEF STANDARD 14CF

Manufacturer: VWR

Model Number: 76580-170

Salient Characteristics:

- Microprocessor temperature controller
- Digital temperature display
- Audible and visual alarm systems
- Interior shelving
- Keyed door lock
- Natural, hydrocarbon refrigerant
- ENERGY STAR certified*
- Manual defrost
- Exterior dimension $23\frac{5}{8}\times 24\frac{3}{8}\times 73$ "

Capabilities:

- -15 to -25 °C storage temperature
- 14 cf of storage volume

Name of Item: VWR FREEZER MAN DEFR 781X737X1896MM 20CF

Manufacturer:

Model Number:

Salient Characteristics:

- Microprocessor temperature controller
- Digital temperature display
- Audible and visual alarm systems
- Interior shelving
- Keyed door lock
- Natural, hydrocarbon refrigerant

- ENERGY STAR certified*
- Manual defrost
- Exterior dimension 30¾×29×74⅝"

Capabilities:

- -15 to -25 °C storage temperature
- 20 cf of storage volume
-

Name of Item: 5.9 CFT. FORCED AIR OVEN 300C 230V

Manufacturer: Memmert

Model Number: UN160

Salient Characteristics:

- Stainless steel interior
- Fully insulated door
- Exterior dimensions 29.3" x 43.5" x 23"
- 161 L interior volume
- Electrical 230 V (+ / - 10%), 50/60 Hz / 13.9 amps

Capabilities:

- Operating temperature of 5°C above ambient up to +300°C
- Digital timer with backwards counter with target time setting, adjustable from 1 minute to 99 days
- adjustable electronic overtemperature monitor and mechanical temperature limiter TB, protection class 1 according to DIN 12880 to switch off the heating approx. 20°C above nominal temperature

2. Delivery

Prices quoted must be FOB Destination

"F.o.b. destination" means --Free of expense to the Government delivered, on board the carrier's conveyance, at a specified delivery point where the consignee's facility (plant, warehouse, store, lot, or other location to which shipment can be made) is located; and

Supplies shall be delivered to the destination consignee's wharf (if destination is a port city and supplies are for export), warehouse unloading platform, or receiving dock, at the expense of the contractor. The Government shall not be liable for any delivery, storage, demurrage, accessorial, or other charges involved before the actual delivery (or "constructive placement" as defined in carrier tariffs) of the supplies to the destination, unless such charges are caused by an act or order of the Government acting in its contractual capacity. If rail carrier is used, supplies shall be delivered to the specified unloading platform of the consignee. If motor carrier (including "piggyback") is used, supplies shall be delivered to truck tailgate at the unloading platform of the consignee, except when the supplies delivered meet the requirements of Item 568 of the National Motor Freight Classification for "heavy or bulky freight." When supplies meeting the requirements of the referenced Item 568 are delivered, unloading (including movement to the tailgate) shall be performed by the consignee, with assistance from the truck driver, if requested. If the contractor uses rail carrier or freight forwarder for less than carload shipments, the contractor shall ensure that the carrier will furnish tailgate delivery when required, if transfer to truck is required to complete delivery to consignee.

Contractor responsibilities. The contractor shall --

- (1)(i) Pack and mark the shipment to comply with contract specifications; or
- (ii) In the absence of specifications, prepare the shipment in conformance with carrier requirements;
- (2) Prepare and distribute commercial bills of lading;
- (3) Deliver the shipment in good order and condition to the point of delivery specified in the contract;
- (4) Be responsible for any loss of and/or damage to the goods occurring before receipt of the shipment by the consignee at the delivery point specified in the contract;
- (5) Furnish a delivery schedule and designate the mode of delivering carrier; and
- (6) Pay and bear all charges to the specified point of delivery.

3. Delivery Location:

Product shall be delivered to the following location:

United States Fish and Wildlife Service
Northeast Fishery Center
227 Washington Avenue
Lamar PA 16848

4. Installation:

No installation required

5. Technical Point of Contact (POC):

Aaron Maloy
aaron_maloy@fws.gov
570-726-4247 x157

6. Delivery Instructions:

Nonholiday business hours are 7:30am – 4:00pm Monday through Friday

No later than three days prior to delivery, please contact the Point of Contact listed above, to arrange a specific time for delivery. Unloading the product is the sole responsibility of the delivery carrier. No labor or equipment will be provided by the government to unload the supplies.

7.0 Customer Specific Delivery requirements

No loading dock available